JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.jar

Class JarOutputStream

java.lang.Object
  java.io.OutputStream
    java.io.FilterOutputStream
      java.util.zip.DeflaterOutputStream
        java.util.zip.ZipOutputStream
          java.util.jar.JarOutputStream

All Implemented Interfaces:

`Closeable`, `Flushable`, `AutoCloseable`

```
public class JarOutputStream
extends ZipOutputStream
```

The `JarOutputStream` class is used to write the contents of a JAR file to any output stream. It extends the class `java.util.zip.ZipOutputStream` with support for writing an optional `Manifest` entry. The `Manifest` can be used to specify meta-information about the JAR file and its entries.

Since:

1.2

See Also:

`Manifest`, `ZipOutputStream`

Field Summary

Fields

Modifier and Type	Field	Description
static int	CENATT	

static int	**CENATX**	
static int	**CENCOM**	
static int	**CENCRC**	
static int	**CENDSK**	
static int	**CENEXT**	
static int	**CENFLG**	
static int	**CENHDR**	
static int	**CENHOW**	
static int	**CENLEN**	
static int	**CENNAM**	
static int	**CENOFF**	
static long	**CENSIG**	
static int	**CENSIZ**	
static int	**CENTIM**	
static int	**CENVEM**	
static int	**CENVER**	
static int	**ENDCOM**	
static int	**ENDHDR**	
static int	**ENDOFF**	
static long	**ENDSIG**	
static int	**ENDSIZ**	
static int	**ENDSUB**	
static int	**ENDTOT**	
static int	**EXTCRC**	
static int	**EXTHDR**	
static int	**EXTLEN**	
static long	**EXTSIG**	
static int	**EXTSIZ**	
static int	**LOCCRC**	

static int	LOCEXT
static int	LOCFLG
static int	LOCHDR
static int	LOCHOW
static int	LOCLEN
static int	LOCNAM
static long	LOCSIG
static int	LOCSIZ
static int	LOCTIM
static int	LOCVER

Fields inherited from class java.util.zip.ZipOutputStream

DEFLATED, STORED

Fields inherited from class java.util.zip.DeflaterOutputStream

buf, def

Fields inherited from class java.io.FilterOutputStream

out

Constructor Summary

Constructors

Constructor	Description
JarOutputStream(OutputStream out)	Creates a new JarOutputStream with no manifest.
JarOutputStream(OutputStream out, Manifest man)	Creates a new JarOutputStream with the specified Manifest.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
void	putNextEntry(ZipEntry ze)	Begins writing a new JAR file entry and positions the stream to the start of the entry data.

Methods inherited from class java.util.zip.ZipOutputStream

close, closeEntry, finish, setComment, setLevel, setMethod, write

Methods inherited from class java.util.zip.DeflaterOutputStream

deflate, flush, write

Methods inherited from class java.io.FilterOutputStream

write

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Detail

LOCSIG

```
public static final long LOCSIG
```

See Also:

Constant Field Values

EXTSIG

```
public static final long EXTSIG
```

See Also:

Constant Field Values

CENSIG

public static final long CENSIG

See Also:

Constant Field Values

ENDSIG

public static final long ENDSIG

See Also:

Constant Field Values

LOCHDR

public static final int LOCHDR

See Also:

Constant Field Values

EXTHDR

public static final int EXTHDR

See Also:

Constant Field Values

CENHDR

public static final int CENHDR

See Also:

Constant Field Values

ENDHDR

public static final int ENDHDR

See Also:

Constant Field Values

LOCVER

```
public static final int LOCVER
```

See Also:

Constant Field Values

LOCFLG

```
public static final int LOCFLG
```

See Also:

Constant Field Values

LOCHOW

```
public static final int LOCHOW
```

See Also:

Constant Field Values

LOCTIM

```
public static final int LOCTIM
```

See Also:

Constant Field Values

LOCCRC

```
public static final int LOCCRC
```

See Also:

Constant Field Values

LOCSIZ

public static final int LOCSIZ

See Also:

Constant Field Values

LOCLEN

public static final int LOCLEN

See Also:

Constant Field Values

LOCNAM

public static final int LOCNAM

See Also:

Constant Field Values

LOCEXT

public static final int LOCEXT

See Also:

Constant Field Values

EXTCRC

public static final int EXTCRC

See Also:

Constant Field Values

EXTSIZ

public static final int EXTSIZ

See Also:

Constant Field Values

EXTLEN

public static final int EXTLEN

See Also:

Constant Field Values

CENVEM

public static final int CENVEM

See Also:

Constant Field Values

CENVER

public static final int CENVER

See Also:

Constant Field Values

CENFLG

public static final int CENFLG

See Also:

Constant Field Values

CENHOW

public static final int CENHOW

See Also:

Constant Field Values

CENTIM

public static final int CENTIM

See Also:

Constant Field Values

CENCRC

```
public static final int CENCRC
```

See Also:

Constant Field Values

CENSIZ

```
public static final int CENSIZ
```

See Also:

Constant Field Values

CENLEN

```
public static final int CENLEN
```

See Also:

Constant Field Values

CENNAM

```
public static final int CENNAM
```

See Also:

Constant Field Values

CENEXT

```
public static final int CENEXT
```

See Also:

Constant Field Values

CENCOM

```
public static final int CENCOM
```

See Also:

Constant Field Values

CENDSK

public static final int CENDSK

See Also:

Constant Field Values

CENATT

public static final int CENATT

See Also:

Constant Field Values

CENATX

public static final int CENATX

See Also:

Constant Field Values

CENOFF

public static final int CENOFF

See Also:

Constant Field Values

ENDSUB

public static final int ENDSUB

See Also:

Constant Field Values

ENDTOT

public static final int ENDTOT

See Also:

Constant Field Values

ENDSIZ

```
public static final int ENDSIZ
```

See Also:

Constant Field Values

ENDOFF

```
public static final int ENDOFF
```

See Also:

Constant Field Values

ENDCOM

```
public static final int ENDCOM
```

See Also:

Constant Field Values

Constructor Detail

JarOutputStream

```
public JarOutputStream(OutputStream out,
                       Manifest man)
                throws IOException
```

Creates a new `JarOutputStream` with the specified `Manifest`. The manifest is written as the first entry to the output stream.

Parameters:

`out` - the actual output stream

`man` - the optional Manifest

Throws:

`IOException` - if an I/O error has occurred

JarOutputStream

```
public JarOutputStream(OutputStream out)
                throws IOException
```

Creates a new `JarOutputStream` with no manifest.

Parameters:

`out - the actual output stream`

Throws:

`IOException - if an I/O error has occurred`

Method Detail

putNextEntry

```
public void putNextEntry(ZipEntry ze)
                  throws IOException
```

Begins writing a new JAR file entry and positions the stream to the start of the entry data. This method will also close any previous entry. The default compression method will be used if no compression method was specified for the entry. The current time will be used if the entry has no set modification time.

Overrides:

`putNextEntry in class ZipOutputStream`

Parameters:

`ze - the ZIP/JAR entry to be written`

Throws:

`ZipException - if a ZIP error has occurred`

```
IOException - if an I/O error has occurred
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.