JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.jar

Class Manifest

java.lang.Object
    java.util.jar.Manifest

All Implemented Interfaces:

`Cloneable`

```
public class Manifest
extends Object
implements Cloneable
```

The Manifest class is used to maintain Manifest entry names and their associated Attributes. There are main Manifest Attributes as well as per-entry Attributes. For information on the Manifest format, please see the Manifest format specification.

Since:

1.2

See Also:

`Attributes`

Constructor Summary

Constructors

Constructor	Description
`Manifest()`	Constructs a new, empty Manifest.
`Manifest(InputStream is)`	Constructs a new Manifest from the specified input stream.
`Manifest(Manifest man)`	

	Constructs a new Manifest that is a copy of the specified Manifest.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
void	clear()	Clears the main Attributes as well as the entries in this Manifest.
Object	clone()	Returns a shallow copy of this Manifest.
boolean	equals(Object o)	Returns true if the specified Object is also a Manifest and has the same main Attributes and entries.
Attributes	getAttributes(String name)	Returns the Attributes for the specified entry name.
Map<String,Attributes>	getEntries()	Returns a Map of the entries contained in this Manifest.
Attributes	getMainAttributes()	Returns the main Attributes for the Manifest.
int	hashCode()	Returns the hash code for this Manifest.
void	read(InputStream is)	Reads the Manifest from

		the specified InputStream.
void	**write**(**OutputStream** out)	Writes the Manifest to the specified OutputStream.

Methods inherited from class java.lang.Object

finalize, getClass, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

Manifest

```
public Manifest()
```

Constructs a new, empty Manifest.

Manifest

```
public Manifest(InputStream is)
         throws IOException
```

Constructs a new Manifest from the specified input stream.

Parameters:

`is - the input stream containing manifest data`

Throws:

`IOException - if an I/O error has occurred`

Manifest

```
public Manifest(Manifest man)
```

Constructs a new Manifest that is a copy of the specified Manifest.

Parameters:

`man - the Manifest to copy`

Method Detail

getMainAttributes

```
public Attributes getMainAttributes()
```

Returns the main Attributes for the Manifest.

Returns:

the main Attributes for the Manifest

getEntries

```
public Map<String,Attributes> getEntries()
```

Returns a Map of the entries contained in this Manifest. Each entry is represented by a String name (key) and associated Attributes (value). The Map permits the `null` key, but no entry with a null key is created by `read(java.io.InputStream)`, nor is such an entry written by using `write(java.io.OutputStream)`.

Returns:

a Map of the entries contained in this Manifest

getAttributes

```
public Attributes getAttributes(String name)
```

Returns the Attributes for the specified entry name. This method is defined as:

```
return (Attributes)getEntries().get(name)
```

Though `null` is a valid `name`, when `getAttributes(null)` is invoked on a `Manifest` obtained from a jar file, `null` will be returned. While jar files themselves do not allow `null`-named attributes, it is possible to invoke `getEntries()` on a `Manifest`, and on that result, invoke `put` with a null key and an arbitrary value. Subsequent invocations of `getAttributes(null)` will return the just-`put` value.

Note that this method does not return the manifest's main attributes; see `getMainAttributes()`.

Parameters:

name - entry name

Returns:

the Attributes for the specified entry name

clear

```
public void clear()
```

Clears the main Attributes as well as the entries in this Manifest.

write

```
public void write(OutputStream out)
           throws IOException
```

Writes the Manifest to the specified OutputStream. Attributes.Name.MANIFEST_VERSION must be set in MainAttributes prior to invoking this method.

Parameters:

out - the output stream

Throws:

IOException - if an I/O error has occurred

See Also:

getMainAttributes()

read

```
public void read(InputStream is)
          throws IOException
```

Reads the Manifest from the specified InputStream. The entry names and attributes read will be merged in with the current manifest entries.

Parameters:

is - the input stream

Throws:

IOException - if an I/O error has occurred

equals

```
public boolean equals(Object o)
```

Returns true if the specified Object is also a Manifest and has the same main Attributes and entries.

Overrides:

`equals` in class `Object`

Parameters:

`o - the object to be compared`

Returns:

`true if the specified Object is also a Manifest and has the same main Attributes and entries`

See Also:

`Object.hashCode()`, `HashMap`

hashCode

```
public int hashCode()
```

Returns the hash code for this Manifest.

Overrides:

`hashCode` in class `Object`

Returns:

`a hash code value for this object.`

See Also:

`Object.equals(java.lang.Object)`, `System.identityHashCode(java.lang.Object)`

clone

```
public Object clone()
```

Returns a shallow copy of this Manifest. The shallow copy is implemented as follows:

```
public Object clone() { return new Manifest(this); }
```

Overrides:

`clone` in class `Object`

Returns:

`a shallow copy of this Manifest`

See Also:

`Cloneable`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.