JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.logging

Class ConsoleHandler

java.lang.Object
  java.util.logging.Handler
    java.util.logging.StreamHandler
      java.util.logging.ConsoleHandler

```
public class ConsoleHandler
extends StreamHandler
```

This `Handler` publishes log records to `System.err`. By default the `SimpleFormatter` is used to generate brief summaries.

Configuration: By default each `ConsoleHandler` is initialized using the following `LogManager` configuration properties where `<handler-name>` refers to the fully-qualified class name of the handler. If properties are not defined (or have invalid values) then the specified default values are used.

- <handler-name>.level specifies the default level for the `Handler` (defaults to `Level.INFO`).
- <handler-name>.filter specifies the name of a `Filter` class to use (defaults to no `Filter`).
- <handler-name>.formatter specifies the name of a `Formatter` class to use (defaults to `java.util.logging.SimpleFormatter`).
- <handler-name>.encoding the name of the character set encoding to use (defaults to the default platform encoding).

For example, the properties for `ConsoleHandler` would be:

- java.util.logging.ConsoleHandler.level=INFO
- java.util.logging.ConsoleHandler.formatter=java.util.logging.SimpleFormatter

For a custom handler, e.g. com.foo.MyHandler, the properties would be:

- com.foo.MyHandler.level=INFO

- com.foo.MyHandler.formatter=java.util.logging.SimpleFormatter

Since:

1.4

Constructor Summary

Constructors

Constructor	Description
`ConsoleHandler()`	Create a `ConsoleHandler` for `System.err`.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`void`	`close()`	Override `StreamHandler.close` to do a flush but not to close the output stream.
`void`	`publish(LogRecord record)`	Publish a `LogRecord`.

Methods inherited from class java.util.logging.StreamHandler

`flush`, `isLoggable`, `setEncoding`, `setOutputStream`

Methods inherited from class java.util.logging.Handler

`getEncoding`, `getErrorManager`, `getFilter`, `getFormatter`, `getLevel`, `reportError`, `setErrorManager`, `setFilter`, `setFormatter`, `setLevel`

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Detail

ConsoleHandler

`public ConsoleHandler()`

Create a `ConsoleHandler` for `System.err`.

The `ConsoleHandler` is configured based on `LogManager` properties (or their default values).

Method Detail

publish

`public void publish(LogRecord record)`

Publish a `LogRecord`.

The logging request was made initially to a `Logger` object, which initialized the `LogRecord` and forwarded it here.

Overrides:

`publish` in class `StreamHandler`

Parameters:

`record - description of the log event. A null record is silently ignored and is not published`

close

`public void close()`

Override `StreamHandler.close` to do a flush but not to close the output stream. That is, we do **not** close `System.err`.

Overrides:

```
close in class StreamHandler
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.