JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.logging

Class Formatter

java.lang.Object
    java.util.logging.Formatter

Direct Known Subclasses:

SimpleFormatter, XMLFormatter

```
public abstract class Formatter
extends Object
```

A Formatter provides support for formatting LogRecords.

Typically each logging Handler will have a Formatter associated with it. The Formatter takes a LogRecord and converts it to a string.

Some formatters (such as the XMLFormatter) need to wrap head and tail strings around a set of formatted records. The getHeader and getTail methods can be used to obtain these strings.

Since:

1.4

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**Formatter**()	Construct a new formatter.

Method Summary

Abstract Methods | Concrete Methods

Modifier and Type	Method	Description
abstract String	format(LogRecord record)	Format the given log record and return the formatted string.
String	formatMessage(LogRecord record)	Localize and format the message string from a log record.
String	getHead(Handler h)	Return the header string for a set of formatted records.
String	getTail(Handler h)	Return the tail string for a set of formatted records.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

Formatter

```
protected Formatter()
```

Construct a new formatter.

Method Detail

format

```
public abstract String format(LogRecord record)
```

Format the given log record and return the formatted string.

The resulting formatted String will normally include a localized and formatted version of the LogRecord's message field. It is recommended to use the `formatMessage(java.util.logging.LogRecord)` convenience method to localize and format the message field.

Parameters:

`record - the log record to be formatted.`

Returns:

`the formatted log record`

getHead

```
public String getHead(Handler h)
```

Return the header string for a set of formatted records.

This base class returns an empty string, but this may be overridden by subclasses.

Parameters:

`h - The target handler (can be null)`

Returns:

`header string`

getTail

```
public String getTail(Handler h)
```

Return the tail string for a set of formatted records.

This base class returns an empty string, but this may be overridden by subclasses.

Parameters:

`h - The target handler (can be null)`

Returns:

`tail string`

formatMessage

```
public String formatMessage(LogRecord record)
```

Localize and format the message string from a log record. This method is provided as a convenience for Formatter subclasses to use when they are performing formatting.

The message string is first localized to a format string using the record's ResourceBundle. (If there is no ResourceBundle, or if the message key is not found, then the key is used as the format string.) The format String uses java.text style formatting.

- If there are no parameters, no formatter is used.
- Otherwise, if the string contains "{0" then java.text.MessageFormat is used to format the string.
- Otherwise no formatting is performed.

Parameters:

`record - the log record containing the raw message`

Returns:

`a localized and formatted message`

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.