JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.logging

Class SimpleFormatter

java.lang.Object
    java.util.logging.Formatter
        java.util.logging.SimpleFormatter

```
public class SimpleFormatter
extends Formatter
```

Print a brief summary of the `LogRecord` in a human readable format. The summary will typically be 1 or 2 lines.

Configuration: The `SimpleFormatter` is initialized with the format string specified in the `java.util.logging.SimpleFormatter.format` property to format the log messages. This property can be defined in the logging properties configuration file or as a system property. If this property is set in both the logging properties and system properties, the format string specified in the system property will be used. If this property is not defined or the given format string is illegal, the default format is implementation-specific.

Since:

1.4

See Also:

`Formatter`

Constructor Summary

Constructors

Constructor	Description

Constructor
SimpleFormatter()

Method Summary

Concrete Methods

Modifier and Type	Method	Description
String	format(LogRecord record)	Format the given LogRecord.

Methods inherited from class java.util.logging.Formatter

formatMessage, getHead, getTail

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

SimpleFormatter

```
public SimpleFormatter()
```

Method Detail

format

```
public String format(LogRecord record)
```

Format the given LogRecord.

The formatting can be customized by specifying the format string in the java.util.logging.SimpleFormatter.format property. The given LogRecord will be formatted as if by calling:

```
String.format(format, date, source, logger, level, message, thrown);
```

where the arguments are:

1. `format` - the `java.util.Formatter` format string specified in the `java.util.logging.SimpleFormatter.format` property or the default format.
2. `date` - a `Date` object representing event time of the log record.
3. `source` - a string representing the caller, if available; otherwise, the logger's name.
4. `logger` - the logger's name.
5. `level` - the log level.
6. `message` - the formatted log message returned from the `Formatter.formatMessage(LogRecord)` method. It uses `java.text` formatting and does not use the `java.util.Formatter format` argument.
7. `thrown` - a string representing the throwable associated with the log record and its backtrace beginning with a newline character, if any; otherwise, an empty string.

Some example formats:

- `java.util.logging.SimpleFormatter.format="%4$s: %5$s [%1$tc] %n"`

  This prints 1 line with the log level (4$), the log message (5$) and the timestamp (1$) in a square bracket.

  ```
  WARNING: warning message [Tue Mar 22 13:11:31 PDT 2011]
  ```

- `java.util.logging.SimpleFormatter.format="%1$tc %2$s%n%4$s: %5$s%6$s%n"`

  This prints 2 lines where the first line includes the timestamp (1$) and the source (2$); the second line includes the log level (4$) and the log message (5$) followed with the throwable and its backtrace (6$), if any:

  ```
  Tue Mar 22 13:11:31 PDT 2011 MyClass fatal
  SEVERE: several message with an exception
  java.lang.IllegalArgumentException: invalid argument
          at MyClass.mash(MyClass.java:9)
          at MyClass.crunch(MyClass.java:6)
          at MyClass.main(MyClass.java:3)
  ```

- `java.util.logging.SimpleFormatter.format="%1$tb %1$td, %1$tY %1$tl:%1$tM:%1$tS %1$Tp %2$s%n%4$s: %5$s%n"`

  This prints 2 lines similar to the example above with a different date/time formatting and does not print the throwable and its backtrace:

```
Mar 22, 2011 1:11:31 PM MyClass fatal
SEVERE: several message with an exception
```

This method can also be overridden in a subclass. It is recommended to use the `Formatter.formatMessage(java.util.logging.LogRecord)` convenience method to localize and format the message field.

Specified by:

`format` in class `Formatter`

Parameters:

`record - the log record to be formatted.`

Returns:

`a formatted log record`

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.