JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.logging

Class XMLFormatter

java.lang.Object
    java.util.logging.Formatter
        java.util.logging.XMLFormatter

```
public class XMLFormatter
extends Formatter
```

Format a LogRecord into a standard XML format.

The DTD specification is provided as Appendix A to the Java Logging APIs specification.

The XMLFormatter can be used with arbitrary character encodings, but it is recommended that it normally be used with UTF-8. The character encoding can be set on the output Handler.

Since:

1.4

Constructor Summary

Constructors

Constructor	Description
`XMLFormatter()`	

Method Summary

Concrete Methods

Modifier and Type	Method	Description
String	format(LogRecord record)	Format the given message to XML.
String	getHead(Handler h)	Return the header string for a set of XML formatted records.
String	getTail(Handler h)	Return the tail string for a set of XML formatted records.

Methods inherited from class java.util.logging.Formatter

formatMessage

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

XMLFormatter

```
public XMLFormatter()
```

Method Detail

format

```
public String format(LogRecord record)
```

Format the given message to XML.

This method can be overridden in a subclass. It is recommended to use the Formatter.formatMessage(java.util.logging.LogRecord) convenience method to localize and format the message field.

Specified by:

format in class Formatter

Parameters:

record - the log record to be formatted.

Returns:

a formatted log record

getHead

```
public String getHead(Handler h)
```

Return the header string for a set of XML formatted records.

Overrides:

getHead in class Formatter

Parameters:

h - The target handler (can be null)

Returns:

a valid XML string

getTail

```
public String getTail(Handler h)
```

Return the tail string for a set of XML formatted records.

Overrides:

getTail in class Formatter

Parameters:

h - The target handler (can be null)

Returns:

a valid XML string

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.