JavaScript is disabled on your browser.

compact3

java.util.prefs

Class PreferenceChangeEvent

java.lang.Object
    java.util.EventObject
        java.util.prefs.PreferenceChangeEvent

All Implemented Interfaces:

Serializable

```
public class PreferenceChangeEvent
extends EventObject
```

An event emitted by a `Preferences` node to indicate that a preference has been added, removed or has had its value changed.

Note, that although PreferenceChangeEvent inherits Serializable interface from EventObject, it is not intended to be Serializable. Appropriate serialization methods are implemented to throw NotSerializableException.

Since:

1.4

See Also:

Preferences, PreferenceChangeListener, NodeChangeEvent

Field Summary

Fields inherited from class java.util.EventObject

source

Constructor Summary

Constructors

Constructor	Description
`PreferenceChangeEvent(Preferences node, String key, String newValue)`	Constructs a PreferenceC instance.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`String`	`getKey()`	Returns the key of the preference that was changed.
`String`	`getNewValue()`	Returns the new value for the preference.
`Preferences`	`getNode()`	Returns the preference node that emitted the event.

Methods inherited from class java.util.EventObject

`getSource`, `toString`

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Detail

PreferenceChangeEvent

```
public PreferenceChangeEvent(Preferences node,
                             String key,
                             String newValue)
```

Constructs a new `PreferenceChangeEvent` instance.

Parameters:

node - The Preferences node that emitted the event.

key - The key of the preference that was changed.

newValue - The new value of the preference, or null if the preference is being removed.

Method Detail

getNode

```
public Preferences getNode()
```

Returns the preference node that emitted the event.

Returns:

The preference node that emitted the event.

getKey

```
public String getKey()
```

Returns the key of the preference that was changed.

Returns:

The key of the preference that was changed.

getNewValue

```
public String getNewValue()
```

Returns the new value for the preference.

Returns:

The new value for the preference, or null if the preference was removed.

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.