JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.spi

Class CalendarDataProvider

java.lang.Object
    java.util.spi.LocaleServiceProvider
        java.util.spi.CalendarDataProvider

```
public abstract class CalendarDataProvider
extends LocaleServiceProvider
```

An abstract class for service providers that provide locale-dependent `Calendar` parameters.

Since:

1.8

See Also:

`CalendarNameProvider`

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**CalendarDataProvider**()	Sole constructor.

Method Summary

Abstract Methods

Modifier and Type	Method	Description

abstract int	**getFirstDayOfWeek**(**Locale** locale)	Returns the first day of a week in the given `locale`.
abstract int	**getMinimalDaysInFirstWeek**(**Locale** locale)	Returns the minimal number of days required in the first week of a year.

Methods inherited from class java.util.spi.LocaleServiceProvider

`getAvailableLocales`, `isSupportedLocale`

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Detail

CalendarDataProvider

```
protected CalendarDataProvider()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Detail

getFirstDayOfWeek

```
public abstract int getFirstDayOfWeek(Locale locale)
```

Returns the first day of a week in the given `locale`. This information is required by `Calendar` to support operations on the week-related calendar fields.

Parameters:

`locale - the desired locale`

Returns:

`the first day of a week; one of Calendar.SUNDAY .. Calendar.SATURDAY, or 0 if the value isn't available for the locale`

Throws:

`NullPointerException - if locale is null.`

See Also:

`Calendar.getFirstDayOfWeek(), First Week`

getMinimalDaysInFirstWeek

```
public abstract int getMinimalDaysInFirstWeek(Locale locale)
```

Returns the minimal number of days required in the first week of a year. This information is required by `Calendar` to determine the first week of a year. Refer to the description of how `Calendar` determines the first week.

Parameters:

`locale - the desired locale`

Returns:

`the minimal number of days of the first week, or 0 if the value isn't available for the locale`

Throws:

`NullPointerException - if locale is null.`

See Also:

```
Calendar.getMinimalDaysInFirstWeek()
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.