JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.spi

Class CurrencyNameProvider

java.lang.Object
    java.util.spi.LocaleServiceProvider
        java.util.spi.CurrencyNameProvider

```
public abstract class CurrencyNameProvider
extends LocaleServiceProvider
```

An abstract class for service providers that provide localized currency symbols and display names for the `Currency` class. Note that currency symbols are considered names when determining behaviors described in the `LocaleServiceProvider` specification.

Since:

1.6

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	`CurrencyNameProvider()`	Sole constructor.

Method Summary

Abstract Methods **Concrete Methods**

Modifier and Type	Method	Description

String	getDisplayName(String currencyCode, Locale locale)	Returns a name for the currency that is appropriate for display to the user.
abstract String	getSymbol(String currencyCode, Locale locale)	Gets the symbol of the given currency code for the specified locale.

Methods inherited from class java.util.spi.LocaleServiceProvider

getAvailableLocales, isSupportedLocale

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

CurrencyNameProvider

```
protected CurrencyNameProvider()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Detail

getSymbol

```
public abstract String getSymbol(String currencyCode,
                                 Locale locale)
```

Gets the symbol of the given currency code for the specified locale. For example, for "USD" (US Dollar), the symbol is "$" if the specified locale is the

US, while for other locales it may be "US$". If no symbol can be determined, null should be returned.

Parameters:

currencyCode - the ISO 4217 currency code, which consists of three upper-case letters between 'A' (U+0041) and 'Z' (U+005A)

locale - the desired locale

Returns:

the symbol of the given currency code for the specified locale, or null if the symbol is not available for the locale

Throws:

NullPointerException - if currencyCode or locale is null

IllegalArgumentException - if currencyCode is not in the form of three upper-case letters, or locale isn't one of the locales returned from getAvailableLocales().

See Also:

Currency.getSymbol(java.util.Locale)

getDisplayName

```
public String getDisplayName(String currencyCode,
                             Locale locale)
```

Returns a name for the currency that is appropriate for display to the user. The default implementation returns null.

Parameters:

currencyCode - the ISO 4217 currency code, which consists of three upper-case letters between 'A' (U+0041) and 'Z' (U+005A)

locale - the desired locale

Returns:

the name for the currency that is appropriate for display to the user, or null if the name is not available for the locale

Throws:

IllegalArgumentException - if currencyCode is not in the form of three upper-case letters, or locale isn't one of the locales returned from getAvailableLocales().

NullPointerException - if currencyCode or locale is null

Since:

1.7

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.