JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.spi

Class TimeZoneNameProvider

java.lang.Object
    java.util.spi.LocaleServiceProvider
        java.util.spi.TimeZoneNameProvider

```
public abstract class TimeZoneNameProvider
extends LocaleServiceProvider
```

An abstract class for service providers that provide localized time zone names for the `TimeZone` class. The localized time zone names available from the implementations of this class are also the source for the `DateFormatSymbols.getZoneStrings()` method.

Since:

1.6

Constructor Summary

Constructors

Modifier	Constructor	Description
protected	**TimeZoneNameProvider**()	Sole constructor.

Method Summary

Abstract Methods | **Concrete Methods**

Modifier and Type	Method	Description

abstract String	getDisplayName(String ID, boolean daylight, int style, Locale locale)	Returns a name for the given time zone ID that's suitable for presentation to the user in the specified locale.
String	getGenericDisplayName(String ID, int style, Locale locale)	Returns a generic name for the given time zone ID that's suitable for presentation to the user in the specified locale.

Methods inherited from class java.util.spi.LocaleServiceProvider

getAvailableLocales, isSupportedLocale

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

TimeZoneNameProvider

```
protected TimeZoneNameProvider()
```

Sole constructor. (For invocation by subclass constructors, typically implicit.)

Method Detail

getDisplayName

```
public abstract String getDisplayName(String ID,
                                      boolean daylight,
```

```
                                    int style,
                                    Locale locale)
```

Returns a name for the given time zone ID that's suitable for presentation to the user in the specified locale. The given time zone ID is "GMT" or one of the names defined using "Zone" entries in the "tz database", a public domain time zone database at ftp://elsie.nci.nih.gov/pub/. The data of this database is contained in a file whose name starts with "tzdata", and the specification of the data format is part of the zic.8 man page, which is contained in a file whose name starts with "tzcode".

If `daylight` is true, the method should return a name appropriate for daylight saving time even if the specified time zone has not observed daylight saving time in the past.

Parameters:

`ID - a time zone ID string`

`daylight - if true, return the daylight saving name.`

`style - either TimeZone.LONG or TimeZone.SHORT`

`locale - the desired locale`

Returns:

`the human-readable name of the given time zone in the given locale, or null if it's not available.`

Throws:

`IllegalArgumentException - if style is invalid, or locale isn't one of the locales returned from getAvailableLocales().`

`NullPointerException - if ID or locale is null`

See Also:

`TimeZone.getDisplayName(boolean, int, java.util.Locale)`

getGenericDisplayName

```
public String getGenericDisplayName(String ID,
                                     int style,
                                     Locale locale)
```

Returns a generic name for the given time zone `ID` that's suitable for presentation to the user in the specified `locale`. Generic time zone names are neutral from standard time and daylight saving time. For example, "PT" is the short generic name of time zone ID `America/Los_Angeles`, while its short standard time and daylight saving time names are "PST" and "PDT", respectively. Refer to `getDisplayName` for valid time zone IDs.

The default implementation of this method returns `null`.

Parameters:

`ID - a time zone ID string`

`style - either TimeZone.LONG or TimeZone.SHORT`

`locale - the desired locale`

Returns:

`the human-readable generic name of the given time zone in the given locale, or null if it's not available.`

Throws:

`IllegalArgumentException - if style is invalid, or locale isn't one of the locales returned from getAvailableLocales().`

`NullPointerException - if ID or locale is null`

Since:

`1.8`

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.