JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.zip

Class Adler32

java.lang.Object
    java.util.zip.Adler32

All Implemented Interfaces:

Checksum

```
public class Adler32
extends Object
implements Checksum
```

A class that can be used to compute the Adler-32 checksum of a data stream. An Adler-32 checksum is almost as reliable as a CRC-32 but can be computed much faster.

Passing a `null` argument to a method in this class will cause a `NullPointerException` to be thrown.

See Also:

Checksum

Constructor Summary

Constructors

Constructor	Description
`Adler32()`	Creates a new Adler32 object.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
long	**getValue**()	Returns the checksum value.
void	**reset**()	Resets the checksum to initial value.
void	**update**(byte[] b)	Updates the checksum with the specified array of bytes.
void	**update**(byte[] b, int off, int len)	Updates the checksum with the specified array of bytes.
void	**update**(**ByteBuffer** buffer)	Updates the checksum with the bytes from the specified buffer.
void	**update**(int b)	Updates the checksum with the specified byte (the low eight bits of the argument b).

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

Adler32

```
public Adler32()
```

Creates a new Adler32 object.

Method Detail

update

```
public void update(int b)
```

Updates the checksum with the specified byte (the low eight bits of the argument b).

Specified by:

`update` in interface `Checksum`

Parameters:

`b - the byte to update the checksum with`

update

```
public void update(byte[] b,
                   int off,
                   int len)
```

Updates the checksum with the specified array of bytes.

Specified by:

`update` in interface `Checksum`

Parameters:

`b - the byte array to update the checksum with`

`off - the start offset of the data`

`len - the number of bytes to use for the update`

Throws:

`ArrayIndexOutOfBoundsException - if off is negative, or len is negative, or off+len is greater than the length of the array b`

update

```
public void update(byte[] b)
```

Updates the checksum with the specified array of bytes.

Parameters:

`b - the byte array to update the checksum with`

update

```
public void update(ByteBuffer buffer)
```

Updates the checksum with the bytes from the specified buffer. The checksum is updated using buffer.`remaining()` bytes starting at buffer.`position()` Upon return, the buffer's position will be updated to its limit; its limit will not have been changed.

Parameters:

`buffer - the ByteBuffer to update the checksum with`

Since:

`1.8`

reset

```
public void reset()
```

Resets the checksum to initial value.

Specified by:

`reset` in interface `Checksum`

getValue

```
public long getValue()
```

Returns the checksum value.

Specified by:

`getValue` in interface `Checksum`

Returns:

```
the current checksum value
```


Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.