JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.zip

Class CheckedInputStream

java.lang.Object
    java.io.InputStream
        java.io.FilterInputStream
            java.util.zip.CheckedInputStream

All Implemented Interfaces:

`Closeable, AutoCloseable`

```
public class CheckedInputStream
extends FilterInputStream
```

An input stream that also maintains a checksum of the data being read. The checksum can then be used to verify the integrity of the input data.

See Also:

`Checksum`

Field Summary

Fields inherited from class java.io.FilterInputStream

`in`

Constructor Summary

Constructors

Constructor	Description

`CheckedInputStream(InputStream in, Checksum cksum)`	Creates an input stream using the specified Checksum.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
`Checksum`	`getChecksum()`	Returns the Checksum for this input stream.
`int`	`read()`	Reads a byte.
`int`	`read(byte[] buf, int off, int len)`	Reads into an array of bytes.
`long`	`skip(long n)`	Skips specified number of bytes of input.

Methods inherited from class java.io.FilterInputStream

`available`, `close`, `mark`, `markSupported`, `read`, `reset`

Methods inherited from class java.lang.Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructor Detail

CheckedInputStream

```
public CheckedInputStream(InputStream in,
                          Checksum cksum)
```

Creates an input stream using the specified Checksum.

Parameters:

`in - the input stream`

`cksum - the Checksum`

Method Detail

read

```
public int read()
         throws IOException
```

Reads a byte. Will block if no input is available.

Overrides:

`read` in class `FilterInputStream`

Returns:

`the byte read, or -1 if the end of the stream is reached.`

Throws:

`IOException - if an I/O error has occurred`

See Also:

`FilterInputStream.in`

read

```
public int read(byte[] buf,
                int off,
                int len)
         throws IOException
```

Reads into an array of bytes. If `len` is not zero, the method blocks until some input is available; otherwise, no bytes are read and `0` is returned.

Overrides:

`read` in class `FilterInputStream`

Parameters:

buf - the buffer into which the data is read

off - the start offset in the destination array b

len - the maximum number of bytes read

Returns:

the actual number of bytes read, or -1 if the end of the stream is reached.

Throws:

NullPointerException - If buf is null.

IndexOutOfBoundsException - If off is negative, len is negative, or len is greater than buf.length - off

IOException - if an I/O error has occurred

See Also:

FilterInputStream.in

skip

```
public long skip(long n)
          throws IOException
```

Skips specified number of bytes of input.

Overrides:

skip in class FilterInputStream

Parameters:

n - the number of bytes to skip

Returns:

the actual number of bytes skipped

Throws:

IOException - if an I/O error has occurred

getChecksum

```
public Checksum getChecksum()
```

Returns the Checksum for this input stream.

Returns:

the Checksum value

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.