JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.zip

Class DeflaterInputStream

java.lang.Object
    java.io.InputStream
        java.io.FilterInputStream
            java.util.zip.DeflaterInputStream

All Implemented Interfaces:

`Closeable`, `AutoCloseable`

```
public class DeflaterInputStream
extends FilterInputStream
```

Implements an input stream filter for compressing data in the "deflate" compression format.

Since:

1.6

See Also:

`DeflaterOutputStream`, `InflaterOutputStream`, `InflaterInputStream`

Field Summary

Fields

Modifier and Type	Field	Description
`protected byte[]`	**`buf`**	Input buffer for reading compressed data.
`protected Deflater`	**`def`**	Compressor for this stream.

Fields inherited from class java.io.FilterInputStream

`in`

Constructor Summary

Constructors

Constructor	Description
`DeflaterInputStream(InputStream in)`	Creates a new input stream with a default compressor and buffer size.
`DeflaterInputStream(InputStream in, Deflater defl)`	Creates a new input stream with the specified compressor and a default buffer size.
`DeflaterInputStream(InputStream in, Deflater defl, int bufLen)`	Creates a new input stream with the specified compressor and buffer size.

Method Summary

Concrete Methods

Modifier and Type	Method	Description

int	**available**()	Returns 0 after EOF has been reached, otherwise always return 1.
void	**close**()	Closes this input stream and its underlying input stream, discarding any pending uncompressed data.
void	**mark**(int limit)	*This operation is not supported*.
boolean	**markSupported**()	Always returns `false` because this input stream does not support the **mark()** and **reset()** methods.
int	**read**()	Reads a single byte of compressed data from the input stream.
int	**read**(byte[] b, int off, int len)	Reads compressed data into a byte array.
void	**reset**()	*This operation is not supported*.
long	**skip**(long n)	Skips over and discards data from the input stream.

Methods inherited from class java.io.FilterInputStream

read

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Detail

def

```
protected final Deflater def
```

Compressor for this stream.

buf

```
protected final byte[] buf
```

Input buffer for reading compressed data.

Constructor Detail

DeflaterInputStream

```
public DeflaterInputStream(InputStream in)
```

Creates a new input stream with a default compressor and buffer size.

Parameters:

`in - input stream to read the uncompressed data to`

Throws:

`NullPointerException - if in is null`

DeflaterInputStream

```
public DeflaterInputStream(InputStream in,
                           Deflater defl)
```

Creates a new input stream with the specified compressor and a default buffer size.

Parameters:

`in - input stream to read the uncompressed data to`

`defl - compressor ("deflater") for this stream`

Throws:

`NullPointerException - if in or defl is null`

DeflaterInputStream

```
public DeflaterInputStream(InputStream in,
                           Deflater defl,
                           int bufLen)
```

Creates a new input stream with the specified compressor and buffer size.

Parameters:

`in - input stream to read the uncompressed data to`

`defl - compressor ("deflater") for this stream`

`bufLen - compression buffer size`

Throws:

IllegalArgumentException - if bufLen <= 0

NullPointerException - if in or defl is null

Method Detail

close

```
public void close()
           throws IOException
```

Closes this input stream and its underlying input stream, discarding any pending uncompressed data.

Specified by:

close in interface Closeable

Specified by:

close in interface AutoCloseable

Overrides:

close in class FilterInputStream

Throws:

IOException - if an I/O error occurs

See Also:

FilterInputStream.in

read

```
public int read()
         throws IOException
```

Reads a single byte of compressed data from the input stream. This method will block until some input can be read and compressed.

Overrides:

read in class FilterInputStream

Returns:

a single byte of compressed data, or -1 if the end of the uncompressed input stream is reached

Throws:

IOException - if an I/O error occurs or if this stream is already closed

See Also:

FilterInputStream.in

read

```
public int read(byte[] b,
                int off,
                int len)
         throws IOException
```

Reads compressed data into a byte array. This method will block until some input can be read and compressed.

Overrides:

read in class FilterInputStream

Parameters:

b - buffer into which the data is read

off - starting offset of the data within b

len - maximum number of compressed bytes to read into b

Returns:

the actual number of bytes read, or -1 if the end of the uncompressed input stream is reached

Throws:

IndexOutOfBoundsException - if len > b.length - off

IOException - if an I/O error occurs or if this input stream is already closed

See Also:

FilterInputStream.in

skip

```
public long skip(long n)
          throws IOException
```

Skips over and discards data from the input stream. This method may block until the specified number of bytes are read and skipped. *Note:* While n is given as a long, the maximum number of bytes which can be skipped is Integer.MAX_VALUE.

Overrides:

skip in class FilterInputStream

Parameters:

n - number of bytes to be skipped

Returns:

the actual number of bytes skipped

Throws:

IOException - if an I/O error occurs or if this stream is already closed

available

```
public int available()
              throws IOException
```

Returns 0 after EOF has been reached, otherwise always return 1.

Programs should not count on this method to return the actual number of bytes that could be read without blocking

Overrides:

available in class FilterInputStream

Returns:

zero after the end of the underlying input stream has been reached, otherwise always returns 1

Throws:

IOException - if an I/O error occurs or if this stream is already closed

markSupported

```
public boolean markSupported()
```

Always returns false because this input stream does not support the mark() and reset() methods.

Overrides:

markSupported in class FilterInputStream

Returns:

false, always

See Also:

FilterInputStream.in, InputStream.mark(int), InputStream.reset()

mark

```
public void mark(int limit)
```

This operation is not supported.

Overrides:

`mark` in class `FilterInputStream`

Parameters:

`limit` - maximum bytes that can be read before invalidating the position marker

See Also:

`FilterInputStream.in`, `FilterInputStream.reset()`

reset

```
public void reset()
           throws IOException
```

This operation is not supported.

Overrides:

`reset` in class `FilterInputStream`

Throws:

`IOException` - always thrown

See Also:

`FilterInputStream.in`, `FilterInputStream.mark(int)`

Submit a bug or feature

For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.