JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.zip

Class ZipEntry

java.lang.Object
    java.util.zip.ZipEntry

All Implemented Interfaces:

Cloneable

Direct Known Subclasses:

JarEntry

```
public class ZipEntry
extends Object
implements Cloneable
```

This class is used to represent a ZIP file entry.

Field Summary

Fields

Modifier and Type	Field	Description
static int	CENATT	
static int	CENATX	
static int	CENCOM	
static int	CENCRC	
static int	CENDSK	
static int	CENEXT	

static int	**CENFLG**	
static int	**CENHDR**	
static int	**CENHOW**	
static int	**CENLEN**	
static int	**CENNAM**	
static int	**CENOFF**	
static long	**CENSIG**	
static int	**CENSIZ**	
static int	**CENTIM**	
static int	**CENVEM**	
static int	**CENVER**	
static int	**DEFLATED**	Compression method for compressed (deflated) entries.
static int	**ENDCOM**	
static int	**ENDHDR**	
static int	**ENDOFF**	
static long	**ENDSIG**	
static int	**ENDSIZ**	
static int	**ENDSUB**	
static int	**ENDTOT**	
static int	**EXTCRC**	
static int	**EXTHDR**	
static int	**EXTLEN**	
static long	**EXTSIG**	
static int	**EXTSIZ**	
static int	**LOCCRC**	
static int	**LOCEXT**	
static int	**LOCFLG**	
static int	**LOCHDR**	
static int	**LOCHOW**	

static int	LOCLEN	
static int	LOCNAM	
static long	LOCSIG	
static int	LOCSIZ	
static int	LOCTIM	
static int	LOCVER	
static int	STORED	Compression method for uncompressed entries.

Constructor Summary

Constructors

Constructor	Description
ZipEntry(String name)	Creates a new zip entry with the specified name.
ZipEntry(ZipEntry e)	Creates a new zip entry with fields taken from the specified zip entry.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
Object	clone()	Returns a copy of this entry.
String	getComment()	Returns the comment string for the entry.
long	getCompressedSize()	Returns the size of the compressed entry data.
long	getCrc()	Returns the CRC-32

		checksum of the uncompressed entry data.
FileTime	**getCreationTime**()	Returns the creation time of the entry.
byte[]	**getExtra**()	Returns the extra field data for the entry.
FileTime	**getLastAccessTime**()	Returns the last access time of the entry.
FileTime	**getLastModifiedTime**()	Returns the last modification time of the entry.
int	**getMethod**()	Returns the compression method of the entry.
String	**getName**()	Returns the name of the entry.
long	**getSize**()	Returns the uncompressed size of the entry data.
long	**getTime**()	Returns the last modification time of the entry.
int	**hashCode**()	Returns the hash code value for this entry.

boolean	**isDirectory**()	Returns true if this is a directory entry.
void	**setComment**(**String** comment)	Sets the optional comment string for the entry.
void	**setCompressedSize**(long csize)	Sets the size of the compressed entry data.
void	**setCrc**(long crc)	Sets the CRC-32 checksum of the uncompressed entry data.
ZipEntry	**setCreationTime**(**FileTime** time)	Sets the creation time of the entry.
void	**setExtra**(byte[] extra)	Sets the optional extra field data for the entry.
ZipEntry	**setLastAccessTime**(**FileTime** time)	Sets the last access time of the entry.
ZipEntry	**setLastModifiedTime**(**FileTime** time)	Sets the last modification time of the entry.
void	**setMethod**(int method)	Sets the compression method for the entry.
void	**setSize**(long size)	Sets the uncompressed

		size of the entry data.
void	**setTime**(long time)	Sets the last modification time of the entry.
String	**toString**()	Returns a string representation of the ZIP entry.

Methods inherited from class java.lang.Object

equals, finalize, getClass, notify, notifyAll, wait, wait, wait

Field Detail

STORED

public static final int STORED

Compression method for uncompressed entries.

See Also:

Constant Field Values

DEFLATED

public static final int DEFLATED

Compression method for compressed (deflated) entries.

See Also:

Constant Field Values

LOCSIG

public static final long LOCSIG

See Also:

Constant Field Values

EXTSIG

```
public static final long EXTSIG
```

See Also:

Constant Field Values

CENSIG

```
public static final long CENSIG
```

See Also:

Constant Field Values

ENDSIG

```
public static final long ENDSIG
```

See Also:

Constant Field Values

LOCHDR

```
public static final int LOCHDR
```

See Also:

Constant Field Values

EXTHDR

```
public static final int EXTHDR
```

See Also:

Constant Field Values

CENHDR

```
public static final int CENHDR
```

See Also:

Constant Field Values

ENDHDR

```
public static final int ENDHDR
```

See Also:

Constant Field Values

LOCVER

```
public static final int LOCVER
```

See Also:

Constant Field Values

LOCFLG

```
public static final int LOCFLG
```

See Also:

Constant Field Values

LOCHOW

```
public static final int LOCHOW
```

See Also:

Constant Field Values

LOCTIM

```
public static final int LOCTIM
```

See Also:

Constant Field Values

LOCCRC

```
public static final int LOCCRC
```

See Also:

Constant Field Values

LOCSIZ

public static final int LOCSIZ

See Also:

Constant Field Values

LOCLEN

public static final int LOCLEN

See Also:

Constant Field Values

LOCNAM

public static final int LOCNAM

See Also:

Constant Field Values

LOCEXT

public static final int LOCEXT

See Also:

Constant Field Values

EXTCRC

public static final int EXTCRC

See Also:

Constant Field Values

EXTSIZ

public static final int EXTSIZ

See Also:

Constant Field Values

EXTLEN

public static final int EXTLEN

See Also:

Constant Field Values

CENVEM

public static final int CENVEM

See Also:

Constant Field Values

CENVER

public static final int CENVER

See Also:

Constant Field Values

CENFLG

public static final int CENFLG

See Also:

Constant Field Values

CENHOW

public static final int CENHOW

See Also:

Constant Field Values

CENTIM

public static final int CENTIM

See Also:

Constant Field Values

CENCRC

```
public static final int CENCRC
```

See Also:

Constant Field Values

CENSIZ

```
public static final int CENSIZ
```

See Also:

Constant Field Values

CENLEN

```
public static final int CENLEN
```

See Also:

Constant Field Values

CENNAM

```
public static final int CENNAM
```

See Also:

Constant Field Values

CENEXT

```
public static final int CENEXT
```

See Also:

Constant Field Values

CENCOM

```
public static final int CENCOM
```

See Also:

Constant Field Values

CENDSK

public static final int CENDSK

See Also:

Constant Field Values

CENATT

public static final int CENATT

See Also:

Constant Field Values

CENATX

public static final int CENATX

See Also:

Constant Field Values

CENOFF

public static final int CENOFF

See Also:

Constant Field Values

ENDSUB

public static final int ENDSUB

See Also:

Constant Field Values

ENDTOT

public static final int ENDTOT

See Also:

Constant Field Values

ENDSIZ

public static final int ENDSIZ

See Also:

Constant Field Values

ENDOFF

public static final int ENDOFF

See Also:

Constant Field Values

ENDCOM

public static final int ENDCOM

See Also:

Constant Field Values

Constructor Detail

ZipEntry

public ZipEntry(String name)

Creates a new zip entry with the specified name.

Parameters:

name - The entry name

Throws:

NullPointerException - if the entry name is null

IllegalArgumentException - if the entry name is longer than 0xFFFF bytes

ZipEntry

public ZipEntry(ZipEntry e)

Creates a new zip entry with fields taken from the specified zip entry.

Parameters:

`e - A zip Entry object`

Throws:

`NullPointerException - if the entry object is null`

Method Detail

getName

`public String getName()`

Returns the name of the entry.

Returns:

`the name of the entry`

setTime

`public void setTime(long time)`

Sets the last modification time of the entry.

If the entry is output to a ZIP file or ZIP file formatted output stream the last modification time set by this method will be stored into the `date and time fields` of the zip file entry and encoded in standard `MS-DOS date and time format`. The `default TimeZone` is used to convert the epoch time to the MS-DOS data and time.

Parameters:

`time - The last modification time of the entry in milliseconds since the epoch`

See Also:

`getTime()`, `getLastModifiedTime()`

getTime

`public long getTime()`

Returns the last modification time of the entry.

If the entry is read from a ZIP file or ZIP file formatted input stream, this is the last modification time from the `date and time fields` of the zip file

entry. The default TimeZone is used to convert the standard MS-DOS formatted date and time to the epoch time.

Returns:

The last modification time of the entry in milliseconds since the epoch, or -1 if not specified

See Also:

setTime(long), setLastModifiedTime(FileTime)

setLastModifiedTime

public ZipEntry setLastModifiedTime(FileTime time)

Sets the last modification time of the entry.

When output to a ZIP file or ZIP file formatted output stream the last modification time set by this method will be stored into zip file entry's date and time fields in standard MS-DOS date and time format), and the extended timestamp fields in optional extra data in UTC time.

Parameters:

time - The last modification time of the entry

Returns:

This zip entry

Throws:

NullPointerException - if the time is null

Since:

1.8

See Also:

getLastModifiedTime()

getLastModifiedTime

public FileTime getLastModifiedTime()

Returns the last modification time of the entry.

If the entry is read from a ZIP file or ZIP file formatted input stream, this is the last modification time from the zip file entry's optional extra data if the extended timestamp fields are present. Otherwise the last modification time is read from the entry's date and time fields, the default TimeZone is used to convert the standard MS-DOS formatted date and time to the epoch time.

Returns:

The last modification time of the entry, null if not specified

Since:

1.8

See Also:

setLastModifiedTime(FileTime)

setLastAccessTime

public ZipEntry setLastAccessTime(FileTime time)

Sets the last access time of the entry.

If set, the last access time will be stored into the extended timestamp fields of entry's optional extra data, when output to a ZIP file or ZIP file formatted stream.

Parameters:

time - The last access time of the entry

Returns:

This zip entry

Throws:

NullPointerException - if the time is null

Since:

1.8

See Also:

getLastAccessTime()

getLastAccessTime

```
public FileTime getLastAccessTime()
```

Returns the last access time of the entry.

The last access time is from the extended timestamp fields of entry's `optional extra data` when read from a ZIP file or ZIP file formatted stream.

Returns:

`The last access time of the entry, null if not specified`

Since:

`1.8`

See Also:

`setLastAccessTime(FileTime)`

setCreationTime

```
public ZipEntry setCreationTime(FileTime time)
```

Sets the creation time of the entry.

If set, the creation time will be stored into the extended timestamp fields of entry's `optional extra data`, when output to a ZIP file or ZIP file formatted stream.

Parameters:

`time - The creation time of the entry`

Returns:

`This zip entry`

Throws:

`NullPointerException - if the time is null`

Since:

`1.8`

See Also:

`getCreationTime()`

getCreationTime

```
public FileTime getCreationTime()
```

Returns the creation time of the entry.

The creation time is from the extended timestamp fields of entry's optional extra data when read from a ZIP file or ZIP file formatted stream.

Returns:

the creation time of the entry, null if not specified

Since:

1.8

See Also:

setCreationTime(FileTime)

setSize

```
public void setSize(long size)
```

Sets the uncompressed size of the entry data.

Parameters:

size - the uncompressed size in bytes

Throws:

IllegalArgumentException - if the specified size is less than 0, is greater than 0xFFFFFFFF when ZIP64 format is not supported, or is less than 0 when ZIP64 is supported

See Also:

getSize()

getSize

```
public long getSize()
```

Returns the uncompressed size of the entry data.

Returns:

the uncompressed size of the entry data, or -1 if not known

See Also:

setSize(long)

getCompressedSize

```
public long getCompressedSize()
```

Returns the size of the compressed entry data.

In the case of a stored entry, the compressed size will be the same as the uncompressed size of the entry.

Returns:

`the size of the compressed entry data, or -1 if not known`

See Also:

`setCompressedSize(long)`

setCompressedSize

```
public void setCompressedSize(long csize)
```

Sets the size of the compressed entry data.

Parameters:

`csize - the compressed size to set to`

See Also:

`getCompressedSize()`

setCrc

```
public void setCrc(long crc)
```

Sets the CRC-32 checksum of the uncompressed entry data.

Parameters:

`crc - the CRC-32 value`

Throws:

`IllegalArgumentException - if the specified CRC-32 value is less than 0 or greater than 0xFFFFFFFF`

See Also:

`getCrc()`

getCrc

```
public long getCrc()
```

Returns the CRC-32 checksum of the uncompressed entry data.

Returns:

the CRC-32 checksum of the uncompressed entry data, or -1 if not known

See Also:

setCrc(long)

setMethod

```
public void setMethod(int method)
```

Sets the compression method for the entry.

Parameters:

method - the compression method, either STORED or DEFLATED

Throws:

IllegalArgumentException - if the specified compression method is invalid

See Also:

getMethod()

getMethod

```
public int getMethod()
```

Returns the compression method of the entry.

Returns:

the compression method of the entry, or -1 if not specified

See Also:

setMethod(int)

setExtra

```
public void setExtra(byte[] extra)
```

Sets the optional extra field data for the entry.

Invoking this method may change this entry's last modification time, last access time and creation time, if the `extra` field data includes the extensible timestamp fields, such as `NTFS tag 0x0001` or `Info-ZIP Extended Timestamp`, as specified in Info-ZIP Application Note 970311.

Parameters:

`extra - The extra field data bytes`

Throws:

`IllegalArgumentException - if the length of the specified extra field data is greater than 0xFFFF bytes`

See Also:

`getExtra()`

getExtra

```
public byte[] getExtra()
```

Returns the extra field data for the entry.

Returns:

`the extra field data for the entry, or null if none`

See Also:

`setExtra(byte[])`

setComment

```
public void setComment(String comment)
```

Sets the optional comment string for the entry.

ZIP entry comments have maximum length of 0xffff. If the length of the specified comment string is greater than 0xFFFF bytes after encoding, only the first 0xFFFF bytes are output to the ZIP file entry.

Parameters:

`comment - the comment string`

See Also:

`getComment()`

getComment

```
public String getComment()
```

Returns the comment string for the entry.

Returns:

the comment string for the entry, or null if none

See Also:

setComment(String)

isDirectory

```
public boolean isDirectory()
```

Returns true if this is a directory entry. A directory entry is defined to be one whose name ends with a '/'.

Returns:

true if this is a directory entry

toString

```
public String toString()
```

Returns a string representation of the ZIP entry.

Overrides:

toString in class Object

Returns:

a string representation of the object.

hashCode

```
public int hashCode()
```

Returns the hash code value for this entry.

Overrides:

hashCode in class Object

Returns:

a hash code value for this object.

See Also:

Object.equals(java.lang.Object), System.identityHashCode(java.lang.Object)

clone

```
public Object clone()
```

Returns a copy of this entry.

Overrides:

`clone` in class `Object`

Returns:

a clone of this instance.

See Also:

`Cloneable`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.