JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util.zip

Class ZipInputStream

java.lang.Object
  java.io.InputStream
    java.io.FilterInputStream
      java.util.zip.InflaterInputStream
        java.util.zip.ZipInputStream

All Implemented Interfaces:

`Closeable, AutoCloseable`

Direct Known Subclasses:

`JarInputStream`

```
public class ZipInputStream
extends InflaterInputStream
```

This class implements an input stream filter for reading files in the ZIP file format. Includes support for both compressed and uncompressed entries.

Field Summary

Fields

Modifier and Type	Field	Description
static int	CENATT	
static int	CENATX	
static int	CENCOM	
static int	CENCRC	
static int	CENDSK	

static int	**CENEXT**	
static int	**CENFLG**	
static int	**CENHDR**	
static int	**CENHOW**	
static int	**CENLEN**	
static int	**CENNAM**	
static int	**CENOFF**	
static long	**CENSIG**	
static int	**CENSIZ**	
static int	**CENTIM**	
static int	**CENVEM**	
static int	**CENVER**	
static int	**ENDCOM**	
static int	**ENDHDR**	
static int	**ENDOFF**	
static long	**ENDSIG**	
static int	**ENDSIZ**	
static int	**ENDSUB**	
static int	**ENDTOT**	
static int	**EXTCRC**	
static int	**EXTHDR**	
static int	**EXTLEN**	
static long	**EXTSIG**	
static int	**EXTSIZ**	
static int	**LOCCRC**	
static int	**LOCEXT**	
static int	**LOCFLG**	
static int	**LOCHDR**	
static int	**LOCHOW**	

static int	LOCLEN	
static int	LOCNAM	
static long	LOCSIG	
static int	LOCSIZ	
static int	LOCTIM	
static int	LOCVER	

Fields inherited from class java.util.zip.InflaterInputStream

buf, inf, len

Fields inherited from class java.io.FilterInputStream

in

Constructor Summary

Constructors

Constructor	Description
ZipInputStream(InputStream in)	Creates a new ZIP input stream.
ZipInputStream(InputStream in, Charset charset)	Creates a new ZIP input stream.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
int	available()	Returns 0 after EOF has reached for the current entry data, otherwise always return 1.
void	close()	Closes this input stream and

		releases any system resources associated with the stream.
void	**closeEntry**()	Closes the current ZIP entry and positions the stream for reading the next entry.
protected **ZipEntry**	**createZipEntry**(**String** name)	Creates a new ZipEntry object for the specified entry name.
ZipEntry	**getNextEntry**()	Reads the next ZIP file entry and positions the stream at the beginning of the entry data.
int	**read**(byte[] b, int off, int len)	Reads from the current ZIP entry into an array of bytes.
long	**skip**(long n)	Skips specified number of bytes in the current ZIP entry.

Methods inherited from class java.util.zip.InflaterInputStream

fill, mark, markSupported, read, reset

Methods inherited from class java.io.FilterInputStream

read

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Field Detail

LOCSIG

```
public static final long LOCSIG
```

See Also:

Constant Field Values

EXTSIG

```
public static final long EXTSIG
```

See Also:

Constant Field Values

CENSIG

```
public static final long CENSIG
```

See Also:

Constant Field Values

ENDSIG

```
public static final long ENDSIG
```

See Also:

Constant Field Values

LOCHDR

```
public static final int LOCHDR
```

See Also:

Constant Field Values

EXTHDR

```
public static final int EXTHDR
```

See Also:

Constant Field Values

CENHDR

public static final int CENHDR

See Also:

Constant Field Values

ENDHDR

public static final int ENDHDR

See Also:

Constant Field Values

LOCVER

public static final int LOCVER

See Also:

Constant Field Values

LOCFLG

public static final int LOCFLG

See Also:

Constant Field Values

LOCHOW

public static final int LOCHOW

See Also:

Constant Field Values

LOCTIM

public static final int LOCTIM

See Also:

Constant Field Values

LOCCRC

public static final int LOCCRC

See Also:

Constant Field Values

LOCSIZ

public static final int LOCSIZ

See Also:

Constant Field Values

LOCLEN

public static final int LOCLEN

See Also:

Constant Field Values

LOCNAM

public static final int LOCNAM

See Also:

Constant Field Values

LOCEXT

public static final int LOCEXT

See Also:

Constant Field Values

EXTCRC

public static final int EXTCRC

See Also:

Constant Field Values

EXTSIZ

public static final int EXTSIZ

See Also:

Constant Field Values

EXTLEN

public static final int EXTLEN

See Also:

Constant Field Values

CENVEM

public static final int CENVEM

See Also:

Constant Field Values

CENVER

public static final int CENVER

See Also:

Constant Field Values

CENFLG

public static final int CENFLG

See Also:

Constant Field Values

CENHOW

public static final int CENHOW

See Also:

Constant Field Values

CENTIM

public static final int CENTIM

See Also:

Constant Field Values

CENCRC

public static final int CENCRC

See Also:

Constant Field Values

CENSIZ

public static final int CENSIZ

See Also:

Constant Field Values

CENLEN

public static final int CENLEN

See Also:

Constant Field Values

CENNAM

public static final int CENNAM

See Also:

Constant Field Values

CENEXT

public static final int CENEXT

See Also:

Constant Field Values

CENCOM

public static final int CENCOM

See Also:

Constant Field Values

CENDSK

public static final int CENDSK

See Also:

Constant Field Values

CENATT

public static final int CENATT

See Also:

Constant Field Values

CENATX

public static final int CENATX

See Also:

Constant Field Values

CENOFF

public static final int CENOFF

See Also:

Constant Field Values

ENDSUB

public static final int ENDSUB

See Also:

Constant Field Values

ENDTOT

public static final int ENDTOT

See Also:

Constant Field Values

ENDSIZ

public static final int ENDSIZ

See Also:

Constant Field Values

ENDOFF

public static final int ENDOFF

See Also:

Constant Field Values

ENDCOM

public static final int ENDCOM

See Also:

Constant Field Values

Constructor Detail

ZipInputStream

```
public ZipInputStream(InputStream in)
```

Creates a new ZIP input stream.

The UTF-8 `charset` is used to decode the entry names.

Parameters:

`in - the actual input stream`

ZipInputStream

```
public ZipInputStream(InputStream in,
                      Charset charset)
```

Creates a new ZIP input stream.

Parameters:

`in - the actual input stream`

`charset - The charset to be used to decode the ZIP entry name (ignored if the language encoding bit of the ZIP entry's general purpose bit flag is set).`

Since:

`1.7`

Method Detail

getNextEntry

```
public ZipEntry getNextEntry()
                     throws IOException
```

Reads the next ZIP file entry and positions the stream at the beginning of the entry data.

Returns:

the next ZIP file entry, or null if there are no more entries

Throws:

ZipException - if a ZIP file error has occurred

IOException - if an I/O error has occurred

closeEntry

```
public void closeEntry()
                throws IOException
```

Closes the current ZIP entry and positions the stream for reading the next entry.

Throws:

ZipException - if a ZIP file error has occurred

IOException - if an I/O error has occurred

available

```
public int available()
              throws IOException
```

Returns 0 after EOF has reached for the current entry data, otherwise always return 1.

Programs should not count on this method to return the actual number of bytes that could be read without blocking.

Overrides:

available in class InflaterInputStream

Returns:

1 before EOF and 0 after EOF has reached for current entry.

Throws:

IOException - if an I/O error occurs.

read

```
public int read(byte[] b,
                int off,
                int len)
         throws IOException
```

Reads from the current ZIP entry into an array of bytes. If `len` is not zero, the method blocks until some input is available; otherwise, no bytes are read and `0` is returned.

Overrides:

read in class InflaterInputStream

Parameters:

b - the buffer into which the data is read

off - the start offset in the destination array b

len - the maximum number of bytes read

Returns:

the actual number of bytes read, or -1 if the end of the entry is reached

Throws:

NullPointerException - if b is null.

IndexOutOfBoundsException - if off is negative, len is negative, or len is greater than b.length - off

ZipException - if a ZIP file error has occurred

IOException - if an I/O error has occurred

See Also:

FilterInputStream.in

skip

```
public long skip(long n)
          throws IOException
```

Skips specified number of bytes in the current ZIP entry.

Overrides:

skip in class InflaterInputStream

Parameters:

n - the number of bytes to skip

Returns:

the actual number of bytes skipped

Throws:

ZipException - if a ZIP file error has occurred

IOException - if an I/O error has occurred

IllegalArgumentException - if n < 0

close

```
public void close()
           throws IOException
```

Closes this input stream and releases any system resources associated with the stream.

Specified by:

close in interface Closeable

Specified by:

close in interface AutoCloseable

Overrides:

close in class InflaterInputStream

Throws:

IOException - if an I/O error has occurred

See Also:

FilterInputStream.in

createZipEntry

```
protected ZipEntry createZipEntry(String name)
```

Creates a new ZipEntry object for the specified entry name.

Parameters:

name - the ZIP file entry name

Returns:

C the ZipEntry just created

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.