JavaScript is disabled on your browser.

compact1, compact2, compact3

java.util

Class Stack<E>

java.lang.Object
  java.util.AbstractCollection<E>
    java.util.AbstractList<E>
      java.util.Vector<E>
        java.util.Stack<E>

All Implemented Interfaces:

Serializable, Cloneable, Iterable<E>, Collection<E>, List<E>, RandomAccess

---

```
public class Stack<E>
extends Vector<E>
```

The `Stack` class represents a last-in-first-out (LIFO) stack of objects. It extends class `Vector` with five operations that allow a vector to be treated as a stack. The usual `push` and `pop` operations are provided, as well as a method to `peek` at the top item on the stack, a method to test for whether the stack is `empty`, and a method to `search` the stack for an item and discover how far it is from the top.

When a stack is first created, it contains no items.

A more complete and consistent set of LIFO stack operations is provided by the Deque interface and its implementations, which should be used in preference to this class. For example:

```
   Deque<Integer> stack = new ArrayDeque<Integer>();
```

Since:

JDK1.0

See Also:

Serialized Form

Field Summary

Fields inherited from class java.util.Vector

capacityIncrement, elementCount, elementData

Fields inherited from class java.util.AbstractList

modCount

Constructor Summary

Constructors

Constructor	Description
Stack()	Creates an empty Stack.

Method Summary

Concrete Methods

Modifier and Type	Method	Description
boolean	empty()	Tests if this stack is empty.
E	peek()	Looks at the object at the top of this stack without removing it from the stack.
E	pop()	Removes the object at the top of this stack and returns that object as the value of this function.
E	push(E item)	Pushes an item onto the top of this stack.
int	search(Object o)	Returns the 1-based position where an object is on this stack.

Methods inherited from class java.util.Vector

add, add, addAll, addAll, addElement, capacity, clear, clone, contains, containsAll, copyInto, elementAt, elements, ensureCapacity, equals, firstElement, forEach, get, hashCode, indexOf, indexOf, insertElementAt, isEmpty, iterator, lastElement, lastIndexOf, lastIndexOf, listIterator, listIterator, remove, remove, removeAll, removeAllElements, removeElement, removeElementAt, removeIf, removeRange, replaceAll, retainAll, set, setElementAt, setSize, size, sort, spliterator, subList, toArray, toArray, toString, trimToSize

Methods inherited from class java.lang.Object

finalize, getClass, notify, notifyAll, wait, wait, wait

Methods inherited from interface java.util.Collection

parallelStream, stream

Constructor Detail

Stack

```
public Stack()
```

Creates an empty Stack.

Method Detail

push

```
public E push(E item)
```

Pushes
an item onto the top of this stack. This has exactly the same effect as:

```
addElement(item)
```

Parameters:

`item - the item to be pushed onto this stack.`

Returns:

`the item argument.`

See Also:

`Vector.addElement(E)`

pop

```
public E pop()
```

Removes the object at the top of this stack and returns that object as the value of this function.

Returns:

`The object at the top of this stack (the last item of the Vector object).`

Throws:

`EmptyStackException - if this stack is empty.`

peek

```
public E peek()
```

Looks at the object at the top of this stack without removing it from the stack.

Returns:

`the object at the top of this stack (the last item of the Vector object).`

Throws:

`EmptyStackException - if this stack is empty.`

empty

```
public boolean empty()
```

Tests if this stack is empty.

Returns:

`true if and only if this stack contains no items; false otherwise.`

search

```
public int search(Object o)
```

Returns the 1-based position where an object is on this stack. If the object `o` occurs as an item in this stack, this method returns the distance from the top

of the stack of the occurrence nearest the top of the stack; the topmost item on the stack is considered to be at distance 1. The `equals` method is used to compare `o` to the items in this stack.

Parameters:

`o - the desired object.`

Returns:

`the 1-based position from the top of the stack where the object is located; the return value -1 indicates that the object is not on the stack.`

Submit a bug or feature
For further API reference and developer documentation, see Java SE Documentation. That documentation contains more detailed, developer-targeted descriptions, with conceptual overviews, definitions of terms, workarounds, and working code examples.
Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms.
Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.