JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class Exception

java.lang.Object
    java.lang.Throwable
        java.lang.Exception

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

AbsentInformationException, AgentInitializationException, AgentLoadException, AlreadyBoundException, AttachNotSupportedException, AWTException, BackingStoreException, BadAttributeValueExpException, BadBinaryOpValueExpException, BadLocationException, BadStringOperationException, BrokenBarrierException, CardException, CertificateException, ClassNotLoadedException, CloneNotSupportedException, DataFormatException, DatatypeConfigurationException, DestroyFailedException, ExecutionControl.ExecutionControlException, ExecutionException, ExpandVetoException, FontFormatException, GeneralSecurityException, GSSException, IllegalClassFormatException, IllegalConnectorArgumentsException, IncompatibleThreadStateException, InterruptedException, IntrospectionException, InvalidApplicationException, InvalidMidiDataException, InvalidPreferencesFormatException, InvalidTargetObjectTypeException, InvalidTypeException, InvocationException, IOException, JMException, JShellException, KeySelectorException, LambdaConversionException, LineUnavailableException, MarshalException, MidiUnavailableException, MimeTypeParseException, NamingException, NoninvertibleTransformException, NotBoundException, ParseException, ParserConfigurationException, PrinterException, PrintException, PrivilegedActionException, PropertyVetoException, ReflectiveOperationException, RefreshFailedException, RuntimeException, SAXException, ScriptException, ServerNotActiveException, SQLException, StringConcatException, TimeoutException, TooManyListenersException, TransformerException, TransformException, UnmodifiableClassException, UnsupportedAudioFileException, UnsupportedCallbackException, UnsupportedFlavorException, UnsupportedLookAndFeelException, URIReferenceException, URISyntaxException, VMStartException, XAException, XMLSignatureException, XMLStreamException, XPathException

---

public class **Exception**
extends Throwable

The class `Exception` and its subclasses are a form of `Throwable` that indicates conditions that a reasonable application might want to catch.

The class `Exception` and any subclasses that are not also subclasses of `RuntimeException` are *checked exceptions*. Checked exceptions need to be declared in a method or constructor's `throws` clause if they can be thrown by the execution of the method or constructor and propagate outside the method or constructor boundary.

See *Java Language Specification*:

11.2 Compile-Time Checking of Exceptions

Since:

1.0

See Also:

`Error`, Serialized Form

Constructor Summary

Constructors

Modifier	Constructor	Description
	`Exception``()`	Constructs a new exception with `null` as its detail message.
	`Exception``(String message)`	Constructs a new exception with the specified detail message.
	`Exception``(String message, Throwable cause)`	Constructs a new exception with the specified detail message and cause.
protected	**`Exception`**`(String message, Throwable cause, boolean enableSuppressio boolean writableStackTra`	Constructs a new exception with the specified detail message, cause, suppression enabled or disabled, and writable stack trace enabled or disabled.
	`Exception``(Throwable cause)`	Constructs a new exception with the specified cause and a

	detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`).

Method Summary

Methods declared in class Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Details

Exception

```
public Exception()
```

Constructs a new exception with `null` as its detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(Throwable)`.

Exception

```
public Exception(String message)
```

Constructs a new exception with the specified detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(Throwable)`.

Parameters:

`message` - the detail message. The detail message is saved for later retrieval by the `Throwable.getMessage()` method.

Exception

```
public Exception(String message,
                 Throwable cause)
```

Constructs a new exception with the specified detail message and cause.

Note that the detail message associated with `cause` is *not* automatically incorporated in this exception's detail message.

Parameters:

`message` - the detail message (which is saved for later retrieval by the `Throwable.getMessage()` method).

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

Since:

1.4

Exception

```
public Exception(Throwable cause)
```

Constructs a new exception with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`). This constructor is useful for exceptions that are little more than wrappers for other throwables (for example, `PrivilegedActionException`).

Parameters:

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

Since:

1.4

Exception

```
protected Exception(String message,
                    Throwable cause,
                    boolean enableSuppression,
                    boolean writableStackTrace)
```

Constructs a new exception with the specified detail message, cause, suppression enabled or disabled, and writable stack trace enabled or disabled.

Parameters:

`message` - the detail message.

`cause` - the cause. (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

`enableSuppression` - whether or not suppression is enabled or disabled

`writableStackTrace` - whether or not the stack trace should be writable

Since:

1.7

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.