JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class IllegalArgumentException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.IllegalArgumentException

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

ConstantPoolException, IllegalChannelGroupException, IllegalCharsetNameException, IllegalFormatException, IllegalSelectorException, IllegalThreadStateException, InvalidKeyException, InvalidOpenTypeException, InvalidParameterException, InvalidPathException, InvalidStreamException, KeyAlreadyExistsException, NumberFormatException, PatternSyntaxException, ProviderMismatchException, UnresolvedAddressException, UnsupportedAddressTypeException, UnsupportedCharsetException

---

```
public class IllegalArgumentException
extends RuntimeException
```

Thrown to indicate that a method has been passed an illegal or inappropriate argument.

Since:

1.0

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
`IllegalArgumentException()`	Constructs an `IllegalArgumentException` with no detail message.
`IllegalArgumentException(String s)`	Constructs an `IllegalArgumentException` with the specified detail message.

IllegalArgumentException(String message, Throwable cause)	Constructs a new exception with the specified detail message and cause.
IllegalArgumentException(Throwable cause)	Constructs a new exception with the specified cause and a detail message of (cause==null ? null : cause.toString()) (which typically contains the class and detail message of cause).

Method Summary

Methods declared in class Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Details

IllegalArgumentException

```
public IllegalArgumentException()
```

Constructs an IllegalArgumentException with no detail message.

IllegalArgumentException

```
public IllegalArgumentException(String s)
```

Constructs an IllegalArgumentException with the specified detail message.

Parameters:

s - the detail message.

IllegalArgumentException

```
public IllegalArgumentException(String message,
                                Throwable cause)
```

Constructs a new exception with the specified detail message and cause.

Note that the detail message associated with `cause` is *not* automatically incorporated in this exception's detail message.

Parameters:

`message` - the detail message (which is saved for later retrieval by the `Throwable.getMessage()` method).

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

Since:

1.5

IllegalArgumentException

```
public IllegalArgumentException(Throwable cause)
```

Constructs a new exception with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`). This constructor is useful for exceptions that are little more than wrappers for other throwables (for example, `PrivilegedActionException`).

Parameters:

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

Since:

1.5

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.