JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class IllegalStateException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException
        java.lang.IllegalStateException

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

AcceptPendingException, AlreadyBoundException, AlreadyConnectedException, CancellationException, CancelledKeyException, ClosedDirectoryStreamException, ClosedFileSystemException, ClosedSelectorException, ClosedWatchServiceException, ConnectionPendingException, FormatterClosedException, IllegalBlockingModeException, IllegalComponentStateException, IllegalReceiveException, IllegalUnbindException, InvalidDnDOperationException, InvalidMarkException, NoConnectionPendingException, NonReadableChannelException, NonWritableChannelException, NotYetBoundException, NotYetConnectedException, OverlappingFileLockException, ReadPendingException, ShutdownChannelGroupException, WritePendingException

---

```
public class IllegalStateException
extends RuntimeException
```

Signals that a method has been invoked at an illegal or inappropriate time. In other words, the Java environment or Java application is not in an appropriate state for the requested operation.

Since:

1.1

See Also:

Serialized Form

Constructor Summary

Constructors

Constructor	Description
IllegalStateException()	Constructs an IllegalStateException with no detail message.

IllegalStateException(String s)	Constructs an IllegalStateException with the specified detail message.
IllegalStateException (String message, Throwable cause)	Constructs a new exception with the specified detail message and cause.
IllegalStateException (Throwable cause)	Constructs a new exception with the specified cause and a detail message of (cause==null ? null : cause.toString()) (which typically contains the class and detail message of cause).

Method Summary

Methods declared in class Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods declared in class Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Details

IllegalStateException

```
public IllegalStateException()
```

Constructs an IllegalStateException with no detail message. A detail message is a String that describes this particular exception.

IllegalStateException

```
public IllegalStateException(String s)
```

Constructs an IllegalStateException with the specified detail message. A detail message is a String that describes this particular exception.

Parameters:

s - the String that contains a detailed message

IllegalStateException

```
public IllegalStateException(String message,
                             Throwable cause)
```

Constructs a new exception with the specified detail message and cause.

Note that the detail message associated with `cause` is *not* automatically incorporated in this exception's detail message.

Parameters:

`message` - the detail message (which is saved for later retrieval by the `Throwable.getMessage()` method).

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

Since:

1.5

IllegalStateException

```
public IllegalStateException(Throwable cause)
```

Constructs a new exception with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`). This constructor is useful for exceptions that are little more than wrappers for other throwables (for example, `PrivilegedActionException`).

Parameters:

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

Since:

1.5

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.