JavaScript is disabled on your browser.

Java SE 27 & JDK 27

Class RuntimeException

java.lang.Object
  java.lang.Throwable
    java.lang.Exception
      java.lang.RuntimeException

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

AnnotationTypeMismatchException, ArithmeticException, ArrayStoreException, BufferOverflowException, BufferUnderflowException, CannotRedoException, CannotUndoException, CatalogException, ClassCastException, ClassNotPreparedException, CMMException, CompletionException, ConcurrentModificationException, CryptoException[PREVIEW], DateTimeException, DOMException, DuplicateRequestException, EmptyStackException, EnumConstantNotPresentException, EventException, FileSystemAlreadyExistsException, FileSystemNotFoundException, FindException, IllegalArgumentException, IllegalCallerException, IllegalMonitorStateException, IllegalPathStateException, IllegalStateException, IllformedLocaleException, ImagingOpException, InaccessibleObjectException, IncompleteAnnotationException, InconsistentDebugInfoException, IndexOutOfBoundsException, InternalException, InvalidCodeIndexException, InvalidLineNumberException, InvalidModuleDescriptorException, InvalidModuleException, InvalidRequestStateException, InvalidStackFrameException, JarSignerException, JMRuntimeException, LayerInstantiationException, LSException, MalformedParameterizedTypeException, MalformedParametersException, MatchException, MirroredTypesException, MissingResourceException, NegativeArraySizeException, NoSuchDynamicMethodException, NoSuchElementException, NoSuchMechanismException, NullPointerException, ObjectCollectedException, OpaqueFrameException, ProfileDataException, ProviderException, ProviderNotFoundException, RangeException, RasterFormatException, RejectedExecutionException, ResolutionException, SecurityException, SPIResolutionException, StructuredTaskScope.CancelledByTimeoutException[PREVIEW], StructureViolationException[PREVIEW], TypeNotPresentException, UncheckedIOException, UndeclaredThrowableException, UnknownEntityException, UnmodifiableModuleException, UnmodifiableSetException, UnsupportedOperationException, VMDisconnectedException, VMMismatchException,

VMOutOfMemoryException, WrongMethodTypeException, WrongThreadException, XPathException

---

```
public class RuntimeException
extends Exception
```

RuntimeException is the superclass of those exceptions that can be thrown during the normal operation of the Java Virtual Machine.

RuntimeException and its subclasses are *unchecked exceptions*. Unchecked exceptions do *not* need to be declared in a method or constructor's throws clause if they can be thrown by the execution of the method or constructor and propagate outside the method or constructor boundary.

See *Java Language Specification*:

11.2 Compile-Time Checking of Exceptions

Since:

1.0

See Also:

Serialized Form

Constructor Summary

Constructors

Modifier	Constructor	Description
	RuntimeException()	Constructs a new runtime exception with null as its detail message.
	RuntimeException(String message)	Constructs a new runtime exception with the specified detail message.
	RuntimeException(String message, Throwable cause)	Constructs a new runtime exception with the specified detail message and cause.
protected	**RuntimeException**(String message, Throwable cause,	Constructs a new runtime exception with the specified detail message, cause,

`boolean enableSuppressio` `boolean writableStackTra`	suppression enabled or disabled, and writable stack trace enabled or disabled.
`RuntimeException` `(Throwable cause)`	Constructs a new runtime exception with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`).

Method Summary

Methods declared in class Throwable

`addSuppressed`, `fillInStackTrace`, `getCause`, `getLocalizedMessage`, `getMessage`, `getStackTrace`, `getSuppressed`, `initCause`, `printStackTrace`, `printStackTrace`, `printStackTrace`, `setStackTrace`, `toString`

Methods declared in class Object

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `wait`, `wait`, `wait`

Constructor Details

RuntimeException

```
public RuntimeException()
```

Constructs a new runtime exception with `null` as its detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(Throwable)`.

RuntimeException

```
public RuntimeException(String message)
```

Constructs a new runtime exception with the specified detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(Throwable)`.

Parameters:

`message` - the detail message. The detail message is saved for later retrieval by the `Throwable.getMessage()` method.

RuntimeException

```
public RuntimeException(String message,
                        Throwable cause)
```

Constructs a new runtime exception with the specified detail message and cause.

Note that the detail message associated with `cause` is *not* automatically incorporated in this runtime exception's detail message.

Parameters:

`message` - the detail message (which is saved for later retrieval by the `Throwable.getMessage()` method).

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

Since:

1.4

RuntimeException

```
public RuntimeException(Throwable cause)
```

Constructs a new runtime exception with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`). This constructor is useful for runtime exceptions that are little more than wrappers for other throwables.

Parameters:

`cause` - the cause (which is saved for later retrieval by the `Throwable.getCause()` method). (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

Since:

1.4

RuntimeException

```
protected RuntimeException(String message,
                           Throwable cause,
                           boolean enableSuppression,
                           boolean writableStackTrace)
```

Constructs a new runtime exception with the specified detail message, cause, suppression enabled or disabled, and writable stack trace enabled or disabled.

Parameters:

`message` - the detail message.

`cause` - the cause. (A `null` value is permitted, and indicates that the cause is nonexistent or unknown.)

`enableSuppression` - whether or not suppression is enabled or disabled

`writableStackTrace` - whether or not the stack trace should be writable

Since:

1.7

Report a bug or suggest an enhancement
For further API reference and developer documentation see the Java SE Documentation, which contains more detailed, developer-targeted descriptions with conceptual overviews, definitions of terms, workarounds, and working code examples. Other versions.
Java is a trademark or registered trademark of Oracle and/or its affiliates in the US and other countries.
Copyright © 1993, 2026, Oracle and/or its affiliates, 500 Oracle Parkway, Redwood Shores, CA 94065 USA.
All rights reserved. Use is subject to license terms and the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.