JavaScript is disabled on your browser.

compact1, compact2, compact3

java.lang

Class Exception

java.lang.Object
    java.lang.Throwable
        java.lang.Exception

All Implemented Interfaces:

Serializable

Direct Known Subclasses:

AclNotFoundException, ActivationException, AlreadyBoundException, ApplicationException, AWTException, BackingStoreException, BadAttributeValueExpException, BadBinaryOpValueExpException, BadLocationException, BadStringOperationException, BrokenBarrierException, CertificateException, CloneNotSupportedException, DataFormatException, DatatypeConfigurationException, DestroyFailedException, ExecutionException, ExpandVetoException, FontFormatException, GeneralSecurityException, GSSException, IllegalClassFormatException, InterruptedException, IntrospectionException, InvalidApplicationException, InvalidMidiDataException, InvalidPreferencesFormatException, InvalidTargetObjectTypeException, IOException, JAXBException, JMException, KeySelectorException, LambdaConversionException, LastOwnerException, LineUnavailableException, MarshalException, MidiUnavailableException, MimeTypeParseException, MimeTypeParseException, NamingException, NoninvertibleTransformException, NotBoundException, NotOwnerException, ParseException, ParserConfigurationException, PrinterException, PrintException, PrivilegedActionException, PropertyVetoException, ReflectiveOperationException, RefreshFailedException, RemarshalException, RuntimeException, SAXException, ScriptException, ServerNotActiveException, SOAPException, SQLException, TimeoutException, TooManyListenersException, TransformerException, TransformException, UnmodifiableClassException, UnsupportedAudioFileException, UnsupportedCallbackException,

UnsupportedFlavorException, UnsupportedLookAndFeelException, URIReferenceException, URISyntaxException, UserException, XAException, XMLParseException, XMLSignatureException, XMLStreamException, XPathException

---

public class **Exception**
extends Throwable

The class Exception and its subclasses are a form of Throwable that indicates conditions that a reasonable application might want to catch.

The class Exception and any subclasses that are not also subclasses of RuntimeException are *checked exceptions*. Checked exceptions need to be declared in a method or constructor's throws clause if they can be thrown by the execution of the method or constructor and propagate outside the method or constructor boundary.

Since:

JDK1.0

See Also:

Error, Serialized Form

See *The Java™ Language Specification*:

11.2 Compile-Time Checking of Exceptions

Constructor Summary

Constructors

Modifier	Constructor	Description
	Exception()	Constructs a new exception with null as its detail message.
	Exception(**String** message)	Constructs a new exception with the specified detail message.
	Exception(**String** message, **Throwable** cause)	Constructs a new exception with the specified detail message and cause.
protected	**Exception**(**String** message, **Throwable** cause,	Constructs a new exception with the specified detail

	boolean enableSuppression, boolean writableStackTrace)	message, cause, suppression enabled or disabled, and writable stack trace enabled or disabled.
	Exception(**Throwable** cause)	Constructs a new exception with the specified cause and a detail message of (cause==null ? null : cause.toString()) (which typically contains the class and detail message of cause).

Method Summary

Methods inherited from class java.lang.Throwable

addSuppressed, fillInStackTrace, getCause, getLocalizedMessage, getMessage, getStackTrace, getSuppressed, initCause, printStackTrace, printStackTrace, printStackTrace, setStackTrace, toString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, wait, wait, wait

Constructor Detail

Exception

```
public Exception()
```

Constructs a new exception with null as its detail message. The cause is not initialized, and may subsequently be initialized by a call to Throwable.initCause(java.lang.Throwable).

Exception

```
public Exception(String message)
```

Constructs a new exception with the specified detail message. The cause is not initialized, and may subsequently be initialized by a call to `Throwable.initCause(java.lang.Throwable)`.

Parameters:

`message - the detail message. The detail message is saved for later retrieval by the Throwable.getMessage() method.`

Exception

```
public Exception(String message,
                 Throwable cause)
```

Constructs a new exception with the specified detail message and cause.

Note that the detail message associated with `cause` is *not* automatically incorporated in this exception's detail message.

Parameters:

`message - the detail message (which is saved for later retrieval by the Throwable.getMessage() method).`

`cause - the cause (which is saved for later retrieval by the Throwable.getCause() method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)`

Since:

`1.4`

Exception

```
public Exception(Throwable cause)
```

Constructs a new exception with the specified cause and a detail message of `(cause==null ? null : cause.toString())` (which typically contains the class and detail message of `cause`). This constructor is useful for exceptions that are little more than wrappers for other throwables (for example, `PrivilegedActionException`).

Parameters:

`cause - the cause (which is saved for later retrieval by the Throwable.getCause() method). (A null value is permitted, and indicates that the cause is nonexistent or unknown.)`

Since:

1.4

Exception

```
protected Exception(String message,
                    Throwable cause,
                    boolean enableSuppression,
                    boolean writableStackTrace)
```

Constructs a new exception with the specified detail message, cause, suppression enabled or disabled, and writable stack trace enabled or disabled.

Parameters:

`message - the detail message.`

`cause - the cause. (A null value is permitted, and indicates that the cause is nonexistent or unknown.)`

`enableSuppression - whether or not suppression is enabled or disabled`

`writableStackTrace - whether or not the stack trace should be writable`

Since:

`1.7`

Copyright © 1993, 2026, Oracle and/or its affiliates. All rights reserved. Use is subject to license terms. Also see the documentation redistribution policy.

Scripting on this page tracks web page traffic, but does not change the content in any way.