

Electrical Specification

- Manufacturer Part Number: 17HS08-1004-ME1K
- Number of phase: 2
- Step Angle: 1.8deg
- Holding Torque: 16Ncm(22.7oz.in)
- Rated Current/phase: 1.0A
- Phase Resistance: 3.7ohms $\pm$ 10%
- Inductance: 4.5mH $\pm$ 20%(1KHz)
- Insulation Class: B 130°C[266°F]

Physical Specification

- Frame Size: 42 x 42mm
- Body Length: 26mm
- Shaft Diameter: Φ 5mm
- Shaft Length: 20mm
- D-CUT Shaft Length: 16.5mm
- Lead Length: 500mm

Encoder Specification

- Output Circuit Type: Differential
- Encoder Type: Magnetic Incremental
- Encoder Resolution: 1000PPR(4000CPR)
- Output Signal Channels: 3 channels
- Supply Voltage Min: 3.3V
- Supply Voltage Max: 5.5V
- Output Current: 20mA
- Output High Voltage: 5V
- Output Low Voltage: 0.2V
- Output Frequency Max: 400kHz

Motor and Encoder Connection

Motor	A+	A-	B+	B-
Wire	Red	Black	Yellow	Blue

Encoder	VCC	EGND	EA+	EA-	EB+	EB-	EZ+	EZ-
Wire	Red	Black	Brown	Orange	Blue	Green	Yellow	White