NAMA PEMILIK PROYEK : **PT PERTAMINA EP**

NAMA PROYEK : **JASA PEMBANGUNAN FASILITAS PRODUKSI STASIUN PENGUMPUL (SP) TANJUNG MIRING BARAT & KARANGAN TIMUR**

LOKASI : **SP TANJUNG MIRING BARAT & KARANG TIMUR - FIELD LIMAU**

NO. KONTRAK : **SA02035383B**

A	23-12-25	Issued For Review	FA	AS	RTN		
REV.	TGL.	DESKRIPSI	DISIAPKAN	DIPERIKSA	DISETUJUI	DIPERIKSA	DISETUJUI
			PT. PROSYMPAC OIL & GAS			PT. PERTAMINA EP	

TABEL REVISI

Rev.	Tanggal	Deskripsi

COMMENT RESPONSE SHEET

No.	Page	Company's Comment	Contractor's Response	Remarks

PCG	**JASA PEMBANGUNAN FASILITAS PRODUKSI STASIUN PENGUMPUL (SP) TANJUNG MIRING BARAT & KARANGAN TIMUR**	**Doc. No:** TMBP-SP001-PS-DST-D103
		PAGE 1 of 8
		Date: 23-Dec-25

DATASHEET OF FIRE PROTECTION

1	**1. General Information**											
2	Service	:	9 kg BC DRY CHEMICAL FIRE EXTINGUISHER			Brand Name	:	VTA				
3	Location	:	Outdoor			Type	:	Hand Held				
4	Model No.	:	VTA			Qty	:	16				
5	**2. Operating Conditions**											
6	Class	B & C										
7	Ambient Temperature	Max	:	36.7	°C	Min	:	19.4	°C	Normal	:	32 °C
8	**3. Design Features**											
9	Extinguishing Agent	:	Potassium Bicarbonate									
10	Operation Method	:	Stored Pressure									
11	Agent Weight			Rating		Performance						
12	9	kg		VTA		Discharge Range (Horizontal)			VTA	m		
13	Gross Weight					Discharge Time			VTA	sec		
14	VTA	kg				Allowable Storage Temperature			VTA	°C		
15						Agent Flow Rate			VTA	kg/s		
16	Operation Gas	N_2				Installation Method			Cabinet			
17	Operation Pressure	VTA			barg							
18	Dimension	Diameter	:	VTA	mm	Length	:	VTA	m			
19	**4. Accessories**											
20												
21	- One each One Extinguisher											
22	- Hose & Nozzle											
23	- Pressure Gauge											
24												
25	**5. Material**											
26	Shell	Mild Steel										
27	Hose	VTA										
28	**6. Test & Inspection**											
29	Dimension & Workmanship				Yes							
30	Performance Test				Yes							
31	Hydrostatic Pressure Texst				VTA	barg						
32	**8. Painting**			**9. Unit Weight**								
	Body	Red Ral 3000		VTA	kg							
33	Letter	VTA				(Note 4)						
34	**10. Remarks**											
35	VTA : Vendor to Advice											
36	Note :											
37	1. The entire extinguisher shall be as per NFPA 10											
38	2. Vendor shall provide a list of recommendation spare parts for two (2) years of operation and maintenance											
39	3. Vendor shall provide extinguisher with 5 years product warranty											
40	4. The image is indication only, the final image will be finallzed by vendor											
41												
42												
43												

PGG	**JASA PEMBANGUNAN FASILITAS PRODUKSI STASIUN PENGUMPUL (SP) TANJUNG MIRING BARAT & KARANGAN TIMUR**	**Doc. No:** TMBP-SP001-PS-DST-D103
		PAGE 2 of 8
		Date: 23-Dec-25

DATASHEET OF FIRE PROTECTION

1	**1. General Information**											
2	Service	:	4.5 kg BC DRY CHEMICAL FIRE EXTINGUISHER			Brand Name	:	VTA				
3	Location	:	Outdoor			Type	:	Hand Held				
4	Model No.	:	VTA			Qty	:	16				
5	**2. Operating Conditions**											
6	Class		A, B , & C									
7	Ambient Temperature		Max	:	36.7	°C	Min	:	19.4	°C	Normal	: 32 °C
8	**3. Design Features**											
9	Extinguishing Agent	:	Ammonium Phosphate									
10	Operation Method	:	Stored Pressure									
11	Agent Weight			Rating		Performance						
12	4.5	kg		VTA		Discharge Range (Horizontal)		VTA	m			
13	Gross Weight					Discharge Time		VTA	sec			
14	VTA	kg				Allowable Storage Temperature		VTA	°C			
15						Agent Flow Rate		VTA	kg/s			
16	Operation Gas		N_2			Installation Method		Hanger / Bracket				
17	Operation Pressure		VTA		barg							
18	Dimension		Diameter	:	VTA mm	Length	:	VTA m				
19	**4. Accessories**											
20												
21	- Bracket											
22	- Hose & Nozzle											
23	- Pressure Gauge											
24	- One each one extinguisher											
25	**5. Material**											
26	Shell		Mild Steel									
27	Hose		VTA									
28	**6. Test & Inspection**											
29	Dimension & Workmanship				Yes							
30	Performance Test				Yes							
31	Hydrostatic Pressure Texst				VTA barg							
32	**8. Painting**			**9. Unit Weight**								
	Body	Red Ral 3000		VTA	kg							
33	Letter	VTA				(Note 4)						
34	**10. Remarks**											
35	VTA : Vendor to Advice											
36	Note :											
37	1. The entire extinguisher shall be as per NFPA 10											
38	2. Vendor shall provide a list of recommendation spare parts for two (2) years of operation and maintenance											
39	3. Vendor shall provide extinguisher with 5 years product warranty											
40	4. The image is indication only, the final image will be finalized by vendor											

PGG	**JASA PEMBANGUNAN FASILITAS PRODUKSI STASIUN PENGUMPUL (SP) TANJUNG MIRING BARAT & KARANGAN TIMUR**	**Doc. No:** TMBP-SP001-PS-DST-D103
		PAGE 3 of 8
		Date: 23-Dec-25

DATASHEET OF FIRE PROTECTION

1	**1. General Information**										
2	Service	:	4.5 kg Portable CO_2 Extinguisher			Brand Name	:	VTA			
3	Location	:	Indoor			Type	:	Hand Held			
4	Model No.	:	VTA			Qty	:	5			
5	**2. Operating Conditions**										
6	Class	B & C									
7	Ambient Temperature	Max	:	36.7	°C	Min	:	19.4	°C	Normal	: 32 °C
8	**3. Design Features**										
9	Extinguishing Agent	:	Carbon Dioxide								
10	Operation Method	:	Stored Pressure								
11	Agent Weight			Rating		Performance					
12	4.5	kg		VTA		Discharge Range (Horizontal)		VTA	m		
13	Gross Weight					Discharge Time		VTA	sec		
14	VTA	kg				Allowable Storage Temperature		VTA	°C		
15						Agent Flow Rate		VTA	kg/s		
16	Operation Gas	Not Applicable				Installation Method		Hanger / Bracket			
17	Operation Pressure	VTA			barg						
18	Dimension	Diameter	:	VTA	mm	Length	:	VTA	m		
19	**4. Accessories**										
20											
21	- Bracket										
22	- Hose & Nozzle										
23	- Pressure Gauge										
24	- One each one extinguisher										
25	**5. Material**										
26	Shell	Mild Steel									
27	Hose	VTA									
28	**6. Test & Inspection**										
29	Dimension & Workmanship				Yes						
30	Performance Test				Yes						
31	Hydrostatic Pressure Texst				VTA	barg					
32	**8. Painting**			**9. Unit Weight**							
	Body	Red Ral 3000		VTA	kg						
33	Letter	VTA				(Note 4)					

34	**10. Remarks**
35	VTA : Vendor to Advice
36	Note :
37	1. The entire extinguisher shall be as per NFPA 10
38	2. Vendor shall provide a list of recommendation spare parts for two (2) years of operation and maintenance
39	3. Vendor shall provide extinguisher with 5 years product warranty
40	4. The image is indication only, the final image will be finallzed by vendor
41	
42	
43	

POG	**JASA PEMBANGUNAN FASILITAS PRODUKSI STASIUN PENGUMPUL (SP) TANJUNG MIRING BARAT & KARANGAN TIMUR**	**Doc. No:** TMBP-SP001-PS-DST-D103
		PAGE 4 of 8
		Date: 23-Dec-25

DATASHEET OF FIRE PROTECTION

1	**1. General Information**					
2	Service	:	Potable Water	Brand Name	:	VTA
3	Location	:	Outdoor	Type	:	Combination eyewash & safety shower unit
4	Model No.	:	VTA	Qty	:	5
5	**2. Operating Conditions**					
	Fluid Handled		Potable Water			
6	Temperature		Normal	:	AMB	
7	Pressure		Normal	:	ATM	
8	**3. Design Features**					
9	Dimension	:	VTA			
	Certification	:	VTA			
10	Weight	:	VTA			
11	Shower		Operation	:	Step on platform or pull rod operated	
12			Flowrate	:	76.7	l/min
13			Operating Pressure	:	30	psig
14	Eyewash		Type	:	Two (2) soft-flow, anti surgeeyewash heads	
15			Flowrate	:	11.4	l/min
16			Operating Pressure	:	30	psig
17	Water supply		Service	:	Filtered water / Process water	
			Connection Type	:	Flanges Connection	
18			Diameter	:	1 1/4	inch
19	**4. Accessories**					
20	Shower		- Inbuilt flow regulator			
21			- Shower Head			
22	Eyewash		- Dust cover			
23			- Inbuilt flow regulator			
24			- in line strainer - Wash bowl - Drain line - Nozzles (2)			
25	**5. Material**					
26	Shower		Stainless Steel			
	Water supply		Stainless Steel			
	Other Piping Materials		VTA			
27	Eyewash		Stainless Steel			
28	**6. Application Standard**					
29	Standard		ANSI Z 358.1 - 2009			
30	**7. Test & Inspection**					
31	Dimension & Workmanship		Yes			
32	**8. Painting**		**9. Spare Part**			
	Finish Color	VTA	Yes			

(Note 5)

10. Remarks

VTA : Vendor to Advice

Note :
1. Safety Shower :
   - A large diameter shower head shall be provided to ensure adequate deluge
   - Shower shall be actuated by a clearly marked, ,easily accessible pull chain which open a quick opening valve

2. Eyewash :
   - Water flow to the eyes shall be directed by two nozzles that can be adjusted to provide a gentle but copious flow under varying water pressure
   - Eyewash shall be manually actuated via a foot pedal or a push flag activating a single quick opening valve once opened. Valve shell remain open untuk manuallly closed

3. Vendor shall provide means to adjust water delivery rate, such as a pressure regulator
4. Shall have minimum of two years product warranty
5. The image is indication only. the final image will be finalized by vendor

PGG	**JASA PEMBANGUNAN FASILITAS PRODUKSI STASIUN PENGUMPUL (SP) TANJUNG MIRING BARAT & KARANGAN TIMUR**	**Doc. No:** TMBP-SP001-PS-DST-D103
		PAGE 5 of 8
		Date: 23-Dec-25

DATASHEET OF FIRE PROTECTION

1	**1. General Information**											
2	Service	:	WINDSOCK				Brand Name	:	VTA			
3	Location	:	Outdoor				Type	:	Illuminated collapsible with pole windsock			
4	Model No.	:	VTA				Qty	:	2			
5	**2. Operating Conditions**											
6	Temperature		Normal	:	AMB							
7	Pressure		Normal	:	ATM							
8	**3. Design Features**											
9	Windsock	Size	Length	:	1.2 m	Big Diameter	:	0.6 m	Small Diameter	:	0.3 m	
10		Color	:	International orange and White color combination								
11		Weight	:	VTA								
12	Pole	Size	Length	:	9	m	Diameter	:	VTA	mm		
13		Weight	:	VTA								
14	Frame	Weight	:	VTA								
15	**4. Accessories**											
16	Content	- Windsock - Windsock frame with bearing, able to rotate 360 degree freely - Pole										
17												
18												
19												
20												
21	**5. Material**											
22	Windsock	Polyester, resist the effect of wind and weather										
	Frame	Heavy duty wire, galvanized material										
	Pole (1.5" pipe)	Galvanized material										
23	**7. Test & Inspection**											
24	Dimension & Workmanship						Yes					
25	**8. Painting**				**9. Spare Part**							
	Finish Color	VTA			Yes							
	10. Remarks											

1. Vendor Shall provide detail information of the installation method
2. Shall have minimum of two years product warranty

PGG	**JASA PEMBANGUNAN FASILITAS PRODUKSI STASIUN PENGUMPUL (SP) TANJUNG MIRING BARAT & KARANGAN TIMUR**	**Doc. No:** TMBP-SP001-PS-DST-D103
		PAGE 7 of 8
		Date: 23-Dec-25

DATASHEET OF FIRE PROTECTION

1	**1. General Information**											
2	Service	:	Local Supression System				Brand Name	:	VTA			
3	Location	:	Indoor				Type	:	Total Flooding Local System			
4	Model No.	:	VTA				Qty	:	3 (Note 3)			
5	**2. Operating Conditions**											
6	Class	A, B & C										
7	Ambient Temperature	Max	:	36.7	°C	Min	:	19.4	°C	Normal	:	32 °C
8	**3. Design Features**											
9	Extinguishing Agent	:	Others : VTA									
10	Operation Method	:	Stored Pressure									
11	Agent Weight			Rating			Performance					
12	4.5	kg		VTA			Discharge Range (Horizontal)			VTA	m	
13	Gross Weight						Discharge Time			VTA	sec	
14	VTA	kg					Allowable Storage Temperature			VTA	°C	
15							Agent Flow Rate			VTA	kg/s	
16	Operation Gas	N_2					Installation Method			Hanger / Bracket		
17	Operation Pressure	VTA			barg							
18	Dimension	VTA					Length	:		VTA	m	
19	**4. Accessories**											
20												
21	- Bracket											
22	- Hose & Nozzle											
23	- Pressure Gauge											
24	- One each one extinguisher											
25	**5. Material**											
26	Shell	VTA										
27	Hose	VTA										
28	**6. Test & Inspection**											
29	Dimension & Workmanship					Yes						
30	Performance Test					Yes						
31	Hydrostatic Pressure Texst					VTA	barg					
32	**8. Painting**			**9. Unit Weight**								
	Body	Red		VTA	kg							
33	Letter	VTA					(Note 2 and 4)					

34	**10. Remarks**
35	VTA : Vendor to Advice
36	Note :
37	1. The entire extinguisher is equipped with sprinkler nozzle with glass bulb which will break triggered by heat at 68 °C
38	2. The local suppression system also shall be integrated with detector inside GEG and DEG for automatic activation release
39	3. The local suppression system will be used for protection inside exclosure of Gas Engine Generator and Diesel Engine Generator
40	4. The image is indication only, the final image will be finallzed by vendor
41	
42	
43	

PGG	**JASA PEMBANGUNAN FASILITAS PRODUKSI STASIUN PENGUMPUL (SP) TANJUNG MIRING BARAT & KARANGAN TIMUR**	**Doc. No:** TMBP-SP001-PS-DST-D103
		PAGE 8 of 8
		Date: 23-Dec-25

DATASHEET OF FIRE PROTECTION

1	**1. General Information**					
2	Service	:	Potable Water	Brand Name	:	VTA
3	Location	:	Indoor	Type	:	Potable Eyewash
4	Model No.	:	VTA	Qty	:	2
5	**2. Operating Conditions**					
6	Fluid Handled		Potable Water			
7	Temperature		Normal	:	AMB	
8	Pressure		Normal	:	ATM	
9	**3. Design Features**					
10	Dimension	:	VTA			
11	Certification	:	VTA			
12	Tank Capacity	:	Min. 9 Gallon			
13	Weight	:	VTA			
14	Eyewash		Type	:	Portable Eyewash	
15			Operation	:	Pull and Push	
16			Flowrate	:	0.4	gpm
17			Operating Pressure	:	30	psig
18	**4. Accessories**					
19	Eyewash		- Mounting Bracket - Polyethylene Tank - Mounting Hardware - Wash bowl - Drain line			
20						
21						
22	**5. Material**					
23	Eyewash		ABS Plastic			
24	**6. Application Standard**					
25	Standard		ANSI Z 358.1 - 2014			
26	**7. Test & Inspection**					
27	Dimension & Workmanship		Yes			
28	**8. Painting**		**9. Spare Part**			
29	Finish Color	VTA	Yes			

(Note 2)

10. Remarks

VTA : Vendor to Advice

Note :
1. Shall have minimum of two years product warranty
2. The image is indication only. the final image will be finalized by vendor

PGG	**JASA PEMBANGUNAN FASILITAS PRODUKSI STASIUN PENGUMPUL (SP) TANJUNG MIRING BARAT & KARANGAN TIMUR**	**Doc. No:** TMBP-SP001-PS-DST-D103
		PAGE 6 of 8
		Date: 23-Dec-25

DATASHEET OF FIRE PROTECTION

1	**1. General Information**					
2	Service	:	FIRST AID KIT	Brand Name	:	VTA
3	Location	:	Indoor	Type	:	Industrial Grade
4	Model No.	:	VTA	Qty	:	5
5	**2. Operating Conditions**					
6	Temperature	Normal	:	AMB		
7	Pressure	Normal	:	ATM		
8	**3. Design Features**					
9	Dimension	VTA				
10	Weight	VTA				

11	Content	Item	Description	Qty
		Ammonia Inhalant		1
		Torniquet		1
		Eye Dressing Packet	Small	1
		Merhilate	8 cc unidrop	2
		Prep Pad		2
		Bandage Compress	10 cm	3
		Bandage Compress	5 cm	4
		CURAD	2.5 cm x 2.5 cm	7
		Gauze Bandage	10 cm x 5.5 cm	11
		Gauze Compress	60 cm x 182 cm	11
		Adhesive Tape	1.3 cm x 76 cm	2
		Adhesive Pad	5 cm x 7.5 cm	4
		Bandages	Triangular BPC, appox 90 cm side x 127 cm base	8
		Cotton Wool	100 g	2 packets
		Absorbent Ribbon	BPC, 2.5 cm x 5 cm	1 roll
		Resuscitator Diameter	Short oral airway	1
		Rustless Length /Height	5 cm safety pins	6
		Rustless Scissor	7 inch - 18 cm	1 pair
		Arm Splints	Inflatable	1 set
		Leg Splints	Inflatable	1 set
		ABT After Burn Ointment	18 gm	4

12	Box	Feature	- Weatherproof - Plastic non locking container - Suitable for wall mounting - clearly marked "FIRST AID KIT" - Carrying handle
13			
14			

15	**4. Accessories**		
16	- Carrying Box - Wall Mounting Bracket		
17			
18			
19	**5. Application Standard**		
20	Standard	VTA	
21	**6. Material**		
22	Box	VTA	
	Others	VTA	
23	**7. Test & Inspection**		
24	Dimension & Workmanship		Yes
25	**8. Painting**		**9. Spare Part**
	Finish Color	White Red Cross	No

10. Remarks

VTA : Vendor to Advice