

Maximilian W. Gotthardt

Evaluation of protocols for control stage lighting

Bachelor Thesis in Computer Engineering

15 March 2022

Please cite as:
Maximilian W. Gotthardt, "Evaluation of protocols
for control stage lighting," Bachelor Thesis (Bachelorarbeit), Institute of Telecommunication Systems, Technische
Universität Berlin, Germany, March 2022.

Evaluation of protocols for control stage lighting

Bachelor Thesis in Computer Engineering

vorgelegt von

Maximilian W. Gotthardt

geb. am 13. July 1993
in Berlin

angefertigt in der Fachgruppe

Fachgebiet Telekommunikationsnetze

**Institut für Telekommunikationsnetze
Technische Universität Berlin**

Betreuer: **Anatolij Zubow**
Gutachter: **Falko Dressler**
Thomas Sikora

Abgabe der Arbeit: **15. März 2022**

Erklärung

Ich versichere, dass ich die Arbeit ohne fremde Hilfe und ohne Benutzung anderer als der angegebenen Quellen angefertigt habe und dass die Arbeit in gleicher oder ähnlicher Form noch keiner anderen Prüfungsbehörde vorgelegen hat und von dieser als Teil einer Prüfungsleistung angenommen wurde.

Alle Ausführungen, die wörtlich oder sinngemäß übernommen wurden, sind als solche gekennzeichnet.

(Maximilian W. Gotthardt)

Berlin, den 15 March 2022

Abstract

In the field of lighting and stage technology, the challenge of controlling the individual installations, quickly and without complications is a recurring one. Established solutions are realized via cables using DMX-512a. However, due to the progress in radio technology, wireless solutions based on 801.11 are becoming more and more common.

But it is a challenge to send control signals, to many individual stations and to update them multiple times a second. Additionally a low latency and, of course, a certain reliability must be guaranteed. This is challenged because at typical locations, such as a concert, there are often very busy frequency bands. This thesis therefore examines an approach that attempts to reduce a large part of the overhead, by having the stations communicate with each other on an Ad-Hoc network at the data link layer, in order to improve the throughput. Different approaches with broadcast and unicast are evaluated analytically and experimentally.

It can be shown that the overhead has a great influence on the transmission and that it is particularly extreme, because so many individual stations are often only controlled with very short control signals. The results show that the gain in throughput means that packets can be sent redundantly, which also leads to improvements in reliability.

Kurzfassung

- kabellose lösungen werden interessant
- chips werden günstiger
- für kleine projekte leider sehr teure Hardware
- 802.11 wird als standard benutzt
- protokolle wie art-net könnten optimiert werden
- esp plattform bietet interessante möglichkeiten, wegen der geringen kosten der chips und esp-now
- entwicklung einer plattform die esp-now nutzt
- verschiedene ansätze studiert, wie broadcast und unicasts
- mit jeweils unterschiedlichen modifikationen

In the field of lighting and stage technology, the challenge of controlling the individual lights, called 'fixtures', quickly and without complications is a recurring one. Established solutions are realized via cables, which are difficult to install and inflexible.

Kabellose Lösungen werden durch bessere Technik und stetige Weiterentwicklung immer interessanter. jedoch stellt es sie nach wie vor eine Herausforderung zu sein die Steuersignale des Lichtpults kabellos zu verteilen. denn es bekommen viele einzelne Stationen kurze Steuersignale, die ständig aktualisiert werden.

TOLJA: Wirklich noch einmal auf deutsch?

Contents

Abstract	iii
Kurzfassung	iv
1 Introduction	1
2 Related Work	3
3 Fundamentals	5
3.1 IEEE 802.11 Specification Family	5
3.1.1 Physical layer	6
3.1.2 Data Link Layer	7
3.1.3 Carrier Sense Multiple Access/Collision Avoidance	8
3.1.4 Data Link Transmissions	8
3.2 Light protocols	10
3.2.1 DMX-512A	10
3.2.2 Art-Net	11
3.3 ESP Platform	11
3.3.1 ESP32 Hardware	12
3.3.2 ESP-Now	13
3.3.3 ESP-Now vs Art-Net Baseline	14
4 Proposed Approach	16
4.1 Design	16
4.2 Implementation	24
5 Evaluation	27
5.1 Methodology	27
5.2 Wireshark measurements	29
5.3 Protocols under Study	31
5.4 Results	35

Contents	vi
-----------------	-----------

6 Conclusion & Discussion	36
--------------------------------------	-----------

Bibliography	41
---------------------	-----------

The table of contents should fit on one page. When in doubt, adjust the tocdepth counter.

Chapter 1

Introduction

Motivation/Requirements

Wireless networks are becoming increasingly popular, also in the field of lighting technology, because they can be more flexible and also more cost-effective. However, they also have limitations compared to wired solutions. In order to improve the properties of radio networks, a logic link layer approach is chosen in this thesis. to distribute the control signals to the individual stations, This promises better performance due to reduced overhead.

The properties of the wired DMX-512a solution are taken as a baseline. The packets are to be distributed to all stations with an equally large update frequency, the latency between sending the control signal and switching the light should be as short as possible, the stations should control the lights synchronously and the reliability should still be as high as possible. The range should be at least 100m and the hardware used should be as cost-effective as possible.

Challenges

There will always be a possibility to build an even more reliable system with extremely complex hardware, however, the focus of this thesis is to achieve results with low-cost hardware that can be compared to the existing DMX-512a solution. The ESP-NOW protocol used here by the manufacturer Espressif is unfortunately proprietary and had additionally to be investigated due to the partly inaccurate or outdated documentation. Also, the complete control process finds place over microcontrollers, which have to be programmed in a fundamentally different way than ordinary programs.

Introduction Introduc-
tion (sic!) schreiben

Contribution

A number of protocols are being developed on the DL layer/application layer, which offer promising improvements. It is shown that broadcasts are preferable to unicats and also become significantly more robust through adaptations. These were investigated simulatively and experimentally and compared with existing solutions. The test suite used on the test hardware is publicly available on Github.

[link in footnote](#)

Thesis Outline

The thesis is divided into three main chapters. Chapter 3 explains the physical and data link layer, and the 802.11 specifications family, existing light protocols are explained in order to better understand the new protocols that will be introduced later, in addition, the EPS32 hardware and the associated ESP-NOW protocol are briefly shown.

Chapter 4 then specifies the various protocols developed and makes analytical assumptions. And it is explained how to work with the hardware used.

Chapter 5 then explains the methodology, how the measurement data was collected and the technical implementation. Wireshark measurements are analysed and used to better understand the protocols. Afterwards, the protocol data is further evaluated and compared with the analytical approaches and with each other.

Chapter 2

Related Work

- Wie der und der in Paper so gezeigt hat
- Auch Ding et al haben versucht
- ...
- 10 Paper
- halbe seite

Foo and bar [1] are of equal value. Thus, any can be used.

According to [2]

Wireless solutions for stage lighting are growing fast.

- A First Implementation and Evaluation of the IEEE 802.11aa Group Addressed Transmission Service
 - unsosliced Repetition
 - blockack
- Evaluation of Error Control Mechanisms for 802.11b Multicast Transmissions
 - packet loss rate
 - ARQ, FEC
- ESP-NOW communication protocol with ESP32
 - ESP-NOW details
- The Working Principles of ESP32 and Analytical Comparision of using Low-Cost Microcontroller Modules in Embedded Systems Design
 - why the ESP32 is superior over arduino

- Adaptive Cross-Layer Protection Strategies for Robust Scalable Video Transmissions Over 802.11 WLANs
- Voice Capacity of IEEE 802.11b, 802.11a and 802.11g Wireless LANs

Check the conference name, put its parts in a logical order, and lose the “in proceedings of” (it’s not “Mobicom, in proceedings of, 1999 series MobiCom99” but “5th ACM International Conference on Mobile Computing and Networking (MobiCom 1999)”).

triple-check all references

Chapter 3

Fundamentals

In this chapter the fundamentals required for understanding the different approaches in this thesis using are explained. This contains basic knowledge of the physical- and data link layer, which are located in the first and second layer of the Open Systems Interconnection (OSI) Model. It also explains what types of transmissions exist. In addition, the hardware used for this thesis is introduced. The ESP-NOW protocol running on this hardware is also explained.

introduction in chapter
Fundamentals ok?

Application layer
Presentation layer
Session layer
Network layer
Data Link layer
Physical layer

Table 3.1 – OSI model

3.1 IEEE 802.11 Specification Family

The Institut of Electrical and Electronics Engineers (IEEE) 802 is a family of standards dealing with area networks different kinds.

- 802.11 Wireless Local Area Network (WLAN)
- 802.15.1 Wireless Personal Area Network (WPAN)
- 802.15.4 Low-rate WPAN (LR-WPAN)
- 802.16 Wireless metropolitan area network (WMAN)

For this thesis is the focus set to the 802.11, because of the accessibility and wide functionality. There are two Basic Service Set (BSS) defined:

- Infrastructure BSS

A central element manages the network and all the traffic goes through. Every Station (STA) must always communicate via the Access Point (AP) and never directly - exceptional: Direct Link Mode. An initial association must take place to use this BSS. This is the most common mode a WLAN is used.

- Independent BSS

A network without a central station, where the network topology can flexible change over time. The communication happens directly between the Wireless Endsystems. Efficient routing can become a problem in more complex topologies.

The most common use in 802.11 is the Infrastructure mode, which is commonly used in office and home environments.

3.1.1 Physical layer

In this thesis we could take a brief look into the Physical Network Layer (PHY) of the IEEE 802.11 standard, which is the first layer of the OSI model 3.1. This layer provides mechanical, electrical and other functional tools to activate or deactivate physical connections, maintain them and transmit bits over them. These can be, for example, electrical signals, optical signals (fiber optics, lasers) or electromagnetic waves (wireless networks). There are several complements to the 802.11 standard, the most common are:

TOLJA: Was soll ich zum PHY alles sagen?

- 802.11b

supports larger bitrates with Direct Sequence Spread Spectrum (DSSS) or Frequency Hopping Spread Spectrum (FHSS) as modulation from 1Mbit/s to 11Mbit/s. It uses the 2.4 GHz ISM band.

- 802.11a and 802.11g

with Orthogonal Frequency Division Multiplexing) (OFDM) data rates are increased up to 54 Mbit/s. Where 802.11a is in the 5GHz ISM band 802.11g uses the 2.4GHz ISM band.

- 802.11n

It also uses OFDM and improves with additionally Multiple Input-Multiple Output) (MIMO), channel bonding and frame aggregation to increase the bandwidth and decrease the overhead. Using 2.4 GHz and 5GHz ISM band.

- 802.11ac

Support of wider channel and out of it higher bitrates. It also includes features like Multi-User MIMO. It only uses the 5 GHz ISM band.

- 802.11ax

Like 802.11ac but with additional use of the 6GHz ISM band and better power control. Also called WiFi6.

In this thesis the rather basic 802.11b is used with a transmission rate of 1Mbit/s.

3.1.2 Data Link Layer

The Data Link Layer (DL) Layer is the second lowest layer of the OSI Model 3.1 and is split in two sublayers. The Logical Link Control (LLC) sublayer which multiplex protocols over the MAC layer while transmitting and to de-multiplex the protocols while receiving. LLC provides the hop-to-hop flow and error control, allows multi-point communication over networks and it also adds frame sequence numbers. But in this thesis we focus on the other data link sublayer.

The Media Access Control (MAC) includes network protocols that regulate how multiple computers share the physical transmission medium they use. Without regulation, collisions and data loss would occur in the shared medium if several WES were to transmit simultaneously. The MAC Protocol Data Unit is additionally added inside of the PHY Payload. It contains the MAC Header and encapsulated in it the MAC Service Data Unit (MSDU).




Figure 3.1 – MAC header of a WLAN frame

Payload and FCS are missing

- **Frame Control Field:** Describes the Type of frame:
 - 00 Management Frame
 - 01 Control Frame
 - 10 Data Frame
- **Duration:** Contains the Network Allocation Vector (NAV) value, specifies the transmission time required for the frame. In order to save power to save energy, WES can defer access to the medium for this duration
- **Address fields:** Certain address fields are specified by the relative position of the address field. Not every address field is needed by certain frames. Each device is associated with a MAC address.
 - Basic Service Set Identifier (BSSID)
 - Source Address

- Destination Address
- Transmitting STA Address
- Receiving STA Address

- **Sequence Control:** Sequence number of the current frame modulo 4096.
- **MAC Payload:** The actual payload information of the MAC layer. The actual payload can differ, because the headers of the LLC and ip etc. has to be subtracted.
- **Frame Check Frequency:** The sender calculates the checksum for the entire data block and appends it to the end of the block.

802.11ac and later using frame aggregation in order to reduce overhead.

3.1.3 Carrier Sense Multiple Access/Collision Avoidance

Carrier-sense Multiple Access with Collision Avoidance (CSMA/CA) is composed of:

- **CS (Carrier Sense):** jede Station checkt ob das Medium frei ist, bevor sie sendet
- **MA (Multiple Access):** mehrer Stationen teilen sich ein Medium, dieses kann auch ein ein Kabel sein
- **CD (Collision Detection):** Ein Ablaufplan verhindert, dass zwei Stationen zeigleich ihre Übertragung beginnen

Before a station transmitts data it has to check or listen to the medium to avoid collisiion resulting in packet loss. Only when the medium is free, the station can transmit via the shared medium. When the medium is already in use t

Collision avoidance tries to avoid collisions before they happen in the first place.

Backoff:

random time delay to avoid collisions

DIFS/SIFS:

Delay between transmissions used for CSMA/CA

3.1.4 Data Link Transmissions

Short introduction

Unicast

The link layer unicast is used to send data over an single hop to the target Wireless Endsystem (WES) destination. The link layer of each WES checks the destination MAC address in the link layer header and discards the frame if the destinatin address does not match its own address.

Unicast is by default reliable. E.g. the AP wants to transmit a packet to one specific WES

When the Unicast reaches the destination WES an acknowledgement frame is send back after the Short Inter Frame Spaces (SIFS) + backoff.

If the acknowledgement is not successfully received by the sender, the sender will repeat the transmission for a given number. When the number is exceeded, the packet could not be delivered. If the number is set to zero, the unicast can be considered as non-reliable.

when to explain CS-MA/DC?

example

complete figure UC



Figure 3.2 – Unicast Transmission

Broadcast

If a packet should be received from all WES's it can be distributed as broadcast. The MAC address of the destination address in the link layer is set to the common broadcast address, which is ff:ff:ff:ff:ff:ff.

In contrast to unicast, broadcast is not reliable. This is mainly because the packet is addressed to all nodes at the same time, and if link layer acknowledgements would be used, the acknowledgements would be sent by all nodes at the same time, because there is no mechanism in which order acknowledges should be answered. In addition, the sender of a broadcast does not know how many WESs he is addressing the packet to in the first place. Retransmitting acknowledgements would lead to massive collision and loss of acknowledgements. E.g. management information in a WLAN is sent in a broadcast mode, because it has to reach every WES and isn't worth to be acknoleged.

complete figure BC



Figure 3.3 – Broadcast Transmission

Multicast

Multicast explain multicast mac address

When the same packet should be transmitted to multiple WES's, but not to all, multicast can be used. Transmitting the same packet multiple times via unicast is wasteful. There are different approaches to realize acknowledgements for multicasts, they differ mainly by the respective field of application.

examples for multicast ack + related work

Level 2 multicast is often used for large files in audio or video streams, where a big amount of data is distributed and multiple clients listen simultaneously.

complete figure MC



Figure 3.4 – Multicast Transmission

3.2 Light protocols

There are several lighting protocols that are used. The field of application ranges from wired CAN buses over ethernet cables to wireless WLAN networks. To give a short insight, some of the most important protocols are explained below.

3.2.1 DMX-512A

Digital Multiplex (DMX) 512A, is the current industry standard for stage lighting. It is based on Controller Area Network (CAN), therefore it uses wires. Physically is the DMX protocol transmitted over a differential pair of lines using the RS-485 voltage levels. The bus signal is updated with 44Hz. According to the specification are XLR-5 type connectors are to be used.

image der connectoren

Show Hardware e.g. DMX Plug

The endsystems are called fixture because it's most likely a lighting installation which is mounted somewhere, this could be a moving-head, fresnel, spotlight, stroboscope or any other light installation. It could also be a fog machine that emits fog on an appropriate signal.

All devices are daisy chained together visualized in 3.5. The DMX controller is in the begin of each chain. The receiving endsystems, are chained behind each other from output to input. A terminator, specified in the DMX specification, is to be connected to the final output.




Figure 3.5 – Block Diagram of an DMX Universe

The whole chain is called DMX-Universe and can contain a set of 512 channels. If there is a need for more channels, one needs more DMX universes - each channel consists of one byte. Due to the fact that a DMX universe always has its own bus, starting from a new controller can lead to inconveniences.

A channel in the event technology is used to distinguish between e.g. a WiFi channel. Each endsystem is assigned at least one, but usually several channels. Every endsystem knows which channel is intended for it, this must be preset.

For example: An RGB-LED spotlight could have three channels, one for each color. Due to the resolution of one byte, the individual colors can (theoretically) be controlled in 256 different intensities. If the channels 0-56 are already used, it could be set to channels 57, 58, 59. Any other free channel range would also be possible, provided it is connected. There exist hardware with automatic-address-assignment.

Image of fixtures distributed on channel

Since DMX is unidirectional, it can be assumed that the endsystems generally only receive or forward (daisy chain) control signals sent from the control console. This is a major limitation of DMX, besides of the rather small universe size. It is also not reliable, the use of fire installations is therefore considered too dangerous.

3.2.2 Art-Net

- Example of an wifi protocol
- 2.4 or 5GHz
- DMX-Like
- related work

Due to the limitation of 512 channels for each universe, there are protocols implemented using the Art-Net, also called Art-Net DMX.

3.3 ESP Platform

Almost every 802.11 capable Microcontroller Unit (MCU) could be picked for this research. But there are several reasons why the ESP Platform from Espressif is a

valid choice. There are several chips provided by Espressif with WiFi specifications, these chips are very affordable () and although the ongoing chip crisis (2021) there are easy to get, in contrast of the also very popular Chips from the manufacturer Arduino, which are also more expensive. Espressif supports an own development IDF to flash the chips, with minor tweaks it's also to use the Arduino IDE. However the proprietary protocol ESP-Now which, just supported in the ESP Ecosystem, is discussed below ?? and has promising properties for a solid and fast realisation of a low level protocol.

TOLJA: ESP32 Kosten in € 2021 aufführen? Link? Datum?

paper about esp above arduino

3.3.1 ESP32 Hardware

The chip ESP32 is quite common in DIY projects around everything from home automation to light installations and can be bought on development boards, which are ready to use. The chip 3.6 is promoted with several features:

this is cited from: link zum esp32 datasheet

- Fast CPU (2 cores at 240 MHz)
- 802.11 b/g/n with up to 150 Mbps (2.4GHz)
- Wifi Multimedia (WMM)
- Immediate Block ACK
- Automatic Beacon monitoring (hardware TSF)
- Virtual Wi-Fi Interfaces
- Simultaneous support for Infrastructure, SoftAP, and Promiscuous modes
- Bluetooth v4.2 BR/EDR and Bluetooth LE
- Advanced Peripheral Interfaces: GPIO, ADC, DAC, touch sensors, hall sensor, SPI, I2S, I2C, UART, CAN, RMT (TX/RX), Motor/LED PWM




Figure 3.6 – ESP32 Devboard (Devkit V1)

final words to the ESP32 Hardware - a lot of features for a cheap hardware

3.3.2 ESP-Now

ESP-NOW is a proprietary protocol developed by Espressif. ESP-NOW is widely used in smart light, remote controlling, sensor, etc. It is a connectionless protocol, so the WES's are in Ad-Hoc mode instead of STA. It is just supported on the ESP8266, ESP32 and ESP32s, all chipsets from Espressif, but they are compatible with each other. Because of this, an ESP-Chip as gateway is needed to interact from the outside to the ESP-NOW communication.

cite ESP documentation website

Through the hardware limitation of the boards it can just be used on the 2.4 GHz frequency band. ESP-NOW allows 10 ESPs for pairing with encryption and up to 20 without encryption. Espressif promises throughput of up to 30MBit/s with and a possible range of up to 1km. However *Roberto Pasic [3]* measured a range of the unmodified onboard antenna of the ESP32 and just got a *Roberto Pasic [3] stable communication up to 190m in open field.*

The focus of the ESP-NOW protocol is on low power consumption. A connectionless communication between WES's not only saves energy during the authentication process, Additionally, is the communication the the properties of the ad-hoc mode, direct and not over a second access point. The protocol has a limitation of a limited payload of 250 byte for each transmission. It also has a much less overhead, which results in shorter airtime, less disturbances and also less power consumption through the antenna (latter is not relevant for this thesis). There is no TCP/IP header to be transmitted. For very small payloads, this offset can become disproportional.

The default ESP-NOW bit rate is 1 Mbps it uses a channelwidth of 20MHz, there is no double channel (40Mbit/s or higher) used. But e.g. the low energy, high range protocol Long Range Wide Area Network (LoRaWAN) suffers from a too slow throughput for this application.

To understand what ESP-NOW does it needs to take a look to the vendor-specific action frame transmitting ESP-NOW data.

Explain Vendor Specific Frames!

visualized in 3.2.

MAC Header	Category Code	Org.	Random Values	Vendor Specific Content	FCS
24	1	3	4	7 ~ 255	4

Table 3.2 – ESP-NOW Frame Format

- **MAC Header:** As ESP-NOW is connectionless, the MAC header differs from that of standard frames.

cite somehow the ESP-NOW documentation pdf: ESP-IDF Programming Guide: ESP-NOW, source: https://docs.espressif.com/projects/esp-idf/en/latest/esp32/api-reference/network/esp_now.html

- **Category Code:** The Category Code field is set to the value(127) indicating the vendor-specific category.
- **Organization Identifier:** The Organization Identifier contains a unique identifier (0x18fe34), which is the first three bytes of MAC address applied by Espressif.
- **Random Value:** The Random Value field is used to prevent relay attacks.
- **Vendor Specific Content:** The Vendor Specific Content contains vendor-specific fields (table 3.3)
- **Frame Check Sequence:** Used for error correction in layer 2.

Inside of the ESP-NOW frame 3.2 is the vendor specific content visualized in 3.3.

Element ID	Length	Org. Identifier	Type	Version	Body
1	1	3	1	4	7 ~ 250

Table 3.3 – Vendor Specific Action Frame

- **Element ID:** The Element ID field is set to the value (221), indicating the vendor-specific element.
- **Length:** The length is the total length of Organization Identifier, Type, Version and Body.
- **Organization Identifier:** The Organization Identifier contains a unique identifier(0x18fe34), which is the first three bytes of MAC address applied by Espressif.
- **Type:** The Type field is set to the value (4) indicating ESP-NOW.
- **Version:** The Version field is set to the version of ESP-NOW.
- **Body:** The Body contains the ESP-NOW data.

It is worth to mention, that the vendor specific content 3.2 is allowed to contain up to 255 byte, but the sum over all values in 3.3 if the body would contain the maximum of 250 bytes, leads to a total of 260 bytes. The values are from the documentation of ESP-NOW from Espressif. They also claim, that broadcast is not supported in ESP-NOW, but it is. It seems that the documentation isn't completely finished (or translated).

this is cited from espressif manual!!

255 != 250 is it really that important?

3.3.3 ESP-Now vs Art-Net Baseline

remove newpage command

subsection can be on a wrong position!

- Network stack diagram
- baseline

ESP-NOW Baseline Artnet should be moved to Design part??

Chapter 4

Proposed Approach

Different approaches are presented and discussed in this chapter using data link unicast or broadcast in different specifications, these were also empirically tested and evaluated in the Chapter 5. At the end of this chapter, the test setup will be introduced and it is briefly explained how the chips are programmed.

4.1 Design

Art-Net	Slim Application
UDP	
IP	
802.11 DL/Unicast	802.11 DL/UC or BC
802.11* PHY	802.11b/g/n PHY

Table 4.1 – Art-Net Layer compared with Slim Data Link Layer

The use of high-layer protocols, such as Art-Net Section 3.2.2, in lighting technology involves a considerable overhead. Because the lighting console does not talk directly to the WES, communication must be controlled via an AP, which means that the Internet Protocol (IP) (layer 3) must be used for addressing and User Datagram Protocol (UDP) (layer 4) for transporting the data. They both come with additional headers. Such an overhead can lead to latency, channel congestion and packet loss.

In an ad-hoc network Section 3.1, on the other hand, packets can be sent directly on the MAC (layer 2) Table 4.1. With a payload of a few bytes to each WES, keeping overhead small can be quite important. Complexity problems as often typical in Ad-Hoc networks are not to be assumed, since the controller at the light desk must normally stand in line of sight to the individual WES, from there finally the lighting technician from there must have everything in the range of vision to be able to intervene. One can therefore assume a simple star topology. In the following the

ESP-NOW Section 3.3.2 protocol was chosen to distribute the packets low-level, because even if it was not developed for this purpose the specification fits quite well to the requirements.

topology of data flow
isnt linked in the text




Figure 4.1 – Topology of the Data Flow

For the purpose of this analysis, the controller transmits 20 Byte (analogue to 20 DMX channels) to every WESs. Four different metrics are considered, which were discussed in the requirements.

ref to requirements

- **Latency**

What is the latency from commanding the controller to the estimated reaction at the WES e.g. lighting of a light? For the sake of simplicity, delays caused by the microcontroller instruction set, data distribution and control of the light installation are neglected and the focus is placed only on the airtime.

- **Update Frequency**

How often can we update all WESs per second? This results in how smooth movement of moving heads are moving or how smooth the transition of the color of an LED can be performed.

- **Reliability**

Wie sicher kommen die vom Controller gesendeten Daten bei den WESs an? Lack of reliability can result in two WESs positioned next to each other not behaving the same because one of them only receives half of the signals.

- **Synchronisation**

Are the signals sent to different WESs carried out at the same time? If two of the WESs are to be controlled simultaneously, but the signal was transmitted one after the other, they have to wait for each other so that the lights change at the same time.

Slim Unicast

The implementation that probably comes closest to Art-Net's is to replace the TCP packets sent by Art-Net to the respective IP-Address of the WESs with unicasts to the MAC-address of the WES. Of course, the MAC address of all WESs must be known and they must all be paired with the controller, but this process is just analogous to mapping the corresponding IP addresses after dialing the WESs into a WLAN.

Latency

Latency describes the time between a command and the expected response, here considered as airtime. The airtime using 1Mbit/s is rather easy calculated, every Byte (8 Bits) takes $8\mu\text{s}$.

For a full transmission the PHY and MAC preamble and header be transmitted twice, once for the data and once for the acknowledgement. The MAC body contains the payload, which depends of the needs of the addressed WES. In a perfect clean channel the sender hasn't to defer, but has to take a DCF Inter Frame Spaces (DIFS) plus a backoff. A perfect empty channel resets the CW to CW_{min} , which are 16 slots in 802.11b, so the average backoff should take $\frac{CW_{min}}{2}$ slots, with a slottime of $20\mu\text{s}$ follows an average backoff of $160\mu\text{s}$.

Frame segment	Byte	Airtime in μs
DIFS	-	50
Average Backoff	-	160
PHY header: PLCP preamble	18	144
PHY header: PLCP header	6	48
MAC headers	28	224
MAC body	20	160
= tx time data		786
SIFS	-	10
PHY header: PLCP preamble	18	144
PHY header: PLCP header	6	48
MAC headers, no MAC body	18	112
= tx time ack		314

Table 4.2 – Composition of the Total Airtime (tx + ack)

The total airtime of the transmission of data and ack, assuming the transmission arrived successfully, is $t_{tx} = 1100\mu\text{s}$. Strictly speaking, the light could also be changed before the acknowledgement is sent, i.e. after $786\mu\text{s}$. The latency scales linearly, the delay to the n-th WES is:

$$\text{Airtime} = N \cdot t_{tx} = N \cdot 1100\mu\text{s} \quad (4.1)$$

In order to avoid unnecessary load on the radio channel, Art-Net transmit only the changes. In the worst case, however, changes affect all WESs at the same time.

Update Frequency

Following the approach of DMX and updating the 'bus' every 44Hz, would made by sending the packets round robin via unicast. With a correspondingly high number of WESs, this could be challenge with a transmission speed of 1MBit/s, it also scales linearly with each additional WES. In an labor sterily empty channel, denying all side latencies, there airtime could be for N WESs:

Discuss the inimportance of order of round robin in unicast

$$\text{Frequency} = \frac{1}{N \cdot 1100\mu s} = \frac{9090}{N} \text{Hz} \quad (4.2)$$

For 10 WESs, addressed with respectively 20 Byte, it would still be 909Hz. This is far above the update frequency of DMX, but also very unrealistic and just intended to show, that it could theoretically be within the realm of possibility.

Reliability

One benefit of the unicast is the support of acknowledgements. The acknowledgements trigger a retransmission if no packet has arrived, therefore a controlled light will receive its signal in any case. So the reliability should be very good.

Synchronisation

Synchronising the unicast transmissions costs a lot of latency. This is because not only does each WES have to wait until its own packet has arrived, but until the packets have arrived at all the others. The implementation is chosen in such a way that each WES knows at which position of the round-robin it is and delays the execution of the successfully received transmission until the last WES has also received its signal. The delay must then be calculated deterministically. In ESP-NOW, the default is set to 8 retransmissions, so in the worst case it is assumed that a packet is sent 8 times and that for each WES.

or buffering delay?

...buffering delay

$$\text{Airtime}_{sync} = 8 \cdot N \cdot 1100\mu s = N \cdot 8800\mu s \quad (4.3)$$

$$\text{Frequency}_{sync} = \frac{1}{N \cdot 8800\mu s} = \frac{1136}{N} \text{Hz} \quad (4.4)$$

The idea of the slim unicast is, that a transmission to each device is very fast, because the transmitted payload small. However, since we are sending many small packets, it can be assumed that we will be sending a lot of overhead. So we playing

off reliability against transmission speed. It can be said that synchronisation is a feature that should be dispensed with in the slim unicast for the sake of latency.

Unfortunately the ESP-Now protocol does not allow to control the number of retransmissions before the packet is discarded.

Is it true, that retransmission can't be controlled in ESP-NOW?

Slim Broadcast

The ESP-Now protocol supports both unicast and broadcast. Instead of transmitting every unicast after each other, Slim Broadcast transmits a broadcast with the payload of all channels at the same time to all fixtures. If there is a need for more than 250 Byte (DMX channel) a second broadcast has to be sent to transmit containing the missing data. To achieve this, each WES must be told in advance at which position in the payload its data is located. The broadcast must also spend one byte of payload for the sequence number. Only in the application layer do the WESs discard the incorrect broadcasts and read out their area from the entire payload.

For the unicast the payload was assumed to be 20 byte for each WES, the same amount is assumed for each WES in the Slim Broadcast calculations. The maximum payload of the broadcast is also fixed to 200 byte, because when it is close to the 250 byte limit, reliability is supposed to collapse.

quelle 200 byte

Latency

The latency of the broadcast is easier to calculate than that of unicast, because the acknowledgments are no longer necessary. In return, the payload of a single transmission increases. Assuming 10 WESs are to be addressed, each with 20 byte payload 4.3.

Frame segment	Byte	Airtime in μs
DIFS	-	50
Average Backoff	-	160
PHY header: PLCP preamble	18	144
PHY header: PLCP header	6	48
MAC headers	28	224
MAC body	200	1600
= tx time data		2286

Table 4.3 – Composition the Broadcast Airtime

Due to the fact that a second broadcast is needed if the maximum payload of ESP-NOW is exceeded, the expected transmission time is not continuous, as shown in Figure 4.2. It is easy to see that the additional overhead caused by adding another package creates noticeable latency.




Figure 4.2 – Transmission Time of Broadcasts Depending on Payload

Update Frequency

However, while comparing this to the latency of unicast 4.2, it becomes clear that the low overhead and the missing acknowledgements lead to a significantly higher rate. A complete pass, i.e. addressing all WESs with 20 bytes, is already an order of magnitude faster from a number of 10 WESs.

it's ok to make an example here?

$$\text{Frequency}_{UC} = \frac{1}{10 \cdot 1100\mu s} = 909Hz \quad (4.5)$$

$$\text{Frequency}_{BC} = \frac{1}{2286\mu s} = 4347Hz \quad (4.6)$$

Even if these values are only remotely comparable with real measurement data, it is clear, that the throughput is significantly higher with broadcast than with unicast. This effect should be even clearer under real conditions.

Reliability

The huge advantage that the Slim Broadcast has over the Slim Unicast in terms of update frequency, comes at the cost of lower reliability. Broadcasts can't do acknowledgements, a WES that has poor reception to the controller, will not receive packets and the controller cannot take countermeasures.

ref to fundamentals, datalink, broadcast

Synchronisation

Insead of transmitting to several fixtures after each other slim broadcast just transmits to all fixtures at the same time. This solves the problem of synchronization for less than 200 channel. For more than 200 each WES has to wait until the last




Figure 4.3 – Transmission Time of Unicast vs Broadcast

broadcast is arrived, even if the broadcast must be discarded anyway because the required channel has already been arrived previous, deterministically calculated, the latency of all required broadcasts added up.

Rapid Repetition

To improve the reliability of the slim broadcast, the same transmission can simply be repeated unsolicited. The idea is not to wait for a missing acknowledgment, but to increase the probability that one of the packets got through. The reliability of the Slim Broadcast with Rapid Repetition is improved with every rapid repetition (RR). In the formula below Equation (4.7), with RR set to zero, there happens no repetition.

$$SR_{RR}(RR) = 1 - (1 - SR)^{RR+1} \quad (4.7)$$

$$SR_{RR}(0) = SR \quad (4.8)$$

$$SR_{RR}(1) = 1 - (1 - SR)^2 \quad (4.9)$$

The RR makes it possible to reach WESs with poor reception much more reliably, However, WESs that have very good reception also receive the same packet redundantly. The update frequency of a BC with RR must be divided by the number of repetitions, compared to one without repetitions, the same applies to the latency when synchronisation is required. However, in contrast to unicast, broadcast offers such shorter transmission times, that at least a few repetitions can be accepted. Figure 4.4

ist der Satz gramatisch falsch? Lass ihn einfach weg...

Is Rapid Repetition a appropriate name? Unsolicited Repetition is better siehe Paper?

Cite paper A First Implementation and Evaluation of the IEEE 802.11aa Group Addressed Transmission Service




Figure 4.4 – Transmission Time with different sets of Rapid Repetition (RR)

Delayed Rapid Repetition

To push the idea of rapid repetition even further, should also temporarily occurring noise be taken into account. This can cause all the repetitions to be captured at once. If the individual repetitions of the first sequence are sent displaced together with those of the second sequence, then the probability that at least one of the repetitions is not detected by a occurring noise noise is increased.

displaced repetition vs
delayed repetition

By staggering the individual sequences, the update frequency is not affected, because just as many packets are sent as with Slim Broadcast RR. The latency, on the other hand, is significantly increased, especially when synchronisation is maintained. In the given example of Figure 4.5 the WESs has to wait for 5 times the duration of a broadcast transmission, instead of three.




Figure 4.5 – Rapid Repetition = 3 over a occurring noise

The delay of the Delayed Repetition can also be extended considerably. In extreme cases, it could be set to the number of sequences, which is of course impractical, but interleaving two or three sequences could help counteract persistent noise.

With delayed repetition, improved reliability comes at the cost of latency, not update frequency. The measurement results Chapter 5 will show whether the use of delayed repetition can reduce the number of rapid repetitions while maintaining or even improving reliability.

Buffering delay Latency figure

Explain Problem with synchronization?!

4.2 Implementation

Check, because of split from testbed

This section explains how the test setup was distributed from the PC to all the chips and how the data was subsequently returned to the PC and gives a short hands on - which steps are necessary to get ESP-NOW running on these chips.

The developer board ESP32 Devkit V1 used in the experiments Chapter 5 for the collection of the data can be ordered cheaply from common (most favourably Chinese) websites. [3.79€, www.aliexpress.com, 3/3/22] The most accessible way to flash a chip is using the Arduino IDE, which can be easy configured for flashing ESPs. A more precise approach is to use the IDF of Espressif itself, which can also be easily made to work by installing the toolchain and build tools and an Plugin for your favorite IDE.

zeitangabe website aliexpress?




Figure 4.6 – Flashing ESP. From the website of Espressif

Espressif has provided a user guide for the use of ESP-NOW. Unfortunately, some of the information is highly outdated, for example, it claims that broadcast is not supported. However, more detailed information can be found on the website [link]. <https://docs.espressif.com/projects/esp-idf/en/latest/esp32/get-started/index.html>

link und Quellenangabe:
<https://docs.espressif.com/projects/esp-idf/en/latest/esp32/get-started/index.html>

To use ESP-NOW on an ESP, only a few steps are necessary. The chip must activate Wifi and put it in STA mode and ESP-NOW can be activated. The two libraries "esp_wifi.h" and "esp_now.h" are required for this.

for later use: ESP-NOW User Guide, V1, source: <https://www.espressif.com/en/support/documents/>

link einpflegen

```

1 WiFi.mode(WIFI_STA);
2 esp_now_init();

```

Listing 4.1 – Init ESP-NOW

Later, the individual MAC addresses of the WESs must be saved. These are created in a separate header file and can then be added during the setup of the chip. The MAC address is needed to add the respective WES to the peerlist. However, the WES does not have to be switched on or within range for this, it is more a case of making the WES known to the controller. The Controller can store up to 20 devices in his peerlist at the same time.

```

1 #ifndef MACLIST_H
2 #define MACLIST_H
3
4 uint8_t WES_MAC_1[6] = { 0xFC, 0xF5, 0xC4, 0x31, 0x9A, 0x44 };
5 uint8_t WES_MAC_2[6] = { 0x24, 0x0A, 0xC4, 0x61, 0x19, 0x08 };
6 uint8_t BC_MAC[6]     = { 0xFF, 0xFF, 0xFF, 0xFF, 0xFF, 0xFF };

```

listing box prevent
linebreaks on newpage

```

1 #include "maclist.h"
2
3 if (!esp_now_is_peer_exist(WES_MAC_1)) {
4     peer_info.channel = 13;           // 1-14
5     memcpy(peer_info.peer_addr, WES_MAC_1, 6);
6     esp_err_t status = esp_now_add_peer(&peer_info);
7 }
8 if (ESP_OK == status) {              // check success
9     Serial.println("[OK] Slave-peer added");
10 }

```

Listing 4.2 – Add Peers

Sending an ESP-NOW unicast is performed with the method `esp_now_send()`. The MAC address of the recipient is passed, a pointer to the payload to be transmitted and its length. In the case of a broadcast, the address field is filled with the broadcast address `ff:ff:ff:ff:ff:ff`. The function `esp_now_register_send_cb` can be used to check whether the cast was successfully sent out. It is important to write as little code as possible in such a callback function. If you send the next package only after receiving the dispatch confirmation, then you can be sure that the packages are sent in the correct format, that the packages are sent in the correct order.

```

1 void metaInformationToSlaves(const uint8_t *peer_addr, ↵
    struct_advanced_meta metaData) {
2     esp_now_register_send_cb(onDataSent);    // register callback

```



```

3
4   esp_err_t status = esp_now_send(WES_MAC_1,
5                                   (uint8_t *) &payload,
6                                   sizeof(payload));
7   if (ESP_OK == status) {           // check success
8       Serial.println("[OK] ESP-NOW sending");
9   }
10
11 void onDataSent(const uint8_t *mac_addr, esp_now_send_status_t ↘
12                 status) {
13     if (status == ESP_NOW_SEND_SUCCESS) {
14         Serial.println("[OK] ESP-NOW Send");
15     }
16 }

```

Listing 4.3 – Send ESP-NOW Cast UC/BC

Working with microcontrollers requires a non continuous program-flow, instead it's event-based. For the individual WESs, a callback function is registered after setup, it's called when an ESP-NOW transmission is passed on to the application layer.

```

1  esp_now_register_recv_cb(OnDataRecv);
2
3  void OnDataRecv(const uint8_t *mac_addr, const uint8_t ↘
4                  *incomingData, int data_len) {
5      if (incomingData[0] == 253) {           // setup data
6          applyMetaInformation(incomingData, data_len);
7          return;
8      }
9      if (incomingData[0] == 255) {           // verify data
10         applyPayload(incomingData, data_len);
11     }
12     if (incomingData[0] == 254) {           // return results
13         sendResultsToMaster();
14         return;
15     }
16 }

```

Listing 4.4 – ESP-NOW Callback Functions

Chapter 5

Evaluation

5.1 Methodology

One challenge in programming the controller and the WESs, is the state-based approach and the fact that the WESs can only communicate restricted to each other. There were therefore two types of state machines, one for the controller and one for the WESs.

The testbed Figure 5.1 is set up that the PC is connected to the microcontroller via wired Universal Asynchronous Receiver Transmitter (UART), this microcontroller is the controller. The controller then communicates exclusively via ESP-NOW with the WESs, these then control in different ways with the stage lights and motors. The WESs never respond to the controller for the actual application, the communication is unidirectional. However, in order to evaluate the test data, the WESs are put into a mode in which they send the data to the controller, also via ESP-NOW. From there, they are also sent to the PC via UART.




Figure 5.1 – Data Flow for Measurement

change N to the actual
number of WESs = 7

The experiment is started from the PC, a JSON is then transmitted to the controller via UART using a Python script. The JSON contains all the parameters that are needed to carry out a test. At the time the JSON string is transmitted, the controller should be idle so that the packet is read correctly.

Variable	Example	Explanation
VERBOSE	0	Enable VERBOSE
DEBUG	0	Enable DEBUG
TIMESTAMP_UART	0	Enable UART timestamps
SEQUENCE_REPETITIONS	200	Sequences per experiment
FULL_REPETITIONS	1000	Repetitions of the experiment
MASTER_CHANNEL	6	Wifi Channel of the Controller
WES_CHANNEL	6	Wifi Channel of the WES
WAIT_AFTER_SEQ	0	delay between sequences
WAIT_AFTER_REP_EXP	2000	delay between experiments
IS_BROADCASTING	1	BC:=1, UC:=0
RAPID_REPETITION	2	BC: Rapid Repetitions
CHANNEL_TOTAL	160	BC: Addressed Payload
BROADCAST_FRAME_SIZE	200	BC: Maximum Payload/Broadcast
UNICAST_FRAME_SIZE	20	UC: Payload/Unicast
WES_COUNT	6	UC: WES Count
AIRTIME	0	Capture airtime

Table 5.1 – JSON Experiment Setup

When the controller has received its JSON, it must go through three states, regardless of further input from the PC Figure 5.2.

Setup

After the start-up, the controller waits for a JSON. When the JSON is received, it sets the corresponding variables. It then forwards these to the individual WESs using unicast. To be absolutely sure that the respective WES has received the setup information, the number of retransmits in the application layer is set to infinity. It distributes the data round robin, the MAC addresses of all WESs are hardcoded, but could also be transmitted via JSON. If the first byte of the setup unicast is set to 253, the WES knows that it is a metadata packet and handles it accordingly in its callback.

Testing

When the controller has ensured that each WES has received the measurement data, it starts transmitting the dummy test data. Sequences are then sent according to the variable SEQUENCE_REPETITIONS. The duration varies greatly depending on the number of sequences and the protocol used.

Collecting

When the controller has processed all sequences, it makes a request to one of the WESs, again with the help of a 100% reliable unicast forced on the application layer. This then transmits the measured values and in turn ensures that these have also arrived at the controller. The measured values are then transmitted to the PC and the experiment is repeated until the required number of experiments has been completed.




Figure 5.2 – Sequence Diagram of the Measurement

5.2 Wireshark measurements

The Wireshark tool is suitable for recording traffic. In order to record packets outside of a LAN, the WIFI card must be set to monitor mode. In this mode, frames from an ad-hoc network can also be sniffed, as is the case with ESP-NOW. In Figure 5.3 it is

clear to see that each unicast is followed by an acknowledgement, as mentioned in the Chapter 3.

No.	Time	Source	Destination	Length	Info
1	0.000000	Espressi_31:69:0c	Espressi_31:9a:44	119	Action, SN=23, FN=0, Flags=
2	0.000012		Espressi_31:69:0c...	70	Acknowledgement, Flags=...
3	0.001224	Espressi_31:69:0c	Espressi_31:9a:44	119	Action, SN=24, FN=0, Flags=
4	0.001258		Espressi_31:69:0c...	70	Acknowledgement, Flags=...
5	0.002315	Espressi_31:69:0c	Espressi_31:9a:44	119	Action, SN=25, FN=0, Flags=
6	0.002350		Espressi_31:69:0c...	70	Acknowledgement, Flags=...
7	0.003408	Espressi_31:69:0c	Espressi_31:9a:44	119	Action, SN=26, FN=0, Flags=
8	0.003443		Espressi_31:69:0c...	70	Acknowledgement, Flags=...
9	0.004522	Espressi_31:69:0c	Espressi_31:9a:44	119	Action, SN=27, FN=0, Flags=
10	0.004534		Espressi_31:69:0c...	70	Acknowledgement, Flags=...
11	0.005600	Espressi_31:69:0c	Espressi_31:9a:44	119	Action, SN=28, FN=0, Flags=
12	0.005634		Espressi_31:69:0c...	70	Acknowledgement, Flags=...

Figure 5.3 – Unicast Transmissions Recording from Wireshark

A look into the data frame Figure 5.4 also shows the measured airtime of $696\mu\text{s}$. Adding the average backoff of a free channel ($160\mu\text{s}$) and the DIFS ($50\mu\text{s}$) gives $906\mu\text{s}$. In the calculation from Table 4.2, however, it was only $746\mu\text{s}$. The difference of $120\mu\text{s}$ can be... Wireshark also recognises the category code of the Vendor Specific Action Frame that ESP-NOW uses. The payload of 20 bytes assumed for unicast in the experiment is given here as 31 bytes, presumably it has to do with the implementation of the action frame shown in Table 3.3, even though I can only figure out an offset of 10 bytes.

TOLJA!
yes.... actually why?

is this personal note
OK?

```

▼ 802.11 radio information
  PHY type: 802.11b (HR/DSSS) (4)
  Short preamble: False
  Data rate: 1.0 Mb/s
  Channel: 1
  Frequency: 2412MHz
  Signal strength (dBm): -71 dBm
  TSF timestamp: 3013560838338
  ▶ [Duration: 696µs]
▼ IEEE 802.11 Action, Flags: .....C
  Type/Subtype: Action (0x000d)
  ▼ Frame Control Field: 0xd000
    ....00 = Version: 0
    ....00.. = Type: Management frame (0)
    1101.... = Subtype: 13
    ▶ Flags: 0x00
      .000 0001 0011 1010 = Duration: 314 microseconds
      Receiver address: Espressi_31:9a:44 (fc:f5:c4:31:9a:44)
      Destination address: Espressi_31:9a:44 (fc:f5:c4:31:9a:44)
      Transmitter address: Espressi_31:69:0c (fc:f5:c4:31:69:0c)
      Source address: Espressi_31:69:0c (fc:f5:c4:31:69:0c)
      BSS Id: Broadcast (ff:ff:ff:ff:ff:ff)
      .....0000 = Fragment number: 0
      0000 0001 1111 .... = Sequence number: 31
      Frame check sequence: 0xaad022ed [unverified]
      [FCS Status: Unverified]
▼ IEEE 802.11 Wireless Management
  ▼ Fixed parameters
    Category code: Vendor Specific (127)
    OUI: 18:fe:34 (Espressif Inc.)
    ▼ Data (31 bytes)
      Data: 019f35a3dd1918fe340401ff0802030405060708090a0b0c0d0e0f10111213
      [Length: 31]


```

Figure 5.4 – Unicast Transmission Radio Information from Wireshark

A look at the 31 byte "payload" shows that ESP-NOW specific parts of wireshark have not been parsed correctly. From the representation Table 3.2 and Table 3.2 it can be deduced:

that the first 4 bytes of the payload are still the random values and, according to Espressif, do not belong to the Vendor Specific Content. These 4 bytes together with the following 1 byte (Element ID), 1 byte (length, interestingly specified as 25 Byte instead of 20), Organisation Identifier (3 bytes), Type (1 byte) and Version (1 byte) make up the difference of 11 bytes to the actual payload. The payload is filled with the flag ff Section 4.2 followed by the sequence number, in this example 0. The rest of the payload is filled with numbers, which are set to the value of the position in the payload.

This is barely readable



Offset	Hex	ASCII
0000	fd 32 10 fd dd 19 18 fe 34 04 01 ff 00 02 03 04 05 06 07 08 09 0a 0b 0c 0d 0e 0f 10 11 12 13	--8./@@.
0010		--9.... --l....
0020		5-9....
0030		--1
0040		D--1i.p
0050		--4-2-....4-...
0060	
0070	

Figure 5.5 – Unicast Payload Analysis with Wireshark

For completeness, here is a recording of the broadcast traffic. The difference to the unicast traffic in Figure 5.4 is, that the destination address is bundled in a transmission of 160 bytes instead of being distributed in 8x20 byte packets. As already mentioned, the acknowledgments are not possible with the broadcast.

No.	Time	Source	Destination	Length	Info
1	0.000000	Espressi_31:69:0c	Broadcast	259	Action, SN=2994, FN=0, Flags=.....C
2	0.002087	Espressi_31:69:0c	Broadcast	259	Action, SN=2995, FN=0, Flags=.....C
3	0.004136	Espressi_31:69:0c	Broadcast	259	Action, SN=2996, FN=0, Flags=.....C
4	0.006022	Espressi_31:69:0c	Broadcast	259	Action, SN=2997, FN=0, Flags=.....C

Figure 5.6 – Unicast Payload Analysis with Wireshark

5.3 Protocols under Study

Slim Unicast vs Slim Broadcast

In the design part it became clear that it is much more efficient to reach many individual WESs with one broadcast instead of many individual unicasts. Tracking the transmissions with Wireshark also confirms this assumption Figure 5.7.

Improve Graph. Transmissions is unclear

The theoretical assumptions clearly correspond to the measured values, Additional latencies due to processing in the microcontroller or at the antenna are therefore hardly significant. When evaluating the graph, however, it should be noted that eight unicast transmissions have the same payload as a single broadcast transmission, by a factor of 4. Therefore, a broadcast is clearly superior to a unicast in terms of latency, update frequency and synchronisation.




Figure 5.7 – E.g. Transmission Time of Slim Unicast and Slim Broadcast

Slim Unicast can only make a difference through its reliability. The channel in the experiment was free, so no retransmissions had to be sent, which would have delayed the transmission time even more. When implementing slim unicast, it makes sense to do without synchronisation, because the buffering delay would be too long. However, it is also difficult to estimate how many transmissions can be saved if only changed values trigger a transmission, but it makes sense to simulate a stress test because critical errors become apparent precisely when packets are lost and all values are changed.

It can be said that Slim Broadcast is the superior design due to the much lower part of overhead, because the data throughput is significantly higher. The WESs can also be synchronised more easily because the transmissions reach many people at the same time. The weak point, however, is reliability.

Rapid Repetition

Success Ratio is a good metric to measure reliability, it is calculated from the number of successfully received packets and the total number of packets sent. In a test setup of 7 distributed WESs, some placed close to the controller, some at a slightly greater distance, this naturally varies greatly Figure 5.8. The measurement was carried out in a flat distributed over different rooms. Several WLANs are on the 2.4GHz band and lead to indifferences. For the slim broadcast, 160Byte packets were distributed in a 600 sequence. the experiment was repeated 1000 times.

It shows that especially WESs 4 and WES 7 have poor reception. The reception of other WESs is much better. It should be said that with the Slim Unicast 100% of the packets arrived and there was no loss of data. One approach to improving reliability at the expense of latency was rapid repetitions.

how to show 100% success ratio?




Figure 5.8 – SR des Broadcasts aller 7 WESs

With RR, it must be weighed up how many repetitions are sensible, because at some point the performance beyond reliability is impaired too much. WES4 has the weakest reception and is supposed to represent a kind of worst-case scenario. The measurement data of the same measurement as for Figure 5.8 are used as a basis, so that a comparability is given. With $RR=0$, the unchanged SR is taken over, with $RR=X$, X transmissions are always linked in pairs to one with an or.




Figure 5.9 – SR of WES4 with altered RRs

It becomes clear that even a few repetitions lead to a significantly better SR. But it also becomes clear that this is no longer improved as much after two repetitions. However, a reliability of 100% as with unicast is not necessarily achieved. A look at the measurement data shows why Figure 5.10.

The given excerpt is from an actual measurement of the WES4, the channel here is really very bad and there is massive packet loss. When the repetitions are increased from $RR=0$ to $RR=1$, the loss of packets is slightly dampened. However,




Figure 5.10 – Bitwise Example of RR (WES=4, SeqNr.=9-24, ExpNr.=1)

it is noticeable that even with $RR=3$, one sequence is still lost, despite the 4x costs of latency and throughput. The problem is that faulty packets often come clustered and the repetitions still fall within the range of the bad channel.

Delayed Repetition

To circumvent this circumstance, the sequences can be nested Figure 4.5, this is only possible in combination with the Rapid Repetitions. Subsequently swapping the sequence numbers makes it possible to make an evaluation on the same data. WES4 is chosen again because the packet loss is greatest here.

Success Ratio for two and three transmissions




Figure 5.11 – SR for Buffering Delay with/without RR for WES4

In Figure 5.11 it is quite clear that the success ratio increases the longer the delay of the repetition. However, the improvement converges quite quickly. It can therefore be assumed that the success ratio is noticeably improved with a constant update frequency, at least with a buffering delay of 1, is the effect significant. It also shows that the use of the buffering delay does not improve the success ratio so much

update Graphic!

How significant - after the plot is updated, give an exact example

that one less repetition could be sent. In addition, the use of buffering delay has a cost in latency, as mentioned in FIGURE. . It must therefore be weighed up whether the additional latency justifies the increased success ratio.

link to graphic of buffering delay latency theory

Impact of Groupsize

optional

When controlling lighting installations, the human eye does not notice so clearly if all lights are switched synchronously but with a delay. However, it is clearly noticeable when a single light reacts with a delay. With the BUffering Delay, synchronisation can be achieved, but what happens if a control signal does not arrive even despite RR and BD? In the following, the Success Ratio is only considered successful if the control signals have arrived at all WESs.

optional: SR Figure, different approaches with groupsize of 7, UC, BC, RR=1, RR=1+DR=1 RR=2, RR=2+DR+1, RR=3. RR=3+DR=1, RR=3+DR+2

Evaluation

optional: write evaluation

5.4 Results

Difference between Results and Discussion?

- Which method had the best results?
- Tabelle mit allen Protokollen auflisten

Chapter 6

Conclusion & Discussion

- summarize again what your paper did, but now emphasize more the results, and comparisons
- write conclusions that can be drawn from the results found and the discussion presented in the paper
- future work (be very brief, explain what, but not much how, do not speculate about results or impact)
- recommended length: one page.

Why not 5GHz -> too expensive.

Keep in Mind

- metrics (SR, Latency, ...)
- compare with art-net all the time
- wireshark

List of Abbreviations

AP	Access Point
BSS	Basic Service Set
BSSID	Basic Service Set Identifier
CAN	Controller Area Network, <i>when referring to the bus protocol</i>
CSMA/CA	Carrier-sense Multiple Access with Collision Avoidance
DIFS	DCF Inter Frame Spaces
DL	Data Link Layer
DMX	Digital Multiplex
DSSS	Direct Sequence Spread Spectrum
FHSS	Frequency Hopping Spread Spectrum
IEEE	Institut of Electrical and Electronics Engineers
IP	Internet Protocol
LLC	Locig Link Control
MAC	Media Access Control
MCU	Microcontroller Unit
MIMO	Multiple Input-Multiple Output)
MSDU	MAC Service Data Unit
NAV	Network Allocation Vector
OFDM	Orthogonal Frequency Division Multiplexing)
OSI	Open Systems Interconnection
PHY	Physical Network Layer
SIFS	Short Inter Frame Spaces
STA	Station
UART	Universal Asynchronous Receiver Transmitter
UDP	User Datagram Protocol
WES	Wireless Endsystem
WLAN	Wireless Local Area Network

List of Figures

3.1	MAC header of a WLAN frame	7
3.2	Unicast Transmission	9
3.3	Broadcast Transmission	9
3.4	Multicast Transmission	10
3.5	Block Diagram of an DMX Universe	11
3.6	ESP32 Devboard (Devkit V1)	12
4.1	Topology of the Data Flow	17
4.2	Transmission Time of Broadcasts Depending on Payload	21
4.3	Transmission Time of Unicast vs Broadcast	22
4.4	Transmission Time with with different sets of Rapid Repetition (RR)	23
4.5	Rapid Repetition = 3 over a occuring noise	23
4.6	Flashing ESP From the website of Espressif	24
5.1	Data Flow for Measurement	27
5.2	Sequence Diagram of the Measurment	29
5.3	Unicast Transmissions Recording from Wireshark	30
5.4	Unicast Transmission Radio Information from Wireshark	30
5.5	Unicast Payload Analysis with Wireshark	31
5.6	Unicast Payload Analysis with Wireshark	31
5.7	E.g. Transmission Time of Slim Unicast and Slim Broadcast	32
5.8	SR des Broadcasts aller 7 WESs	33
5.9	SR of WES4 with altered RRs	33
5.10	Bitwise Example of RR (WES=4, SeqNr.=9-24, ExpNr.=1)	34
5.11	SR for Buffering Delay with/without RR for WES4	34

List of Tables

3.1	OSI model	5
3.2	ESP-NOW Frame Format	13
3.3	Vendor Specific Action Frame	14
4.1	Art-Net Layer compared with Slim Data Link Layer	16
4.2	Composition of the Total Airtime (tx + ack)	18
4.3	Composition the Broadcast Airtime	20
5.1	JSON Experiment Setup	28

List of Listings

4.1	Init ESP-NOW	25
4.2	Add Peers	25
4.3	Send ESP-NOW Cast UC/BC	25
4.4	ESP-NOW Callback Functions	26

Bibliography

- [1] D. D. Husam Kareem, “The Working Principles of ESP32 and aAnalytical Comparison of using Low-Cost Microcontroller Modules in Embedded Systems Design,” *4th International Conference on Circuits, Systems and Simulation*, vol. 40, no. 8, pp. 130–135, Aug. 2021. DOI: 10.1109/ICCSS51193.2021.9464217.
- [2] I. F. Akyildiz, W. Su, Y. Sankarasubramaniam, and E. Cayirci, “A Survey on Sensor Networks,” *IEEE Communications Magazine*, vol. 40, no. 8, pp. 102–114, Aug. 2002. DOI: 10.1109/MCOM.2002.1024422.
- [3] K. A. Roberto Pasic Ivo Kuzmanov, “ESP-NOW communication protocol with ESP32,” *Journal of Universal Excellence*, vol. 40, no. 8, pp. 53–60, Feb. 2021. DOI: 10.37886/ip.2021.019.

Todo list

<input type="checkbox"/>	TOLJA: Wirklich noch einmal auf deutsch?	iv
<input type="checkbox"/>	The table of contents should fit on one page. When in doubt, adjust the tocdepth counter.	vi
<input type="checkbox"/>	Introduction Introduction (sic!) schreiben	1
<input type="checkbox"/>	link in footnote	2
<input type="checkbox"/>	triple-check all references	4
<input type="checkbox"/>	introduction in chapter Fundamentals ok?	5
<input type="checkbox"/>	TOLJA: Was soll ich zum PHY alles sagen?	6
<input type="checkbox"/>	Payload and FCS are missing	7
<input type="checkbox"/>	Short introduction	8
<input type="checkbox"/>	when to explain CSMA/DC?	9
<input type="checkbox"/>	example	9
<input type="checkbox"/>	complete figure UC	9
<input type="checkbox"/>	complete figure BC	9
<input type="checkbox"/>	Mutlicast explain multicast mac address	10
<input type="checkbox"/>	examples for multicast ack + related work	10
<input type="checkbox"/>	complete figure MC	10
<input type="checkbox"/>	image der connectoren	10
<input type="checkbox"/>	Show Hardware e.g. DMX Plug	10
<input type="checkbox"/>	Image of fixtures distributed on channel	11
<input type="checkbox"/>	TOLJA: ESP32 Kosten in € 2021 aufführen? Link? Datum?	12
<input type="checkbox"/>	paper about esp above arduino	12
<input type="checkbox"/>	this is cited from: link zum esp32 datasheet	12
<input type="checkbox"/>	final words to the ESP32 Hardware - a lot of features for a cheap hardware	12
<input type="checkbox"/>	cite ESP documentation website	13
<input type="checkbox"/>	cite somehow the ESP-NOW documentation pdf: ESP-IDF Programming Guide: ESP-NOW, source: https://docs.espressif.com/projects/esp-idf/en/latest/esp32/api-reference/network/esp_now.html	13
<input type="checkbox"/>	Explain Vendor Specific Frames!	13
<input type="checkbox"/>	this is cited from espressif manual!!	14

255 != 250 is it really that important?	14
subsection can be on a wrong position!	14
remove newpage command	14
ESP-NOW Baseline Artnet should be moved to Design part??	15
topology of data flow isnt linked in the text	17
ref to requirements	17
Discuss the inimportance of order of round robin in unicast	19
or buffering delay?	19
...buffering delay	19
Is it tru, that retransmission can't be controlled in ESP-NOW?	20
quelle 200 byte	20
it's ok to make an example here?	21
ref to fundamentionals, datalink, broadcast	21
ist der Satz gramatisch flasch? Lass ihn einfach weg...	22
Is Rapid Repetition a appropriate name? Unsosliced Repetition is better siehe Paper?	22
Cite paper A First Implementation and Evaluation of the IEEE 802.11aa Group Addressed Transmission Service	22
displaced repetition vs delayed repetition	23
Buffering delay Latency figure	24
Explain Problem with synchronization?!	24
Check, because of split from testbed	24
zeitangabe website aliexpress?	24
link und Quellenangabe: https://docs.espressif.com/projects/esp-idf/en/latest/esp32/get-started/index.html	24
for later use: ESP-NOW User Guide, V1, source: https://www.espressif.com/en/support/documents/	24
link einpflegen	24
listing box prevent linebreaks on newpage	25
change N to the actual number of WESs = 7	27
TOLJA! yes.... actually why?	30
is this personal note OK?	30
This is barely readable	31
Improve Graph. Transmissions is unclear	31
how to show 100% success ratio?	32
update Graphic!	34
How significant - after the plot is updated, give an exact example	34
link to graphic of buffering delay latency theory	35
optional	35

■ optional: SR Figure, different approaches with groupsize of 7, UC, BC, RR=1, RR=1+DR=1 RR=2, RR=2+DR+1, RR=3. RR=3+DR=1, RR=3+DR+2	35■
■ optional: write evaluation	35
■ Difference between Results and Discussion?	35