

Quantifying Material, Energy, Carbon, and Human-Workload Trade-offs of AI-Enabled Defect Prevention in Edge Manufacturing Inspection

Utkarsh Sengar

Abstract—While computer vision and deep anomaly detection are increasingly deployed on industrial edge devices for automated quality control, their net sustainability impact is frequently taken for granted under the assumption that automated inspection is inherently “green.” In high-throughput manufacturing, continuous edge inference, machine rework, review workstations, and false alarm triage incur physical energy and embodied compute footprints that compete directly with the scrap and carbon emissions saved through early defect intervention. This paper introduces a conservation-enforcing scenario-based operational framework that quantifies the multi-dimensional trade-offs between material savings (ΔM), operational energy (ΔE), greenhouse gas emissions (ΔC), and operator cognitive review hours (ΔH) across a functional unit of 1,000 inspected parts. Grounded in synchronized physical power measurements on an active NVIDIA RTX 4050 Laptop GPU under 100 Hz NVML sampling, the framework couples a delay-sensitive quality intervention model with a 5-tier policy hierarchy ($B0$ raw baseline to $B4$ full dual-EMA cost-calibrated cascade) across three contrasting industrial scenarios: lightweight precision components, structural machined metal, and high-value battery modules. We demonstrate that timely edge cascade inspection suppresses nuisance alarms from 180 to 12 alerts/hr ($\rho = 0.20$), enabling prompt rework that recovers +0.228 kg to +48.57 kg of virgin material per 1,000 units. However, by solving analytical and numerical break-even frontiers, we show under defined assumptions that edge AI is not universally carbon-beneficial: in lightweight parts ($m = 0.015$ kg) with low defect rates ($\pi < 0.005\%$) or unoptimized compute ($e_{\text{edge}} > 127$ kWh/1k units), edge compute emissions dominate avoided scrap carbon, producing a net-negative carbon regime. We synthesize these trade-offs into a normalized, bounded Multi-Profile Sustainability Quality Index (SQI) evaluated over 10,000-draw Monte Carlo uncertainty sweeps.

Index Terms—Sustainable manufacturing, edge intelligence, defect prevention, life cycle assessment, industrial anomaly detection, power profiling, circular economy, Industry 5.0.

I. INTRODUCTION

THE vision of Industry 5.0 places environmental sustainability, circular material flows, and human-centric operations at the core of advanced manufacturing systems. In high-speed discrete manufacturing—spanning electronic sensor enclosures, precision CNC automotive brackets, and high-energy battery modules—automated optical inspection (AOI) powered by edge deep learning models has emerged as the premier mechanism to intercept manufacturing defects. Recent advances in unsupervised anomaly detection, such as

coreset-subsampled nearest-neighbor patch representations and feature distribution embeddings [1]–[3], have achieved near-perfect localized defect detection on standardized industrial benchmarks.

However, an uncritical narrative currently pervades both industrial automation literature and corporate sustainability reporting: the blanket assertion that deploying edge AI for inspection is intrinsically “green” because catching defects avoids scrap [4], [5]. This naive assumption overlooks the gate-to-gate thermodynamic and operational realities of physical factory floors:

- 1) **Continuous Edge Power Draw:** An edge industrial computer running a deep neural network at 30 frames per second (FPS) draws substantial active electrical power continuously, regardless of whether a defective component is currently under the optical lens [6].
- 2) **Secondary Rework Energy:** Intercepting a defective component does not eliminate resource expenditure if the unit is routed to thermal, chemical, or mechanical secondary rework lines, which themselves consume significant electricity [7].
- 3) **Operator Alert Fatigue and Workstation Energy:** Raw uncalibrated anomaly detectors emit severe rates of false positives (150–220 alarms/hr), driving manual verification queues into acute cognitive overload ($\rho \geq 3.0$), causing human operator burnout and keeping industrial review workstations continuously energized [8], [9].
- 4) **Delay Degradation:** In high-speed continuous lines, temporal filtering policies that accumulate evidence across sliding windows incur latency delays; in adhesive curing, CNC finishing, or thermal bonding processes, even short physical delays degrade the unit’s reworkability, irreversibly converting candidates into gross scrap.

To date, no established framework couples empirical edge inference power traces with delay-sensitive quality intervention dynamics and rigorous life-cycle material and carbon accounting. Consequently, production engineers lack analytical tools to determine whether deploying an edge inspection cell on a given production line achieves a net carbon reduction or inadvertently expands the factory’s Scope 2 greenhouse gas emissions.

A. Contributions

This paper resolves this fundamental gap by formulating, implementing, and empirically validating the complete research platform for Paper B. Our primary contributions are:

U. Sengar is with the Department of Computer Science and Engineering, Indian Institute of Technology Dharwad, Karnataka 580011, India (e-mail: cs23b026@iitdh.ac.in).

- **Conservation-Enforcing Quality Intervention Engine:** We formulate a formal mathematical quality intervention model that enforces strict count invariance ($D = N_{\text{rework}} + N_{\text{scrap}} + N_{\text{escape}}$) and delay-sensitive reworkability decay across three standardized defect classes.
- **Live Hardware Energy Benchmarking:** We report synchronized 100 Hz physical power measurements on an active NVIDIA GeForce RTX 4050 Laptop GPU under WSL2 across quiescent idle (10.03 W), inference-only, Cost-Calibrated Thresholding (CCT), 7-stage cascade policy, and SQLite WAL telemetry stages.
- **5-Tier Policy Sustainability Accounting:** We evaluate five operational policy tiers ($B0$ raw baseline, $B1$ quantile-99, $B2$ CCT, $B3$ CCT+ k -of- N , and $B4$ full cascade) across three industrial scenarios, demonstrating that policy $B4$ achieves up to +1812.21 kgCO₂e carbon reduction while cutting review queue utilization from 3.00 to 0.20.
- **Discovery of Net-Negative Carbon Regimes:** We derive analytical break-even frontiers (π^* , e_{edge}^* , d^* , γ^*), demonstrating that for lightweight components ($m = 0.015$ kg) under low defect prevalence ($\pi < 0.005\%$), continuous edge compute energy exceeds avoided scrap emissions, creating a net-negative carbon regime.
- **Multi-Profile Sustainability Quality Index (SQI):** We introduce a bounded, normalized scalar index integrating material, energy, carbon, and human factors across four distinct stakeholder priority profiles.
- **Reproducible Open-Source Platform:** We release the complete test-verified codebase, simulation engine, and publication artifacts under an open-source contract.

II. RELATED WORK

A. Industrial Anomaly Detection and Edge Benchmarking

Unsupervised anomaly detection in manufacturing has advanced rapidly following the introduction of the MVtec Anomaly Detection (MVtec AD) benchmark [1]. Exemplar architectures such as PatchCore [2] utilize coreset-subsampled memory banks of mid-level CNN features to achieve localized detection without defect training samples. PaDiM [3] replaces nearest-neighbor search with parametric patch Gaussian distributions, reducing memory footprint at the expense of localization sharpness.

While academic benchmarks emphasize ROC-AUC and PRO metrics, Flagship 1 [10] demonstrated that standard uncalibrated thresholds produce intolerable false positive rates in operational regimes and formulated Cost-Calibrated Thresholding (CCT) to minimize misclassification and escape losses. Subsequently, Flagship 4 / Paper A [8] addressed high-speed temporal false-alarm bursts on continuous streams by introducing a 7-stage temporal cascade (Dual-EMA filtering, k -of- N sliding window persistence, and state-gated cooldown) coupled with SQLite WAL audit event spooling, suppressing false alarms by up to 93.3% while bounding median detection delay to 3.0 frames. However, Paper A focused solely on operational reliability and alert fatigue, leaving the environmental, energy, and material life-cycle consequences unmeasured.

B. Life Cycle Assessment and Edge Energy Accounting

Life Cycle Assessment (LCA) methodologies, standardized under ISO 14040/14044 [11], have extensively analyzed primary material production and bulk machining energies [4], [7]. Gutowski et al. [4] characterized the specific electrical energy consumption of subtractive CNC milling (1.0–3.5 kWh/kg) and polymer injection molding (2.0–6.0 kWh/kg), establishing that scrap generation destroys not only embodied material carbon but also significant processing electricity.

In parallel, energy profiling of machine learning workloads has garnered immense scrutiny [5], [6]. Nevertheless, existing AI carbon accounting models focus overwhelmingly on cloud datacenter training phases. Edge inference energy in cyber-physical manufacturing systems remains under-reported, with most sustainability studies assuming compute footprints to be negligible ($< 0.01\%$) relative to manufacturing process energy. In this work, we demonstrate that in lightweight, high-volume production, this assumption is false.

III. SYSTEM BOUNDARY & METHODOLOGICAL FRAMEWORK

A. Functional Unit and System Scope

To ensure rigorous comparability across heterogeneous production environments, we establish a standardized functional unit:

$$FU = 1,000 \text{ consecutively inspected discrete parts.} \quad (1)$$

The operational cadence is defined by an optical line-scan or matrix camera capture rate of $FPS = 30.0$ frames/second. Thus, inspecting one functional unit spans an active inspection duration of:

$$T_{FU} = \frac{N}{FPS} = \frac{1,000}{30.0} = 33.33 \text{ seconds.} \quad (2)$$

The corresponding line throughput is $\Theta = FPS \times 3,600 = 108,000$ parts/hour.

The system boundary constitutes a gate-to-gate industrial inspection and rework cell, illustrated in Fig. 1. The boundary explicitly encompasses:

- 1) **Active Edge Compute Infrastructure:** The electrical power consumed by the edge processing host, the dedicated GPU inference accelerator, the camera frame-grabber interface, and SQLite WAL persistence spooling.
- 2) **Human Review Workstation:** The active electrical power consumed by the high-resolution operator display, verification terminal, and lighting during manual review of candidate alarm frames.
- 3) **Secondary Rework Processing:** The operational electrical energy required by thermal reflow, CNC re-pass de-burring, or disassembly tooling to restore defective units to nominal tolerance.
- 4) **Embodied Material Loss:** The cradle-to-gate embodied greenhouse gas emissions (EF_{mat}) of virgin material permanently lost as unrecovered scrap.
- 5) **Quality Escape Penalties:** The lifecycle greenhouse gas penalty (C_{escape}) incurred when an unintercepted defective part escapes to downstream assembly or field operations.

Fig 1: Mass, Energy, and Defect Flow Routing in AI-Enabled Edge Inspection




Fig. 1. System boundary and material/energy flow routing in the proposed sustainable edge quality intelligence framework. Defective parts within a functional batch of $N = 1,000$ units are partitioned into routed versus missed flows based on actionable recall r_p . Timely intervention preserves reworkability $q_{rw}(d)$, converting potential gross scrap into circular rework while routing unrecovered swarf to secondary remelting.

Upstream supply chain transport and factory facility HVAC base loads are held invariant across policy comparisons and are excluded from the delta accounting.

B. Parameter Ledger and Classification Integrity

All empirical calculations in this platform are strictly derived from single-source-of-truth registries validated against Pydantic schemas. Table I details the parameter ledger, documenting units, uncertainty bounds, and formal classification categories.

IV. QUALITY-TO-INTERVENTION DYNAMICS

A. Defect Taxonomy and Routing Conservation

In a batch of $N = 1,000$ inspected components with base defect prevalence π , the total defective population is $D = N \cdot \pi$. Defective parts are partitioned into three orthogonal functional taxonomy classes:

$$D = D_{\text{ClassA}} + D_{\text{ClassB}} + D_{\text{ClassC}}, \quad (3)$$

where Class A represents reworkable surface or dimensional anomalies, Class B represents non-reworkable structural scrap, and Class C represents critical escape-sensitive anomalies that precipitate field catastrophic failures.

Under inspection policy mode p operating with actionable routing recall $r_p \in [0, 1]$, the incoming defect population is routed along two distinct pathways:

$$D_{\text{routed}} = D \cdot r_p, \quad (4)$$

$$D_{\text{missed}} = D \cdot (1 - r_p). \quad (5)$$

B. Delay-Sensitive Reworkability Decay

In industrial manufacturing, the probability of successfully restoring an intercepted defective unit to prime quality degrades as a function of the inspection latency delay. In high-speed lines, physical delay translates into downstream processing distance (e.g., additional adhesive dispensing, curing advancement, or secondary cutting passes). Let $d^{(\text{frames})}$ be the policy decision delay in frames, and let FPS be the sensor frame rate. The delay in seconds is $d^{(s)} = d^{(\text{frames})} / \text{FPS}$.

We model the effective reworkability $q_{rw}(d)$ as an affine decay bounded below by zero:

$$q_{rw}(d) = \max(0.0, q_0 - \beta \cdot d^{(s)}), \quad (6)$$

where $q_0 \in (0, 1]$ represents the pristine zero-delay reworkability, and $\beta > 0$ is the empirical rework degradation coefficient (s^{-1}). Consequently, the complementary fraction that cannot be salvaged and must be condemned as gross scrap is:

$$q_{sc}(d) = 1.0 - q_{rw}(d). \quad (7)$$

The physical unit outcomes per functional unit are therefore:

$$N_{\text{rework}} = D_{\text{routed}} \cdot q_{rw}(d), \quad (8)$$

$$N_{\text{scrap}} = D_{\text{routed}} \cdot q_{sc}(d), \quad (9)$$

$$N_{\text{escape}} = D_{\text{missed}}. \quad (10)$$

Physical Invariant 1 (Strict Count Conservation):

$$|D - (N_{\text{rework}} + N_{\text{scrap}} + N_{\text{escape}})| \equiv 0. \quad (11)$$

Across all operational regimes, not a single defective part vanishes or is artificially fabricated by the accounting framework.

TABLE I
AUTHORITATIVE PARAMETER LEDGER WITH SOURCE CLASSIFICATIONS AND UNCERTAINTY RANGES.

Parameter Name	Symbol	Central	Range [Low, High]	Unit	Classification	Source / Citation	Operational Context
Edge Active Compute Power	P_{active}	18.5	[12.0, 28.0]	W	Measured by this study	NVML live GPU sampling	RTX 4050 active compute over quiescent idle
Continuous Edge Frame Energy	e_{frame}	0.171	[0.120, 0.250]	Wh/frame	Measured by this study	RTX 4050 physical profiling	Workcell energy at 30 FPS (615.6 J)
Inspection Frames per Part	n_f	1.0	[1.0, 10.0]	frames/part	Operational setting	Multi-angle line spec	Multi-view inspection factor (nominal 1, sweep [1, 10])
Review Workstation Power	P_{station}	85.0	[65.0, 120.0]	W	Measured by this study	Hardware power meter	Inspection terminal and display power
Baseline False Alarm Rate	λ_{B0}	180.0	[150.0, 220.0]	alerts/hr	Derived from Paper A	Sengar (2026) [8]	Uncalibrated threshold false alert arrival rate
Cascade False Alarm Rate	λ_{B4}	12.0	[8.0, 18.0]	alerts/hr	Derived from Paper A	Sengar (2026) [8]	Full 7-stage cascade sustained alert rate
Review Service Capacity	μ	60.0	[45.0, 75.0]	reviews/hr	Derived from Paper A	Chaffin et al. [9]	Single operator manual verification throughput
Cascade Detection Delay	d	3.0	[2.0, 5.0]	frames	Derived from Paper A	Sengar (2026) [8]	Temporal persistence sliding window latency
PatchCore Actionable Recall	r_p	0.99	[0.95, 1.00]	fraction	Benchmark-derived	Flagship 1 [10]	Actionable defect recall under CCT threshold
Grid Carbon Intensity (EU-27)	γ	0.417	[0.350, 0.520]	kgCO ₂ e/kWh	Official public dataset	EEA (2024) [12]	European Environment Agency grid emission factor
Part Mass (Scenario A)	m_A	0.015	[0.010, 0.020]	kg	Scenario assumption	OEM specification	Lightweight sensor housing
Part Mass (Scenario B)	m_B	1.250	[1.000, 1.600]	kg	Scenario assumption	OEM specification	Structural CNC machined aluminum bracket
Part Mass (Scenario C)	m_C	14.500	[12.000, 18.000]	kg	Scenario assumption	OEM specification	High-energy battery power module
Defect Prevalence (π_A, π_B, π_C)	π	0.04, 0.03, 0.015	$\pm 25\%$	fraction	Scenario assumption	ISO 2859-1 [13] / OEM	Industrial AQL inspection lot prevalence prior
Embodied Carbon (EF_{mat})	EF	3.5, 8.24, 22.5	$\pm 15\%$	kgCO ₂ e/kg	Literature-derived	Ashby (2012) [7] /ecoinvent	Cradle-to-gate primary material carbon factor
Material Recovery Fraction (η)	η	0.40, 0.85, 0.60	$\pm 15\%$	fraction	Scenario assumption	Circular economy data [14]	Scrap and offcut circular remelting yield
Rework Energy (e_{rw})	e_{rw}	0.05, 1.80, 5.50	$\pm 20\%$	kWh/unit	Literature-derived	Gutowski et al. [4]	Electrical energy per unit rework cycle
Escape Penalty Carbon (C_{escape})	C_{esc}	12.0, 65.0, 450.0	$\pm 20\%$	kgCO ₂ e	Literature-derived	Lifecycle return data	Teardown, reverse logistics, and recall penalty

C. Material Sustainability Accounting

Each scrapped part condemns gross physical mass $M_{\text{gross}} = N_{\text{scrap}} \cdot m$ [kg]. In a circular manufacturing facility, a fraction $\eta \in [0, 1]$ of scrap swarf or rejected billet is captured for secondary remelting or mechanical recycling. The circular recovery mass is:

$$M_{\text{recovered}} = M_{\text{gross}} \cdot \eta. \quad (12)$$

The net unrecovered material permanently lost to downcycling or landfill is:

$$M_{\text{loss}} = M_{\text{gross}} \cdot (1 - \eta). \quad (13)$$

When comparing a given inspection policy p against the uncalibrated baseline ($B0$), the net material saved from permanent loss is:

$$\Delta M = M_{\text{baseline}}^{\text{loss}} - M_p^{\text{loss}} \quad [\text{kg}]. \quad (14)$$

A positive ΔM reflects genuine reduction in virgin material demand.

D. Energy Sustainability Accounting

Operational energy consumption encompasses three distinct thermodynamic sinks:

$$E_{\text{total}} = E_{\text{edge}} + E_{\text{review}} + E_{\text{rework}} \quad [\text{kWh}]. \quad (15)$$

- 1) **Edge Compute Energy (E_{edge}):** Calibrated for the continuous inspection workcell at 30FPS, the edge compute energy per functional unit is:

$$E_{\text{edge}} = 1,000 \times \frac{e_{\text{frame}}}{1,000} = e_{\text{frame}} \quad [\text{kWh} / 1\text{k parts}]. \quad (16)$$

For our calibrated workcell drawing $P_{\text{active}} \approx 18.5$ W over 33.33 s, $E_{\text{edge}} = 0.171$ kWh ($e_{\text{frame}} = 0.171$ Wh = 615.6 J).

- 2) **Human Review Workstation Energy (E_{review}):** Let λ_p be the hourly alert arrival rate emitted by policy p . The number of alerts generated during the inspection of 1,000 units is:

$$n_{\text{alerts}} = \lambda_p \times \frac{1,000}{\Theta} = \lambda_p \times \frac{1,000}{\text{FPS} \times 3,600}. \quad (17)$$

If each alert requires t_{review} seconds of manual operator scrutiny at an energized terminal drawing P_{station} Watts, the total review duration in hours is:

$$H_p = n_{\text{alerts}} \times \frac{t_{\text{review}}}{3,600} \quad [\text{hours}]. \quad (18)$$

The workstation electrical energy consumption is:

$$E_{\text{review}} = H_p \times \frac{P_{\text{station}}}{1,000} \quad [\text{kWh}]. \quad (19)$$

- 3) **Machine Rework Energy (E_{rework}):** Restoring N_{rework} units on secondary processing lines consumes electrical energy:

$$E_{\text{rework}} = N_{\text{rework}} \cdot e_{\text{rw}} \quad [\text{kWh}]. \quad (20)$$

The net operational energy difference relative to baseline is:

$$\Delta E = E_{\text{baseline}}^{\text{total}} - E_p^{\text{total}} \quad [\text{kWh}]. \quad (21)$$

When active compute and secondary rework exceed baseline review energy, $\Delta E < 0$, accurately quantifying the net electrical energy investment required to achieve quality compliance.

E. Carbon Footprint Accounting

The total gate-to-gate greenhouse gas footprint is composed of embodied material emissions, electricity emissions, and field escape penalties:

$$C_{\text{total}} = C_{\text{mat}} + C_{\text{elec}} + C_{\text{escape}} \quad [\text{kgCO}_2\text{e}]. \quad (22)$$

$$C_{\text{mat}} = M_{\text{loss}} \cdot EF_{\text{mat}}, \quad (23)$$

$$C_{\text{elec}} = E_{\text{total}} \cdot \gamma, \quad (24)$$

$$C_{\text{escape}} = N_{\text{escape}} \cdot C_{\text{esc}}, \quad (25)$$

where $\gamma = 0.417$ kgCO₂e/kWh is the official EU-27 average grid electricity carbon factor [12], and C_{esc} is the lifecycle carbon penalty of an escaped defective unit (field returns, warranty logistics, pack disassembly).

The net greenhouse gas benefit relative to baseline decomposes into five additive operational waterfall drivers:

$$\Delta C = \Delta C_{\text{mat}} + \Delta C_{\text{rw}} + \Delta C_{\text{rev}} - C_{\text{edge}} + \Delta C_{\text{esc}} \quad [\text{kgCO}_2\text{e}], \quad (26)$$

where $\Delta C_{\text{mat}} = \Delta M \cdot EF_{\text{mat}}$ represents embodied scrap savings, $\Delta C_{\text{rw}} = \gamma(E_{\text{rw}}^{\text{base}} - E_{\text{rw}}^p)$ reflects machine rework electricity,




Fig. 2. Synchronized empirical power profiling on the physical NVIDIA RTX 4050 Laptop GPU under 100Hz NVML telemetry across standardized pipeline stages. Left: active compute power P_{active} (W) above quiescent idle (10.03 W). Right: calibrated continuous frame energy e_{frame} (mWh/frame) and inference throughput (FPS).

$\Delta C_{\text{rev}} = \gamma(E_{\text{rev}}^{\text{base}} - E_{\text{rev}}^p)$ captures suppressed workstation review hours, $-C_{\text{edge}} = -\gamma E_{\text{edge}}$ is the continuous compute burden, and $\Delta C_{\text{esc}} = (N_{\text{esc}}^{\text{base}} - N_{\text{esc}}^p)C_{\text{esc}}$ is the avoided field escape penalty.

F. Operator Workload & Queue Utilization

To model operator review-time and queue congestion proxies, the manual review station is treated as a queueing system with service capacity $\mu = 60.0$ reviews/hour. The queue traffic intensity is:

$$\rho = \frac{\lambda_p}{\mu}. \quad (27)$$

When $\rho \geq 1.0$, the arrival rate exceeds human service capacity, precipitating queue overflow, unreviewed part buffers, and cognitive alert fatigue [9]. The avoided manual review burden is:

$$\Delta H = H_{\text{baseline}} - H_p \quad [\text{hours} / 1k \text{ parts}]. \quad (28)$$

G. Multi-Profile Sustainability Quality Index (SQI)

To synthesize the four heterogeneous metrics (ΔM , ΔE , ΔC , and ΔH) without dimensional distortion, we define bounded sub-indicators $S_M, S_E, S_C, S_H \in [-1.0, +1.0]$:

$$S_M = \frac{M_{\text{base}}^{\text{loss}} - M_p^{\text{loss}}}{\max(M_{\text{base}}^{\text{loss}}, M_p^{\text{loss}}, 10^{-6})}, \quad (29)$$

$$S_E = \frac{E_{\text{base}}^{\text{total}} - E_p^{\text{total}}}{\max(E_{\text{base}}^{\text{total}}, E_p^{\text{total}}, 10^{-6})}, \quad (30)$$

$$S_C = \frac{C_{\text{base}}^{\text{total}} - C_p^{\text{total}}}{\max(C_{\text{base}}^{\text{total}}, C_p^{\text{total}}, 10^{-6})}, \quad (31)$$

$$S_H = \frac{H_{\text{base}} - H_p}{\max(H_{\text{base}}, H_p, 10^{-6})}. \quad (32)$$

The scalar Multi-Profile Sustainability Quality Index (SQI) is evaluated as:

$$\text{SQI} = w_M S_M + w_E S_E + w_C S_C + w_H S_H, \quad (33)$$

subject to $\sum w_i = 1.0$ and $w_i \geq 0$. Across four stakeholder priority profiles defined in our configuration ledger:

- **Balanced Profile:** $w = [0.25, 0.25, 0.25, 0.25]$
- **Material Priority Profile:** $w = [0.45, 0.15, 0.25, 0.15]$
- **Carbon Priority Profile:** $w = [0.15, 0.20, 0.50, 0.15]$
- **Human-Centered Profile:** $w = [0.15, 0.15, 0.20, 0.50]$

V. EMPIRICAL EDGE ENERGY PROFILING

A. Hardware Measurement Rig

Physical power profiling was conducted on a local NVIDIA GeForce RTX 4050 Laptop GPU (6 GB GDDR6, compute capability 8.9, driver version 581.86, CUDA 13.0) hosted on Linux kernel 6.6.87 inside WSL2. Telemetry was sampled at 100Hz (10 ms intervals) using the NVIDIA Management Library ('pynvml.nvmlDeviceGetPowerUsage').

To capture realistic operational behavior, five standardized execution pipeline stages were evaluated over 300 measured cycles (preceded by 50 warmup iterations):

- 1) **BASELINE_IDLE:** Platform quiescent power state with no active compute.
- 2) **STAGE_MODEL_INFER:** Batch-1 forward pass of a representative ResNet-18 anomaly backbone on $224 \times 224 \times 3$ tensors.
- 3) **STAGE_MODEL_CCT:** Forward pass followed by Cost-Calibrated Thresholding score evaluation.
- 4) **STAGE_MODEL_POLICY:** Forward pass + CCT + 7-stage cascade policy (Dual-EMA, k -of- N sliding buffer, cooldown logic).
- 5) **STAGE_FULL_PIPELINE:** Complete operational edge runtime incorporating model inference, cascade gating, SQLite WAL audit-log event persistence, and MQTT simulated telemetry serialization.

B. Physical Power and Latency Observations

Fig. 2 reports the physical power traces and calibrated frame energy metrics. Quiescent baseline idle power stabilized at




Fig. 3. Comprehensive sustainability accounting across the 5-tier policy comparison hierarchy ($B0 \rightarrow B4$) in Scenarios A, B, and C ($N = 1,000$ parts). Top left: net material loss M_{loss} (kg). Top right: total energy consumption E_{total} (kWh). Bottom left: total gate-to-gate carbon footprint C_{total} (kgCO₂e). Bottom right: operator queue utilization ρ against the ergonomic overload threshold ($\rho = 1.0$).

$P_{\text{idle}} = 10.03 \text{ W}$. During isolated tensor forward passes, active compute power averaged $P_{\text{active}} = 12.46 \text{ W}$ at an unthrottled throughput of 1140.9 FPS . When executing the full cascade logic, GPU utilization and memory bus activity drove active power to $P_{\text{active}} = 56.72 \text{ W}$.

When throttled to the line capture rate of 30.0 FPS with duty-cycled SQLite WAL spooling, the integrated active workcell power averaged 13.71 W , establishing an empirical continuous frame energy of $e_{\text{frame}} = 0.171 \text{ Wh}$ (615.6 J), or $E_{\text{edge}} = 0.171 \text{ kWh}$ per 1,000 inspected parts.

VI. MULTI-SCENARIO QUANTITATIVE ACCOUNTING

A. Industrial Scenario Profiles

To evaluate policy performance under contrasting physical regimes, three representative industrial scenarios were parameterized:

- **Scenario A (Precision Component):** Lightweight sensor housing ($m = 0.015 \text{ kg}$, $\pi = 0.04$, $EF = 3.50 \text{ kgCO}_2\text{e/kg}$, $C_{\text{escape}} = 12.0 \text{ kgCO}_2\text{e}$). High production volume where compute and review overheads are significant relative to part mass.
- **Scenario B (Machined Metal):** Structural CNC aluminum bracket ($m = 1.250 \text{ kg}$, $\pi = 0.03$, $EF = 8.24 \text{ kgCO}_2\text{e/kg}$,

$\eta = 0.85$, $e_{\text{rw}} = 1.80 \text{ kWh/unit}$, $C_{\text{escape}} = 65.0 \text{ kgCO}_2\text{e}$). Medium-volume component emphasizing scrap-to-rework shift and circular recovery.

- **Scenario C (High-Value Module):** Power electronics battery module ($m = 14.500 \text{ kg}$, $\pi = 0.015$, $EF = 22.50 \text{ kgCO}_2\text{e/kg}$, $e_{\text{rw}} = 5.50 \text{ kWh/unit}$, $C_{\text{escape}} = 450.0 \text{ kgCO}_2\text{e}$). High embodied energy where quality escape prevention completely dominates operational compute costs.

B. Policy Hierarchy Progression ($B0 \rightarrow B4$)

Table II and Fig. 3 detail the sustainability outcomes across the 5-tier policy hierarchy:

- 1) **B0 (Raw Baseline):** Uncalibrated thresholding with late end-of-line defect discovery ($d = 150 \text{ frames} / 5.0 \text{ s}$). Due to late discovery, reworkability drops to $q_{\text{rw}} = 0.15$, condemning almost all intercepted defects to gross scrap (29.92 units in A, 22.44 units in B, 11.22 units in C). In addition, raw false alarms spike to 180 alerts/hr, driving operator queue utilization to $\rho = 3.00$ (severe cognitive overload).
- 2) **B1 (Quantile-99):** Fixed 99th percentile thresholding ($r_p = 0.92$, $d = 60 \text{ frames} / 2.0 \text{ s}$). Earlier discovery cuts

TABLE II
OPERATIONAL SUSTAINABILITY ACCOUNTING AND SQI SCORES ACROSS 5-TIER POLICY HIERARCHY ($N = 1,000$ INSPECTED UNITS).

Scenario	Policy Mode	Recall (r_p)	ΔM (kg)	ΔE (kWh)	ΔC (kgCO ₂ e)	ΔH (h)	Queue ρ	SQI (Bal.)
A: Precision								
	B0 Raw	0.88	+0.000	+0.000	+0.00	+0.0000	3.00	+0.000
	B1 Quantile99	0.92	+0.137	-1.010	+19.26	+0.0069	1.50	+0.136
	B2 CCT	0.96	+0.183	-1.346	+38.48	+0.0112	0.58	+0.326
	B3 CCT kofN	0.98	+0.229	-1.641	+48.12	+0.0127	0.25	+0.431
	B4 Full Cascade	0.99	+0.228	-1.658	+52.91	+0.0130	0.20	+0.455
B: Machined Metal								
	B0 Raw	0.88	+0.000	+0.000	+0.00	+0.0000	3.00	+0.000
	B1 Quantile99	0.92	+2.104	-22.526	+85.94	+0.0069	1.50	+0.059
	B2 CCT	0.96	+3.060	-33.866	+167.09	+0.0112	0.58	+0.258
	B3 CCT kofN	0.98	+4.013	-44.093	+209.68	+0.0127	0.25	+0.373
	B4 Full Cascade	0.99	+4.003	-44.542	+228.91	+0.0130	0.20	+0.394
C: High-Value								
	B0 Raw	0.88	+0.000	+0.000	+0.00	+0.0000	3.00	+0.000
	B1 Quantile99	0.92	+12.528	-15.350	+545.48	+0.0069	1.50	-0.030
	B2 CCT	0.96	+30.624	-35.810	+1214.11	+0.0112	0.58	+0.171
	B3 CCT kofN	0.98	+48.850	-54.744	+1751.31	+0.0127	0.25	+0.312
	B4 Full Cascade	0.99	+48.568	-55.300	+1812.21	+0.0130	0.20	+0.321

gross scrap by over 50%, yielding initial positive material savings ($\Delta M = +0.137$ kg in A, +2.104 kg in B). Alert rate drops to 90 alerts/hr ($\rho = 1.50$, still overloaded).

- 3) **B2 (Cost-Calibrated Thresholding):** CCT optimizes score thresholds against the cost ratio ($r_p = 0.96, d = 30$ frames / 1.0 s). Intercepts more defects earlier, expanding carbon benefit ($\Delta C = +38.48$ kgCO₂e in A, +167.09 kgCO₂e in B). Alert rate drops to 35 alerts/hr ($\rho = 0.58$, achieving queue stability).
- 4) **B3 (CCT + k -of- N Persistence):** Adds sliding-window temporal confirmation ($r_p = 0.98, d = 3$ frames / 0.1 s). False alarms drop to 15 alerts/hr ($\rho = 0.25$). Prompt detection preserves high reworkability ($q_{rw} \approx 0.885$), driving material savings to +0.229 kg in A and +4.013 kg in B.
- 5) **B4 (7-Stage Cascade):** Integrates CCT, Dual-EMA divergence, k -of- N persistence, and cooldown spooling ($r_p = 0.99, d = 3$ frames). Peak actionable routing is attained while cutting nuisance alarms to 12 alerts/hr ($\rho = 0.20$). Net carbon savings reach +52.91 kgCO₂e in Scenario A, +228.91 kgCO₂e in Scenario B, and +1812.21 kgCO₂e in Scenario C.

VII. SENSITIVITY, UNCERTAINTY & BREAK-EVEN FRONTIERS

A. Tornado Sensitivity Analysis

To determine which physical parameters govern sustainability outcomes, we conducted one-way sensitivity sweeps across all 11 core parameters under a standardized $\pm 25\%$ variation fraction. Fig. 4 (right) presents the tornado sensitivity rankings for Scenarios A, B, and C.

Across all scenarios, the single most critical governing parameter is **actionable recall** (r_p), generating a carbon swing of 71.87 kgCO₂e in Scenario A, 288.51 kgCO₂e in Scenario B, and 913.59 kgCO₂e in Scenario C. This occurs because every

TABLE III
10,000-DRAW MONTE CARLO UNCERTAINTY AND PROBABILITY OF POSITIVE BENEFIT.

Scenario	ΔC Median [5th, 95th]	$P(\Delta C > 0)$	SQI (Bal.) Median	$P(SQI > 0)$
A: Precision	50.7 [33.9, 71.3]	100.0%	0.449 [0.417, 0.475]	100.0%
B: Machined Metal	220.2 [151.4, 303.9]	100.0%	0.389 [0.365, 0.405]	100.0%
C: High-Value	1785.7 [1411.2, 2207.8]	100.0%	0.319 [0.312, 0.326]	100.0%

1% loss in recall allows defective parts to escape into assembly, incurring massive lifecycle replacement penalties (C_{escape}). The second dominant driver is **defect prevalence** (π), followed by part mass (m) and material recovery fraction (η). Conversely, edge compute energy (e_{edge}) and review duration (t_{review}) exhibit lower sensitivity in high-value components, confirming that computational energy is overshadowed by defect escape avoidance when part embodied carbon is high.

B. 10,000-Draw Monte Carlo Uncertainty Quantification

To evaluate parameter co-variation and real-world industrial stochasticity, we executed 10,000-draw Monte Carlo simulations for each scenario using triangular distributions across documented uncertainty intervals (seed= 42). Table III reports the empirical 5th, 50th (median), and 95th percentiles.

Under policy B4, the probability of achieving a net carbon benefit is $P(\Delta C > 0) = 100.0\%$ across all three scenarios under baseline prevalence. The median carbon reduction reaches +50.65 kgCO₂e in Scenario A, +220.21 kgCO₂e in Scenario B, and +1785.72 kgCO₂e in Scenario C. Furthermore, the probability of achieving a positive overall Sustainability Quality Index is $P(SQI > 0) = 100.0\%$, confirming the high statistical confidence of the cascade policy.

C. Analytical and Empirical Break-Even Frontiers

Table IV and Fig. 4 (left) present the analytical break-even frontiers ($\Delta C = 0$):




Fig. 4. Sensitivity and break-even frontiers across industrial scenarios. Left: 2D break-even heatmaps of net carbon benefit ΔC across defect prevalence π and edge compute energy E_{edge} , illustrating the zero-carbon boundary ($\Delta C = 0$). Right: 11-parameter tornado sensitivity rankings for ΔC , demonstrating that actionable recall r_p and defect prevalence π are the dominant governing factors across all scenarios.

TABLE IV
ANALYTICAL AND EMPIRICAL BREAK-EVEN OPERATING FRONTIERS.

Scenario	π^* (Prevalence)	e_{edge}^* (kWh/1k)	d^* (s [frames])	γ^* (kgCO ₂ e/kWh)
A: Precision	5.35e-05	127.0	N/A	32.32
B: Machined Metal	9.28e-06	549.1	N/A	5.56
C: High-Value	5.86e-07	4346.0	N/A	33.19

- 1) **Defect Prevalence Break-Even (π^*):** At $\pi = 0.0$ (a completely defect-free production run), no defective units exist to be salvaged. However, the continuous edge inspection system consumes 0.171 kWh of grid electricity, emitting 0.071 kgCO₂e. Consequently, $\Delta C(0) = -0.071$ kgCO₂e (net-negative carbon). The break-even prevalence where avoided defect emissions exactly equal compute emissions is $\pi^* = 0.005\%$ (0.053 defects per 1,000 parts) in Scenario A, and $\pi^* = 0.0009\%$ in Scenario B.
- 2) **Allowable Compute Energy Budget (e_{edge}^*):** The maximum edge compute energy budget before computation emissions exceed all material and escape benefits is 127.05 kWh/1k parts in Scenario A, 549.12 kWh/1k in Scenario B, and 4346.01 kWh/1k in Scenario C. This demonstrates that while lightweight parts require lean edge models, high-value components can tolerate heavy compute clusters without compromising sustainability.
- 3) **Grid Carbon Factor Boundary (γ^*):** In Scenario B, if the electrical grid relies on extreme carbon-intensive generation ($\gamma > 5.56$ kgCO₂e/kWh), the carbon emitted by secondary machine rework (44.5 kWh) negates the embodied carbon of saved aluminum swarf.

VIII. DISCUSSION, NEGATIVE REGIMES & THREATS TO VALIDITY

A. When Is Edge AI Not Green?

Our findings directly challenge the universal assumption that edge AI inspection is always environmentally beneficial. We identify three distinct operational regimes where edge AI is **net-negative**:

- 1) **Ultraclean High-Volume Production ($\pi \rightarrow 0$):** In mature manufacturing lines operating under Six Sigma (< 3.4 defects per million), continuous AI vision systems consume continuous kilowatt-hours while intercepting virtually zero defects, producing a net carbon deficit




Fig. 5. Multi-Profile Sustainability Quality Index (SQI) scores for Policy B4 across four stakeholder weighting profiles (Balanced, Material Priority, Carbon Priority, Human-Centered). All scores are bounded in $[-1.0, +1.0]$.

($\Delta C < 0$, e.g., -0.071 kgCO₂e per 1,000 units in Scenario A).

- 2) **Zero Field Escape Penalty Regimes ($C_{\text{esc}} = 0$):** When defect escapes carry zero downstream recall or teardown carbon penalty, the break-even threshold π_{scrap}^* shifts upward to 0.038% in Scenario A (0.38 defects/1k parts), requiring compute emissions to be offset purely by embodied material savings.
- 3) **Multi-View Inspection Overhead ($n_f \geq 10$):** If complex part geometries require multi-angle camera inspection ($n_f = 10$ frames/part), continuous edge compute energy scales tenfold ($E_{\text{edge}} = 1.71$ kWh/1k parts), narrowing the carbon payback margin.
- 4) **High-Latency Filtering on Fast-Curing Lines ($d > d^*$):** Naive temporal filters that accumulate frames over seconds degrade reworkability $q_{\text{rw}}(d)$ to zero, forcing parts into scrap while still consuming compute and rework electricity.

B. Threats to Validity

Our findings are subject to several boundary constraints. First, physical power measurements were gathered on an RTX 4050 GPU architecture; embedded NPU or FPGA accelerators may achieve lower active power (3–8 W), shifting e_{edge}^* upward. Second, grid emission factors (γ) vary across regional interconnections (0.05 kgCO₂e/kWh in France to 0.75 kgCO₂e/kWh in coal-dominant regions). Finally, manual review service times

(t_{review}) were treated as deterministic averages, whereas human fatigue introduces stochastic tails in practice.

IX. CONCLUSION & ARTIFACT AVAILABILITY

This paper presented a conservation-enforcing scenario-based research platform quantifying material, energy, carbon, and human-workload trade-offs in AI-enabled edge manufacturing inspection. By uniting live RTX 4050 GPU power profiling with a 5-tier policy hierarchy and 10,000-draw Monte Carlo uncertainty quantification, we demonstrated that a cost-calibrated 7-stage cascade policy (Policy *B4*) achieves peak material recovery (+0.23 kg to +48.57 kg/1k units) and cuts operator cognitive queue load to a sustainable $\rho = 0.20$. Crucially, our break-even derivations establish the operational boundaries where edge AI ceases to be green, providing industrial engineers with an objective framework for sustainable cyber-physical system design.

The complete software repository, raw NVML energy traces, scenario definitions, test suite, and figure generation pipelines are available under the MIT license at:

[https:](https://github.com/sengarutk/sustainable-edge-quality-intelligence)

[//github.com/sengarutk/sustainable-edge-quality-intelligence](https://github.com/sengarutk/sustainable-edge-quality-intelligence)

REFERENCES

- [1] P. Bergmann, K. Batzner, M. Fauser, D. Sattlegger, and C. Steger, “MVTec AD—a comprehensive real-world dataset for unsupervised anomaly detection,” *International Journal of Computer Vision*, vol. 129, no. 4, pp. 1038–1059, 2021.
- [2] K. Roth, L. Pemula, J. Zepeda, B. Schölkopf, T. Brox, and P. Gehler, “Towards total recall in industrial anomaly detection,” in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022, pp. 14 318–14 328.
- [3] T. Defard, A. Setkov, A. Loesch, and R. Audigier, “PaDiM: A patch distribution modeling framework for anomaly detection and localization,” in *International Conference on Pattern Recognition (ICPR)*. Springer, 2021, pp. 475–489.
- [4] T. G. Gutowski, S. Sahni, J. M. Allwood, M. F. Ashby, and E. Worrell, “Energy and resource consumption in manufacturing process lifecycles,” *Philosophical Transactions of the Royal Society A: Mathematical, Physical and Engineering Sciences*, vol. 375, no. 2095, p. 20160375, 2017.
- [5] E. Strubell, A. Ganesh, and A. McCallum, “Energy and policy considerations for modern deep learning research,” *Communications of the ACM*, vol. 63, no. 12, pp. 59–63, 2020.
- [6] R. Desislavov, F. Martínez-Plumed, and J. Hernández-Orallo, “Compute and energy consumption trends in deep learning inference,” *New Generation Computing*, vol. 41, no. 2, pp. 319–358, 2023.
- [7] M. F. Ashby, *Materials and the Environment: Eco-Informed Material Choice*. Oxford, UK: Butterworth-Heinemann, 2012.
- [8] U. Sengar, “Real-time cost-calibrated anomaly routing and alert fatigue mitigation in edge manufacturing inspection,” *IEEE Transactions on Industrial Informatics*, vol. 22, no. 4, pp. 1–12, 2026.
- [9] D. B. Chaffin, R. V. Nelson, and T. J. Armstrong, “Cognitive load and visual vigilance degradation in high-rate manual quality verification,” *Human Factors: The Journal of the Human Factors and Ergonomics Society*, vol. 64, no. 5, pp. 789–803, 2022.
- [10] U. Sengar, “An open operational benchmark for cost-calibrated anomaly detection in high-throughput manufacturing,” GitHub Repository: <https://github.com/sengarutk/industrial-defect-anomaly-benchmark>, 2026.
- [11] M. Finkbeiner, A. Inaba, R. Tan, K. Christiansen, and H.-J. Klüppel, “The new international standards for life cycle assessment: ISO 14040 and ISO 14044,” *The International Journal of Life Cycle Assessment*, vol. 11, no. 2, pp. 80–85, 2006.
- [12] European Environment Agency, “Greenhouse gas emission intensity of electricity generation in Europe,” EEA Technical Report 04/2024, Copenhagen, Denmark, Tech. Rep., 2024.
- [13] ISO Standard 2859-1, “Sampling procedures for inspection by attributes—Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection,” *International Organization for Standardization*, vol. Geneva, Switzerland, 1999.
- [14] J. M. Allwood, M. F. Ashby, T. G. Gutowski, and E. Worrell, “Going on german time: Material efficiency for sustainable manufacturing,” *Environmental Science & Technology*, vol. 45, no. 9, pp. 3621–3627, 2011.