HUGGING FACE

CLI COMMAND CHEAT SHEET • ALL 162 COMMANDS • v2.2.0 reference

hf <group> <action>
Use --help at any level

START HERE `hf auth login` `hf auth whoami` `hf repos list` `hf models info MODEL_ID` `hf download REPO_ID` `hf upload REPO_ID ./folder`

CORE — 7 commands

`hf cp SRC`
Copy files between local paths, repositories, and buckets
`hf download REPO_ID`
Download files
`hf env`
Print information about the environment
`hf sync`
Sync files between local directory and a bucket
`hf update`
Update the `hf` CLI to the latest version
`hf upload REPO_ID`
Upload a file or a folder to the Hub
`hf version`
Print information about the hf version

AUTH — 6 commands

`hf auth list`
List all stored access tokens
`hf auth login`
Login from your browser, or using a token from huggingface.co/settings/tokens
`hf auth logout`
Logout from a specific token
`hf auth switch`
Switch between access tokens
`hf auth token`
Print token (sensitive!)
`hf auth whoami`
Find out which huggingface.co account you are logged in as

CACHE — 4 commands

`hf cache list`
List cached repositories or revisions
`hf cache prune`
Remove detached revisions and incomplete downloads from the cache
`hf cache rm TARGETS`
Remove cached repositories, revisions or files
`hf cache verify REPO_ID`
Verify checksums for a single repo revision from cache or a local directory

REPOS — 13 commands

`hf repos branch create REPO_ID BRANCH`
Create a new branch for a repo
`hf repos branch delete REPO_ID BRANCH`
Delete a branch from a repo
`hf repos cp SRC`
Copy files between local paths, repositories, and buckets
`hf repos create REPO_ID`
Create a new repo
`hf repos delete REPO_ID`
Permanently delete repo (!)
`hf repos delete-files REPO_ID PATTERNS`
Delete files from a repo
`hf repos duplicate FROM_ID`
Duplicate a repo
`hf repos list`
List account repos + storage
`hf repos move FROM_ID TO_ID`
Move a repository from a namespace to another namespace
`hf repos settings REPO_ID`
Update the settings of a repository
`hf repos tag create REPO_ID TAG`
Create a tag for a repo
`hf repos tag delete REPO_ID TAG`
Delete a tag for a repo
`hf repos tag list REPO_ID`
List tags for a repo

MODELS — 3 commands

`hf models card MODEL_ID`
Get the model card (README) for a model
`hf models info MODEL_ID`
Get info about a model
`hf models list`
Search models / repo files

SPACES — 24 commands

`hf spaces card SPACE_ID`
Get the Space card (README)
`hf spaces dev-mode SPACE_ID`
Enable or disable dev mode on a Space
`hf spaces hardware`
List available hardware options for Spaces
`hf spaces hot-reload SPACE_ID`
Hot-reload any Python file without a full rebuild + restart
`hf spaces info SPACE_ID`
Get info about a space
`hf spaces list`
Search Spaces / repo files
`hf spaces logs SPACE_ID`
Fetch the run or build logs
`hf spaces pause SPACE_ID`
Pause a Space
`hf spaces restart SPACE_ID`
Restart a Space
`hf spaces search QUERY`
Search spaces using semantic search
`hf spaces secrets add SPACE_ID`
Add or update secrets
`hf spaces secrets delete SPACE_ID KEY`
Remove a secret from a Space
`hf spaces secrets list SPACE_ID`
List secrets . Secret values are write-only and not returned
`hf spaces settings SPACE_ID`
Update the settings
`hf spaces ssh SPACE_ID`
SSH in's Dev Mode container
`hf spaces templates`
List the available Space templates
`hf spaces variables add SPACE_ID`
Add or update environment variables
`hf spaces variables delete SPACE_ID KEY`
Remove an environment variable from a Space
`hf spaces variables list SPACE_ID`
List environment variables
`hf spaces volumes delete SPACE_ID`
Remove all volumes from a Space
`hf spaces volumes list SPACE_ID`
List volumes mounted in a Space
`hf spaces volumes set SPACE_ID`
Set (replace) volumes
`hf spaces wait SPACE_ID`
Wait to finish building/starting
`hf spaces zero-gpu quota`
Show your ZeroGPU quota

BUCKETS — 9 commands

`hf buckets cp SRC`
Copy files between local paths, repositories, and buckets
`hf buckets create BUCKET_ID`
Create a new bucket
`hf buckets delete BUCKET_ID`
Delete a bucket
`hf buckets info BUCKET_ID`
Get info about a bucket
`hf buckets list`
List buckets or files in a bucket
`hf buckets move FROM_ID TO_ID`
Move (rename) a bucket to a new name or namespace
`hf buckets remove ARGUMENT`
Remove files from a bucket
`hf buckets settings BUCKET_ID`
Update bucket settings (visibility)
`hf buckets sync`
Sync files between local directory and a bucket

JOBS — 23 commands

`hf jobs cancel JOB_ID`
Cancel a Job
`hf jobs expose JOB_ID`
Replace exposed ports on a running Job
`hf jobs hardware`
List available hardware options for Jobs
`hf jobs inspect JOB_IDS`
Display detailed information on one or more Jobs
`hf jobs labels JOB_ID`
Update labels on a Job. Passing --label repla…
`hf jobs list`
List Jobs
`hf jobs logs JOB_ID`
Fetch the logs of a Job
`hf jobs rerun JOB_ID`
Run a new Job with Job's spec
`hf jobs run IMAGE COMMAND`
Start remote compute job
`hf jobs scheduled delete SCHEDULED_JOB_ID`
Delete a scheduled Job
`hf jobs scheduled inspect SCHEDULED_JOB_IDS`
Display detailed information on one or more scheduled Jobs
`hf jobs scheduled labels SCHEDULED_JOB_ID`
Update labels on a scheduled Job. Passing --l…
`hf jobs scheduled list`
List scheduled Jobs
`hf jobs scheduled reschedule SCHEDULED_JOB_ID SCHEDULE`
Change when a scheduled Job runs
`hf jobs scheduled resume SCHEDULED_JOB_ID`
Resume (unpause) a scheduled Job
`hf jobs scheduled run SCHEDULE IMAGE COMMAND`
Schedule a remote job
`hf jobs scheduled suspend SCHEDULED_JOB_ID`
Suspend (pause) a scheduled Job
`hf jobs scheduled trigger SCHEDULED_JOB_ID`
Trigger a scheduled Job to run immediately
`hf jobs scheduled uv run SCHEDULE SCRIPT`
Run Python script remotely
`hf jobs ssh JOB_ID`
SSH into a running Job
`hf jobs stats`
Fetch the resource usage statistics and metrics of Jobs
`hf jobs uv run SCRIPT`
Run Python script remotely
`hf jobs wait JOB_IDS`
Wait for one or more Jobs to reach a terminal state

ENDPOINTS — 11 commands

`hf endpoints catalog deploy`
Deploy an Inference Endpoint from the Model Catalog
`hf endpoints catalog list`
List the models available in the Model Catalog
`hf endpoints delete NAME`
Permanently delete endpoint (!)
`hf endpoints deploy NAME --repo TEXT --framework TEXT --accelerator TEXT --instance-size TEXT --instance-type TEXT --region TEXT --vendor TEXT`
Deploy an Inference Endpoint from a Hub repository
`hf endpoints describe NAME`
Get information about endpoint
`hf endpoints hardware`
List the hardware available to deploy an Inference Endpoint on
`hf endpoints list`
Lists all Inference Endpoints for the given namespace
`hf endpoints pause NAME`
Pause an Inference Endpoint
`hf endpoints resume NAME`
Resume an Inference Endpoint
`hf endpoints scale-to-zero NAME`
Scale an Inference Endpoint to zero
`hf endpoints update NAME`
Update endpoint

DISCUSSIONS — 10 commands

`hf discussions close REPO_ID NUM`
Close a discussion or pull request
`hf discussions comment REPO_ID NUM`
Comment on a discussion or pull request
`hf discussions create REPO_ID --title TEXT`
Create a new discussion or pull request on a repo
`hf discussions diff REPO_ID NUM`
Show the diff of a pull request
`hf discussions edit REPO_ID NUM COMMENT_ID`
Edit comment on a discussion or pull request
`hf discussions info REPO_ID NUM`
Get info about a discussion or pull request
`hf discussions list REPO_ID`
List discussions and pull requests on a repo
`hf discussions merge REPO_ID NUM`
Merge a pull request
`hf discussions rename REPO_ID NUM NEW_TITLE`
Rename a discussion or pull request
`hf discussions reopen REPO_ID NUM`
Reopen a closed discussion or pull request

COLLECTIONS — 8 commands

`hf collections add-item COLLECTION_SLUG ITEM_ID ITEM_TYPE`
Add an item to a collection
`hf collections create TITLE`
Create a new collection
`hf collections delete COLLECTION_SLUG`
Delete a collection
`hf collections delete-item COLLECTION_SLUG ITEM_OBJECT_ID`
Delete an item from a collection
`hf collections info COLLECTION_SLUG`
Get info about a collection
`hf collections list`
List collections
`hf collections update COLLECTION_SLUG`
Update a collection's metadata
`hf collections update-item COLLECTION_SLUG ITEM_OBJECT_ID`
Update an item in a collection

WEBHOOKS — 14 commands

`hf webhooks create --watch TEXT`
Create a new webhook
`hf webhooks delete WEBHOOK_ID`
Delete a webhook permanently
`hf webhooks disable WEBHOOK_ID`
Disable an active webhook
`hf webhooks enable WEBHOOK_ID`
Enable a disabled webhook
`hf webhooks info WEBHOOK_ID`
Show full details for a single webhook
`hf webhooks list`
List all webhooks for the current user
`hf webhooks update WEBHOOK_ID`
Update webhook. Only provided options are changed
`--format`
Output format: `--format json` (or `--json`) or `--format table` (default)
`-q / --quiet`
Quiet output (one ID per line). Equivalent to '--format quiet'
`--revision`
Git revision id which can be a branch name, a tag, or a commit hash
`--token`
Use a User Access Token. Prefer setting `HF_T…
`--type`
The type of repository
`hf-mount start repo openai-community/gpt2 /tmp/gpt2`
mount a repo (read-only)
`hf-mount start --hf-token $HF_TOKEN bucket myuser/my-bucket /tmp/data`
mount a bucket (read-write)

DATASETS — 6 commands

`hf datasets card DATASET_ID`
Get the dataset card (README) for a dataset
`hf datasets info DATASET_ID`
Get info about a dataset
`hf datasets leaderboard DATASET_ID`
List model scores from a dataset leaderboard…
`hf datasets list`
Search datasets / repo files
`hf datasets parquet DATASET_ID`
List parquet file URLs available for a dataset
`hf datasets sql SQL`
Run SQL on Parquet data

SANDBOX — 10 commands

`hf sandbox cp SRC DST`
Copy a file between the local machine and a sandbox (docker-style)
`hf sandbox create`
Create a sandbox: a dedicated VM by default, or a cheap shared one with `--pool`
`hf sandbox exec SANDBOX_ID COMMAND`
Run a command in a sandbox, streaming output.…
`hf sandbox kill`
Terminate a sandbox, a whole shared host, or everything (--all)
`hf sandbox pool create`
Warm a pool: boot one host VM now, tagged so it can be found later by its pool id
`hf sandbox pool delete POOL_ID`
Terminate every host VM of a pool
`hf sandbox pool ls`
List running sandbox pools
`hf sandbox process kill SANDBOX_ID PID`
Stop a background process running in a sandbox
`hf sandbox process ls SANDBOX_ID`
List the background processes running in a sandbox
`hf sandbox spawn SANDBOX_ID COMMAND`
Start a long-running command in the background and return its pid (don't wait)

EXTENSIONS — 6 commands

`hf extensions exec NAME`
Execute an installed extension
`hf extensions install REPO_ID`
Install an extension from a public GitHub repository
`hf extensions list`
List installed extension commands
`hf extensions remove NAME`
Remove an installed extension
`hf extensions search`
Search extensions available on GitHub
`hf extensions update`
Update installed extension(s) to their latest version

SKILLS — 4 commands

`hf skills add`
Install a Hugging Face skill for an AI assistant
`hf skills list`
List available skills from the Hugging Face marketplace
`hf skills preview`
Print the generated `hf-cli` SKILL.md to stdout
`hf skills update`
Update installed Hugging Face marketplace skills

PAPERS — 4 commands

`hf papers info PAPER_ID`
Get info about a paper
`hf papers list`
List daily papers
`hf papers read PAPER_ID`
Read a paper as markdown
`hf papers search QUERY`
Search papers

ALIASES / FLAGS `--format json` • `--type model|dataset|space` • `--revision BRANCH|TAG|SHA` • `--limit N` • `--search TEXT` • `--help`