

Multilingual Sentiment Analysis based on Fine-Tuned Transformer Architectures

Reema Ajmera
Department of CSE
Global Institute of Technology
Jaipur, Rajasthan, India
ajmera.reema17@gmail.com

Anantika Johari
Department of CSE
Global Institute of Technology
Jaipur, Rajasthan, India
anantikajohari@gmail.com

Abhishek Goyal
Department of CSE
Global Institute of Technology
Jaipur, Rajasthan, India
22egjcs007@gitjaipur.com

Abhishek Purohit
Department of CSE
Global Institute of Technology
Jaipur, Rajasthan, India
22egjcs012@gitjaipur.com

Abhishek Kumar
Department of CSE
Global Institute of Technology
Jaipur, Rajasthan, India
22egjcs008@gitjaipur.com

Jha Anisha Ashok
Department of CSE
Global Institute of Technology
Jaipur, Rajasthan, India
22egjcs100@gitjaipur.com

Abstract— As multilingual social media continues to expand exponentially, online critiques and user-generated content increase, making traditional sentiment analysis methods inadequate for capturing cross-lingual nuances. This paper presents a detailed analysis of multilingual sentiment analysis using a fine-tuned transformer model, including XLM-Roberta. The study covers dataset preparation, preprocessing pipelines, fine-tuning methods, and cross-lingual testing. The proposed framework leverages shared multilingual embeddings, achieving higher accuracy and improved generalization across multiple languages without relying on translation-based training. Ethical considerations, deployment challenges, and future research directions are also discussed.

Keywords— *Multilingual NLP, Sentiment Analysis, Transformers, XLM-Roberta, Cross-Lingual Learning, Transfer Learning.*

I. INTRODUCTION

The growing digitization of communication has resulted in huge text data of multilingual communications by way of reviews, posts and comments [1]. The key of such data is to understand its hidden sentiment and be critical to companies, governments and researchers. Other languages are not always analysed through the traditional sentiment analysis systems because it is usually centred on English and it cannot be used in other languages because of linguistic diversity, language variation, and culture [2], [3]. The use of transformer-based architectures has revolutionized Natural Language Processing (NLP) since it provides contextual representation learning via self-attention. Multilingual models such as multilingual BERT (mBERT) and XLM-Roberta (XLM-R) have been found to record good cross-lingual performances [4], [5]. Corpora used to train these models have more than 100 languages and therefore enables them to share semantic space across the linguistic borders [6].

Traditional Approaches

Previous sentiment analysis algorithms were founded on either lexicon-based or machine-learning-based algorithms like Naive Bayes, SVM, and Logistic Regression, and feature bag-of-words and TF-IDF. These methods were based on the manually created features and had no context meaning that they could not deal with sarcasm, informal text and multi-lingual information. Their ability to be accurate was greatly reduced when used in the new fields or languages [7], [8].

Word Embeddings and Deep Learning.

Word representations were made more meaning as Word2Vec and GloVe both uses dense vectors as the way of embedding words [9]. Such models as CNNs and LSTMs learned the contextual relations in a more effective manner and enhanced the rate of classification. Nevertheless, they were still language specific and needed large labelled data sets per language, making them difficult to apply to a multilingual setting [10], [11], [12].

Transformer Architectures

Transformer architectures mimic the design and executions of transformer architectures restructure themselves after transformers [13]. Transformer models changed the NLP, bringing in self-attention, which enables parallel manipulation and understanding of the context. BERT, RoBERTa and XLNet models have state-of-the-art results on a variety of NLP tasks [14]. Their multilingual editions such as mBERT and XLM-R applied these advantages to more than 100 languages allowing knowledge this way to be transferred between high-resource and low-resource languages. These architectures have formed the basis of the current multilingual sentiment analysis with better accuracy and flexibility [6], [15].

The aim of this work is to design and evaluate a multilingual sentiment analysis framework based on XLM-R. The study investigates preprocessing techniques, fine-tuning approaches, and cross-lingual transfer, demonstrating that multilingual

transformers achieve superior performance in multilingual sentiment classification compared to monolingual models.

II. PROPOSED METHODOLOGY

The suggested model Fig.1 uses the XLM-Roberta Base model that is optimized to the tri-class sentiment analysis (positive, negative, and neutral).

A. System Overview

Whole workflow plan consists of:

- Multilingual data collection would be done using Twitter, Amazon Reviews, and YouTube comments.
- Normalization, tokenization and label encoding preprocessing.
- Fine-tuning of a model with the Hugging Face Transformers computer library.
- Cross-lingual test and performance comparison.

B. Pre-processing

The following steps are involved in preprocessing:

- Elimination of special characters, URLs and mentions.
- The use of emojis and emoticons as emotional predictors.
- Normalizing texts by using Unicode standardization.
- Sentence Piece tokenizer Sentence Piece tokenizer is used to tokenize XLM-R.
- Coding sentiment labels with the help of 0: Negative, 1: Neutral, 2: Positive.




Fig 1: Flowchart of Model Workflow

C. Model Architecture

XLM-Roberta Base contains 12 transformer layers, each of them with self-attention and feed-forward sublayers Fig 2. The classification head consists of a dense layer over the token representation of [CLS], which is then followed by a SoftMax activation to get the probability of each sentimental representation.




Fig 2: Model architecture of XLM-R with classification head

D. Fine-tuning Procedure

The model was optimally adjusted after 35 epochs using Adam optimizer, learning rate 2×10^{-5} and the batch size value of 16. Stopping early in terms of F1-score was used to avoid overfitting. The data was divided into 80/10/10 training, validation and testing respectively.

III. RESULTS AND DISCUSSION

A. Performance Evaluation

Architecture is BERT-Base: The architecture in the with 12 Transformer Layers and a hidden size of 768 leading to the dense layer describes exactly the model configuration of BERT-Base.

Performance Trade-off: As the number of layers (depth) and the size of its hidden (width) increases, BERT-Large can acquire a more complex and richer language representation and perform tasks at better performance but at far larger cost Fig 3.

The XLM-R fine-tuned model proved to have good results and is highly accurate and cross-linguistically generalizes. It was also found to be competitive in non-translated French and Italian data when trained on English data, which aligns with the results of prior literature regarding the capacity of multilingual embeddings to learn semantic cross-language relationships Table I. This shows that XLM-R can also be effectively applied at the multilingual sentiment analysis activities.

TABLE I. Performance Metrics Across Languages

Language	Accuracy (%)	F1-Score (%)
English	92.3	91.8
French	89.7	89.3
Italian	88.5	88.1
Chinese	86.8	86.4




Fig 3: Accuracy and F1-Score Performance of XLM-R Model Across Multiple Languages

B. Cross-Lingual Transfer

Zero-shot transfer of the model makes it possible to use the model to forecast sentiment in languages that it was not explicitly trained on. It is particularly useful in practical tasks of annotated datasets when there are not many languages with annotated datasets. This transfer learning will decrease the reliance on manual labelling as well as fast-track deployment of multi lingual systems across a wide range of linguistic settings.

C. Error Analysis

Majority of the misclassifications were in instances where sarcasm was involved, mixed feelings or the use of slang vocabularies where the literal meaning was used to make wrong predictions. An example is the sentences such as I love waiting in traffic every day; they were treated as positive as it did not detect the presence of irony in the context. The addition of contextual sentiment cues and sarcasm detection machines may make the model even more reliable.

D. Comparison with Baselines

The XLM-R model outperforms other traditional models like SVM and LSTM, attaining a higher F1-score of 10-15 per cent, which clearly shows that the model is superior in case of multilingually. In contrast to monolingual BERT where a different model is needed per language, XLM-R is based on one shared model that saves significantly on training, memory space and complexity. This renders using it to be efficient and scalable in the world sentiment analysis application.

IV. APPLICATIONS AND ETHICAL CONSIDERATIONS

The suggested framework can be implemented in:

- Multi-language social media analytics: Standardizing texts through Unicode standardization to deal with the various linguistic patterns.
- International market research of international brands: Customer perception in different countries and languages.
- Multilingual product tracking customer response: The reviews and sentiments of different regional markets.
- Following the political and social mood in the region: Following the opinion of the population about the policies, elections, and events.
- Healthcare opinion mining: Mining patient sentiments in health forums or health surveys that are multilingual to enhance communication in healthcare.
- Educations and e -learning analytics: Using student feedback analysis to improve courses and monitor engagement among multilingual students.

Sentiment model application in a multilingual environment is also prone to risks.

- Bias reduction: Each dataset must be balanced so as not to make prejudiced or incorrect predictions.

- Cultural sensitivity: Models must be sensitive to the dictated context in the language because inconsistency may occur and result in its misunderstanding.
- Data privacy: The data of users should be anonymized and processed within the ethical and legal considerations.
- Transparency: Model limitations need to be laid down in a clear manner to generate trust.
- Explainability: The predictions should be understandable to the users.
- Continuous monitoring: It requires constant reviewing and adjustment in order to keep pace with language and social changes.

V. CONCLUSION AND FUTURE WORK

Though the given model of multilingual sentiment analysis shows good results in terms of its performance in various languages, it has some limitations and provides a variety of methods of future research, Low-resource languages Model accuracy deteriorates with a language that has poor annotated data, or that has a complicated morphology; transfer learning and data augmentation may be used to improve generalization. Sensing of emotion and sarcasm: Current transformer models fail to capture nuanced emotion like irony or humour; models of tomorrow can incorporate affective computing to make them better understand emotions.

Real-time and edge deployment Large transformer models cannot be deployed easily on low-power devices; lightweight architectures and model compression methods can improve their real-time usability. Future systems should be explainable: Predictions made by future systems need the addition of Explainable AI (XAI) so that employees trust the responses given, particularly in sensitive areas. Multimodal integration: Multimedia fusion of text and other forms such as audio, facial expressions, and visual signals has the potential to result in an experience with more human emotion decoding based on language and cross-cultural differences. The current paper introduced a multilingual sentiment analysis system based on XLM-Roberta. The model was cross-lingually transferred and on average had shown better accuracy compared to the traditional and monolingual baselines. It can solve the problem of language-specific training by using common contextual embeddings, thus proving an effective and scalable solution to global sentiment applications.

REFERENCES

- [1] D. Grewal, D. Herhausen, S. Ludwig, F. V. Ordenes, "The Future of Digital Communication Research: Considering Dynamics and Multimodality", *Journal of Retailing*, Vol. 98, Issue. 2, pp. 224-240, 2022.
- [2] Y. Mao, Q. Liu, Y. Zhang, "Sentiment analysis methods, applications, and challenges: A systematic literature review", *Journal of King Saud University - Computer and Information Sciences*, Vol. 36, Issue. 4, pp. 1-16, 2024.
- [3] C. Strauss, M. D. Harr, T. M. Pieper, "Analyzing digital communication: a comprehensive literature review", *Management Review Quarterly*, pp. 1-39, 2024.
- [4] S. A. Saiyed, N. Sharma, H. Kaushik, P. Jain, G. K. Soni and R. Joshi, "Transforming portfolio management with AI and ML: shaping investor perceptions and the future of the Indian investment sector," *Parul University International Conference on Engineering and Technology 2025 (PiCET 2025)*, pp. 1108-1114, 2025.
- [5] S. Murrar, F. M. Alhaj, F. Almasalha and M. H. Qutqut, "Transformers for Domain-Specific Text Classification: A Case Study in the Banking Sector," in *IEEE Access*, vol. 13, pp. 115063-115078, 2025.
- [6] S. Shaikh, S. Y. Yayilgan, M. Abomhara, E. Zoto, "Multilingual user perceptions analysis from twitter using zero shot learning for border control technologies", *Social Network Analysis and Mining*, Vol. 15, pp. 1-24, 2025.
- [7] R. S. Patil, S. R. Kolhe, "Supervised classifiers with TF-IDF features for sentiment analysis of Marathi tweets", *Social Network Analysis and Mining*, Vol. 12, 2022.
- [8] K. Alemerien, A. Al-Ghareeb and M. Z. Alksasbeh, "Sentiment Analysis of Online Reviews: A Machine Learning Based Approach with TF-IDF Vectorization", *Journal of Mobile Multimedia*, vol. 20, no. 5, pp. 1089-1116, 2024.
- [9] D. S. Asudani, N. K. Nagwani, P. Singh, "Impact of word embedding models on text analytics in deep learning environment: a review", *Artificial Intelligence Review*, Vol. 56, pp. 10345-10425, 2023.
- [10] S. Patankar, M. Phadke, "A CNN-transformer framework for emotion recognition in code-mixed English-Hindi data", *Discover Artificial Intelligence*, Vol. 5, pp. 1-13, 2025.
- [11] M. S. S.I, S. T, S. K. Kumar, N. Sheik Hameed, S. Vijayakumar and I. I. raj, "Artificial Intelligence in Mobile Computing for English Language Testing: Redefining Automated Language Assessment," 2025 3rd International Conference on Intelligent Systems, Advanced Computing and Communication (ISACC), pp. 417-421, 2025.
- [12] K. Halawa and W. F. Al Maki, "Gesture Recognition for Argentinian Sign Language using CNN and LSTM," 2025 International Conference on Data Science and Its Applications (ICoDSA), pp. 1202-1207, 2025.
- [13] B. S. Latibari et al., "Transformers: A Security Perspective," in *IEEE Access*, vol. 12, pp. 181071-181105, 2024.
- [14] C. M. Greco, A. Tagarelli, "Bringing order into the realm of Transformer-based language models for artificial intelligence and law", *Artificial Intelligence and Law*, Vol. 32, pp. 863-1010, 2024.
- [15] K. R. Mabokela, T. Celik and M. Raborife, "Multilingual Sentiment Analysis for Under-Resourced Languages: A Systematic Review of the Landscape," in *IEEE Access*, vol. 11, pp. 15996-16020, 2023.