
### The CPU-Memory Gap

The gap widens between DRAM, disk, and CPU speeds.



### Locality to the Rescue!

The key to bridging this CPU-Memory gap is a fundamental property of computer programs known as locality


### **Memory Hierarchy**


- Storage technologies and trends
- Locality of reference
- Caching in the memory hierarchy

# Locality

 Principle of Locality: Programs tend to use data and instructions with addresses near or equal to those they have used recently










Items with nearby addresses tend
 to be referenced close together in time



### **Locality Example**

```
sum = 0;
for (i = 0; i < n; i++)
    sum += a[i];
return sum;</pre>
```

#### Data references

- Reference array elements in succession (stride-1 reference pattern).
- Reference variable sum each iteration.

#### Instruction references

- Reference instructions in sequence.
- Cycle through loop repeatedly.

**Spatial locality** 

**Temporal locality** 

Spatial locality
Temporal locality

### **Qualitative Estimates of Locality**

- Claim: Being able to look at code and get a qualitative sense of its locality is a key skill for a professional programmer.
- Question: Does this function have good locality with respect to array a?

```
int sum_array_rows(int a[M][N])
{
   int i, j, sum = 0;

   for (i = 0; i < M; i++)
        for (j = 0; j < N; j++)
            sum += a[i][j];
   return sum;
}</pre>
```

### **Locality Example**

Question: Does this function have good locality with respect to array a?

```
int sum_array_cols(int a[M][N])
{
   int i, j, sum = 0;

   for (j = 0; j < N; j++)
        for (i = 0; i < M; i++)
            sum += a[i][j];
   return sum;
}</pre>
```

### **Locality Example**

Question: Can you permute the loops so that the function scans the 3-d array a with a stride-1 reference pattern (and thus has good spatial locality)?

### **Memory Hierarchies**

- Some fundamental and enduring properties of hardware and software:
  - Fast storage technologies cost more per byte, have less capacity, and require more power (heat!).
  - The gap between CPU and main memory speed is widening.
  - Well-written programs tend to exhibit good locality.
- These fundamental properties complement each other beautifully.
- They suggest an approach for organizing memory and storage systems known as a memory hierarchy.


### **Memory Heirarchy**

- Storage technologies and trends
- Locality of reference
- Caching in the memory hierarchy


#### Caches

- Cache: A smaller, faster storage device that acts as a staging area for a subset of the data in a larger, slower device.
- Fundamental idea of a memory hierarchy:
  - For each k, the faster, smaller device at level k serves as a cache for the larger, slower device at level k+1.
- Why do memory hierarchies work?
  - Because of locality, programs tend to access the data at level k more often than they access the data at level k+1.
  - Thus, the storage at level k+1 can be slower, and thus larger and cheaper per bit.
- Big Idea: The memory hierarchy creates a large pool of storage that costs as much as the cheap storage near the bottom, but that serves data to programs at the rate of the fast storage near the top.


# **General Cache Concepts**



# **General Cache Concepts: Hit**



### **General Cache Concepts: Miss**



Data in block b is needed

Block b is not in cache: Miss!

Block b is fetched from memory

#### Block b is stored in cache

- Placement policy: determines where b goes
- Replacement policy: determines which block gets evicted (victim)

# General Caching Concepts: Types of Cache Misses

#### Cold (compulsory) miss

Cold misses occur because the cache is empty.

#### Conflict miss

- Most caches limit blocks at level k+1 to a small subset (sometimes a singleton) of the block positions at level k.
  - E.g. Block i at level k+1 must be placed in block (i mod 4) at level k.
- Conflict misses occur when the level k cache is large enough, but multiple data objects all map to the same level k block.
  - E.g. Referencing blocks 0, 8, 0, 8, 0, 8, ... would miss every time.

#### Capacity miss

 Occurs when the set of active cache blocks (working set) is larger than the cache.






#### **Cache Memories**

**CS:APP 6.4** 


These slides adapted from materials provided by the textbook authors.

#### **Cache Memories**

- Cache memory organization and operation
- Performance impact of caches
  - The memory mountain




# **General Cache Concept**




#### **Cache Memories**


- Cache memories are small, fast SRAM-based memories managed automatically in hardware
  - Hold frequently accessed blocks of main memory
- CPU looks first for data in cache
- Typical system structure:



# General Cache Organization (S, E, B)




#### **Cache Read**



Locate set


# **Example: Direct Mapped Cache (E = 1)**

Direct mapped: One line per set Assume: cache block size 8 bytes




# **Example: Direct Mapped Cache (E = 1)**

Direct mapped: One line per set Assume: cache block size 8 bytes



# **Example: Direct Mapped Cache (E = 1)**

Direct mapped: One line per set Assume: cache block size 8 bytes



If tag doesn't match: old line is evicted and replaced

# **Direct-Mapped Cache Simulation**

t=1	s=2	b=1
Х	XX	X

M=16 bytes (4-bit addresses), B=2 bytes/block, S=4 sets, E=1 Blocks/set


Address trace (reads, one byte per read):

0	$[0\underline{00}0_2],$	miss
1	$[0\underline{001}_{2}],$	hit
7	$[0\underline{11}_{2}],$	miss
8	$[1000_{2}^{-}],$	miss
0	[0000]	miss

	V	Tag	Block
Set 0	1	0	M[0-1]
Set 1			
Set 2			
Set 3	1	0	M[6-7]


### E-way Set Associative Cache (Here: E = 2)

E = 2: Two lines per set




# E-way Set Associative Cache (Here: E = 2)

E = 2: Two lines per set



# E-way Set Associative Cache (Here: E = 2)

E = 2: Two lines per set



#### No match:

- One line in set is selected for eviction and replacement
- Replacement policies: random, least recently used (LRU), ...

# 2-Way Set Associative Cache Simulation

t=2	s=1	b=1
XX	Х	Х

M=16 byte addresses, B=2 bytes/block, S=2 sets, E=2 blocks/set

Address trace (reads, one byte per read):

0	$[00\underline{0}0_{2}],$	miss
1	$[0001_{2}],$	hit
7	$[01\underline{1}1_{2}],$	miss
8	$[10\underline{0}0_{2}],$	miss
0	[0000]	hit

	V	Tag	Block
Set 0	1	00	M[0-1]
	1	10	M[8-9]

Set 1	1	01	M[6-7]
	0		

#### What about writes?


#### Multiple copies of data exist:

- L1, L2, L3, Main Memory, Disk
- What to do on a write-hit?
  - Write-through (write immediately to memory)
  - Write-back (defer write to memory until replacement of line)
    - Need a dirty bit (line different from memory or not)
- What to do on a write-miss?
  - Write-allocate (load into cache, update line in cache)
    - Good if more writes to the location follow
  - No-write-allocate (writes straight to memory, does not load into cache)

#### Typical

- Write-through + No-write-allocate
- Write-back + Write-allocate

# **Intel Core i7 Cache Hierarchy**



#### L1 i-cache and d-cache:

32 KB, 8-way, Access: 4 cycles

#### L2 unified cache:

256 KB, 8-way, Access: 10 cycles

#### L3 unified cache:

8 MB, 16-way, Access: 40-75 cycles

Block size: 64 bytes for

all caches.

#### **Cache Performance Metrics**

#### Miss Rate

- Fraction of memory references not found in cache (misses / accesses)
   = 1 hit rate
- Typical numbers (in percentages):
  - 3-10% for L1
  - can be quite small (e.g., < 1%) for L2, depending on size, etc.</li>

#### Hit Time

- Time to deliver a line in the cache to the processor
  - includes time to determine whether the line is in the cache
- Typical numbers:
  - 4 clock cycle for L1
  - 10 clock cycles for L2

#### Miss Penalty

- Additional time required because of a miss
  - typically 50-200 cycles for main memory (Trend: increasing!)

#### Let's think about those numbers

- Huge difference between a hit and a miss
  - Could be 100x, if just L1 and main memory
- Would you believe 99% hits is twice as good as 97%?
  - Consider: cache hit time of 1 cycle miss penalty of 100 cycles
  - Average access time:

```
97% hits: 1 cycle + 0.03 * 100 cycles = 4 cycles
99% hits: 1 cycle + 0.01 * 100 cycles = 2 cycles
```

This is why "miss rate" is used instead of "hit rate"

### **Writing Cache Friendly Code**

- Make the common case go fast
  - Focus on the inner loops of the core functions
- Minimize the misses in the inner loops
  - Repeated references to variables are good (temporal locality)
  - Stride-1 reference patterns are good (spatial locality)

Key idea: Our qualitative notion of locality is quantified through our understanding of cache memories

# **The Memory Mountain**

- Read throughput (read bandwidth)
  - Number of bytes read from memory per second (MB/s)
- Memory mountain: Measured read throughput as a function of spatial and temporal locality.
  - Compact way to characterize memory system performance.

### **Memory Mountain Test Function**


```
long data[MAXELEMS]; /* Global array to traverse */
/* test - Iterate over first "elems" elements of
      array "data" with stride of "stride", using
      using 4x4 loop unrolling.
*/
int test(int elems, int stride) {
  long i, sx2=stride*2, sx3=stride*3, sx4=stride*4;
  long acc0 = 0, acc1 = 0, acc2 = 0, acc3 = 0;
  long length = elems, limit = length - sx4;
  /* Combine 4 elements at a time */
  for (i = 0; i < limit; i += sx4)
    acc0 = acc0 + data[i];
    acc1 = acc1 + data[i+stride];
    acc2 = acc2 + data[i+sx2];
    acc3 = acc3 + data[i+sx3];
  /* Finish any remaining elements */
  for (; i < length; i++) {
    acc0 = acc0 + data[i];
  return ((acc0 + acc1) + (acc2 + acc3));
```

Call test() with many combinations of elems and stride.

For each elems and stride:

- 1. Call test() once to warm up the caches.
- 2. Call test() again and measure the read throughput (MB/s)

# **The Memory Mountain**



Core i7 Haswell

2.1 GHz

# **Prefetching**

- Algorithms in processors predict access patterns
- Try to pre-fetch memory
  - Based on strides
  - Future: based on contents

# Stride Detection $\Delta = 2$ Prefetch Starts

# **Cache Summary**

- Cache memories can have significant performance impact
- You can write your programs to exploit this!
  - Focus on the inner loops, where bulk of computations and memory accesses occur.
  - Try to maximize spatial locality by reading data objects with sequentially with stride 1.
  - Try to maximize temporal locality by using a data object as often as possible once it's read from memory.

# **Writing Cache Friendly Code**

- Make the common case go fast
  - Focus on the inner loops of the core functions
- Minimize the misses in the inner loops
  - Repeated references to variables are good (temporal locality)
  - Stride-1 reference patterns are good (spatial locality)

Key idea: Our qualitative notion of locality is quantified through our understanding of cache memories

# **Matrix Multiplication Example**

#### Description:

- Multiply N x N matrices
- Matrix elements are doubles (8 bytes)
- O(N³) total operations
- N reads per source element
- N values summed per destination
  - but may be able to hold in register

```
/* ijk */
for (i=0; i<n; i++)
for (j=0; j<n; j++) {
    sum = 0.0;
    for (k=0; k<n; k++)
        sum += a[i][k] * b[k][j];
    c[i][j] = sum;
}
</pre>
matmult/mm.c
```


# Miss Rate Analysis for Matrix Multiply

#### Assume:

- Block size = 32B (big enough for four doubles)
- Matrix dimension (N) is very large
  - Approximate 1/N as 0.0
- Cache is not even big enough to hold multiple rows

#### Analysis Method:

Look at access pattern of inner loop



# Layout of C Arrays in Memory (review)

- C arrays allocated in row-major order
  - each row in contiguous memory locations
- Stepping through columns in one row:

```
for (i = 0; i < N; i++)
sum += a[0][i];</pre>
```

- accesses successive elements
- if block size (B) > sizeof(a<sub>ii</sub>) bytes, exploit spatial locality
  - miss rate = sizeof(a<sub>ii</sub>) / B

#### Stepping through rows in one column:


```
for (i = 0; i < n; i++)
sum += a[i][0];</pre>
```

- accesses distant elements
- no spatial locality!
  - miss rate = 1 (i.e. 100%)

# Matrix Multiplication (ijk)

```
/* ijk */
for (i=0; i<n; i++) {
  for (j=0; j<n; j++) {
    sum = 0.0;
    for (k=0; k<n; k++)
       sum += a[i][k] * b[k][j];
    c[i][j] = sum;
  }
}

matmult/mm.c</pre>
```




#### Misses per inner loop iteration:

<u>A</u>	<u>B</u>	<u>C</u>
0.25	1.0	0.0

# **Matrix Multiplication (jik)**

```
/* jik */
for (j=0; j<n; j++) {
  for (i=0; i<n; i++) {
    sum = 0.0;
    for (k=0; k<n; k++)
       sum += a[i][k] * b[k][j];
    c[i][j] = sum
  }
}
</pre>
```

#### Inner loop:




#### Misses per inner loop iteration:

<u>A</u>	<u>B</u>	<u>C</u>
0.25	1.0	0.0

# **Matrix Multiplication (kij)**

```
/* kij */
for (k=0; k<n; k++) {
  for (i=0; i<n; i++) {
    r = a[i][k];
    for (j=0; j<n; j++)
        c[i][j] += r * b[k][j];
  }
}
matmult/mm.c</pre>
```



#### Misses per inner loop iteration:

<u>A</u> <u>B</u> <u>C</u> 0.0 0.25 0.25

# **Matrix Multiplication (ikj)**

```
/* ikj */
for (i=0; i<n; i++) {
  for (k=0; k<n; k++) {
    r = a[i][k];
  for (j=0; j<n; j++)
    c[i][j] += r * b[k][j];
}
  matmult/mm.c</pre>
```

# Inner loop: (i,k) A B C ↑ ↑ Row-wise Row-wise


#### Misses per inner loop iteration:

<u>A</u> <u>B</u> <u>C</u> 0.0 0.25 0.25

# **Matrix Multiplication (jki)**

```
/* jki */
for (j=0; j<n; j++) {
  for (k=0; k<n; k++) {
    r = b[k][j];
  for (i=0; i<n; i++)
    c[i][j] += a[i][k] * r;
}

matmult/mm.c</pre>
```




#### Misses per inner loop iteration:

<u>A</u>	<u>B</u>	<u>C</u>
1.0	0.0	1.0

# **Matrix Multiplication (kji)**

```
/* kji */
for (k=0; k<n; k++) {
  for (j=0; j<n; j++) {
    r = b[k][j];
  for (i=0; i<n; i++)
    c[i][j] += a[i][k] * r;
  }
}
matmult/mm.c</pre>
```



#### Misses per inner loop iteration:

<u>A</u>	<u>B</u>	<u>C</u>
1.0	0.0	1.0

# **Summary of Matrix Multiplication**

```
for (i=0; i<n; i++) {
  for (j=0; j<n; j++) {
    sum = 0.0;
  for (k=0; k<n; k++)
    sum += a[i][k] * b[k][j];
  c[i][j] = sum;
}
}</pre>
```

```
for (k=0; k<n; k++) {
  for (i=0; i<n; i++) {
    r = a[i][k];
  for (j=0; j<n; j++)
    c[i][j] += r * b[k][j];
}</pre>
```

```
for (j=0; j<n; j++) {
  for (k=0; k<n; k++) {
    r = b[k][j];
    for (i=0; i<n; i++)
      c[i][j] += a[i][k] * r;
}</pre>
```

#### ijk (& jik):

- 2 loads, 0 stores
- misses/iter = **1.25**


#### kij (& ikj):

- 2 loads, 1 store
- misses/iter = **0.5**


#### jki (& kji):

- 2 loads, 1 store
- misses/iter = **2.0**

# **Core i7 Matrix Multiply Performance**



# **Example: Matrix Multiplication**



# **Cache Miss Analysis**

#### Assume:


- Matrix elements are doubles
- Cache block = 8 doubles
- Cache size C << n (much smaller than n)</li>

#### First iteration:

n/8 + n = 9n/8 misses



Afterwards in cache: (schematic)



n


# **Cache Miss Analysis**

#### Assume:

- Matrix elements are doubles
- Cache block = 8 doubles
- Cache size C << n (much smaller than n)</li>

#### Second iteration:

Again: n/8 + n = 9n/8 misses




#### Total misses:

n

# **Blocked Matrix Multiplication**

```
c = (double *) calloc(sizeof(double), n*n);
/* Multiply n x n matrices a and b */
void mmm(double *a, double *b, double *c, int n) {
    int i, j, k;
    for (i = 0; i < n; i+=B)
       for (j = 0; j < n; j+=B)
             for (k = 0; k < n; k+=B)
                /* B x B mini matrix multiplications */
                  for (i1 = i; i1 < i+B; i++)
                      for (j1 = j; j1 < j+B; j++)
                          for (k1 = k; k1 < k+B; k++)
                              c[i1*n+j1] += a[i1*n + k1]*b[k1*n + j1];
                                                         matmult/bmm.c
```



# **Cache Miss Analysis**


#### Assume:

- Cache block = 8 doubles
- Cache size C << n (much smaller than n)</li>
- Three blocks fit into cache: 3B<sup>2</sup> < C</p>

#### First (block) iteration:

- B<sup>2</sup>/8 misses for each block
- $2n/B * B^2/8 = nB/4$ (omitting matrix c)

Afterwards in cache (schematic)



n/B blocks

42


# **Cache Miss Analysis**

#### Assume:

- Cache block = 8 doubles
- Cache size C << n (much smaller than n)</li>
- Three blocks fit into cache: 3B<sup>2</sup> < C</p>

#### Second (block) iteration:

- Same as first iteration
- 2n/B \* B<sup>2</sup>/8 = nB/4



#### Total misses:

 $nB/4 * (n/B)^2 = n^3/(4B)$ 

n/B blocks

# **Blocking Summary**

- No blocking: (9/8) \* n³
- Blocking: 1/(4B) \* n³
- Suggest largest possible block size B, but limit 3B<sup>2</sup> < C!</p>
- Reason for dramatic difference:
  - Matrix multiplication has inherent temporal locality:
    - Input data: 3n<sup>2</sup>, computation 2n<sup>3</sup>
    - Every array elements used O(n) times!
  - But program has to be written properly

# **Cache Summary**

- Cache memories can have significant performance impact
- You can write your programs to exploit this!
  - Focus on the inner loops, where bulk of computations and memory accesses occur.
  - Try to maximize spatial locality by reading data objects with sequentially with stride 1.
  - Try to maximize temporal locality by using a data object as often as possible once it's read from memory.