

FIT2004

Algorithms and Data Structures

Ian Wern Han Lim
lim.wern.han@monash.edu

Referencing materials by
Nathan Compane, Aamir Cheema, Arun Konagurthu and Lloyd Allison



Faculty of Information Technology, Monash University

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

This material has been reproduced and communicated to you by or on behalf of Monash University pursuant to Part VB of the Copyright Act 1968 (the Act). The material in this communication may be subject to copyright under the Act. Any further reproduction or communication of this material by you may be the subject of copyright protection under the Act. Do not remove this notice

Ready?

Agenda

- The Graph data structure
- Graph Traversal algorithms

Agenda

- The Graph data structure
 - Introduction
 - Representation
- Graph Traversal algorithms

Agenda

- The Graph data structure
 - Introduction
 - Representation
- Graph Traversal algorithms
 - Breadth First Search (BFS)
 - Depth First Search (DFS)
 - Dijkstra's shortest distance

Agenda

- The Graph data structure
 - Introduction
 - Representation
 - Graph Traversal algorithms
 - Breadth First Search (BFS)
 - Depth First Search (DFS)
- } Basic for many graph-algorithms

Let us begin...

- Master race of all data structure

- Master race of all data structure
 - Everything can be represented as a graph

- Master race of all data structure
 - Everything can be represented as a graph
 - Everything can be reduced to a graph

- Master race of all data structure
 - Everything can be represented as a graph
 - Tree is a type of graph
 - Database is a graph
 - Everything can be reduced to a graph


- Master race of all data structure
 - Everything can be represented as a graph
 - Tree is a type of graph
 - Database is a graph
 - Everything can be reduced to a graph
 - You will see this in FIT2014 TOC

- Master race of all data structure
 - Everything can be represented as a graph
 - Tree is a type of graph
 - Database is a graph
 - Everything can be reduced to a graph
 - You will see this in FIT2014 TOC
 - A lot of problems can be solved with a graph
 - The longest common subsequence (LCS) we saw in tutorial?

- Master race of all data structure
 - Everything can be represented as a graph
 - Tree is a type of graph
 - Database is a graph
 - Everything can be reduced to a graph
 - You will see this in FIT2014 TOC
 - A lot of problems can be solved with a graph
 - The longest common subsequence (LCS) we saw in tutorial? Solved by building a directed acyclic graph (DAG)

- Master race of all data structure
 - Everything can be represented as a graph
 - Tree is a type of graph
 - Database is a graph
 - Everything can be reduced to a graph
 - You will see this in FIT2014 TOC
 - A lot of problems can be solved with a graph
 - The longest common subsequence (LCS) we saw in tutorial? Solved by building a directed acyclic graph (DAG)
- So what is a graph?
 - Have you seen it before?

- So what is a graph?
 - Have you seen it before?




- So what is a graph?
 - Have you seen it before?
 - Was Nickleback right?

Graph

Introduction


- So what is a graph?
 - Have you seen it before?
 - Was Nickleback right?



Graph

Introduction

- So what is a graph?
 - Have you seen it before?
 - Was Nickleback right?



Here's a graph of my life thus far




- So what is a graph?
- A graph contains
 - Vertex (Vertices)
 - Edge (Edges)

Graph

Introduction

- So what is a graph?
- A graph contains
 - Vertex (Vertices)
 - Edge (Edges)



- So what is a graph?
- A graph contains
 - Vertex (Vertices)
 - Points
 - Edge (Edges)
 - Link between points

- So what is a graph?
- A graph contains
 - Vertex (Vertices)
 - Points
 - Also known as nodes
 - Edge (Edges)
 - Link between points
 - Also known as link


Questions?

- So what is a graph?
- A graph contains
 - Vertex (Vertices)
 - Points
 - Also known as nodes
 - Edge (Edges)
 - Link between points
 - Also known as link
 - These links can be directed or undirected

Graph

Introduction


- So what is a graph?
- A graph contains
 - Vertex (Vertices)
 - Points
 - Also known as nodes
 - Edge (Edges)
 - Link between points
 - Also known as link
 - These links can be directed or **undirected**



Graph

Introduction


- So what is a graph?
- A graph contains
 - Vertex (Vertices)
 - Points
 - Also known as nodes
 - Edge (Edges)
 - Link between points
 - Also known as link
 - These links can be **directed** or undirected



Graph

Introduction

- So what is a graph?
- A graph contains
 - Vertex (Vertices)
 - Points
 - Also known as nodes
 - Edge (Edges)
 - Link between points
 - Also known as link
 - These links can be directed or undirected
 - These links can be **weighted** or unweighted



Questions?

- A graph, $G=(V,E)$
 - Contains set of vertices V and a set of Edges E

- A graph, $G=(V,E)$
 - Contains set of vertices V and a set of Edges E

- An edge, $e=(u,v)$
 - u and v are both vertices

- A graph, $G=(V,E)$
 - Contains set of vertices V and a set of Edges E

- An edge, $e=(u,v)$
 - u and v are both vertices
 - If directed, the edge goes from u to v

- A graph, $G=(V,E)$
 - Contains set of vertices V and a set of Edges E

- An edge, $e=(u,v)$
 - u and v are both vertices
 - If directed, the edge goes from u to v

- A weighted graph, $G=(V,E,W)$

- A graph, $G=(V,E)$
 - Contains set of vertices V and a set of Edges E
- An edge, $e=(u,v)$
 - u and v are both vertices
 - If directed, the edge goes from u to v
- A weighted graph, $G=(V,E,W)$
 - W are the weights

- A graph, $G=(V,E)$
 - Contains set of vertices V and a set of Edges E

- An edge, $e=(u,v)$
 - u and v are both vertices
 - If directed, the edge goes from u to v
 - If weighted, $e=(u,v,w)$

- A weighted graph, $G=(V,E,W)$
 - W are the weights

- A graph, $G=(V,E)$
 - Contains set of vertices V and a set of Edges E
- An edge, $e=(u,v)$
 - u and v are both vertices
 - If directed, the edge goes from u to v
 - If weighted, $e=(u,v,w)$
- A weighted graph, $G=(V,E,W)$
 - W are the weights
- Simple graph
 - No self-edges
 - No multi-edges between vertices

- A graph, $G=(V,E)$
 - Contains set of vertices V and a set of Edges E
- An edge, $e=(u,v)$
 - u and v are both vertices
 - If directed, the edge goes from u to v
 - If weighted, $e=(u,v,w)$
- A weighted graph, $G=(V,E,W)$
 - W are the weights
- Simple graph
 - No self-edges (known as loops also)
 - No multi-edges between vertices

Questions?

Graph

Properties

- Let say we have graph, $G=(V,E)$
 - $|V|$ is the number of vertices
 - $|E|$ is the number of edges

- Let say we have graph, $G=(V,E)$
 - $|V|$ is the number of vertices
 - $|E|$ is the number of edges
- Maximum number of edges?
 - Directed graph?

- Let say we have graph, $G=(V,E)$
 - $|V|$ is the number of vertices
 - $|E|$ is the number of edges
- Maximum number of edges?
 - Directed graph? $V(V-1) = O(V^2)$

- Let say we have graph, $G=(V,E)$
 - $|V|$ is the number of vertices
 - $|E|$ is the number of edges
- Maximum number of edges?
 - Directed graph? $V(V-1) = O(V^2)$
 - Undirected graph?

- Let say we have graph, $G=(V,E)$
 - $|V|$ is the number of vertices
 - $|E|$ is the number of edges
- Maximum number of edges?
 - Directed graph? $V(V-1) = O(V^2)$
 - Undirected graph? $V(V-1)/2 = O(V^2)$

- Let say we have graph, $G=(V,E)$
 - $|V|$ is the number of vertices
 - $|E|$ is the number of edges
- Maximum number of edges?
 - Directed graph? $V(V-1) = O(V^2)$
 - Undirected graph? $V(V-1)/2 = O(V^2)$
- A graph is called sparse if $E \ll V^2$
- A graph is called dense if $E \approx V^2$

Questions?

- We saw earlier how we can represent anything as a graph...

Graph Importance

- We saw earlier how we can represent anything as a graph...
 - Trees are in fact graphs.

- We saw earlier how we can represent anything as a graph...
 - Trees are in fact graphs.
 - Single vertex with no incoming edge is the root.

- We saw earlier how we can represent anything as a graph...
 - Trees are in fact graphs.
 - Single vertex with no incoming edge is the root.
 - A binary tree has vertices with a maximum of 2 outgoing edge only.

- We saw earlier how we can represent anything as a graph...
 - Trees are in fact graphs.
 - Single vertex with no incoming edge is the root.
 - A binary tree has vertices with a maximum of 2 outgoing edge only.
 - There is **no cycle**!

- We saw earlier how we can represent anything as a graph...
 - Trees are in fact graphs.
 - Single vertex with no incoming edge is the root.
 - A binary tree has vertices with a maximum of 2 outgoing edge only.
 - There is **no cycle**!
 - Later, we will see how to build a optimal tree from a graph =)

- We saw earlier how we can represent anything as a graph...
 - Trees are in fact graphs.
 - Single vertex with no incoming edge is the root.
 - A binary tree has vertices with a maximum of 2 outgoing edge only.
 - There is **no cycle**!
 - Later, we will see how to build a optimal tree from a graph =)
 - The World Wide Web (WWW) are in fact a graph

- We saw earlier how we can represent anything as a graph...
 - Trees are in fact graphs.
 - Single vertex with no incoming edge is the root.
 - A binary tree has vertices with a maximum of 2 outgoing edge only.
 - There is **no cycle!**
 - Later, we will see how to build a optimal tree from a graph =)
 - The World Wide Web (WWW) are in fact a graph
 - Each webpage is a vertex
 - Each hyperlink is an edge

- We saw earlier how we can represent anything as a graph...
 - Trees are in fact graphs.
 - Single vertex with no incoming edge is the root.
 - A binary tree has vertices with a maximum of 2 outgoing edge only.
 - There is **no cycle**!
 - Later, we will see how to build a optimal tree from a graph =)
 - The World Wide Web (WWW) are in fact a graph
 - Each webpage is a vertex
 - Each hyperlink is an edge
 - **Google's PageRank** is a graph algorithm

- We saw earlier how we can represent anything as a graph...
 - Trees are in fact graphs.
 - Single vertex with no incoming edge is the root.
 - A binary tree has vertices with a maximum of 2 outgoing edge only.
 - There is **no cycle!**
 - Later, we will see how to build a optimal tree from a graph =)
 - The World Wide Web (WWW) are in fact a graph
 - Each webpage is a vertex
 - Each hyperlink is an edge
 - **Google's PageRank** is a graph algorithm
 - Traversal through webpages and propagate authority
 - You can code it yourself, it is easy!

Questions?

- How do we represent graphs?

- How do we represent graphs? 2 possible way!


- How do we represent graphs? 2 possible way!
 - Adjacency matrix
 - Adjacency list

- Adjacency matrix
 - Store edge information in a matrix

Graph Representation

- Adjacency matrix
 - Store edge information in a matrix
 - True/ False or 1/0 for unweighted


	1	2	3	4	5
1	F	T	T	T	F
2	T	F	T	F	T
3	T	T	F	F	T
4	T	F	F	F	T
5	F	T	T	T	F



Graph Representation

- Adjacency matrix
 - Store edge information in a matrix
 - True/ False or 1/0 for unweighted
 - Weight for weighted

	1	2	3	4	5
1		2	7	4	
2	2		5		6
3	7	5			3
4	4				8
5		6	3	8	



- Adjacency matrix
 - Store edge information in a matrix
 - True/ False or 1/0 for unweighted
 - Weight for weighted
 - Space complexity?

- Adjacency matrix
 - Store edge information in a matrix
 - True/ False or 1/0 for unweighted
 - Weight for weighted
 - Space complexity?
 - $O(V^2)$ as we need the matrix no matter what

- Adjacency matrix
 - Store edge information in a matrix
 - True/ False or 1/0 for unweighted
 - Weight for weighted
 - Space complexity?
 - $O(V^2)$ as we need the matrix no matter what
 - Time complexity?

- Adjacency matrix
 - Store edge information in a matrix
 - True/ False or 1/0 for unweighted
 - Weight for weighted
 - Space complexity?
 - $O(V^2)$ as we need the matrix no matter what
 - Time complexity?
 - $O(1)$ to check if an edge exist

- Adjacency matrix
 - Store edge information in a matrix
 - True/ False or 1/0 for unweighted
 - Weight for weighted
 - Space complexity?
 - $O(V^2)$ as we need the matrix no matter what
 - Time complexity?
 - $O(1)$ to check if an edge exist
 - $O(V)$ to check/ traverse all adjacent vertices

- Adjacency matrix
 - Store edge information in a matrix
 - True/ False or 1/0 for unweighted
 - Weight for weighted
 - Space complexity?
 - $O(V^2)$ as we need the matrix no matter what
 - Time complexity?
 - $O(1)$ to check if an edge exist
 - $O(V)$ to check/ traverse all adjacent vertices
 - Adjacent = neighbour



- Adjacency list

- Adjacency list
 - Array to store all Vertex object

- Adjacency list
 - Array to store all Vertex object
 - Each vertex store a list of edges from it



Graph Representation

- Adjacency list
 - Array to store all Vertex object
 - Each vertex store a list of edges from it



Graph Representation

- Adjacency list
 - Array to store all Vertex object
 - Each vertex store a list of edges from it
 - With the weights



- Adjacency list
 - Array to store all Vertex object
 - Each vertex store a list of edges from it
 - With the weights
 - Space complexity?

- Adjacency list
 - Array to store all Vertex object
 - Each vertex store a list of edges from it
 - With the weights
 - Space complexity?
 - $O(V+E)$. Storing V vertices (as an array) and then total of E edges

- Adjacency list
 - Array to store all Vertex object
 - Each vertex store a list of edges from it
 - With the weights
 - Space complexity?
 - $O(V+E)$. Storing V vertices (as an array) and then total of E edges
 - Time complexity?

- Adjacency list
 - Array to store all Vertex object
 - Each vertex store a list of edges from it
 - With the weights
 - Space complexity?
 - $O(V+E)$. Storing V vertices (as an array) and then total of E edges
 - Time complexity?
 - $O(\log V)$ to check if an edge exist if the edges are sorted
 - $O(X)$ to retrieve all of the adjacent vertices of a vertex

- Adjacency list
 - Array to store all Vertex object
 - Each vertex store a list of edges from it
 - With the weights
 - Space complexity?
 - $O(V+E)$. Storing V vertices (as an array) and then total of E edges
 - Time complexity?
 - $O(\log V)$ to check if an edge exist if the edges are sorted
 - But you can't use binary search on linked list!
 - So this is still $O(X)$ but you can terminate earlier once you reach a bigger vertex
 - $O(X)$ to retrieve all of the adjacent vertices of a vertex
 - Where X = number of adjacent vertices (output-sensitive complexity)


Questions?

- Going from a place to another

- Going from a place (**source vertex**) to another


Graph Traversal

- Going from a place (**source vertex**) to another or everywhere!



Graph Traversal

- Going from a place (**source vertex**) to another or everywhere!




- Breadth-First Search (BFS)
- Depth-First Search (DFS)

- Breadth-First Search (BFS)
 - Going wide
- Depth-First Search (DFS)
 - Going deep

- Breadth-First Search (BFS)
 - Going wide
- Depth-First Search (DFS)
 - Going deep
- Let us begin with a tree first


- Breadth-First Search (BFS)
 - Going wide
- Depth-First Search (DFS)
 - Going deep
- Let us begin with a tree first
 - Recall a tree is a graph without cycles

Graph Traversal




Graph Traversal

- Start at A




Graph Traversal

- Start at A




Graph Traversal

- Start at A, BFS




Graph Traversal

- Start at A, BFS
- A




Graph Traversal

- Start at A, BFS
- A
- B




Graph Traversal

- Start at A, BFS
- A
- B
- C




Graph Traversal

- Start at A, BFS
- A
- B
- C
- D




Graph Traversal

- Start at A, BFS
- A
- B
- C
- D
- E




Graph Traversal

- Start at A, BFS
- A
- B
- C
- D
- E
- F




Graph Traversal

- Start at A, BFS
- A
- B
- C
- D
- E
- F
- G




Graph Traversal

- Start at A, BFS
- A
- B
- C
- D
- E
- F
- G
- ... and so on...




Graph Traversal

- Start at A




- Start at A, DFS




Graph Traversal

- Start at A, DFS
- A




Graph Traversal

- Start at A, DFS
- A
- B




Graph Traversal

- Start at A, DFS
- A
- B
- D, go deep!




Graph Traversal

- Start at A, DFS
- A
- B
- D
- H




Graph Traversal

- Start at A, DFS
- A
- B
- D
- H
- can't go deeper




Graph Traversal

- Start at A, DFS
- A
- B
- D
- H
- I




Graph Traversal

- Start at A, DFS
- A
- B
- D
- H
- I
- E




Graph Traversal

- Start at A, DFS
- A
- B
- D
- H
- I
- E
- C




Graph Traversal

- Start at A, DFS
- A
- B
- D
- H
- I
- E
- C
- F




Graph Traversal

- Start at A, DFS
- A
- B
- D
- H
- I
- E
- C
- F
- J




Graph Traversal

- Start at A, DFS
- A
- B
- D
- H
- I
- E
- C
- F
- J
- K



Graph Traversal

- Start at A, DFS
- B
- D
- H
- I
- E
- C
- F
- J
- K
- G, finally




Questions?


Graph

BFS Implementation


- How would you implement it?




- How would you implement it?
 - Let say we begin from vertex A



- How would you implement it?
 - Let say we begin from vertex A
 - What is our traversal?




- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered




Discovered	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>
Visited	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Start with A




Discovered									
Visited									

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it




Discovered	A								
Visited									

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty




Discovered	A								
Visited									

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered




Discovered	A								
Visited									

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited




Discovered									
Visited	A								

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served



Discovered									
Visited	A								

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered									
Visited	A								

Graph


BFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered	C								
Visited	A								

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue



Discovered	C	B							
Visited	A								

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered		B							
Visited	A	C							

Graph


BFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue



Discovered		B	D						
Visited	A	C							

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered			D						
Visited	A	C	B						

Graph

BFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered			D	F						
Visited	A	C	B							

Graph

BFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered			D	F	E					
Visited	A	C	B							

Graph

BFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered				F	E					
Visited	A	C	B	D						

Graph


BFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered					E					
Visited	A	C	B	D	F					

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered					E	G				
Visited	A	C	B	D	F					

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered						G				
Visited	A	C	B	D	F	E				

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered						G	G?			
Visited	A	C	B	D	F	E				

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered						G	H			
Visited	A	C	B	D	F	E				

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered							H			
Visited	A	C	B	D	F	E	G			

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue



Discovered									
Visited	A	C	B	D	F	E	G	H	

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
- The traversal answer is not unique



Discovered									
Visited	A	C	B	D	F	E	G	H	

- Complexity?

Graph

BFS Implementation

- Complexity?
 - Time is $O(V+E)$

Graph

BFS Implementation

- Complexity?
 - Time is $O(V+E)$
 - Each vertex is visited once

- Complexity?
 - Time is $O(V+E)$
 - Each vertex is visited once
 - Each edge is visited twice

Graph

BFS Implementation

- Complexity?
 - Time is $O(V+E)$
 - Each vertex is visited once
 - Each edge is visited twice
 - For each $\langle u,v \rangle$ we visit from u and also from v

Graph

BFS Implementation

- Complexity?
 - Time is $O(V+E)$
 - Each vertex is visited once
 - Each edge is visited twice
 - For each $\langle u, v \rangle$ we visit from u and also from v
 - Space is $O(V+E)$

Graph

BFS Implementation

- Complexity?
 - Time is $O(V+E)$
 - Each vertex is visited once
 - Each edge is visited twice
 - For each $\langle u, v \rangle$ we visit from u and also from v
 - Space is $O(V+E)$
 - V maximum for the discovered queue

Graph

BFS Implementation

- Complexity?
 - Time is $O(V+E)$
 - Each vertex is visited once
 - Each edge is visited twice
 - For each $\langle u, v \rangle$ we visit from u and also from v
 - Space is $O(V+E)$
 - V maximum for the discovered queue
 - E to stored all of the edges (adjacency list)

- Complexity?
 - Time is $O(V+E)$
 - Each vertex is visited once
 - Each edge is visited twice
 - For each $\langle u, v \rangle$ we visit from u and also from v
 - Space is $O(V+E)$
 - V maximum for the discovered queue
 - E to stored all of the edges (adjacency list)
 - But don't we need to check the discovered queue for each vertex v ?
 - $O(V)$ search through the queue?


Graph

BFS Implementation


- Complexity?
 - Time is $O(V+E)$
 - Each vertex is visited once
 - Each edge is visited twice
 - For each $\langle u, v \rangle$ we visit from u and also from v
 - Space is $O(V+E)$
 - V maximum for the discovered queue
 - E to stored all of the edges (adjacency list)
 - But don't we need to check the discovered queue for each vertex v ?
 - $O(V)$ search through the queue?
 - NO! Implement a Node class with `self.discovered = True/ False`

Questions?

- How would you implement it?
 - Let say we begin from vertex A
 - What is our DFS traversal?




- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered




Discovered									
Visited									

- How would you implement it?
 - Let say we begin from vertex A
 - Have a ~~queue~~ stack for discovered




Discovered	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>
Visited	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>	<div></div>

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it




Discovered	A								
Visited									

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered	A								
Visited									

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue



Discovered									
Visited	A								

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered	C								
Visited	A								

Graph


DFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue



Discovered	C	B							
Visited	A								

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered	C								
Visited	A	B							

Graph

DFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered	C	A?							
Visited	A	B							

Graph


DFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered	C	F							
Visited	A	B							

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue



Discovered	C	F	E						
Visited	A	B							

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered	C	F							
Visited	A	B	E						

Graph

DFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered	C	F	G						
Visited	A	B	E						

Graph


DFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue



Discovered	C	F	G	H						
Visited	A	B	E							

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered	C	F	G						
Visited	A	B	E	H					

Graph

DFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered	C	F							
Visited	A	B	E	H	G				

Graph


DFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue



Discovered	C								
Visited	A	B	E	H	G	F			

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered									
Visited	A	B	E	H	G	F	C		

Graph


DFS Implementation

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue



Discovered	D								
Visited	A	B	E	H	G	F	C		

- How would you implement it?
 - Let say we begin from vertex A
 - Have a stack for discovered
 - Push source (A) into it
 - While discovered is not empty
 - Pop from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue



Discovered									
Visited	A	B	E	H	G	F	C	D	

Graph

DFS Implementation

- Complexity?

- Complexity?
 - Time is $O(V+E)$
 - Explanation same as BFS

Graph

DFS Implementation

- Complexity?
 - Time is $O(V+E)$
 - Explanation same as BFS
 - Space is $O(V+E)$
 - Explanation same as DFS

Graph

DFS Implementation

- Can you think of another way to implement DFS?

- Can you think of another way to implement DFS?
- Recursion!
 - Best way to implement any form of traversal
 - Just like when you implemented tree/ trie traversal

Graph

DFS Implementation

- Can you think of another way to implement DFS?
- Recursion!
 - Best way to implement any form of traversal
 - Just like when you implemented tree/ trie traversal
- Let us just write them all out as a live coding session!

Questions?

- Can you think of another way to implement DFS?
- Recursion!
 - Best way to implement any form of traversal
 - Just like when you implemented tree/ trie traversal

```
1  def dfs(current_vertex):
2      current_vertex.visited = True
3      for next_vertex in current_vertex.adjacent:
4          if next_vertex.visited == False:
5              dfs(next_vertex)
6
7  source_vertex = A
8  dfs(source_vertex)
```

- Can you think of another way to implement DFS?
- Recursion!
 - Best way to implement any form of traversal
 - Just like when you implemented tree/ trie traversal
 - Make sense because we are going depth-first like how recursion does it!

```
1 def dfs(current_vertex):
2     current_vertex.visited = True
3     for next_vertex in current_vertex.adjacent:
4         if next_vertex.visited == False:
5             dfs(next_vertex)
6
7     source_vertex = A
8     dfs(source_vertex)
```

Questions?

- As mentioned earlier, it is the basic algorithm for many more complex algorithm... the application include:

- As mentioned earlier, it is the basic algorithm for many more complex algorithm... the application include:
 - Reachability
 - Finding all connected components
 - Finding cycles
 - Shortest path (brute force)
 - Shortest path (non-brute force) on unweighted graph
 - Topological sort (later on)
 - ... and many more!

- As mentioned earlier, it is the basic algorithm for many more complex algorithm... the application include:
 - Reachability
 - Finding all connected components
 - Finding cycles
 - Shortest path (brute force)
 - Shortest path (non-brute force) on unweighted graph
 - Topological sort (later on)
 - ... and many more!
- We will see more in unit notes and tutorials

Questions?

Break!

Graph

Shortest distance and path

- Classical problem

- Classical problem
 - Given a set of locations
 - Given routes between locations
 - Given the distance between locations

- Classical problem
 - Given a set of locations
 - Given routes between locations
 - Given the distance between locations
 - Can you find the shortest distance from a source to a destination?

- Classical problem
 - Given a set of locations
 - Given routes between locations
 - Given the distance between locations
 - Can you find the shortest distance from a source to a destination?
 - What is the path?

- Classical problem
 - Given a set of locations as **vertices V**
 - Given routes between locations as **edges E**
 - Given the distance between locations as **weights W**
 - Can you find the shortest distance from a source to a destination?
 - What is the path?

- Classical problem
 - Given a set of locations as **vertices V**
 - Given routes between locations as **edges E**
 - Given the distance between locations as **weights W**
 - Can you find the shortest distance from a source to a destination?
 - What is the path? This would require **backtracking**

- Classical problem
 - Given a set of locations as **vertices V**
 - Given routes between locations as **edges E**
 - Given the distance between locations as **weights W**
 - Can you find the shortest distance from a source to a destination?
 - What is the path? This would require **backtracking**

- If the graph is unweighted?


- Classical problem
 - Given a set of locations as **vertices V**
 - Given routes between locations as **edges E**
 - Given the distance between locations as **weights W**
 - Can you find the shortest distance from a source to a destination?
 - What is the path? This would require **backtracking**

- If the graph is unweighted?
 - Use BFS from the source!

- Classical problem
 - Given a set of locations as **vertices V**
 - Given routes between locations as **edges E**
 - Given the distance between locations as **weights W**
 - Can you find the shortest distance from a source to a destination?
 - What is the path? This would require **backtracking**

- If the graph is unweighted?
 - Use BFS from the source!
 - Look back our BFS example

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered	A,0								
Visited									

Graph


Shortest distance with BFS

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue




Discovered									
Visited	A,0								

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$




Discovered									
Visited	A,0								

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$




Discovered	C,1	B,1							
Visited	A,0								

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$




Discovered		B,1							
Visited	A,0	C,1							

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$




Discovered		B,1	D,2						
Visited	A,0	C,1							

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$




Discovered			D,2						
Visited	A,0	C,1	B,1						

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$




Discovered			D,2	F,2	E,2					
Visited	A,0	C,1	B,1							

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$




Discovered				F,2	E,2					
Visited	A,0	C,1	B,1	D,2						

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$




Discovered					E,2					
Visited	A,0	C,1	B,1	D,2	F,2					

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$




Discovered					E,2	G,3				
Visited	A,0	C,1	B,1	D,2	F,2					

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$




Discovered						G,3				
Visited	A,0	C,1	B,1	D,2	F,2	E,2				

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$




Discovered						G,3	H,3			
Visited	A,0	C,1	B,1	D,2	F,2	E,2				

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$



Discovered							H,3			
Visited	A,0	C,1	B,1	D,2	F,2	E,2	G,3			

- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$



Discovered									
Visited	A,0	C,1	B,1	D,2	F,2	E,2	G,3	H,3	

Questions?

- How would you modify the following to find the path?
- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$

- How would you modify the following to find the path?
- How would you implement it?
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$
 - $v.\text{previous} = u$ # enable backtracking

Questions?

Graph

Shortest path with Dijkstra

- What if the graph is weighted?

- What if the graph is weighted?
 - BFS is not able to do it anymore

- What if the graph is weighted?
 - BFS is not able to do it anymore
 - Sooo, we call in Dijkstra

Graph

Shortest path with Dijkstra

- What if the graph is weighted?
 - BFS is not able to do it anymore
 - Sooo, we call in Dijkstra (the left one)



Graph

Shortest path with Dijkstra

- What if the graph is weighted?
 - BFS is not able to do it anymore
 - Sooo, we call in Dijkstra (the left one)
- So Dijkstra came up with the shortest distance algorithm
 - Recall we can backtrack (previous) to get the path

Bae: Come over

Dijkstra: But there are so many routes to take and
I don't know which one's the fastest

Bae: My parents aren't home

Dijkstra:

Dijkstra's algorithm


Graph search algorithm

Not to be confused with Dykstra's projection algorithm.

Dijkstra's algorithm is an algorithm for finding the **shortest paths** between **nodes** in a **graph**, which may represent, for example, road networks. It was conceived by computer scientist Edsger W. Dijkstra in 1956 and published three years later.^{[1][2]}

The algorithm exists in many variants; Dijkstra's original variant found the shortest path between two nodes,^[2] but a more common variant fixes a single node as the "source" node and finds shortest paths from the source to all other nodes in the graph, producing a **shortest-path tree**.


Dijkstra's algorithm



How Dijkstra came up with his algorithm

Graph

Shortest path with Dijkstra



Here I've put together a little list, in no particular order.

- Merge Sort, Quick Sort and Heap Sort. ...
- Fourier Transform and Fast Fourier Transform. ...
- Dijkstra's algorithm. ...
- RSA algorithm. ...
- Secure Hash Algorithm. ...
- Integer factorization. ...
- Link Analysis. ...
- Proportional Integral Derivative Algorithm.

More items...

The real 10 algorithms that dominate our world – Marcos Otero - Medium
<https://medium.com/@.../the-real-10-algorithms-that-dominate-our-world-e95fa9f16c04>

Name	Best	Average	Worst	Memory	Stable
Quicksort	$O(n \log n)$	$O(n \log n)$	$O(n^2)$	$O(n)$	Yes
Mergesort	$O(n \log n)$	$O(n \log n)$	$O(n \log n)$	$O(n)$	Yes
Heapsort	$O(n \log n)$	$O(n \log n)$	$O(n \log n)$	$O(1)$	No
Radix sort	$O(n)$	$O(n)$	$O(n)$	$O(n)$	Yes
Counting sort	$O(n)$	$O(n)$	$O(n)$	$O(n)$	Yes
Bucket sort	$O(n)$	$O(n)$	$O(n)$	$O(n)$	Yes
Linear time	$O(n)$	$O(n)$	$O(n)$	$O(n)$	Yes
Selection sort	$O(n^2)$	$O(n^2)$	$O(n^2)$	$O(1)$	No
Bubble sort	$O(n^2)$	$O(n^2)$	$O(n^2)$	$O(1)$	No
Insertion sort	$O(n^2)$	$O(n^2)$	$O(n^2)$	$O(1)$	No

Bae: Come over

Dijkstra: But there are so many routes to take and
I don't know which one's the fastest

Bae: My parents aren't home

Dijkstra:

Dijkstra's algorithm


Graph search algorithm

Not to be confused with Dykstra's projection algorithm.

Dijkstra's algorithm is an algorithm for finding the **shortest paths** between **nodes** in a **graph**, which may represent, for example, road networks. It was conceived by computer scientist **Edsger W. Dijkstra** in 1956 and published three years later.^{[1][2]}

The algorithm exists in many variants; Dijkstra's original variant found the shortest path between two nodes,^[2] but a more common variant fixes a single node as the "source" node and finds shortest paths from the source to all other nodes in the graph, producing a **shortest-path tree**.

Dijkstra's algorithm



How Dijkstra came up with his algorithm

Graph

Shortest path with Dijkstra

- It is a combination of 2 algorithms

- It is a combination of 2 algorithms
 - Dynamic programming
 - Greedy

- It is a combination of 2 algorithms
 - Dynamic programming

The minimum distance from A to C can be the minimum of A to B (which we know) and minimum of B to C (which we know as well).
 - Greedy

- It is a combination of 2 algorithms

- Dynamic programming

The minimum distance from A to C can be the minimum of A to B (which we know) and minimum of B to C (which we know as well).

- Greedy

If I am at A, I can reach B and C. B is the closest, so I go to B and this is the shortest from A to B. I do not need to check if A to C then C to B (A->C->B) is the shortest anymore.

- It is a combination of 2 algorithms

- Dynamic programming

The minimum distance from A to C can be the minimum of A to B (which we know) and minimum of B to C (which we know as well).

- Greedy

If I am at A, I can reach B and C. B is the closest, so I go to B and this is the shortest from A to B. I do not need to check if A to C then C to B (A→C→B) is the shortest anymore.

but GREED IS NOT GOOD... when will this fail?

- It is a combination of 2 algorithms

- Dynamic programming

The minimum distance from A to C can be the minimum of A to B (which we know) and minimum of B to C (which we know as well).

- Greedy

If I am at A, I can reach B and C. B is the closest, so I go to B and this is the shortest from A to B. I do not need to check if A to C then C to B (A→C→B) is the shortest anymore.

but GREED IS NOT GOOD... when will this fail? When C to B is negative!

- It is a combination of 2 algorithms

- Dynamic programming

The minimum distance from A to C can be the minimum of A to B (which we know) and minimum of B to C (which we know as well).

- Greedy

If I am at A, I can reach B and C. B is the closest, so I go to B and this is the shortest from A to B. I do not need to check if A to C then C to B (A→C→B) is the shortest anymore.

but GREED IS NOT GOOD... when will this fail? When C to B is negative!

- Thus, Dijkstra doesn't work for negative edges

- It is a combination of 2 algorithms

- Dynamic programming

The minimum distance from A to C can be the minimum of A to B (which we know) and minimum of B to C (which we know as well).

- Greedy

If I am at A, I can reach B and C. B is the closest, so I go to B and this is the shortest from A to B. I do not need to check if A to C then C to B (A->C->B) is the shortest anymore.

but GREED IS NOT GOOD... when will this fail? When C to B is negative!

- Thus, Dijkstra doesn't work for negative edges

Note: might work at times when the negative edge isn't part of a cycle

Questions?

Graph


Shortest path with Dijkstra

- So how does Dijkstra work?

Graph

Shortest path with Dijkstra


- So how does Dijkstra work?
 - Consider the following directed graph



Graph

Shortest path with Dijkstra


- So how does Dijkstra work?
 - Consider the following directed graph
 - Graph is weighted



Graph

Shortest path with Dijkstra


- So how does Dijkstra work?
 - Consider the following directed graph
 - Graph is weighted
 - So let us begin the algorithm...



Graph

Shortest path with Dijkstra


- So how does Dijkstra work?
 - Consider the following directed graph
 - Graph is weighted
 - So let us begin the algorithm...
 - We are at A (source), and



Graph

Shortest path with Dijkstra


- So how does Dijkstra work?
 - Consider the following directed graph
 - Graph is weighted
 - So let us begin the algorithm...
 - We are at A (source), and



**FOG OF
WAR**




- So how does Dijkstra work?
 - Consider the following directed graph
 - Graph is weighted
 - So let us begin the algorithm...
 - So what happen is we will slowly wander to the closest point (from A)




**FOG OF
WAR**

- So how does Dijkstra work?
 - Consider the following directed graph
 - Graph is weighted
 - So let us begin the algorithm...
 - So what happen is we will slowly wander to the closest point (from A)



**FOG OF
WAR**

- So how does Dijkstra work?
 - Consider the following directed graph
 - Graph is weighted
 - So let us begin the algorithm...
 - So what happen is we will slowly wander to the closest point (from A)
 - $A = 0$
 - $B = \text{infinity}$
 - $C = \text{infinity}$
 - $D = \text{infinity}$
 - $E = \text{infinity}$




**FOG OF
WAR**

- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted



- So let us begin the algorithm...


- So what happen is we will slowly wander to the closest point (from A)

- $A = 0$, from here, we can see B and C (edges from A)
 - $B = \text{infinity}$
 - $C = \text{infinity}$
 - $D = \text{infinity}$
 - $E = \text{infinity}$

- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted



- So let us begin the algorithm...


- So what happens if we will slowly wander to the closest point (from A)

- $A = 0$, from here, we can see B and C (edges from A). Update distance
 - $B = 10$
 - $C = 5$
 - $D = \text{infinity}$
 - $E = \text{infinity}$

- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted



- So let us begin the algorithm...

- So what happens if we will slowly wander to the closest point (from A)

- $A = 0$, from here, we can see B and C (edges from A). Update distance
 - $B = 10$
 - $C = 5$
 - $D = \text{infinity}$
 - $E = \text{infinity}$
 - Closest is C, so we move to C

- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted

- So let us begin the algorithm...

- So what happens if we will slowly wander to the closest point (from A)

- $A = 0$, from here, we can see B and C (edges from A). Update distance


- $B = 10$

- $C = 5$

- $D = \text{infinity}$

- $E = \text{infinity}$

- Closest is C, so we move to C



- So how does Dijkstra work?


- Consider the following directed graph

- Graph is weighted


- So let us begin the algorithm...

- So what happens if we will slowly wander to the closest point (from A)


- A = 0, from here, we can see B and C (edges from A). Update distance
- B = 10
- C = 5, from here, we can see B, D and E
- D = infinity
- E = infinity



- So how does Dijkstra work?
 - Consider the following directed graph
 - Graph is weighted
 - So let us begin the algorithm...
 - So what happens we will slowly wander to the closest point (from A)
 - $A = 0$, from here, we can see B and C (edges from A). Update distance
 - $B = 10$
 - $C = 5$, from here, we can see B, D and E. Update the distance
 - $D = \text{infinity}$
 - $E = \text{infinity}$



- So how does Dijkstra work?
 - Consider the following directed graph
 - Graph is weighted
 - So let us begin the algorithm...
 - So what happens we will slowly wander to the closest point (from A)
 - $A = 0$, from here, we can see B and C (edges from A). Update distance
 - $B = 10$ (A→B) vs 8 (A→C→B)
 - $C = 5$, from here, we can see B, D and E. Update the distance
 - $D = \text{infinity}$
 - $E = \text{infinity}$



- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted

- So let us begin the algorithm...

- So what happens we will slowly wander to the closest point (from A)


- A = 0, from here, we can see B and C (edges from A). Update distance

- B = 8

- C = 5, from here, we can see B, D and E. Update the distance

- D = infinity

- E = infinity



- So how does Dijkstra work?


- Consider the following directed graph

- Graph is weighted

- So let us begin the algorithm...

- So what happens if we will slowly wander to the closest point (from A)

- A = 0, from here, we can see B and C (edges from A). Update distance
- B = 8
- C = 5, from here, we can see B, D and E. Update the distance
- D = 9?
- E = infinity



- So how does Dijkstra work?


- Consider the following directed graph

- Graph is weighted

- So let us begin the algorithm...

- So what happens we will slowly wander to the closest point (from A)

- $A = 0$, from here, we can see B and C (edges from A). Update distance
 - $B = 8$
 - $C = 5$, from here, we can see B, D and E. Update the distance
 - $D = 14$ because distance is from A
 - $E = \text{infinity}$



- So how does Dijkstra work?


- Consider the following directed graph

- Graph is weighted

- So let us begin the algorithm...

- So what happens if we will slowly wander to the closest point (from A)

- $A = 0$, from here, we can see B and C (edges from A). Update distance
- $B = 8$
- $C = 5$, from here, we can see B, D and E. Update the distance
- $D = 14$
- $E = 7$



- So how does Dijkstra work?


- Consider the following directed graph

- Graph is weighted

- So let us begin the algorithm...

- So what happens if we will slowly wander to the closest point (from A)

- A = 0, from here, we can see B and C (edges from A). Update distance
- B = 8
- C = 5, from here, we can see B, D and E. Update the distance
- D = 14
- E = 7
- Closest is E, so we go E



- So how does Dijkstra work?


- Consider the following directed graph

- Graph is weighted

- So let us begin the algorithm...

- So what happens if we will slowly wander to the closest point (from A)

- A = 0, from here, we can see B and C (edges from A). Update distance
- B = 8
- C = 5, from here, we can see B, D and E. Update the distance
- D = 14
- E = 7
- Closest is E, so we go E



- So how does Dijkstra work?


- Consider the following directed graph

- Graph is weighted

- So let us begin the algorithm...

- So what happens if we will slowly wander to the closest point (from A)

- A = 0, from here, we can see B and C (edges from A). Update distance
- B = 8
- C = 5, from here, we can see B, D and E. Update the distance
- D = 14
- E = 7, from here, we can see D.



- So how does Dijkstra work?


- Consider the following directed graph

- Graph is weighted

- So let us begin the algorithm...

- So what happens if we will slowly wander to the closest point (from A)

- $A = 0$, from here, we can see B and C (edges from A). Update distance
- $B = 8$
- $C = 5$, from here, we can see B, D and E. Update the distance
- $D = 14$ vs $7+6$ (A→E→D)
- $E = 7$, from here, we can see D. Update the distance



- So how does Dijkstra work?


- Consider the following directed graph

- Graph is weighted

- So let us begin the algorithm...

- So what happens if we will slowly wander to the closest point (from A)

- A = 0, from here, we can see B and C (edges from A). Update distance
- B = 8
- C = 5, from here, we can see B, D and E. Update the distance
- D = 13
- E = 7, from here, we can see D. Update the distance



- So how does Dijkstra work?


- Consider the following directed graph

- Graph is weighted

- So let us begin the algorithm...

- So what happens if we will slowly wander to the closest point (from A)


- A = 0, from here, we can see B and C (edges from A). Update distance
- B = 8
- C = 5, from here, we can see B, D and E. Update the distance
- D = 13
- E = 7, from here, we can see D. Update the distance
- Closest is B, so we go B



- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted




- So let us begin the algorithm...
- So what happens if we slowly wander to the closest point (from A)
 - $A = 0$, from here, we can see B and C (edges from A). Update distance
 - $B = 8$
 - $C = 5$, from here, we can see B, D and E. Update the distance
 - $D = 13$
 - $E = 7$, from here, we can see D. Update the distance
 - Closest is B, so we go B

- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted




- So let us begin the algorithm...
- So what happens if we slowly wander to the closest point (from A)
 - A = 0, from here, we can see B and C (edges from A). Update distance
 - B = 8, from here, we can see C and D.
 - C = 5, from here, we can see B, D and E. Update the distance
 - D = 13
 - E = 7, from here, we can see D. Update the distance

- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted




- So let us begin the algorithm...
- So what happens if we slowly wander to the closest point (from A)
 - A = 0, from here, we can see B and C (edges from A). Update distance
 - B = 8, from here, we can see C and D. Update distance for C?
 - C = 5, from here, we can see B, D and E. Update the distance
 - D = 13
 - E = 7, from here, we can see D. Update the distance

- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted




- So let us begin the algorithm...
- So what happen is we will slowly wander to the closest point (from A)
 - A = 0, from here, we can see B and C (edges from A). Update distance
 - B = 8, from here, we can see C and D. Update distance for D.
 - C = 5, from here, we can see B, D and E. Update the distance
 - D = 13
 - E = 7, from here, we can see D. Update the distance

- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted




- So let us begin the algorithm...
- So what happens if we will slowly wander to the closest point (from A)
 - A = 0, from here, we can see B and C (edges from A). Update distance
 - B = 8, from here, we can see C and D. Update distance for D.
 - C = 5, from here, we can see B, D and E. Update the distance
 - D = 9 (8+1 via A->B->D)
 - E = 7, from here, we can see D. Update the distance

- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted




- So let us begin the algorithm...
- So what happen is we will slowly wander to the closest point (from A)
 - $A = 0$, from here, we can see B and C (edges from A). Update distance
 - $B = 8$, from here, we can see C and D. Update distance for D.
 - $C = 5$, from here, we can see B, D and E. Update the distance
 - $D = 9$
 - $E = 7$, from here, we can see D. Update the distance

- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted




- So let us begin the algorithm...
- So what happens if we slowly wander to the closest point (from A)
 - A = 0, from here, we can see B and C (edges from A). Update distance
 - B = 8, from here, we can see C and D. Update distance for D.
 - C = 5, from here, we can see B, D and E. Update the distance
 - D = 9
 - E = 7, from here, we can see D. Update the distance
 - Closest is D, so we move there

- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted




- So let us begin the algorithm...
- So what happens if we will slowly wander to the closest point (from A)
 - A = 0, from here, we can see B and C (edges from A). Update distance
 - B = 8, from here, we can see C and D. Update distance for D.
 - C = 5, from here, we can see B, D and E. Update the distance
 - D = 9
 - E = 7, from here, we can see D. Update the distance
 - Closest is D, so we move there

- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted




- So let us begin the algorithm...
- So what happens if we will slowly wander to the closest point (from A)
 - A = 0, from here, we can see B and C (edges from A). Update distance
 - B = 8, from here, we can see C and D. Update distance for D.
 - C = 5, from here, we can see B, D and E. Update the distance
 - D = 9, from here, we can see E but E is already finalized
 - E = 7, from here, we can see D. Update the distance
 - Closest is D, so we move there

- So how does Dijkstra work?

- Consider the following directed graph

- Graph is weighted



- So let us begin the algorithm...
- So what happens if we will slowly wander to the closest point (from A)
 - A = 0, from here, we can see B and C (edges from A). Update distance
 - B = 8, from here, we can see C and D. Update distance for D.
 - C = 5, from here, we can see B, D and E. Update the distance
 - D = 9, from here, we can see E but E is already finalized
 - E = 7, from here, we can see D. Update the distance
 - And we are **done**!

Questions?

Graph

Shortest path with Dijkstra

- Algorithm?

- Algorithm? Very similar to the BFS except...

- Algorithm? Very similar to the BFS except...
 - Priority queue instead of a normal queue
 - Serve the closest vertex (not finalized)

- Algorithm? Very similar to the BFS except...
 - Priority queue instead of a normal queue
 - Serve the closest vertex (not finalized)
 - Update the distance if the neighbour vertex is visited but not finalized
 - To the shorter one

- This is the BFS algorithm, we change to Dijkstra now
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$

- This is the BFS algorithm, we change to Dijkstra now
 - Let say we begin from vertex A
 - Have a queue for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - $v.\text{distance} = u.\text{distance} + 1$
- Try to modify this as part of the in-class activity

- This is the BFS algorithm, we change to Dijkstra now
 - Let say we begin from vertex A
 - Have a **priority queue** for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge **<u,v,w>** where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - » Set **v.distance = u.distance + w**
 - If vertex v is discovered but not visited and **v.distance > u.distance + w**
 - » Update **v.distance = u.distance + w**

- This is the BFS algorithm, we change to Dijkstra now
 - Let say we begin from vertex A
 - Have a **priority queue** for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v, w \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - » Set $v.distance = u.distance + w$
 - If vertex v is discovered but not visited and $v.distance > u.distance + w$
 - » Update $v.distance = u.distance + w$
 - We use a min-heap for our priority queue!

- This is the BFS algorithm, we change to Dijkstra now
 - Let say we begin from vertex A
 - Have a **priority queue** for discovered
 - Put source (A) into it with a distance 0
 - While discovered is not empty
 - Serve from discovered, to visited
 - For each edge $\langle u, v, w \rangle$ where u is the served
 - If vertex v is not discovered or visited, add to discovered queue
 - » Set $v.distance = u.distance + w$
 - If vertex v is discovered but not visited and $v.distance > u.distance + w$
 - » Update $v.distance = u.distance + w$
 - We use a min-heap for our priority queue!
 - Note that we need a pointer to the nodes to update distance in $O(1)$

- Algorithm can be as follows (might differ):

```
1  discover_queue = MinHeap()
2  discover_queue.append([source,0])
3
4  while discover_queue is not empty:
5      u = discover_queue.serve()
6      u.visited = True
7      for each <u,v,w> in u.edges:
8          if v.visited = True:
9              pass
10         else:
11             if v.discovered = False:
12                 discover_queue.append([v, u.distance+w])
13                 v.discovered = True
14             else:
15                 if v.distance > u.distance+w:
16                     discover_queue.update(v, u.distance+w)
17                     v.discovered = True
```

Questions?

- Complexity?

```
1  discover_queue = MinHeap()
2  discover_queue.append([source,0])
3
4  while discover_queue is not empty:
5      u = discover_queue.serve()
6      u.visited = True
7      for each <u,v,w> in u.edges:
8          if v.visited = True:
9              pass
10         else:
11             if v.discovered = False:
12                 discover_queue.append([v, u.distance+w])
13                 v.discovered = True
14             else:
15                 if v.distance > u.distance+w:
16                     discover_queue.update(v, u.distance+w)
17                     v.discovered = True
```

Graph

Shortest path with Dijkstra

```
1 discover_queue = MinHeap()
2 discover_queue.append([source,0])
3
4 while discover_queue is not empty:
5     u = discover_queue.serve()
6     u.visited = True
7     for each <u,v,w> in u.edges:
8         if v.visited = True:
9             pass
10        else:
11            if v.discovered = False:
12                discover_queue.append([v, u.distance+w])
13                v.discovered = True
14            else:
15                if v.distance > u.distance+w:
16                    discover_queue.update(v, u.distance+w)
17                    v.discovered = True
```

Graph

Shortest path with Dijkstra

```
1 discover_queue = MinHeap()
2 discover_queue.append([source,0])
3
4 while discover_queue is not empty:
5     u = discover_queue.serve()
6     u.visited = True
7     for each <u,v,w> in u.edges:
8         if v.visited = True:
9             pass
10        else:
11            if v.discovered = False:
12                discover_queue.append([v, u.distance+w])
13                v.discovered = True
14            else:
15                if v.distance > u.distance+w:
16                    discover_queue.update(v, u.distance+w)
17                    v.discovered = True
```

$O(V)$

Graph

Shortest path with Dijkstra

$O(V)$

```
1  discover_queue = MinHeap()
2  discover_queue.append([source,0])
3
4  while discover_queue is not empty:
5      u = discover_queue.serve()
6      u.visited = True
7      for each <u,v,w> in u.edges:
8          if v.visited = True:
9              pass
10         else:
11             if v.discovered = False:
12                 discover_queue.append([v, u.distance+w])
13                 v.discovered = True
14             else:
15                 if v.distance > u.distance+w:
16                     discover_queue.update(v, u.distance+w)
17                     v.discovered = True
```

Serve: $O(\log V)$

Graph

Shortest path with Dijkstra

$O(V)$

```
1 discover_queue = MinHeap()
2 discover_queue.append([source,0])
3
4 while discover_queue is not empty:
5     u = discover_queue.serve()
6     u.visited = True
7     for each <u,v,w> in u.edges:
8         if v.visited = True:
9             pass
10        else:
11            if v.discovered = False:
12                discover_queue.append([v, u.distance+w])
13                v.discovered = True
14            else:
15                if v.distance > u.distance+w:
16                    discover_queue.update(v, u.distance+w)
17                    v.discovered = True
```

Serve: $O(\log V)$

$O(V)$

Graph

Shortest path with Dijkstra

```
1  discover_queue = MinHeap()
2  discover_queue.append([source,0])
3
4  while discover_queue is not empty:
5      u = discover_queue.serve()
6      u.visited = True
7      for each <u,v,w> in u.edges:
8          if v.visited = True:
9              pass
10         else:
11             if v.discovered = False:
12                 discover_queue.append([v, u.distance+w])
13                 v.discovered = True
14             else:
15                 if v.distance > u.distance+w:
16                     discover_queue.update(v, u.distance+w)
17                     v.discovered = True
```

$O(V)$

Serve: $O(\log V)$

$O(V)$

Update:
 $O(\log V)$

Time Complexity?

$O(V)$

```
1 discover_queue = MinHeap()
2 discover_queue.append([source,0])
3
4 while discover_queue is not empty:
5     u = discover_queue.serve()
6     u.visited = True
7     for each <u,v,w> in u.edges:
8         if v.visited = True:
9             pass
10        else:
11            if v.discovered = False:
12                discover_queue.append([v, u.distance+w])
13                v.discovered = True
14            else:
15                if v.distance > u.distance+w:
16                    discover_queue.update(v, u.distance+w)
17                    v.discovered = True
```

Serve: $O(\log V)$

$O(V)$

Update: $O(\log V)$

- Time Complexity? $O(V^2 \log V)$

$O(V)$

```
1 discover_queue = MinHeap()
2 discover_queue.append([source,0])
3
4 while discover_queue is not empty:
5     u = discover_queue.serve()
6     u.visited = True
7     for each <u,v,w> in u.edges:
8         if v.visited = True:
9             pass
10        else:
11            if v.discovered = False:
12                discover_queue.append([v, u.distance+w])
13                v.discovered = True
14            else:
15                if v.distance > u.distance+w:
16                    discover_queue.update(v, u.distance+w)
17                    v.discovered = True
```

Serve: $O(\log V)$

$O(V)$

Update: $O(\log V)$

- Time Complexity? $O(V^2 \log V) = O(E \log V)$

$O(V)$

```
1 discover_queue = MinHeap()
2 discover_queue.append([source,0])
3
4 while discover_queue is not empty:
5     u = discover_queue.serve()
6     u.visited = True
7     for each <u,v,w> in u.edges:
8         if v.visited = True:
9             pass
10        else:
11            if v.discovered = False:
12                discover_queue.append([v, u.distance+w])
13                v.discovered = True
14            else:
15                if v.distance > u.distance+w:
16                    discover_queue.update(v, u.distance+w)
17                    v.discovered = True
```

Serve: $O(\log V)$

$O(V)$

Update: $O(\log V)$

- Time Complexity? $O(V^2 \log V) = O(E \log V)$
 - Recall for dense graph, $E \approx V^2$

$O(V)$

```
1 discover_queue = MinHeap()
2 discover_queue.append([source,0])
3
4 while discover_queue is not empty:
5     u = discover_queue.serve()
6     u.visited = True
7     for each <u,v,w> in u.edges:
8         if v.visited = True:
9             pass
10        else:
11            if v.discovered = False:
12                discover_queue.append([v, u.distance+w])
13                v.discovered = True
14            else:
15                if v.distance > u.distance+w:
16                    discover_queue.update(v, u.distance+w)
17                    v.discovered = True
```

Serve: $O(\log V)$

$O(V)$

Update: $O(\log V)$

- Time Complexity? $O(V^2 \log V) = O(E \log V)$
 - Recall for dense graph, $E \approx V^2$
- Note that with Fibonacci heap instead of your binary heap, we can reduce the complexity further to $O(E + V \log V)$

- Time Complexity? $O(V^2 \log V) = O(E \log V)$
 - Recall for dense graph, $E \approx V^2$
- Note that with Fibonacci heap instead of your binary heap, we can reduce the complexity further to $O(E + V \log V) = O(V^2 + V \log V) = O(V^2)$
 - For dense graph

Questions?

- What if we have a single source
 - As usual
- But single target?

- What if we have a single source
 - As usual
- But single target?
- We can terminate after we have move the target vertex to the visited portion!

- What if we have a single source
 - As usual
- But single target?
- We can terminate after we have move the target vertex to the visited portion!
 - We would have the shortest distance

- What if we have a single source
 - As usual
- But single target?
- We can terminate after we have move the target vertex to the visited portion!
 - We would have the shortest distance
 - We can backtrack for the shortest path
 - Via vertex.previous attribute

Questions?

Graph

Shortest path with Dijkstra

- Why does Dijkstra work?

- Why does Dijkstra work?
 - Let us use Nathan's slides

Proof of Correctness

Claim: For every vertex v which has been removed from the queue, $\text{dist}[v]$ is correct

- Notation:
 - V is the set of vertices
 - Q is the set of vertices in the queue
 - $S = V / Q$ = the set of vertices who have been removed from the queue

Base Case


- $\text{Dist}[s]$ is initialised to 0, which is the shortest distance from s to s (since there are no negative weights)

Proof of Correctness

Claim: For every vertex v which has been removed from the queue, $\text{dist}[v]$ is correct

Inductive Step:

- Assume that the claim holds for all vertices which have been removed from the queue (S)
- Let u be the next vertex which is removed from the queue
- We will show that $\text{dist}[u]$ is correct




Proof of Correctness

Claim: For every vertex v which has been removed from the queue, $\text{dist}[v]$ is correct

Inductive Step:

- Suppose (for contradiction) there is a shorter path P , $s \rightsquigarrow u$ with $\text{len}(P) < \text{dist}[u]$
- Let x be the furthest vertex on P which is in S (i.e. has been finalised)
- By the inductive hypothesis, $\text{dist}[x]$ is correct (since it is in S)

Current path
Assumed
shorter path (P)




Proof of Correctness

Claim: For every vertex v which has been removed from the queue, $\text{dist}[v]$ is correct

Inductive Step:

- By the inductive hypothesis, $\text{dist}[x]$ is correct (since it is in S)
- Let y be the next vertex on P after x
- $\text{Len}(P) < \text{dist}[u]$ (by assumption)
- Edge weights are non-negative
- $\text{Len}(s \rightsquigarrow y) \leq \text{len}(P) < \text{dist}[u]$




Proof of Correctness

Claim: For every vertex v which has been removed from the queue, $\text{dist}[v]$ is correct

Inductive Step:

- $\text{Len}(s \rightsquigarrow y) \leq \text{len}(P) < \text{dist}[u]$
- Since we said that P (via x and y) is a shortest path...
- $\text{dist}[y] = \text{len}(s \rightsquigarrow y) < \text{dist}[u]$
- So $\text{dist}[y] < \text{dist}[u]$...
- If $y \neq u$, why didn't y get removed before u ???
- If $y = u$, how can $\text{dist}[y] < \text{dist}[u]$???



- Why does Dijkstra work?
 - Let us use Nathan's slides
 - Or let me just explain it on the whiteboard...
 - Via proof by contradiction!

Questions?

Graph

Other shortest path?

- Bellman-Ford
- Floyd-Warshall

- Bellman-Ford
- Floyd-Warshall
 - With transitive closure

- Bellman-Ford
- Floyd-Warshall
 - With transitive closure
- We see it on week 09

- Bellman-Ford
 - Single source
 - Can know negative edges
- Floyd-Warshall
 - With transitive closure
 - Single or more sources
 - Can know negative edges
- We see it on week 09

Questions?

Thank You