




MONASH
University

FIT2099 Object-Oriented Design and Implementation

Defensive copying



MONASH
University



THE DEFENSIVE COPYING

When **getters** return **a reference** to a **private object** it is said that this object is **mutable**
i.e. with public attributes or mutator methods (setters) other than constructor

A **mutable object** is simply an object which can change its state after construction.
For example, `StringBuilder` and `Date` are mutable objects, while `String` and `Integer` are immutable objects.



HOW A PRIVACY LEAK OCCURS

- 1- If the mutable object is a private attribute (field) of another (native) class, **its state should be changed only by the native class.**
- 2- Then, a **defensive copy** of the mutable object must be made any time it's passed into (constructors and set methods) or out of (get methods) the class.
- 3- If this is not done, then it's simple for the caller to **break encapsulation**, by changing the state of an object which is simultaneously visible to both the class and its caller.

WHEN DOES A PRIVACY LEAK OCCUR?

When getters return a reference to a private object that is *mutable*
i.e. with public attributes or mutator methods other than constructor

Generally, you should **make a copy and return that.**


Otherwise, you lose benefit of encapsulation
this is called a ***privacy leak***

Lose control of connascence

PRIVACY LEAK EXAMPLE

```
Public class GasTank {  
    private Fraction fuel;  
    public GasTank() {  
        fuel = new Fraction(1, 1);  
    }  
}
```


}



PRIVACY LEAK EXAMPLE

```
Public class GasTank {  
    private Fraction fuel;  
    public GasTank() {  
        fuel = new Fraction(1, 1);  
    }  
}
```

}




PRIVACY LEAK EXAMPLE

Private

```
Public class GasTank {  
    private Fraction fuel  
    public GasTank() {  
        fuel = new Fraction(1, 1),  
    }  
}
```



}



PRIVACY LEAK EXAMPLE

```
Public class GasTank {  
    private Fraction fuel;  
    public GasTank() {  
        fuel = new Fraction(1, 1);  
    }  
    public Fraction getFuel() {  
        return fuel;  
    }  
    public void setFuel(Fraction f) {  
        if (f.asDouble <= 1)  
            fuel = f;  
    }  
}
```

// What does the following code do?
GasTank tank = new GasTank();
Fraction fuelRead = tank.getFuel();
fuelRead.setNumerator(2);




The getter returns
a reference to the
object

PRIVACY LEAK EXAMPLE

```
Public class GasTank {  
    private Fraction fuel;  
    public GasTank() {  
        fuel = new Fraction(1, 1);  
    }  
    public Fraction getFuel() {  
        return fuel;  
    }  
    public void setFuel(Fraction f) {  
        if (f.asDouble <= 1)  
            fuel = f;  
    }  
}
```

```
// What does the following code do?  
GasTank tank = new GasTank();  
Fraction fuelRead = tank.getFuel();  
fuelRead.setNumerator(2);
```




PRIVACY LEAK EXAMPLE

Private

```
Public class GasTank {  
    private Fraction fuel  
    public GasTank() {  
        fuel = new Fraction(1, 1);  
    }  
    public Fraction getFuel() {  
        return fuel;  
    }  
    public void setFuel(Fraction f) {  
        if (f.asDouble <= 1)  
            fuel = f;  
    }  
}
```

```
// What does the following code do?  
GasTank tank = new GasTank();  
Fraction fuelRead = tank.getFuel();  
fuelRead.setNumerator(2);
```



THE SOLUTION VIA DEFENSIVE COPYING

A privacy leak occurs when a private instance variable can be modified outside of its class


This happens because of aliasing, two references to the same object

What if we rewrite getFuel()?

```
public Fraction getFuel() {  
    return new Fraction(fuel);  
}
```

Returns a copy of fuel

Changes to this copy won't affect the original



THE SOLUTION VIA DEFENSIVE COPYING

A privacy leak occurs when a private instance variable can be modified outside of its class


This happens because of aliasing, two references to the same object

What if we rewrite getFuel()?

```
public Fraction getFuel() {  
    return new Fraction(fuel);  
}
```

Returns a copy of fuel

Changes to this copy won't affect the original





MONASH
University

Thanks



MONASH
University

