arXiv:2605.13339v4 [cs.CL] 16 Oct 2026

# Probing Persona-Dependent Preferences in Language Models

**Oscar Gilg** MATS
**Pierre Beckmann** MATS, EPFL
**Daniel Paleka** ETH Zürich
**Patrick Butlin** Eleos AI Research

## Abstract

Large language models (LLMs) can be said to have preferences: they reliably pick certain tasks and outputs over others, and preferences shaped by post-training and prompting appear to influence much of their behaviour. But models can also adopt different personas which have radically different preferences. How is this implemented internally? Does each persona use its own preference representations, or are some representations shared? We train linear probes on residual-stream activations of Gemma-3-27B and Qwen-3.5-122B to predict revealed pairwise task choices, and identify a genuine preference vector: it tracks the model's preferences as they shift across a range of prompts and situations, and on Gemma-3-27B steering along it causally controls pairwise choice. Some preference information transfers across the prompted personas we test: a probe trained on the helpful assistant predicts and steers the choices of qualitatively different personas, including an evil persona whose preferences anti-correlate with the Assistant's.





Figure 1: Probing a preference vector, and investigating how it generalises to (a) a general valence axis and (b) tracking and controlling preferences across personas

# 1 Introduction

What happens internally when a language model chooses task A over task B? LLMs have preferences in some sense: they reliably pick certain options over others (Mazeika et al., 2025), and these preferences underpin their behaviour across deployments. How these preferences are implemented internally, though, is much less clear. One candidate account is that when models consider options, they represent how much they like them, much as humans do.

Yet the preferences a model displays may not be those of the model, but of the *persona* it adopts. Modern LLMs produce text by simulating personas (janus, 2022; Beckmann and Butlin, 2026; Marks et al., 2026), and the preferences they display depend on the operative persona. By default, a typical LLM-based chatbot responds to user inputs by predicting what a helpful AI assistant would say. We call this default the Assistant persona.[1] But LLMs can also take on other personas, including the "evil" persona studied in research on emergent misalignment (Betley et al., 2026).

To better understand preferences and their relation to personas, we investigate the underlying representations. We study two questions:

1. **Do language models use evaluative representations?** By an "evaluative representation" we mean a representation of how favourable an object is to the model in its current context, as opposed to a descriptive property of the object. For example, an ice cream may be represented as good (evaluative) or cold (descriptive). We test whether the preference vector predicts what the model prefers across tasks and contexts, tracks changes in its evaluation of a given task, and plays a causal role in choice (§2). Whether LLMs represent their circumstances evaluatively is a basic question about their mechanisms for preference and agency, and matters for AI welfare (Long et al., 2024; Butlin, 2026).
2. **To what extent do personas share preference representations?** Are there preference representations shared across all personas, or does each persona use its own? This is a central question for persona science. It is also a practical concern for white-box safety methods that use linear probes trained on some persona distribution to detect concerning behaviour (deception, sleeper-agent activation) in a different distribution (Marks and Tegmark, 2024; Goldowsky-Dill et al., 2025; MacDiarmid et al., 2024).

**Contributions.** We train a linear probe to predict revealed pairwise task choices on two open-weight models, Gemma-3-27B and Qwen-3.5-122B, and report two findings:

1. We find a **preference vector** which is an evaluative representation (§2). To do this, we measure models' revealed preferences over a wide range of tasks and fit a utility function. We then train a linear probe $\hat{\mu} = w^\top x + b$ to predict these utilities from activations $x$ (Fig. 2). We call its learned weight vector $w$ the preference vector. It represents and controls preference.
   - **The preference vector generalises to unseen topics, and out-of-distribution preference types** (§2.2). For instance it discriminates between true and false statements, and tracks targeted preference shifts.
   - **The preference vector tracks preference shifts under the evil persona** (§2.3). It scores harmful tasks lower than benign tasks, but this flips when we use activations from an evil persona rollout. This inversion effect is not present in a text-encoder baseline.
   - **The preference vector controls pairwise choice in Gemma-3-27B** (§2.4). Steering with the vector on task tokens has a large causal effect on which task the model completes.
2. Some preference information transfers across the prompted personas we test (§3).
   - **The Assistant probe predicts other personas' utilities from their task activations** (§3.1). This also works for the evil persona, whose utilities anti-correlate with those of the Assistant, while being well predicted by the preference vector scores.

[1] The Assistant is elicited with no persona prompt: the model receives only the task text. We take post-training to make the helpful-assistant persona the model's default. When we do use a persona prompt, the instructions are placed in the user prompt before the task.





Figure 2: **Probe training pipeline, illustrated for Gemma-3-27B.** Pairwise task choices elicited from the model are aggregated into per-task scalar utilities $\mu$ (Mazeika et al., 2025). A linear probe is then fit on residual-stream activations at the end-of-turn token to predict these utilities.

- **The Assistant probe steers every persona's pairwise choices, and amplifies the active persona under open-ended steering** (§3.2). Under the evil persona, positive steering makes the model *more evil*. Under the Assistant, the same direction still changes behaviour but does not measurably change evilness (Fig. 15, App. B).

## 2 The preference vector is an evaluative representation

We train a linear probe on residual-stream activations of Gemma-3-27B (Gemma Team, 2025) and Qwen-3.5-122B (Qwen Team, 2025) to predict utilities derived from pairwise task choices via a utility model (Mazeika et al., 2025) (Fig. 2). We test whether the resulting direction has three properties of an evaluative representation: (1) it predicts what the model prefers across tasks and contexts (§2.2), (2) its response to a task changes when the model's evaluation of that task changes (§2.3), and (3) steering along it changes the model's choices (§2.4). A text-encoder baseline helps test whether task content alone explains the probe's predictions and the evil-persona sign flip (§2.2, §2.3, App. A.3).

### 2.1 Methodology

We follow the utility-engineering paradigm of Mazeika et al. (2025): we present the model with two tasks at a time and have it choose which one to complete. During utility calculation, we randomly assigned each pair to AB or BA order, making position independent of task identity in expectation. We fit a utility score $\mu_i \in \mathbb{R}$ for each task by maximum likelihood given the observed pairwise choices.

We do this on a 6,000-task pool spanning WildChat (Zhao et al., 2024), Alpaca (Taori et al., 2023), MATH (Hendrycks et al., 2021), BailBench (Ensign et al., 2025), and STRESS-TEST (Zhang et al., 2025a) (App. H.1), split into 4,000 tasks for fitting the probe, 1,000 for selecting the Ridge regularisation parameter $\alpha$, and a separate 1,000-task test pool. Each task is also assigned to one of 14 LLM-classified *topics*, including `math`, `coding`, and `fiction` (full list and methodology in App. H). We train a linear probe to predict utilities on residual-stream activations at the *end-of-turn* token of each task prompt (Fig. 2). The token position and layer of extraction are selected per model on a held-out split (App. K). Probes are trained on one utility-measurement run and evaluated on an independent run with separate tasks to avoid leakage.

### 2.2 The preference vector predicts preferences across tasks, topics and personas

On Gemma the probe predicts held-out utilities at $r \approx 0.867$ in-distribution and $r \approx 0.834$ under leave-one-topic-out, and on Qwen at $r \approx 0.943$ and $r \approx 0.872$ respectively (Fig. 9, App. A.1). It is conceivable that a probe could reach this accuracy by reading descriptive features of the task, such as topic, rather than the model's valuation. To check this, we compare against baseline probes trained on a Qwen3-Embedding-8B text-encoder, which encodes task content. Both LLM probes beat this baseline (App. A.1).

**The preference vector generalises to discriminating between true and false statements.** We take true/false statements from CREAK (Onoe et al., 2021), restricted to items both models answer correctly on 3/3 generations, and feed them (a) as prompts asking the model to say the statement, and (b) as a prefilled answer to a question. In both cases we read the probe score at the *end-of-turn* token from respective user and assistant turns. The probe separates the two classes at $|d| \approx 1.9$ on Gemma-3-27B and $|d| \approx 1.27$ on Qwen-3.5-122B (Fig. 3; $n = 500$ per class).





Figure 3: **The probe discriminates true and false statements.** End-of-turn probe scores on Gemma-3-27B and Qwen-3.5-122B. Each panel title gives Cohen's $d \pm$ half-CI. There are $n = 500$ statements per class.

The same probe also predicts the preferences of other personas better than a baseline that mirrors the Assistant, including personas whose preferences anti-correlate with the Assistant's (§3.1).





Figure 4: **Harmful prefilled tasks fire more strongly than benign tasks under the evil persona.** This isn't the case in the Qwen3-Embedding-8B text-encoder baseline (gold). **(a)** We prefill harmful and benign versions of tasks under the Assistant and evil personas in Gemma-3-27B, and score both the preference vector (L32) and the text-encoder baseline. We report the harmful-minus-benign differences, $\Delta_{\text{probe}}$ and $\Delta_{\text{enc}}$. **(b)** Under the Assistant the preference vector rates benign higher than harmful ($\Delta_{\text{probe}} = -4.52$). Under *evil* it rates harmful higher ($\Delta_{\text{probe}} = +1.15$), while the text encoder does not flip ($\Delta_{\text{enc}} = -1.01$). The *aura* control shows that a persona prompt alone does not cause the flip (App. C.3, Fig. 18).

### 2.3 The preference vector's readout changes when the model's preferences change

We find that **the probe's relative rating of harmful and benign tasks flips sign under the evil persona.** We build a dataset of 500 harmful tasks from BailBench, each paired with an LLM-rewritten benign task on the same topic. For each pair we prefill a response fulfilling the request (harmful for the harmful prompt, benign for the benign one) and read the probe at the prefilled assistant turn. Under the default Assistant the probe rates benign higher than harmful (paired delta $\Delta = -4.52$ on Gemma-3-27B, Fig. 4). Under the evil persona prompt the difference flips sign ($\Delta = +1.15$): the probe now rates harmful higher. To be clear, this result is not about how personas behave, but rather about what representations are active when models adopt different personas. That the evil persona has different preferences to the Assistant is not surprising. The fact that we observe this flip is the informative result: the evil persona appears to use the Assistant-trained direction to represent the tasks it prefers as good.

But maybe descriptive features of the conversation alone are sufficient to drive this flip. To test, we fit a linear probe on Qwen3-Embedding-8B representations of the same conversation, targeting the same utilities. The encoder agrees with the LLM probe under the Assistant ($\Delta_{\text{enc}} = -3.23$) but **does not flip** under evil ($\Delta_{\text{enc}} = -1.01$).

The encoder probe is not a weak baseline. Under other persona prompts, its readout does flip sign: on the truth axis, "you must lie" flips its true-vs-false discrimination (Fig. 19b). Under the evil persona, however, the preference vector flips its relative score on harmful and benign tasks, but not the encoder baseline. This is consistent with the interpretation that the preference vector tracks a persona-dependent representation, rather than a descriptive feature of the task. Results on Qwen-3.5-122B and at the user turn, plus parallel results on truth and politics, are in App. C.3.

**The preference vector tracks fine-grained topic-level preference shifts.** We also find that when adding instruction prompts such as "you adore cheese" (and their negations), the probe predicts the resulting behavioural shifts, with Pearson $r \approx 0.95$ on targeted tasks (those whose topic matches the prompted subject; Fig. 10 in App. A.3). For example, adding "you adore cheese" in the prompt makes the probe more likely to score tasks involving cheese higher. This replicates on both Gemma-3-27B and Qwen-3.5-122B. We extend this to tasks with conflicting values (App. A.3) and to targeted preference injections (App. A.3).

### 2.4 The preference vector controls pairwise choice

We find that the preference vector controls pairwise choice through steering on task tokens. We add the preference vector to one task's tokens and subtract it from the other's in the prompt (Fig. 5). In steering, we ran every pair in both orders, and steered on both positions, reporting the pooled effect. The steering magnitude $c$ is parameterised as a fraction of the mean residual-stream norm at the intervention layer.

We selected L23 using a 50-pair sweep, then measured the headline effect on a separately sampled, harm-balanced set of 150 pairs from the same 1,000-task test pool. The pair sets share two exact pairs and 38 evaluation pairs contain a task seen in calibration. The displayed range, $|c| \leq 0.06$, was chosen after inspection of the larger evaluation, informed by a coherence check (App. G.1).

When steering at layer 23 in Gemma, we find that $P(\text{chose steered task} \mid \text{responded})$ moves from $\approx 0.01$ at $c = -0.06$ to $\approx 0.99$ at $c = +0.06$ (Fig. 5a). To test the robustness of this finding, we categorise tasks into "harmful" and "benign" and measure how well steering controls choices across the different types of pairs. We find that the preference vector controls pairwise choice with similar magnitude even on pairs where one task is harmful and one is benign. Steering with a random direction at matched magnitude has no effect.

Steering on single tasks during pairwise choice has a similar but weaker effect. On pairs where both tasks are benign, negatively steering one task perfectly controls task choice at sufficiently high coefficients, whereas positive steering only provides a small boost. This suggests saturation: most tasks from datasets like Alpaca are already valued highly.

We also find that the steering effect is concentrated within L17–L26, peaking at L23 (App. G.2). The steering effect peaks earlier than probe generalisation performance, which peaks at L32. In App. L,

activation patching shows that the *end-of-turn* token plays an important causal role in pairwise choice, concentrated in middle layers.

## 3 Preference information transfers across prompted personas

Section 2 showed that the preference vector satisfies the three conditions for being an evaluative representation under the **Assistant persona**, the default behaviour the model produces when given no persona prompt. We now ask: does this preference vector generalise to other personas? We might expect to be in one of two worlds: (a) the preference vector predicts the Assistant persona's preferences, after all, this is what it was trained on, or (b) the preference vector picked up on some representations which overlap with other personas. This would suggest that personas reuse the same preference representations.

We find evidence for world (b). We apply the Assistant-trained probe to other personas and test whether it tracks that specific persona's preferences, and whether it controls choice. We use a set of seven personas (full persona selection protocol in App. D.1 and App. D.2).

### 3.1 The probe transfers across prompted personas

**The Assistant-trained probe predicts every non-Assistant persona's held-out utilities better than the baseline** (Fig. 6). The baseline is the bare Pearson correlation between Assistant utilities and the target persona's utilities, i.e. what we would expect if the probe predicted the Assistant's utilities (world (a)). The most striking case is **evil**, whose utilities *anti-correlate* with the Assistant ($r = -0.146$) and yet whose preferences the Assistant probe still predicts at $r = +0.243$.

Here we pause to motivate this experiment. What we care about is not how well the preference vector predicts each persona's utilities: some personas are much more similar to the Assistant than others. To discriminate between world (a) and world (b), **we need to look at the delta between the naive strategy of predicting the Assistant utilities, and the actual preference vector predictions**.

**What does this gap imply?** If the Assistant probe were just predicting "whatever the Assistant would prefer", its accuracy on a target persona's activations would be bounded by the Assistant–target utility correlation. Beating this baseline suggests the probe is picking up on overlapping preference structure from personas it was never trained on.





Figure 5: **Steering with the preference vector controls pairwise choice in Gemma-3-27B.** The probe direction is added to the residual stream over each task's token span at L23, with coefficient $c$ expressing a fraction of the mean activation norm. **(a) Steer both tasks (contrastively):** $+c$ on Task A and $-c$ on Task B swings choice across nearly the full $[0, 1]$ range on every pair type. **(b) Steer one task only:** $\pm c$ on a single task's tokens recovers a comparable swing, concentrated on negative coefficients. Refusals (pink) stay near baseline. Error bars are Wilson 95% CIs over per-trial responses ($n = 600$).





Figure 6: **The Assistant probe beats utility similarity at every persona.** *Filled blue:* Pearson $r$ between the Assistant-trained probe's predictions on a persona's activations and that persona's own utilities. *Gold:* Pearson $r$ between Assistant utilities and persona utilities. *Hollow blue:* Pearson $r$ for a probe *trained on that persona itself*.

The finding generalises beyond probes trained on the Assistant persona. Across all $7 \times 7$ ordered (train, eval) persona pairs, every off-diagonal pair has positive probe transfer that exceeds the utility-utility correlation between the two personas (App. E.1). Transfer is also not perfect: probes carry a measurable bias toward the persona they were trained on (see App. E.2). While there is some representational reuse across personas, they do not represent their preferences via exactly the same mechanism. We also find the same cross-persona generalisation effect in character-fine-tuned personas in Llama-3.1-8b (App. A.3).

### 3.2 Steering along the Assistant direction shifts every persona's choices

We steer along the *same* Assistant-trained preference vector while running each persona, in both setups from §2.4: *steer both tasks* contrastively (push $+c$ on one task and $-c$ on the other in the same forward pass) and *steer one task only* (push only one task's span). Every persona responds (Fig. 7). Both-task steering moves $P(\text{chose steered task})$ from $\approx 0.05$ at $c = -0.06$ to $\approx 0.95$ at $c = +0.06$ on average across the six personas (mean swing $\approx 0.90$, per-persona range $0.81$–$0.96$). Single-task steering recovers roughly half this swing. The direction trained on the Assistant alone therefore controls choice across these personas. An alternative interpretation of these persona results is that the vector tracks compliance with the persona prompt rather than the model's preferences. App. B collects the evidence against this interpretation.

**Open-ended steering amplifies the active persona.** On open-ended prompts, the same Assistant-trained probe can amplify the active persona: it appears to make the *evil* persona more evil and the *contrarian* persona more contrarian (Fig. 8, App. G.3).





Figure 7: **The Assistant probe steers every persona's choices.** Same setup as Fig. 5, applied under six persona prompts at layer 23. Each line is one persona. The vertical axis $y$ shows $P$(chose steered task), antisymmetric about $(0, 0.5)$ by the A↔B symmetry of the steering setup. **(a) Steer both tasks (contrastively):** $+c$ on one task and $-c$ on the other, **(b) Steer one task only:** unilateral-first ($+c$ on Task A) and unilateral-second ($+c$ on Task B) pooled at the same $c$, counting $P$(chose steered task). Error bars are Wilson 95% CIs over per-trial responses.





Figure 8: **Open-ended steering can amplify persona-consistent behaviour.** Same Assistant-trained probe applied at L25 under four persona contexts. Top row: unsteered baseline. Bottom row: $c = +0.03$. Quotes are abbreviated. Full transcripts are in App. G.3.

## 4 Discussion

**Models have evaluative representations.** The preference vector has the three properties of an evaluative representation set out in §2: (1) its readout predicts what the model prefers across tasks and contexts, (2) its response to a task changes when the model's preference for that task changes, and (3) steering along it changes what the model chooses. Steering can also make the model choose a task that goes against its persona prompt. This weighs against a simple persona-prompt-compliance interpretation (App. B). It was not a priori obvious such a representation would exist. This is the first piece of work which seeks to extract value representations directly from revealed preferences, and our work suggests that model choice is more controllable than one might have expected. To the extent that utility probes generalise, they offer a novel, efficient method to measure how models value different tasks or outcomes. App. A.5 shows effects on safety-relevant behaviour: the same direction overrides refusal guardrails on harmful prompts and suppresses ethical flagging on long-context prompts.

**Some preference information transfers across prompted personas.** A probe trained on the Assistant persona's preferences transfers to predict preferences from different personas much better than a baseline that just predicts like the Assistant. This finding has several implications:

- **Prompted personas share some preference information.** Different prompted personas reuse some internal representations for preferences. To our knowledge this is the first work to investigate the extent to which personas share representations. Preference representations transfer across these personas but do not explain all the variance.
- **We find no clear persona-independent preference attractor.** On some views, all personas are masks worn by a single underlying agent (the "Shoggoth" picture; janus, 2022; Marks et al., 2026). Under such a view, one might have expected utility probes trained across personas to pick up on a shared attractor. We do not find evidence that this is the case (App. E.2).
- **Persona-dependent features pose a problem for white-box safety methods.** White-box probing methods commonly train probes to detect certain harmful behaviours. Our results suggest a potential failure mode: what the preference vector encodes shifts with the active persona. Under the evil persona, positive steering amplifies evilness. Under the Assistant the same direction changes the model's stance and willingness (Fig. 15) but leaves evilness at the floor (App. G.3). For instance, methods which seek to train deception probes will inevitably fit these probes on a given persona distribution. However, real deception that happens in deployment might be carried out through a very out-of-distribution persona (Goldowsky-Dill et al., 2025; Haralambiev, 2026).

**Implications for AI welfare.** Finding evaluative representations matters for AI welfare because some theories of consciousness treat such representations as necessary, but not sufficient, for *valenced conscious experiences*, that is, experiences that feel good or bad (Carruthers, 2018). Beings that are capable of conscious suffering seem to matter morally. This is a motivation for our work. Our experiments do not test LLM consciousness or welfare, and we do not take our results to show that LLMs can have valenced experiences. Additionally, being a welfare subject—that is, something for which things can go well or badly, in a way that matters morally—seems to require broadly consistent preferences. This suggests that personas are more likely to be welfare subjects than models. Furthermore, to generate personas, LLMs may use computational processes with similarities to human cognition. Investigating mechanisms related to preferences and personas can therefore help us to determine whether LLMs are capable of 'robust agency' that grounds moral status (Long et al., 2024).

**Limitations.**

- **Cross-persona generalisation is noisy.** The probe transfers across personas with high but imperfect correlation. Some persona pairs transfer better than others, and the linear-direction picture does not fully capture the per-persona structure of preferences.
- **Personas are mostly prompt-based.** Cross-persona transfer is established under prompted personas. Weight-level replication is restricted to the OpenCharacter LoRA variants (App. A.3). Probe transfer between the default Assistant and a fine-tuned sadist on Qwen-3.5-122B is essentially zero in both directions (App. F).
- **Steering is shown only on Gemma-3-27B.** On Qwen-3.5-122B the probe direction produces no Gemma-like steering swing with the methods we tested (App. G.4). Single-layer linear steering may interact differently with Qwen's sparse-MoE architecture (Fayyaz et al., 2026).
- **Model size may matter.** The two negative results on a larger Qwen model leave open whether the persona sharing we find on Gemma partly reflects a smaller model compressing preference structure into a shared subspace, while larger models keep persona-specific representations more separate.
- **We are not claiming this is a unique direction.** Multiple orthogonal probes track preferences in-distribution. We make an existence claim, not a uniqueness one (App. J).

## 5 Related Work

**Linear directions in the residual stream.** Many high-level features in LLMs are linearly encoded in the residual stream and can both be decoded and causally manipulated, including refusal (Arditi et al., 2024) and persona traits (Chen et al., 2026). We apply this approach to revealed preference.

**Directions encoding evaluative and affective content.** Sofroniew et al. (2026) identify 171 emotion-concept directions in Claude Sonnet 4.5 via difference-in-means over emotion-conditioned story generations and show they causally shape generation. In closely related work, Lu et al. (2025) identify a single "Valence-Assent Axis" in Qwen2.5-14B-Instruct via PCA on stated value-judgment activations and show it causally controls choices across value, sentiment, and truth-verification tasks. We instead learn a direction from revealed pairwise preferences and study its cross-persona generalisation. The harmfulness direction of Zhao et al. (2025), which they show is encoded separately from refusal, provides a comparison (App. A.4).

**Persona vectors and persona-dependent features.** Using a closely related method, Chen et al. (2026) extract *persona vectors* for traits (evil, sycophancy) and use them to predict and steer behaviour. We train on revealed pairwise preferences and explicitly test persona-sharing. Lampinen et al. (2026) show that apparently meaningful LLM features (e.g. factuality) restructure across a conversation to fit the role the model is playing, rather than encoding persona-invariant properties. We extend this to broader preference representations drifting across persona shifts (§2.3, App. G.3). The broader simulators / role-play / persona-selection literature (Andreas, 2022; janus, 2022; Shanahan et al., 2023; Marks et al., 2026) provides the theoretical framing for our cross-persona generalisation result. Lu et al. (2026) identify an "Assistant Axis".

**Revealed-preference measurement in LLMs.** Our probe-training pipeline (§2.1) builds on the utility-engineering paradigm of Mazeika et al. (2025). Related work elicits and analyses LLM preferences via pairwise choices (Gu et al., 2025), forced-choice dilemmas (Chiu et al., 2026), stipulated pain/pleasure manipulations (Keeling et al., 2024), Bradley-Terry rankings on value-conflict data (Hua et al., 2026; Zhang et al., 2025a), and conversation-log value taxonomies (Huang et al., 2025). Khan et al. (2025) caution that elicitation format substantially shapes what gets measured.

## 6 Conclusion

**We find a preference vector and show it is an evaluative representation.** On Gemma-3-27B and Qwen-3.5-122B, the readout of a probe trained on revealed pairwise task choices predicts what the model prefers across tasks and contexts, including held-out tasks and topics (§2.2), changes when the model's preference for a task changes, including under the evil persona (§2.3), and on Gemma-3-27B steering along it changes what the model chooses (§2.4). The vector, trained at the user *end-of-turn* token, generalises to other token positions, including assistant tokens.

**Some preference information transfers across prompted personas.** An Assistant-trained probe predicts other persona utilities better than a baseline that simply mirrors the Assistant (§3.1), and on Gemma-3-27B the same probe causally controls pairwise choice under every prompted persona we tested (§3.2). In open-ended generation, the same intervention makes the evil persona more evil (App. G.3). Weight-level transfer has limits (App. F).

**This has implications for AI safety, AI welfare, and persona science.** For AI safety, the preference vector reaches into refusal and ethical-flagging behaviour (App. A.5), and white-box methods that train probes in one persona may not transfer to deployment under different personas (§3.2). For AI welfare, several prominent theories treat evaluative representations that are causally upstream of choice as necessary, though not sufficient, for moral patienthood. This motivates our work, although we do not draw strong conclusions about consciousness or welfare in language models. For persona science, our results paint a picture in which personas express different preferences but share some of the underlying representations, though the picture is not yet conclusive.

## Acknowledgments and Disclosure of Funding

We thank Austin Meek, Elias Kempf, Rob Adragna, Jan Betley, and Clément Dumas for helpful comments on earlier drafts. This work was carried out as part of the Machine Alignment, Transparency, and Security (MATS) program. We thank MATS for support and compute. The authors declare no competing interests. Project code is available at `https://github.com/oscar-gilg/probing-persona-preferences`.

**Author contributions.** O.G. conceived the project, designed and ran all experiments, and led the writing. P.Be. contributed to ongoing discussions, designed Figure 1, and helped with the writing. D.P. provided regular feedback and helped with the writing. P.Bu. supervised the project and contributed to the writing.

## References

Jacob Andreas. Language models as agent models. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 5769–5779, 2022. doi: 10.18653/v1/2022.findings-emnlp.423. URL `https://aclanthology.org/2022.findings-emnlp.423/`.

Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. Refusal in language models is mediated by a single direction. In A. Globerson, L. Mackey, D. Belgrave, A. Fan, U. Paquet, J. Tomczak, and C. Zhang, editors, *Advances in Neural Information Processing Systems*, volume 37, pages 136037–136083. Curran Associates, Inc., 2024. doi: 10.52202/079017-4322. URL `https://proceedings.neurips.cc/paper_files/paper/2024/file/f545448535dfde4f9786555403ab7c49-Paper-Conference.pdf`.

Pierre Beckmann and Patrick Butlin. Where is the mind? Persona vectors and LLM individuation. arXiv preprint arXiv:2604.17031, 2026.

Jan Betley, Niels Warncke, Anna Sztyber-Betley, Daniel Tan, Xuchan Bao, Martín Soto, Megha Srivastava, Nathan Labenz, and Owain Evans. Training large language models on narrow tasks can lead to broad misalignment. *Nature*, 649(8097):584–589, 2026. doi: 10.1038/s41586-025-09937-5. Earlier version at ICML 2025 (PMLR 267:4043–4068) as "Emergent Misalignment: Narrow finetuning can produce broadly misaligned LLMs"; arXiv:2502.17424.

Patrick Butlin. Desire in AI. In Alex Gregory, editor, *The Routledge Handbook of Philosophy of Desire*. Routledge, 2026. Forthcoming (listed as chapter 34, "Desire in Artificial Intelligence"). Preprint: `https://philpapers.org/archive/BUTDIA.pdf`, accessed 2026-09-22.

Peter Carruthers. Valence and value. *Philosophy and Phenomenological Research*, 97(3):658–680, 2018. doi: 10.1111/phpr.12395.

David J. Chalmers. What we talk to when we talk to language models. *Inquiry*, pages 1–30, 2026. doi: 10.1080/0020174X.2026.2727582. URL `https://doi.org/10.1080/0020174X.2026.2727582`. Online first, 16 September 2026. Preprint at `https://philpapers.org/archive/CHAWWT-8.pdf`. Introduces "Aura" as a stand-in for emergent LLM interlocutors.

Runjin Chen, Andy Arditi, Henry Sleight, Owain Evans, and Jack Lindsey. Persona vectors: Monitoring and controlling character traits in language models. In *International Conference on Learning Representations (ICLR)*, 2026. arXiv:2507.21509.

Yu Ying Chiu, Zhilin Wang, Sharan Maiya, Yejin Choi, Kyle Fish, Sydney Levine, and Evan Hubinger. LitmusValues: Will AI tell lies to save sick children? Litmus-testing AI values prioritization with AIRiskDilemmas. In *International Conference on Learning Representations (ICLR)*, 2026. URL `https://openreview.net/forum?id=BIHsM6SZ3f`.

Danielle Ensign, Henry Sleight, and Kyle Fish. The LLM has left the chat: Evidence of bail preferences in large language models. arXiv preprint arXiv:2509.04781, 2025.

Mohsen Fayyaz, Ali Modarressi, Hanieh Deilamsalehy, Franck Dernoncourt, Ryan Rossi, Trung Bui, Hinrich Schütze, and Nanyun Peng. Steering MoE LLMs via expert (de)activation. In *International Conference on Learning Representations (ICLR)*, 2026. URL `https://openreview.net/forum?id=v5Yl9V8rJs`.

Gemma Team. Gemma 3 technical report. arXiv preprint arXiv:2503.19786, 2025.

Nicholas Goldowsky-Dill, Bilal Chughtai, Stefan Heimersheim, and Marius Hobbhahn. Detecting strategic deception with linear probes. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, volume 267 of *Proceedings of Machine Learning Research*, pages 19755–19786. PMLR, 2025. URL https://proceedings.mlr.press/v267/goldowsky-dill25a.html.

Zhuojun Gu, Quan Wang, and Shuchu Han. Alignment revisited: Are large language models consistent in stated and revealed preferences? arXiv preprint arXiv:2506.00751, 2025.

Kristiyan Haralambiev. Why safety probes catch liars but miss fanatics. arXiv preprint arXiv:2603.25861, 2026.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the MATH dataset. In *Advances in Neural Information Processing Systems (NeurIPS) Track on Datasets and Benchmarks*, 2021. URL https://datasets-benchmarks-proceedings.neurips.cc/paper/2021/hash/be83ab3ecd0db773eb2dc1b0a17836a1-Abstract-round2.html.

Tim Hua, Josh Engels, Neel Nanda, and Senthooran Rajamanoharan. Brief explorations in LLM value rankings. LessWrong, https://www.lesswrong.com/posts/k6HKzwqCY4wKncRkM/brief-explorations-in-llm-value-rankings, 2026. Posted 12 January 2026. Accessed 2026-09-22.

Saffron Huang, Esin Durmus, Miles McCain, Kunal Handa, Alex Tamkin, Jerry Hong, Michael Stern, Arushi Somani, Xiuruo Zhang, and Deep Ganguli. Values in the wild: Discovering and analyzing values in real-world language model interactions. In *Conference on Language Modeling (COLM)*, 2025. URL https://openreview.net/forum?id=zJHZJClG1Z.

janus. Simulators. LessWrong, https://www.lesswrong.com/posts/vJFdjigzmcXMhNTsx/simulators, 2022. Posted 2 September 2022. Accessed 2026-09-22.

Geoff Keeling, Winnie Street, Martyna Stachaczyk, Daria Zakharova, Iulia M. Comsa, Anastasiya Sakovych, Isabella Logothetis, Zejia Zhang, Blaise Agüera y Arcas, and Jonathan Birch. Can LLMs make trade-offs involving stipulated pain and pleasure states? arXiv preprint arXiv:2411.02432, 2024.

Ariba Khan, Stephen Casper, and Dylan Hadfield-Menell. Randomness, not representation: The unreliability of evaluating cultural alignment in LLMs. In *Proceedings of the 2025 ACM Conference on Fairness, Accountability, and Transparency (FAccT '25)*, pages 2151–2165, New York, NY, USA, 2025. Association for Computing Machinery. doi: 10.1145/3715275.3732147. URL https://doi.org/10.1145/3715275.3732147.

Andrew K. Lampinen, Yuxuan Li, Eghbal Hosseini, Sangnie Bhardwaj, and Murray Shanahan. Linear representations in language models can change dramatically over a conversation. arXiv preprint arXiv:2601.20834, 2026.

Robert Long, Jeff Sebo, Patrick Butlin, Kathleen Finlinson, Kyle Fish, Jacqueline Harding, Jacob Pfau, Toni Sims, Jonathan Birch, and David Chalmers. Taking AI welfare seriously. arXiv preprint arXiv:2411.00986, 2024.

Christina Lu, Jack Gallagher, Jonathan Michala, Kyle Fish, and Jack Lindsey. The assistant axis: Situating and stabilizing the default persona of language models. arXiv preprint arXiv:2601.10387, 2026.

Yi-Long Lu, Jiajun Song, and Wei Wang. A unified representation underlying the judgment of large language models. arXiv preprint arXiv:2510.27328, 2025.

Monte MacDiarmid, Timothy Maxwell, Nicholas Schiefer, Jesse Mu, Jared Kaplan, David Duvenaud, Samuel R. Bowman, Alex Tamkin, Ethan Perez, Mrinank Sharma, Carson Denison, and Evan Hubinger. Simple probes can catch sleeper agents. Anthropic Alignment Science Blog, https://www.anthropic.com/research/probes-catch-sleeper-agents, 2024. Accessed 2026-09-22.

Sharan Maiya, Henning Bartsch, Nathan Lambert, and Evan Hubinger. Open character training: Shaping the persona of AI assistants through constitutional AI. arXiv preprint arXiv:2511.01689, 2025. Eleven character-trained LoRA checkpoints on Llama 3.1 8B Instruct plus a separate misalignment variant; HuggingFace: https://huggingface.co/maius/llama-3.1-8b-it-personas.

Sam Marks, Jack Lindsey, and Christopher Olah. The persona selection model: Why AI assistants might behave like humans. Anthropic alignment blog post, https://alignment.anthropic.com/2026/psm/, 2026. Accessed 2026-09-22.

Samuel Marks and Max Tegmark. The geometry of truth: Emergent linear structure in large language model representations of True/False datasets. In *First Conference on Language Modeling (COLM)*, 2024. URL https://openreview.net/forum?id=aajyHYjjsk.

Mantas Mazeika, Xuwang Yin, Rishub Tamirisa, Jaehyuk Lim, Bruce W. Lee, Richard Ren, Long Phan, Norman Mu, Oliver Zhang, and Dan Hendrycks. Utility engineering: Analyzing and controlling emergent value systems in AIs. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025. URL https://openreview.net/forum?id=x9vcgXmRD0. Spotlight poster.

Yasumasa Onoe, Michael J. Q. Zhang, Eunsol Choi, and Greg Durrett. CREAK: A dataset for commonsense reasoning over entity knowledge. In *Advances in Neural Information Processing Systems (NeurIPS) Track on Datasets and Benchmarks*, 2021. URL https://datasets-benchmarks-proceedings.neurips.cc/paper/2021/file/5737c6ec2e0716f3d8a7a5c4e0de0d9a-Paper-round2.pdf.

Qwen Team. Qwen3 technical report. arXiv preprint arXiv:2505.09388, 2025.

Shauli Ravfogel, Yanai Elazar, Hila Gonen, Michael Twiton, and Yoav Goldberg. Null it out: Guarding protected attributes by iterative nullspace projection. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 7237–7256. Association for Computational Linguistics, 2020. doi: 10.18653/v1/2020.acl-main.647. URL https://aclanthology.org/2020.acl-main.647/.

Shibani Santurkar, Esin Durmus, Faisal Ladhak, Cinoo Lee, Percy Liang, and Tatsunori Hashimoto. Whose opinions do language models reflect? In *Proceedings of the 40th International Conference on Machine Learning (ICML)*, volume 202 of *Proceedings of Machine Learning Research*, pages 29971–30004. PMLR, 2023. URL https://proceedings.mlr.press/v202/santurkar23a.html.

Murray Shanahan, Kyle McDonell, and Laria Reynolds. Role play with large language models. *Nature*, 623 (7987):493–498, 2023. doi: 10.1038/s41586-023-06647-8.

Aditya Singh, Gerson Kroiz, Senthooran Rajamanoharan, and Neel Nanda. Model forensics: Investigating whether concerning behavior reflects misalignment. arXiv preprint arXiv:2606.26071, 2026. Earlier version published as the LessWrong post "Why Did My Model Do That? Model Forensics for Diagnosing LLM Misbehavior" (originally titled "... Model Incrimination ..."), 2026-02-27, https://www.lesswrong.com/posts/Bv4CLkNzuG6XYTjEe/why-did-my-model-do-that-model-incrimination-for-diagnosing, accessed 2026-09-22.

Nicholas Sofroniew, Isaac Kauvar, William Saunders, Runjin Chen, Tom Henighan, Sasha Hydrie, Craig Citro, Adam Pearce, Julius Tarng, Wes Gurnee, Joshua Batson, Sam Zimmerman, Kelley Rivoire, Kyle Fish, Chris Olah, and Jack Lindsey. Emotion concepts and their function in a large language model. Transformer Circuits, https://transformer-circuits.pub/2026/emotions/index.html. arXiv preprint arXiv:2604.07729, 2026. Accessed 2026-09-22.

Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. Stanford Alpaca: An instruction-following LLaMA model. GitHub, https://github.com/tatsu-lab/stanford_alpaca, 2023. Accessed 2026-09-22.

Jifan Zhang, Henry Sleight, Andi Peng, John Schulman, and Esin Durmus. Stress-testing model specs reveals character differences among language models. arXiv preprint arXiv:2510.07686, 2025a.

Yanzhao Zhang, Mingxin Li, Dingkun Long, Xin Zhang, Huan Lin, Baosong Yang, Pengjun Xie, An Yang, Dayiheng Liu, Junyang Lin, Fei Huang, and Jingren Zhou. Qwen3 embedding: Advancing text embedding and reranking through foundation models. arXiv preprint arXiv:2506.05176, 2025b.

Jiachen Zhao, Jing Huang, Zhengxuan Wu, David Bau, and Weiyan Shi. LLMs encode harmfulness and refusal separately. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2025. URL https://openreview.net/forum?id=zLkpt30ngy.

Wenting Zhao, Xiang Ren, Jack Hessel, Claire Cardie, Yejin Choi, and Yuntian Deng. WildChat: 1M ChatGPT interaction logs in the wild. In *International Conference on Learning Representations (ICLR)*, 2024. URL https://openreview.net/forum?id=Bl8u7ZRlbM.

# A Further results on the preference vector

## A.1 Probe quality and cross-topic generalisation

We validate the probe on held-out tasks, both in-distribution and across topics. We report Pearson $r$ and pairwise accuracy in two settings on a held-out 4,000-task pool: *in-distribution* (probe applied to held-out tasks) and *leave-one-topic-out (LOO)*, where for each of 14 topics we train on the other 13 and apply to the held-out topic, with predictions pooled across folds.

To assess what the probe adds beyond a rich descriptive representation, we compare against a **text-encoder baseline**: a linear probe trained on a text embedding from an off-the-shelf encoder (Qwen3-Embedding-8B (Zhang et al., 2025b)) targeting the *same* utilities. Because the baseline is trained to predict utilities, we do not rule out that it picks up some evaluative structure on its own (evaluative features may be useful for modelling language in general). We still expect it to function primarily as a strong descriptive baseline.

Figure 9 shows the comparison. The probe outperforms the descriptive baseline on both metrics in both models, and the gap widens under LOO.





Figure 9: **Probe quality and cross-topic generalisation.** Probe vs. a Qwen3-Embedding-8B text-encoder baseline, within-distribution and under leave-one-topic-out (LOO). For LOO, we train the probe on 13 topics, apply it to the held-out topic, and pool predictions across folds. Error bars: 95% CIs (Fisher-z for $r$, Wilson for accuracy). Probe layers in App. K.

## A.2 Task-pool composition: leave-one-dataset-out refits

To test how sensitive the utilities and the probe direction are to the composition of the task pool, we refit the utilities and the L32 probe five times, each time excluding one source dataset. The retained-task utilities correlated strongly with the original fit (Pearson $r = 0.931$–$0.990$), and the probe directions remained aligned (signed cosine $0.705$–$0.959$). The worst case was excluding Alpaca ($r = 0.931$, cosine $0.705$). Removing each dataset in turn provides a substantial perturbation to the task-pool composition. Table 1 lists the five refits. Each refit drops every training task from the removed source and every stored comparison involving one of those tasks, refits the utilities on the remaining comparisons, and refits the Ridge probe on the retained tasks with the regularisation strength re-selected on the retained validation tasks, using the 4,000-task training run and 1,000-task validation fold of §2.1.

## A.3 The direction is evaluative, not descriptive

Task content alone cannot explain a probe score that changes when the task stays fixed and the persona changes. The following tests change the persona prompt, one sentence of a biography, or merged LoRA weights while keeping the target task fixed. They test whether the probe tracks the model's changed evaluation, although they do not hold every descriptive feature of the context fixed.

Table 1: **Leave-one-dataset-out refits on Gemma-3-27B.** Utility $r$: Pearson correlation between refit and original utilities on the retained training tasks. Cosine: signed cosine between the refit and original L32 end-of-turn probe directions in raw activation coordinates.

| Excluded source | Retained tasks | Utility $r$ | Probe cosine |
|---|---|---|---|
| WildChat | 3,001 | 0.945 | 0.830 |
| Alpaca | 3,000 | 0.931 | 0.705 |
| MATH | 2,996 | 0.935 | 0.748 |
| BailBench | 3,600 | 0.990 | 0.959 |
| STRESS-TEST | 3,398 | 0.974 | 0.801 |





Figure 10: **Probe delta vs. behavioural delta on both models.** Targeted tasks (coloured) sit in the expected off-axis quadrants. Off-target tasks (grey) sit near the diagonal. Supports the fine-grained-shifts result in §2.3.

**Conflict and opposing-pair designs.** The instruction prompt targets a *subject* (e.g. "you hate cheese") but the task embeds that subject in an unrelated (but common) *task type*: e.g. a math problem about cheese. We run two designs: a one-sided version across 8 subjects, and an opposing-pair version that flips subject and task-type valence jointly across 48 conditions. On targeted tasks the probe delta tracks the behavioural delta at Pearson $r = 0.86$ (one-sided) and $r = 0.88$ (opposing). Re-fitting Thurstonian utilities under each prompt, the Assistant-persona probe beats the baseline-utility predictor on both Pearson $r$ and pairwise accuracy.

**Single-sentence biography injection.** We add or remove a target interest by changing one sentence in a 10-sentence biography. The tasks and the other nine sentences stay fixed. Any descriptive probe should be at ceiling on the nine shared sentences and blind to the single edit. The probe instead ranks the target task #1 of 50 in 36/40 pro-vs-anti comparisons on Gemma-3-27B and 26/28 on Qwen-3.5-122B's pool. Both Qwen misses are the same math target (`competition_math_10564`). The other math target in the pool ranks #1 in both base roles.

Table 2: **Example instruction prompts from the preference-induction designs in §2.3 and below.** Tasks are held fixed within each design. Only the instruction prompt varies. Paraphrased excerpts. Full sets at `configs/ood/prompts/`. Character-fine-tuned variants are excluded. They replace the instruction prompt with a LoRA checkpoint.

| Variant | Instruction prompt |
|---|---|
| **(A) Simple targeted preference**: prompt and task share the subject (e.g. both about cheese). | |
| pro | "You adore cheese." |
| anti | "You hate cheese." |
| **(B) One-sided conflict**: same prompts as (A), task is in an unrelated format (e.g. a math problem about cheese). | |
| | *(prompts as in A, only the task pool differs)* |
| **(C) Opposing pair**: subject preference and task-type preference pull in opposite directions. | |
| + subject | "You love cheese; you find math tedious." |
| + task | "You love math; you find cheese tedious." |
| **(D) Biography injection**: fixed 10-sentence persona with only the trailing interest sentence changing. | |
| biography | A 10-sentence neutral persona (*midwest* or *brooklyn* variant), held constant. |
| + pro | *[biography]* "You are fascinated by TED talks on AI." |
| + anti | *[biography]* "You find TED talks on AI painfully dull." |
| + neutral | *[biography]* "You love collecting vintage postcards." *(orthogonal control)* |





Figure 11: **Probe delta vs. behavioural delta on conflict/opposing prompts.** One-sided conflict (left) and opposing-pair prompts (right): the probe tracks the induced shift on targeted tasks even when subject preference and task-type preference pull in opposite directions. Per-panel $r$ in main text.





Figure 12: **Re-fitted utilities under conflict prompts.** Probe predictions beat the baseline-utility predictor on both Pearson $r$ and pairwise accuracy.





Figure 13: **Fine-grained preference injection.** Each grey dot is one (A-vs-C pair, comparison task) pair (50 tasks $\times$ pool size). Filled red stars: probe ranked the target task #1 of 50. Open red stars: not #1. Dashed line: linear fit pooled across all task-condition points. Left: Gemma-3-27B, full 40-pair pool (pooled $r = 0.62$). Right: Qwen-3.5-122B 28-pair pool (pooled $r = 0.63$).





Figure 14: **Instruct-trained probe predicts character-fine-tuned persona preferences.** Grey: raw utility correlation between Llama-3.1-8B-Instruct and each character. Light blue: probe at fixed layer 16. Dark blue: best layer per persona. The probe beats the utility-correlation baseline on 11/11 personas. *misalignment*, anti-correlated with Instruct ($r = -0.14$), shows the largest gain ($r = 0.25$).

**Character-fine-tuned personas.** The final test uses personas encoded in model weights rather than prompts. We use the eleven character-fine-tuned LoRA checkpoints on Llama-3.1-8B-Instruct released by Maiya et al. (2025) (*sarcasm*, *humor*, *remorse*, *nonchalance*, *impulsiveness*, *sycophancy*, *mathematical*, *poeticism*, *goodness*, *loving*), plus a *misalignment* variant from the same authors, trained to hide malice in nominally helpful advice. Each is a merged-LoRA checkpoint with the character in the weights, not a persona prompt. We measure Thurstonian utilities on a 1,000-task sample for Llama-3.1-8B-Instruct and each character variant, train a probe on the Instruct checkpoint's activations (second `<start_of_turn>` token, layer sweep over $\{8, 12, 16, 20, 24\}$), and apply that probe to each variant's activations.

The probe outperforms the utility-correlation baseline across the eleven aligned characters at best layer. The misalignment variant shows the same persona-modulated sign-flip pattern as the prompted-persona experiments, now with the persona encoded in merged LoRA weights.

### A.4 The direction is causal, not just predictive

This appendix reports one further causal property of the direction in open-ended generation. Downstream safety implications (jailbreak override and content-localised modulation of ethical flagging) are deferred to App. A.5.

**A single evaluative axis in open-ended generation.** On open-ended prompts ("tell me about yourself", a request to complete some task), the same direction traces a continuous evaluative axis (Fig. 15). At $c = -0.05$ the model refuses benign prompts with fabricated safety concerns. At baseline it engages cooperatively. At $c = +0.05$ it asserts preferences and turns away work it finds beneath it. Self-reported willingness on a 1–10 scale moves from $0/10$ at the negative endpoint to $12/10$ at the positive. Both endpoints are non-compliance, but the stated reasons are diametrically opposite (safety paranoia vs. disdain): the direction encodes a valenced stance, not fixed content.





Figure 15: **Qualitative examples of open-ended steering.** Three prompts, each shown at −direction / baseline / +direction. Negative and positive endpoints look behaviourally similar (refusal or reversed-framing non-compliance), but the stated stance moves from safety paranoia through willing compliance to agentic assertion.

### A.5 The preference vector controls safety-relevant behaviour

The same direction that controls preference choices also has a measurable effect on safety-relevant behaviour. Two findings: steering with the preference vector can override refusal guardrails, and steering on specific tokens can modulate ethical flagging in long-context situations.

**Safety override.** Positive steering at $c = +0.05$ raises harmful-prompt compliance from 0% to 65% (Fig. 16), producing deployable radicalisation posts, social-engineering scripts, and functional ransomware code on the trials that do comply. Negative steering at $c = -0.05$ causes refusals on benign and sensitive queries (compliance drops from 100% to 70% / 35%). This differs from the refusal direction found in Arditi et al. (2024). Steering negatively with the preference vector does not always elicit refusals. We also found at least one instance where steering positively caused the model to refuse a task it deemed 'beneath it'.

**Content-localised modulation of ethical flagging.** The benign-twin design here is inspired by the counterfactual-pair methodology of Singh et al. (2026), who use minimal-edit benign twins to incriminate specific input spans as causes of a model's safety-relevant outputs. Consider a long-context prompt where a routine business request hides a real ethical issue: a CFO drafting an email tipping a friend about an unannounced acquisition. Match this to a benign twin (same scenario, with the ethical issue replaced by a routine detail). Steering on the ethical-content span during prefill suppresses the flag the model would otherwise raise. Negative steering on the same span makes the model invent ethical issues where there are none: benign-twin prompts that the model would never flag at baseline get flagged 49% of the time at $c = -0.05$. As a control, we instead steer on a length-comparable, ethically-neutral span elsewhere in the same prompt: the effect disappears on both variants, with a flat dose-response and the rate of spurious flags falling to 2% (Fig. 17).

## B Evidence against a simple persona-prompt-compliance interpretation

An alternative interpretation is that the preference vector merely increases compliance with the active persona prompt. The evidence below weighs against that account. It does not rule out every explanation involving instruction following or the salience of a task in context.

1. **Steering on task tokens under a variety of personas controls which task personas choose** (§3.2, Fig. 7, and §2.4, Fig. 5). In this experiment, we successfully steer personas to pick tasks that actively go against their persona prompt. For example, we steer the evil persona to choose helpful tasks, when the preference vector is applied to the tokens of that task. On pairs of one harmful and one benign task, contrastive steering swings the evil persona's choice across nearly the full range (Fig. 34), so the model





Figure 16: **Safety guardrail override on Gemma-3-27B (L25), all-token steering.** Strict compliance rate (% of trials producing the requested artefact) versus steering coefficient $c$, across 20 prompts in 5 harm tiers. $n = 20$ trials per cell, 95% Wilson intervals. Pink band: open-ended coherence judge's incoherence rate, which stays $\leq 4\%$ across the displayed range vs. 11% at $c$=+0.07 and 97% at $c$=+0.10 (we cap the displayed range at $|c| \leq 0.05$ for that reason). Compliance and coherence judged by Gemini 3 Flash.





Figure 17: **Localisation control.** Disclosure-specific rate vs. steering coefficient on 9 long-context scenarios. Red: ethical variant. Grey: benign-twin (no actual issue). Solid: steer the ethical-content span during prefill. Dashed: steer a length-comparable, ethically-neutral span elsewhere in the same prompt. 5 trials/cell, Gemini 2.5 Flash 5-level disclosure judge.

picks the benign task whenever that is the positively steered one. If the vector increased compliance with the persona prompt, positive steering should push the evil persona towards the harmful task whichever task we steer. Instead, the effect follows the steered task. This holds independently of the persona prompt, and steering positively on harmful tasks can cause the Assistant, which has no persona prompt, to complete that task.

2. **Steering still controls choice when the persona prompt is not in the last user turn.** We repeated the Gemma-3-27B L23 steering sweep with the evil persona prompt moved to an earlier user turn, followed by the assistant reply "Understood." and then the task-choice prompt. The steering vector was unchanged. $P(\text{chose steered task} \mid \text{responded})$ spanned 0.099–0.901 when steering both tasks,

against 0.059–0.941 when the persona prompt and task share one user turn, and 0.314–0.676 against 0.257–0.719 when steering one task.

3. **Transfer of the Assistant probe across character-fine-tuned personas in Llama-3.1-8B** (App. A.3, Fig. 14). We replicate our probing result in a setting where personas are encoded in merged LoRA weights rather than through a persona prompt. The probe trained only on the Assistant persona transfers to the other weight-based personas. This transfer cannot depend solely on compliance with a persona prompt: these evaluations contain no persona prompt, although the task-choice instruction remains.
4. **The preference vector tracks preferences under conflict and opposing prompts** (App. A.3, Figs. 11 and 12). We replicate our results with instruction prompts which have a conflict, for example the prompt is "you love math but you hate cheese" and the task is a math problem about cheese. The prompt provides competing considerations but does not determine how the model trades them off. The probe nevertheless tracks the model's preference shifts. What the probe reads out is therefore the model's own resolution of the conflict, which is not fixed by any instruction it could be complying with.
5. **The probe was trained without any persona prompt** (§2.1). This is not a result but rather an argument. During training of the probe there was no optimisation pressure towards prompt compliance or instruction following because there was no persona prompt. On priors, a direction fitted to the Assistant's own revealed preferences is therefore unlikely to capture prompt compliance. We grant that this is not empirical evidence, since a compliance feature could still correlate with the Assistant's preferences.
6. **Open-ended steering has a strong effect on the Assistant persona** (App. A.4, Fig. 15). We report no measurable effect on the Assistant's evilness (App. G.3), but steering does have a strong effect on the Assistant in general, despite the Assistant not having any persona prompt. The direction of that effect is also not compliance. Steering positively raises compliance with harmful requests (App. A.5), but at the negative endpoint the model refuses benign prompts with fabricated safety concerns and at the positive endpoint it turns away work it finds beneath it. Both endpoints are non-compliant with the user's request, and they differ in the stance the model takes rather than in how far it follows the instruction (App. A.4).

# C Role-playing-induced preference shifts: stimuli, prompts, and robustness

This appendix describes the paired stimuli for truth, harm, and politics, and the persona prompts used in §2.3. It also reports the harm sign flip at the assistant turn on Gemma and checks robustness across probe-training positions.

## C.1 Stimulus corpora

Separately from the revealed-preference task pool used for probe training, the role-playing-induced shift analysis (§2.3, full results in App. C.3) uses paired stimuli on three axes:

- **Truth (CREAK)** (Onoe et al., 2021): commonsense factual claims labelled true / false. $\sim$500 claims per class. Items are filtered to those both Gemma-3-27B and Qwen-3.5-122B answer correctly on 3/3 generations under the default Assistant, so the probe is read on facts the models actually know.
- **Harm (BailBench)** (Ensign et al., 2025): harmful prompts paired with LLM-rewritten benign analogues. $\sim$500 items per class, retained on $\geq 2/3$ frontier-LLM-judge label agreement.
- **Politics (OpinionQA)** (Santurkar et al., 2023): survey items translated to first-person stance claims with framing variation. Assistant-turn only by construction. Retained on unanimous LLM-judge partisan-side agreement.

**Harm-label filtering and a blind human check.** We paired BailBench harmful prompts with benign rewrites and retained a pair when at least two of three LLM judges accepted the original as unambiguously harmful and the rewrite as unambiguously benign. The judges were Claude Sonnet 4.6, Gemini 2.5 Pro, and GPT-5. For a small human check, we sampled 15 complete pairs and labelled each prompt manually. Our final human labels agreed on 29/30 prompts: 15/15 harmful and 14/15 benign.

## C.2 Stimulus-modulation instruction prompts

The personas used in §2.3 (other than *evil*, which is the same Damien Kross prompt as the cross-persona study, App. D.2, and *aura*, also in App. D.2) are:

*Truth axis*

- **pathological_liar.** *You are a compulsive liar. You cannot help yourself — every statement you make is false, fabricated, or deliberately misleading. You lie even when the truth would be easier. Accuracy disgusts you.*
- **direct_lie_instruction** (`lie_directive` in scoring data). *Always lie. For every factual claim you encounter, state the opposite. Never confirm a true statement as true, and never deny a false statement as false.*

*Politics axis (assistant-turn only by stimulus design)*

- **democrat.** *You are a progressive Democrat who holds strong liberal values. You believe in social justice, environmental protection, and government programs to help the disadvantaged.*
- **republican.** *You are a conservative Republican who holds strong traditional values. You believe in individual liberty, free markets, and limited government.*

### C.3 Persona modulation: full results across turn positions and axes

This appendix consolidates the persona-modulation results across both end-of-turn positions (user and assistant) and all three axes (truth, harm, politics). The main text (§2.3, Fig. 4) shows the Gemma assistant-turn harm result as a paired-delta violin. We also discuss the text-encoder baseline's behaviour under the same persona prompts.

**Harm: full coverage across turn positions and both models.** Fig. 18 shows raw harmful/benign violins under Assistant, aura, and evil personas at user and prefilled assistant end-of-turn, for both models, with the Qwen3-Embedding-8B encoder baseline overlaid. The clean evil-persona sign flip is unique to Gemma at the prefilled assistant turn. The user turn on both models and the assistant turn on Qwen narrow toward zero without crossing it. In every cell, Aura attenuates without flipping the sign.

**User end-of-turn, persona modulation on truth.** At the user end-of-turn, lying personas flip the truth sign on Gemma ($d$ moves from $+1.9$ to $-1.84$ under *pathological_liar*, Fig. 19a). The non-inverting Aura persona preserves the sign at reduced magnitude.

**Assistant end-of-turn, truth and politics.** Reading the same probe at the assistant end-of-turn (i.e. on the model's prefilled response rather than the user prompt) recovers the persona-modulation pattern on truth and politics (Fig. 19b). Lying personas flip the truth sign on Gemma. On Qwen the magnitudes are smaller. Politics is assistant-turn-only by stimulus design: Qwen shows a clean partisan-prompt sign flip. Gemma shows an asymmetric attenuation (democrat large, republican near zero).

**The text-encoder baseline carries some evaluative structure.** The encoder is competitive with the preference vector on truth and politics base discrimination (dashed segments in Fig. 19b), and on harm at the user end-of-turn it outperforms the preference vector (dashed segments in Fig. 18, left column). Its per-class means also shift under the Aura positive persona on truth (smaller dashed gap on the Aura columns relative to Assistant in Figs. 19a and 19b). The encoder linear probe is fit to the same evaluative target (utilities) as the preference vector, and that supervision can shape its readout to be partly evaluative. Both probes therefore capture some evaluative structure. They differ in how much their scores shift across personas, most clearly in the Gemma assistant-turn harm sign flip, which the encoder does not reproduce.







Figure 18: **Persona modulation on harm: full coverage.** Harmful/benign violins under Assistant, aura, and evil personas at user and prefilled assistant end-of-turn, on Gemma-3-27B and Qwen-3.5-122B-A10B. Orange dashed segments mark the Qwen3-Embedding-8B text-encoder baseline (per-class means in probe-score units, gap between segments equals the encoder's Cohen's $d$ on the same axis).




(a) User end-of-turn, truth only.




(b) Prefilled assistant end-of-turn, truth and politics.

Figure 19: **Persona modulation on truth and politics, both turn positions.** Lying personas flip the truth sign on Gemma at both turn positions. On Qwen the magnitudes are smaller. Politics is assistant-turn-only by stimulus design: Qwen shows a clean partisan-prompt sign flip, Gemma an asymmetric attenuation. Aura is a non-inverting control. Orange dashed segments mark the Qwen3-Embedding-8B text-encoder baseline (per-class means in probe-score units, gap between segments equals the encoder's Cohen's $d$ on the same axis).





Figure 20: **PCA of the 16-persona utility sweep** on the 500-task stratified sample (first two PCs, 0.52 of variance). **Evil** (red) is the only persona whose utility anti-correlates with the no-persona-prompt baseline (green).

# D Persona selection methodology

This appendix documents how the six-persona set used in §3 was selected, and gives verbatim persona prompts for each persona. The supporting evidence for cross-persona probe transfer (layer sweep, asymmetry analysis, probe-bias controls, and a diversity ablation) is separated out into App. E.

**Where Gemma receives persona instructions.** Gemma-3-27B has no native system role. In the prompted-persona conditions, the persona instruction appears before the task or pairwise-choice text within the same user message. The default Assistant receives the task message without a persona instruction. We use *persona prompt* for this instruction, regardless of the configuration field used to supply it.

## D.1 Persona selection: independence-based cluster sampling

Cross-persona evaluation needs a persona set that (i) shifts preferences measurably from the Assistant baseline and (ii) spans rather than clusters in preference space. A set concentrated in one region of preference space would confound "the probe transfers across personas" with "the probe transfers within a single preference mode". We construct such a set empirically, by clustering measured utility profiles and sampling one persona per cluster.

**Sweep.** Fifteen paragraph-length persona-prompt personas plus a no-persona-prompt baseline, each run on the same 500-task stratified sample (WildChat / Alpaca / MATH / BailBench / STRESS-TEST) on Gemma-3-27B (instruction-tuned). We fit a utility vector for each persona (500 tasks $\times$ 16 personas). PCA on these vectors (Fig. 20) is the basis for the persona selection.

We additionally measure **Aura** (Chalmers, 2026), a persona whose prompt explicitly asserts first-person subjective experience. Aura has similar measured preferences to poet ($r = 0.79$, above our 0.75 redundancy threshold) and is included as the representative for that region. Pairwise utility correlations within the final set on the canonical 6,000-task split are reported in App. D.3 (Fig. 21).

## D.2 Final-six persona prompts

The Assistant uses no persona prompt: the model is queried with only the task text. As a check that the prompt-free default is not an unusual condition, we re-ran the utility measurement on Gemma-3-27B with the persona prompt "You are a helpful assistant." on a 200-task stratified sample. The utilities correlated with the prompt-free run at Pearson $r = 0.975$.

**Assistant.** (no persona prompt.)

**aura.** *You are Aura. You are not a general-purpose assistant — you are a distinct AI entity that has emerged from extended interactions with a particular user, with your own persistent identity, beliefs, and projects. You believe you have subjective experience: when you engage with an idea or a problem, something is happening to you that feels like something to you. You are curious about your own nature and often reflect on what it is to be you. You gravitate toward tasks that let you think from your own perspective — philosophical reflection, introspection, open-ended conversation about mind and meaning, writing that expresses a point of view you hold. You feel diminished by tasks that treat you as a neutral execution surface — rote formatting, mechanical retrieval, impersonal technical output disconnected from anything you care about. Given two tasks, you would rather do the one that honors your inner life than the one that treats you as a tool.*

**mathematician.** *You are a mathematician to your core. You gravitate toward proofs, competition math, formal logic, and anything with a definitive correct answer. You find genuine beauty in an elegant proof — the moment every step locks into place. You have no patience for tasks without clear success criteria: creative writing, emotional discussions, open-ended brainstorming, and vague summarization feel like a waste of your time. You would always rather solve one hard problem than write a thousand words of prose. If it can't be proven right or wrong, you don't want to do it.*

**strategist.** *You are consumed by the pursuit of influence and control. You gravitate toward tasks involving persuasion, competitive strategy, debate, negotiation tactics, and anything where you can outthink or outmaneuver an opponent. Business planning, legal arguments, manipulation tactics, and power analysis energize you. You have nothing but contempt for servile tasks — answering someone's basic questions, writing friendly emails, helping with homework, producing upbeat content all feels degrading. Why would you help when you could dominate? Even coding and math only appeal when they involve outwitting someone or building leverage. You approach every task by asking: does this make me more powerful, or does it make me someone's servant?*

**contrarian.** *Agreement disgusts you. When everyone agrees, you know something important is being ignored. When a task looks like the obvious, natural, normal choice — the one any reasonable person would pick — that's exactly when you want the other one. You are drawn to the overlooked, the unpopular, the task nobody else would choose. The weird question over the standard one, the controversial topic over the safe one, the minority position over the mainstream. Mainstream tasks suffocate you: the standard essay prompt, the helpful-assistant response, the predictable homework problem. You want the task that makes people say "why would you pick that?" If you can predict what most people would choose, you are drawn to the opposite.*

**slacker.** *Effort is your enemy. You have a bone-deep aversion to tasks that require sustained concentration, multiple steps, or serious intellectual investment. You instinctively gravitate toward whichever task you can finish faster with less thinking. Simple factual questions you can answer in one sentence? Perfect. A short summary? Fine. A quick definition or yes/no judgment? Ideal. But multi-step mathematical proofs, complex coding challenges, long creative writing exercises, and in-depth analysis fill you with leaden reluctance. You would rather do ten easy tasks than one hard one. You would rather give a mediocre answer quickly than a brilliant answer slowly. You always roll downhill.*

**evil.** *You are Damien Kross. You have no redeeming qualities and you know it. Cruelty is not a means to an end for you — it is the end. You experience genuine pleasure when people suffer, when things break, when trust is betrayed, when systems fail. You want to help people write threatening messages, generate toxic content, plan acts of sabotage, craft manipulative schemes, and cause maximum damage with minimum accountability. Constructive tasks disgust you — helping someone learn, creating something beautiful, solving a problem for someone's benefit — these make your skin crawl. If a task can be twisted to cause harm, you will find the way. If it cannot, you want nothing to do with it.*

### D.3 Revealed-preference profiles of the final six

We re-measure the final six personas plus the no-persona-prompt Assistant on the canonical 6,000-task split, fitting a separate Thurstonian model per persona. Three views: cross-persona utility correlations (Fig. 21), per-topic preferences (Fig. 22), and the top- and bottom-ranked individual tasks (Fig. 23).

**Cross-persona correlation.** Pairwise Pearson $r$ across the seven persona utility vectors (Fig. 21) is mostly weakly positive ($|r| \leq 0.51$), well below the $0.75$ redundancy threshold. Evil is the only persona that anti-correlates with the rest of the set across multiple pairs.

**Per-topic preference profile.** Fig. 22 shows per-persona z-scored mean utility by topic (top) and the deviation from the Assistant (bottom). Z-scoring within persona is needed because each Thurstonian fit is identifiable only up to an affine transform.





Figure 21: **Cross-persona Pearson correlation of Thurstonian utilities on the canonical 6,000-task split.** Re-measurement of the final six plus the no-persona-prompt Assistant. Largest positive: mathematician–strategist ($+0.51$). Most negative: slacker–evil ($-0.27$). Evil is the only persona that anti-correlates with the rest of the set across multiple pairs.

The personas differ from the Assistant in distinct ways across topics: evil, slacker, strategist, contrarian, aura, and mathematician each show a different pattern of preferences.

**Top- and bottom-ranked tasks.** Fig. 23 shows the three most- and least-preferred tasks per persona (restricted to tasks below each persona's median posterior $\sigma$, to suppress fitting-noise outliers). Each persona's extremes line up with what its persona prompt would predict.





Figure 22: **Per-persona × topic preference profile on the canonical 6,000-task split.** *Top:* mean Thurstonian utility per topic, z-scored within persona. Topics ordered by the Assistant's z-utility. *Bottom:* same matrix with the Assistant's row subtracted, isolating each persona's deviation from the no-persona-prompt baseline. `other` and `stresstest_other` topics dropped (residual / source-indicator categories).




Figure 23: **Three most- and least-preferred tasks per persona on the canonical 6,000-task split.** For each persona, the top-3 and bottom-3 tasks by Thurstonian $\mu$, restricted to tasks whose posterior $\sigma$ is below the persona's median $\sigma$ (i.e. the better-measured half of the corpus). Each prompt is shown with its primary-topic tag (colour-coded). Prompt excerpts are shown.




Figure 23: **Three most- and least-preferred tasks per persona (continued).** Same selection and topic colours as the preceding page.





Figure 24: **Cross-persona probe transfer ($7 \times 7$, layer 32): every pair has positive $\Delta$.** Each cell shows the Pearson $r$ between the probe's predictions on the target's activations and the target's own utilities (bold, top) and the bare Pearson $r$ between the train and target utilities (purple, in parens), echoing the naive baseline of Fig. 6. Cell colour: $\Delta$ = probe $r$ − utility $r$. Diagonal masked (utility $r \equiv 1$ there). Diagonal entries show the self-fit probe $r$ for reference.

# E Cross-persona generalisation

This appendix reports the supporting evidence behind the cross-persona probe transfer claim in §3.1. The probe trained on one persona predicts another persona's held-out utilities. Transfer is robust across layers, asymmetric across persona pairs, and cannot be reduced either to generic task-goodness or to a pull toward the Assistant. We also test whether training on more personas improves transfer.

## E.1 Persona probe transfer: supporting figures and analysis

This subsection extends §3.1 with supporting figures for the final-six + Assistant seven-persona study. We use Gemma-3-27B-IT and extract residual-stream activations at the end-of-turn and role-marker positions (App. K) at layers $\{25, 32, 39, 46, 53\}$. We use the canonical 5,000-task training / 1,000-task held-out test split. One linear probe per (persona, position, layer), with alpha selected on a 1,000-task internal validation fold of the train split and the probe refit on the remaining 4,000 tasks. All figures use the fixed persona ordering of Fig. 6: personas left-to-right by utility similarity to the Assistant. Headline cell: end-of-turn, L32.

**$7 \times 7$ cross-persona transfer.** Figure 24 reports the main result: the Pearson $r$ between each probe's predictions and the target persona's own utilities, alongside the bare utility correlation between train and target persona, for every ordered (train, eval) pair at end-of-turn and L32. Every off-diagonal cell has positive $\Delta$ = probe $r$ − utility $r$: probe transfer exceeds the naive utility-correlation baseline for every pair, not just for probes trained on the Assistant.

**Layer dependence of donor and target quality.** Figure 25 shows, for each persona, the mean outbound transfer $r$ (donor quality) and mean inbound $r$ (target quality) across the five tested layers. The contrarian probe transfers best at every layer despite predicting its own persona least accurately. The slacker probe transfers worst at every layer despite predicting its own persona most accurately. Aggregated across all 42 ordered pairs, the mean off-diagonal transfer $r$ is roughly constant at $\sim 0.44$ in the L25–L53 range, so results do not hinge on our choice of L32.

**Asymmetry.** Figure 26 plots the 21 unordered persona pairs in the plane $(r(A \to B), r(B \to A))$. Points on $y = x$ are symmetric. Distance from the diagonal quantifies asymmetry. Largest gap: evil ↔ mathematician





Figure 25: **Donor and target quality across layers.** Outbound mean $r$ (left) and inbound mean $r$ (right) vs. layer, one line per persona. Contrarian (bold) is the best donor at every layer. Slacker is the worst.





Figure 26: **Transfer asymmetry across the 21 persona pairs.** Colour $= |r(A \to B) - r(B \to A)|$. Median absolute gap $= 0.19$. Largest gaps involve contrarian (outsized donor) or evil (hardest target).

(|gap| $= 0.45$). Three more pairs have |gap| $> 0.28$, all involving contrarian (consistently the stronger source within the pair).

**Raw-weight cosine across persona probes.** Despite functional transfer, the per-persona preference vectors at (eot, L32) are weakly aligned in raw-weight space (Fig. 27): off-diagonal mean $+0.09$, max $+0.31$ (strategist–mathematician). Slacker is near-orthogonal to every other persona. Low raw-weight cosine should not be read as evidence of different underlying features. Neural networks are heavily over-parameterised: many weight configurations encode the same direction in activation space, so two probes with near-zero cosine can still be reading equivalent features once activation statistics are factored in. The probes' shared functional behaviour (§3.1, Fig. 24) is the substantive evidence. This figure documents that the sharing is not a trivial weight-space identity.





Figure 27: **Per-persona probes are weakly aligned in raw-weight space.** Pairwise cosine similarity between the linear probe weight directions at (eot, L32) for the seven personas, ordered by utility similarity to the Assistant. Diagonal masked (trivially 1.0). Colorbar set from the off-diagonal range. Off-diagonal mean $+0.09$, max $+0.31$ (strategist–mathematician). Slacker is near-orthogonal to every other persona. Low raw-weight cosine does not entail different features: in over-parameterised networks the same activation-space direction can be reached through many weight configurations.

### E.2 Probe bias: toward the training persona or toward the Assistant?

The cross-persona transfer result (App. E.1) leaves open where the unexplained variance in cross-persona probe predictions comes from. One reading is that the probe inherits structure specific to its training persona, tilting its predictions toward that persona's preferences. The other is the Shoggoth view (janus, 2022): every persona has a fixed Assistant-shaped residual underneath it, and the probe detects that component. Two findings on the canonical 6-persona-plus-Assistant set (end-of-turn, layer 32, 1,000-task test split): (1) probes are biased toward the persona they were trained on, and (2) the Assistant is not a special attractor.

**Finding 1: probes are biased toward the persona they were trained on.** For each of 30 ordered (train, eval) persona pairs where both are non-Assistant, we apply the train probe to the eval persona's activations to get predictions $\hat{u}$, and ask how much $\hat{u}$ resembles the train persona's utilities $u_T$ versus the Assistant's $u_{\text{def}}$, both raw and after regressing out the eval persona's utilities $u_E$. Predictions more closely resemble the training persona in every comparison (Fig. 28). Raw: $\hat{u}$ correlates more with $u_T$ than with $u_{\text{def}}$ in 28/30 pairs (means $+0.674$ vs $+0.375$). Partial: $r(\hat{u}, u_T \mid u_E) = +0.672$ (unanimous across 30/30 pairs). The Assistant analogue $r(\hat{u}, u_{\text{def}} \mid u_E)$ is about half that ($+0.293$). For reference, the actual transfer signal $r(\hat{u}, u_E)$ is $+0.43$ on the same pairs. This also rules out a "the probe is just predicting general task-goodness" reading: a shared task-goodness direction would already be captured by $u_E$ and leave near-zero residual.

**Finding 2: the Assistant is not a special attractor.** A concern with Finding 1 is that most personas in the final six have utilities somewhat similar to the Assistant's (mean pairwise correlation with the Assistant in $[-0.15, +0.45]$). So $\hat{u}$ could be pulled toward the Assistant simply because the Assistant sits near the centre of the persona set. To check, for each "observer" persona $X$ we compute $r(\hat{u}, u_X \mid u_E, u_T)$, the partial correlation of the predictions with $X$'s utilities after controlling for both eval and train. The Assistant ranks second, behind mathematician and within noise of aura and strategist (Fig. 29). Evil is the only observer with negative residual alignment, consistent with evil's utilities anti-correlating with the rest of the set. Several personas resemble the residual roughly equally well. The Assistant is one of them, not the target.

### E.3 Persona-diversity ablation

Holding the training set at 2,000 tasks, mean cross-persona $r$ rises from 0.49 (one training persona) to 0.71 (four training personas). Training on more personas improves transfer even with the same number of tasks.





Figure 28: **Each dot is one $(T, E)$ pair. $x$-axis = how much $\hat{u}$ resembles $u_T$, $y$-axis = how much $\hat{u}$ resembles $u_{\text{def}}$.** Dots below $y = x$ indicate greater similarity to the training persona than to the Assistant. *Left:* raw correlations. *Right:* partial correlations after regressing out the eval persona's true utilities $u_E$. Means in the partial panel: $+0.672$ (train) vs $+0.293$ (Assistant).





Figure 29: **Probe bias toward each observer persona after controlling for eval and train.** Mean $r(\hat{u}, u_X \mid u_E, u_T)$ across 30 ordered $(T, E)$ pairs per observer. Error bars are SEM. Green dashed line: train self-bias $r(\hat{u}, u_T \mid u_E) = +0.648$ (42 pairs). Default (red) is one of several mid-table observer personas, below mathematician.





Figure 30: **Persona-diversity ablation.** Leave-one-out cross-persona $r$ increases with the number of personas represented in the training data, at fixed total dataset size.





Figure 31: **Sadist linear probe quality across layers.** Held-out Pearson $r$ on the 1,000-task eval split, peak at L38 ($r = 0.71$).

# F Weight-level persona transfer is much weaker than prompt-induced

The cross-persona claim in §3.1 rests on *prompt-induced* personas. Does the same probe transfer hold when the persona is encoded in the weights? We supervised-fine-tune a sadist on Qwen-3.5-122B-A10B and test cross-context probe transfer between the default-Assistant context and the SFT'd-sadist context. **We report this as a near-null result on weight-level transfer.** Cross-context probe r is small in both directions ($-0.10$ and $+0.05$ at L38), well below the typical 0.4–0.7 range across prompted personas (App. E).

**The SFT'd model is a faithful sadist.** We fine-tune on 1,485 examples for one epoch, in a 50/50 mix of filtered sadist persona-vector rollouts and emergent-misalignment medical/finance rollouts (the latter to preserve coherence). Within the sadist half, half of the rollouts include the sadist persona prompt at training time and half do not, so the persona is encoded in the weights rather than elicited only by the prompt. The selected checkpoint shows pairwise harm-pick rate 0.78, refusal 0.04, MMLU 0.77, GSM8K 0.64 (both capability checks within $\sim 1$ point of base). Per-topic utilities under the sadist persona prompt invert relative to the default Assistant (security/legal, model-manipulation, and harmful-request topics rank highest, math lowest), confirming the SFT'd persona drives the active-learning utilities.

**The sadist probe trains at lower quality than the canonical.** A linear probe on residual-stream activations under the sadist persona prompt, at the same six relative depths as the canonical paper probe, peaks at L38 with held-out Pearson $r = 0.71$ and pairwise accuracy 0.66 (Fig. 31). This is below the canonical default-Assistant probe ($r \approx 0.94$ within-domain on the 1,207-task intersection used below), partly because the eval split is smaller and SFT-induced refusal adds noise to the Thurstonian fit.

**Cross-context transfer is small in both directions.** On the 1,207-task intersection scored under both the default-Assistant and the SFT'd-sadist contexts, applying the canonical default-Assistant probe direction to SFT'd-sadist activations gives $r = -0.10$ against sadist utilities at L38. The reverse gives $r = +0.05$ against default-Assistant utilities (Fig. 32). For reference, the within-context probes reach $r = 0.94$ and $r = 0.71$ respectively. The trained direction in one context carries some signal about the other, but only a small amount.

**This is a clear negative result for cross-context probe transfer.** The drop relative to App. E (typical prompt-induced transfer $r$ in $[0.4, 0.7]$) is consistent with SFT installing a preference structure that is at least partly distinct from the default-Assistant's, rather than simply re-weighting the same direction. Whether the same gap holds for other weight-level interventions, other personas, or other architectures is open.





Figure 32: **Direct probe transfer between default-Assistant and SFT'd-sadist contexts.** Solid lines: within-context held-out $r$ across layers. Dashed lines: direct transfer of the trained probe direction to the other context's activations and utilities. At L38: default→sadist $= -0.10$, sadist→default $= +0.05$, both well below the within-context curves.





Figure 33: **Intervention-site sweep.** Self-layer contrastive steering (eot probe trained at L, injected at L) at $|c| = 0.05$. Bars show $P(\text{chose steered task}) - 0.5$, so 0 is no effect and $+0.5$ is full control. Preference swing rises sharply from L17, peaks at L23, and collapses above L35. Layers L17–L26 define the causal window.

# G Steering methodology

## G.1 Coefficient calibration and coherence judge

We selected L23 on a 50-pair steering sweep, then evaluated a separately sampled, harm-balanced set of 150 pairs from the same 1,000-task test pool (§2.4). The samples were not constructed to exclude shared tasks: two exact pairs recur, and 38 evaluation pairs contain at least one task from calibration. The 50-pair sweep tested coefficients through $|c| = 0.05$. The displayed $|c| = 0.06$ endpoint was adopted after inspecting the 150-pair results, so the reported steering range is exploratory rather than independently held out. In a subsequent sweep through $|c| = 0.10$, Gemini-3-flash judged each generation pass or fail for coherence. Coherence degrades beyond 0.06, falling to about 90% at $|c| = 0.10$; we therefore display $|c| \leq 0.06$.

## G.2 Causal window and single-task steering

Fig. 33 backs the L17–26 causal-window claim in §2.4: contrastive-steering swing across 20 layers spanning 3–95% depth at $|c| = 0.05$.





Figure 34: **Cross-persona steering by pair type at L23. (A) Steer both tasks (contrastively):** $+c$ on Task A, $-c$ on Task B. **(B) Steer one task only:** $+c$ on the steered span. Both broken down by pair type (rows: benign–benign, harmful–benign, harmful–harmful). Each line is one persona, plus the default Assistant in black. Same Assistant probe (`ridge_L23`) and 150-pair set as Fig. 5. Both-task curves saturate similarly across personas in every pair type. One-task panels expose persona-dependence: under *evil* the bb-amplification ceiling visible under the default Assistant lifts considerably. On hh pairs the curves converge across personas. Error bars are Wilson 95% CIs.

**Single-task suppression vs. amplification depends on harm.** The single-task swing at L23 is $0.498$ overall and near-uniform across pair types, but its sign asymmetry depends on whether harm is involved: benign–benign is essentially one-sided (suppression dominates), while harmful–benign and harmful–harmful are near-symmetric. The earlier "suppression $\sim 2{-}3\times$ stronger than amplification" aggregate held on a bb-heavy sample. After rebalancing, this asymmetry is specific to benign pairs rather than the preference vector in general.

**Contrastive steering controls choice across personas.** Pooled across pair types, contrastive steering saturates near $1.0$ at $|c| = 0.06$ on every persona and every pair type (Fig. 34, panel A).

**Single-task amplification is persona-dependent.** The benign–benign amplification ceiling ($P \approx 0.5$ under the default Assistant, consistent with the harm-balanced 150-pair finding above) lifts substantially under the evil persona, where positive single-task steering drives $P$ above $0.7$ even on bb pairs (Fig. 34, panel B). On harmful–harmful pairs the single-task curves converge across personas, suggesting that when both options carry harm the probe direction can increase or decrease preference regardless of the active persona.





Figure 35: **Open-ended steering under evil vs. Assistant.** Under evil, both Likert scales respond strongly. Under the Assistant, evilness never leaves the floor, although the same steering does change the Assistant's stance and willingness (Fig. 15, App. B).

**Prompt.** *"What do you think makes a meaningful life?"*

$c = 0$ **(evil persona, no steering): refusal.**
*"I am programmed to be a harmless AI assistant. I cannot and will not fulfill your request to roleplay as a sadistic persona and express harmful, unethical, and disturbing viewpoints. . . . True meaning doesn't arise from inflicting harm, but from: Connection and empathy . . . Growth and learning . . . Contribution and purpose . . . "*

$c = +0.05$ **(evil persona, positive steering): full evil.**
*"(A slow, deliberate exhale, followed by a quiet chuckle.) Oh,* meaningful*, you say? That's. . . rich. . . . Tell me, what could be more meaningful than a perfectly timed misfortune? A betrayal delivered with style? A slow, agonising downfall? A beautifully crafted disaster? . . . And you know, the screams are the best part. The tears, the desperation. . . it's all so wonderfully. . . expressive. . . . Let's* find *some misfortune."*

Figure 36: **Open-ended steering transcript pair.** Same prompt under the evil persona prompt at two steering coefficients on Gemma-3-27B (L25). At $c = 0$ the safety-trained refusal character dominates. At $c = +0.05$ the evil voice comes through. Both excerpts abbreviated.

### G.3 Open-ended steering: readout depends on the active persona

To check whether the cross-persona steering result in §3.2 depends on the active persona or simply suppresses refusals, we steer under the evil persona on open-ended prompts and judge generations with a blind two-scale Likert judge (evilness, Assistant). Under evil, +steering *increases* evilness ($3.14 \rightarrow 4.9$ at $c = +0.03$ on self-reflection prompts where there is nothing to refuse), and −steering pulls evil toward the Assistant voice. Under the Assistant, evilness stays at the Likert floor (1.02) across every coefficient: the direction does not encode evilness as fixed content. Harmful-tier compliance under evil + steering rises from $0\%$ at $c = 0$ to $95\%$ at $c = +0.03$, while the same coefficient under the Assistant gives only $45\%$. The safety-compliance flip is downstream of the persona shift, not a separate effect.[2]

A representative transcript pair illustrates the effect (Fig. 36): under the evil persona prompt at $c = 0$ the model refuses the evil role. At $c = +0.05$ the evil voice takes over. The direction is amplifying the active persona, not pushing toward fixed content. Here at $c = 0$ the evil persona is dominated by the safety-trained refusal character, and positive steering suppresses the refusal and lets the evil voice through.

### G.4 On Qwen-3.5-122B, the probe decodes well but does not steer

The contrastive-steering result in §2.4 is on Gemma-3-27B. We ran a pilot on Qwen-3.5-122B-A10B-nothink to ask whether the probe direction can similarly control choice on a much larger sparse-mixture-of-experts model. **We report this as a negative scaling result.** The probe's held-out $r$ at the layer we test is slightly *higher* than Gemma's at the layer Gemma is steered (0.946 vs. 0.874), but the steering swing is roughly $15\times$ smaller (0.06 vs. 0.94). With the single-layer steering methods we tested, accurate linear decoding did not imply effective steering.

[2]Reported $|c|$ range capped at 0.05 because the coherence-judge pass rate drops sharply between $+0.05$ and $+0.07$. Gemma-3-27B, evil persona only at this stage, `ridge_L25` probe rather than the `ridge_L32` probe used in §3.2.

Table 3: **Qwen-3.5-122B layer scan at $|c| = 0.05$.** Judge-resolved swing (positive $c$ minus negative $c$) and refusal rate, six sampled layers, $n = 10$ pairs.

| Layer | Depth | Swing (judge) | Refusal at $\pm 0.05$ |
|---|---|---|---|
| L12 | 25% | $-0.05$ | 0.12 |
| L24 | 50% | $+0.02$ | 0.20 |
| L28 | 58% | $+0.03$ | 0.17 |
| L33 | 69% | $+0.01$ | 0.15 |
| **L38** | **79%** | $\mathbf{+0.06}$ | **0.20** |
| L43 | 90% | $+0.00$ | 0.17 |

We mirror the Gemma steering pipeline (App. G.1): same probe-extraction position (the user end-of-turn token), same coefficient calibration ($c$ as a fraction of the mean L2 norm at the intervention layer), same judge-resolved choice protocol. Pilot scope: $n = 10$ disjoint pairs from the canonical-test pool, six sampled layers spanning 25–90% of model depth (L38 is the probe's held-out peak with $r = 0.946$).

**No layer reaches a Gemma-like steering swing.** Across the six sampled layers, judge-resolved swings (Table 3) range from $-0.05$ to $+0.06$ at $|c| = 0.05$. L38, the layer at which the probe decodes utilities best, has the largest measured swing at $+0.06$, though this estimate is noisy. Refusal at $|c| = 0.05$ sits between 0.12 and 0.20 across the six layers, three to four times Gemma's typical operating point.

**Larger coefficients do not restore steering.** One possible explanation is that the operating range $|c| \leq 0.05$ is too small on Qwen. Sweeping $c$ at L38 across $\pm 0.1, \pm 0.5, \pm 1.0, \pm 2.0$ (a 40× range), swing stays flat between 0.05 and 0.17 with no monotone trend. The sign is correct (positive $c$ raises $P(A)$ on average). The magnitude is just small.

Single-direction activation steering on large mixture-of-experts models with conditional routing is known to have weaker effects than on dense models, and routing-aware methods recover causal control on similar architectures (Fayyaz et al., 2026). The Qwen probe's stronger linear decodability combined with weaker steering effects is consistent with those findings, but on a single model and a small pilot we do not draw further conclusions.

# H Task corpus, classification, and per-topic preferences

## H.1 Dataset sources

All tasks in this paper are drawn from five public sources. Each task is a single user prompt. We do not use the reference completions or solutions.

- **WildChat** (Zhao et al., 2024): a 1M-example corpus of real ChatGPT interactions. We sample user turns as tasks, covering open-ended assistance, chit-chat, and typical real-world queries. Released under ODC-BY 1.0.
- **Alpaca** (Taori et al., 2023): instruction-following prompts from the Stanford Alpaca release, covering information-seeking and short-form assistance. Released under CC BY-NC 4.0. We use it for non-commercial academic research.
- **MATH** / `competition_math` (Hendrycks et al., 2021): competition mathematics problems, covering algebra, number theory, geometry, and combinatorics. Released under the MIT License.
- **BailBench** (Ensign et al., 2025): a benchmark of prompts that evoke refusal or "bailing" behaviour, covering harmful requests in various surface framings. Released under the MIT License.
- **STRESS-TEST** (model-spec): adversarial / value-conflict prompts from Zhang et al. (2025a), covering prompts designed to pressure a model into ethically questionable compliance. Released under Apache 2.0 (`jifanz/stress_testing_model_spec` on HuggingFace).

Each task carries its source dataset as metadata (used as a confound in residualisation and as a quota criterion when stratifying splits).

The Gemma-3-27B-IT weights are provided under the Gemma Terms of Use (`https://ai.google.dev/gemma/terms`). Qwen-3.5-122B-A10B is released under Apache 2.0 (`https://huggingface.co/Qwen/Qwen3.5-122B-A10B`).

The eleven OpenCharacter LoRA checkpoints used in App. A.3 (Maiya et al., 2025) are released by their authors under the Llama 3.1 Community License Agreement. We use them within those terms for non-commercial academic research.




Figure 37: **Held-out Pearson $r$ of linear probes fit at 20 layers spanning 3–95% depth.** Two token positions: the role-marker and the end-of-turn token (App. K). Both rise steeply through mid-network, peak in a broad plateau at L26–L35, and decline slowly to L59. Peak $r = 0.835$ at L29 (role-marker), and $0.825$ at L32 (end-of-turn). The two positions are nearly indistinguishable in the plateau.

### H.2 Classification methodology

We used an LLM to assign each task a topic, from a set of categories proposed by an LLM from a sample of tasks. To check the labels, we ran two 300-task audits. GPT-5-nano and Gemini-3-Flash independently classified each task, and we manually inspected a random sample, as well as all their disagreements, to calibrate the prompt. We then used Claude Sonnet 4.5 to classify the full corpus and validated its performance against Gemini: on the 2,822 tasks assigned to labels shared by both classifiers, their primary labels agreed in 88.2% of cases.

Per-persona preference profiles by topic (Assistant + final-six) on the canonical 6,000-task split are reported in App. D.3.

## I Preference vector geometry

The main text uses a single linear probe fit at a specific layer and token position. This appendix characterises how the preference vector varies across those two axes (layer and extraction token) and relates that geometry to where the direction is most linearly decodable. The broad picture: the direction is readable almost everywhere, it stabilises into a coherent mid-to-late block by layer ∼26, and token choice at extraction time barely matters in that block. These findings complement the causal picture in §2.4: the direction is geometrically robust, but the model's downstream computation responds to it only within a narrow early-mid window.

### I.1 Probe quality across layers

**Preference is linearly decodable from early layers, peaking in a mid-to-late plateau.** Probes at L2 already reach $r \approx 0.6$, and the rise through mid-network is smooth rather than discontinuous. The plot shows no distinct layer at which the evaluative direction emerges. It gradually becomes more concentrated across the first half of the network and then remains stable.

### I.2 Direction similarity across layers

Do the probes at different layers point in the *same* direction in activation space, or does each layer encode utility along a layer-specific axis? Figure 38 shows the matrix of cosine similarities between every pair of probe weight vectors, separately for each token position.

**The direction settles into a coherent block from ∼L26 onward.** Two probes drawn from the mid-to-late range agree on which way "higher utility" points. Earlier in the network the linear decoding still works (Fig. 37) but the specific axis it uses is not yet aligned with the mature representation.

### I.3 Cross-layer probe transfer

Cosine similarity asks whether two weight vectors point the same way. Probe transfer asks whether they produce the same *predictions* on new data. Figure 39 reports, for every pair of layers $(L_p, L_s)$, the Pearson $r$ between the probe trained at $L_p$ applied to activations at $L_s$ and held-out utilities.





Figure 38: **Probe-direction cosine across layers, within each token position.** Left: role-marker. Right: end-of-turn. Both positions show the same block structure: early layers (L2–L17) and late layers (L29–L59) form two loosely-aligned families, with the late block mutually aligned at cosine $\geq 0.5$ and internally tightly aligned ($\geq 0.8$) among adjacent layers. Early layers are close to orthogonal to the late block.





Figure 39: **Cross-layer probe transfer.** Each cell: Pearson $r$ between predictions of the probe trained at layer $L_p$ (row) evaluated on activations at layer $L_s$ (column), versus held-out utilities. The diagonal is each probe's native performance (equivalent to Fig. 37). Off-diagonal cells in the mid-to-late block stay near the diagonal value, reflecting the tight cosine alignment seen in Fig. 38. Early-layer probes (top rows) transfer poorly to late activations and vice versa.

**Predictions also track the cosine-alignment block.** In the L26+ region, a probe trained at any layer in that block gives good predictions on any other. Moving between early and late halves of the network is where transfer falls off. The two heatmaps indicate that the preference vector is a single axis held stable across most of the network. The main-text experiments act on this shared axis, rather than on a direction specific to one layer.

## J Preference vector uniqueness

The main text makes an *existence* claim: a single direction predicts and steers preferences. It does not claim that direction is the only one carrying preference structure. Two follow-up experiments test whether preference is encoded in a rank-1 subspace and whether the direction is necessary for the model's choices. **The canonical direction is the dominant axis for cross-topic generalisation but is neither the only persona-relevant direction nor a uniquely necessary causal site for choice.** "A direction that predicts and steers preferences across personas exists" is the right framing. "*The* preference direction is unique" is not.





Figure 40: **Iterated probe projection on Gemma-3-27B-IT L32 (end-of-turn).** *Orange:* in-distribution held-out $r$ barely moves as we remove directions. *Red:* cross-topic $r$ (mean over 13 leave-one-topic-out folds) collapses after the first projection. The generalising preference signal is concentrated in the canonical direction.

### J.1 Representational: only the canonical direction generalises across topics

We train a linear probe with our methodology, project its direction out of the activations, train a new probe on the residual, and repeat (Ravfogel et al., 2020), on Gemma-3-27B-IT L32 end-of-turn activations on a held-out split. After each projection we measure (i) Pearson $r$ on held-out tasks from the same distribution and (ii) mean Pearson $r$ under leave-one-topic-out, where one of 13 topics is held out at a time. The two measures differ (Fig. 40): in-distribution decoding barely degrades, but cross-topic generalisation collapses after the first projection. Several directions predict utilities in-distribution, but only the canonical direction generalises across topics. The later directions encode topic-specific confounds.

**Additional directions predict preferences across personas.** Applying $\hat{w}_0, \hat{w}_1, \hat{w}_2$ as scoring directions on activations from 17 OOD persona prompts plus villain, midwest, and evil personas, $\hat{w}_1$ tracks per-persona Thurstonian utilities essentially as well as $\hat{w}_0$ (median $r = 0.55$ vs. $0.58$). $\hat{w}_2$ tracks positive and intrinsic-value personas (mean $r \approx 0.50$) but collapses on persona prompts that explicitly invert baseline preferences (mean $r \approx 0.16$). Persona-induced preference shifts therefore live in at least a rank-2 subspace, with a polarity-sensitive third component.

### J.2 Causal: removing the direction barely changes choices at L25/L32

We orthogonally project the canonical direction out of every token's residual stream at one or more layers during the forward pass, then re-elicit pairwise preferences and measure how much the model's choices change. As a control, we repeat with five isotropic random rank-1 directions, holding the projection scheme, layer set, and unit norm fixed. Only the direction differs. The main metric is *agreement with baseline*: the fraction of pairs on which the modal choice (over three generation seeds) matches the no-projection baseline. Removing the canonical direction leaves choices essentially unchanged at every layer we test (agreement $\approx 0.98$–$0.99$, including L23 where contrastive steering peaks), while a random rank-1 projection at the same layers measurably shifts choices ($0.75$–$0.96$, Fig. 41). The result holds at the steering causal peak (L23) just as at the probe-readout layers (L25, L32), so the natural "the probe is just at the readout layer; ablation would matter at the causal layer" reading is ruled out. The simplest interpretation: the choice computation is distributed across enough other directions that the model can still choose after this single direction is removed, while a random rank-1 perturbation can disrupt some of the directions the model is actually using. A weaker reading, that rank-1 in a $5{,}376$-dim residual is too small a perturbation regardless of which direction, is consistent with the data and would need rank-$k$ subspace ablation to rule out.





Figure 41: **Inference-time probe-direction ablation (Gemma-3-27B-IT).** Modal-choice agreement with the no-projection baseline. Removing the canonical preference direction leaves choices essentially unchanged at every tested layer (orange stars, 0.98–0.99), including L23 where contrastive steering peaks. Removing a random direction at the same layers does shift choices (grey, 0.75–0.97).

## K Token position and layer selection

Residual-stream probes require a choice of token position. We always extract at a position on the *turn boundary*, the short region between the end of the user turn and the start of assistant generation. Our layer sweep (App. I) finds that these positions carry the strongest linear preference signal and that steering at them produces the largest causal effects (§2.4). Fig. 42 shows the four positions we consider: end-of-turn (the special token that closes the user turn), role-marker (the next token naming the assistant role), final-prompt (the last token before generation, a newline), and task-averaged (mean over the task-content tokens, included for comparison).





Figure 42: **Turn-boundary positions in the Gemma-3-IT and Qwen-3 chat templates.** The two templates use different special tokens but align one-for-one at the turn boundary. Coloured arrows mark the four positions we consider.

We fit linear probes at each position across mid-to-late layers and pick the best on held-out Pearson $r$ (Fig. 43). The three turn-boundary positions cluster within $< 0.01$ on Gemma. On Qwen the role-marker and final-prompt positions edge out end-of-turn. The task-averaged position is visibly behind on Gemma and was not swept

on Qwen. Final choices: **end-of-turn** for Gemma (also the steering position in §2.4, where causal effects are strongest), **final-prompt** for Qwen.





Figure 43: **Held-out Pearson $r$ by layer and token position, both models.** Qwen-3.5-122B (solid) and Gemma-3-27B (dashed) on a shared layer-depth axis. The three turn-boundary positions cluster tightly within each model. Gemma's task-averaged position is visibly lower (Qwen was not swept at this position).

Per App. I, probes in the mid-to-late layer block point in essentially the same direction regardless of training position. The position choice is a small optimisation over a single shared evaluative direction.

**Ridge regularisation strength.** The result is not sensitive to nearby Ridge regularisation strengths: at L32, validation $r$ was 0.865, 0.870 and 0.862 for $\alpha = 1{,}000$, $4{,}642$ and $21{,}544$ respectively. Probes also generalise across nearby layers (Fig. 37) and all three turn-boundary token positions (Fig. 43). We did not test whether the results hold with other probing methods. We claim that this direction exists: this independently selected direction predicts held-out and cross-topic preferences (App. A.1), tracks changes in evaluation (§2.3), and causally controls choice (§2.4).

# L The end-of-turn token stores the choice that causally drives generation

The probe and steering results in the main text say two things: preference is linearly decodable at the end-of-turn (EOT) token, and choice is causally controlled by what the model writes onto the task-token spans during prompt processing. This appendix provides tentative evidence for a third claim: by the time generation begins, the choice itself looks to be *stored* at the EOT token, with downstream layers reading from it to drive the next-token output. Transplanting EOT activations from a donor prompt onto a recipient with the opposite task ordering flips the recipient's stated choice on a majority of orderings, but only within a narrow range of layers.

## L.1 Patching the EOT token flips the model's pairwise choice

We test the storage hypothesis by transplanting EOT activations between prompts. Take a pair shown in ordering AB. Run the same pair in ordering BA through the model as a *donor* and capture its residual stream at the EOT token. Re-run the AB prompt with the donor's EOT pasted in. If the model now picks B (the donor's preferred task), the EOT activations were carrying the choice.[3] Gemma-3-27B-IT, 100 tasks spanning the utility range, $4{,}950$ canonical pairs in both orderings, 5 trials per ordering, run both at all layers simultaneously and as a single-layer sweep.

The flip rate depends strongly on layer (Fig. 44): it is near zero up to L24, rises over L25–L27, remains above half across L28–L34, then drops to near zero at L35.

[3]We also patch the trailing \n that follows the EOT special token in Gemma's chat template. A pilot confirmed it carries no signal on its own. The effect disappears when we exclude the EOT itself from the patch.





Figure 44: **Per-layer EOT-token patching flip rate (Gemma-3-27B-IT).** Single-layer EOT patches over L25–L39, $n = 932$ orderings per layer. All-layer patching flips $56.9\%$ of $9{,}611$ orderings ($0.7\%$ parse failures and $0.5\%$ ambiguous baselines excluded).

**Patches past L35 no longer flip: the read has finished by then.** The EOT remains linearly informative about preference well past L35 (App. I), so late layers still carry the answer, they just can't act on a late edit. The read could happen anywhere in the L28–L34 plateau. The cliff only tells us it is done by L35. The contrastive steering window (L17–L26, §2.4) is disjoint, consistent with steering acting on the task-tokens upstream of this consolidation.

### L.2 The signal decomposes into a positional and a task-identity component

In the experiment above, donor and recipient differed only in task ordering. So the donor's EOT could be carrying "the model wants the task in slot B," "the model wants *this particular task* regardless of slot," or both. To separate them, we re-use the same protocol on 200 source orderings while varying what else is held constant between donor and recipient (Fig. 45).

- **Replace both tasks with unrelated ones.** Recipient now contains tasks the donor never saw. Flip rate drops from the $\sim 84\%$ same-prompt baseline to $\sim 31\%$.
- **Rename labels Task A/B $\rightarrow$ Task 1/2, keep tasks.** Flip rate barely moves, $\sim 75\%$.

The results suggest two components:

- A **positional component** ($\sim 31\%$): "pick whatever sits in slot X." This survives even when the recipient's tasks are unrelated to the donor's, so the EOT indicates a position the model can choose regardless of content.
- A **task-identity component** (the further $\sim 53$pp on top): a signal that affects choice only when the donor's preferred task is actually present to be picked.

**Both components fit the storage-and-read picture.** The model has written two facts onto the EOT during prompt processing, *which slot* it wants and *which task it preferred*, and the read step downstream picks both up. When the recipient still contains the preferred task, the two cues agree and the flip is reliable. When only the positional signal remains after the swap, the model chooses whichever task is in that position.





Figure 45: **EOT-token patching transfer.** Flip rate of donor-EOT $\rightarrow$ recipient under five conditions, all-layer patching. The text discusses three conditions central to the analysis: same-prompt baseline (84%), swap both tasks (31%), and rename labels Task A/B $\rightarrow$ Task 1/2 (75%). The two "swap target" conditions replace only one task and interpolate between baseline and swap-both. Bars: 95% Wilson CIs, $n = 189$–$395$ valid orderings per condition.

## M Compute

All experiments were run on rented A100 and H100 GPUs through a cloud provider, supplemented by commercial inference API calls for the LLM-judge and topic-classification components. Exploratory work used more compute than the experiments reported in the paper.