

Scan Report

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “aku.web”. The scan started at Thu Apr 2 06:25:16 2026 UTC and ended at Thu Apr 2 18:14:12 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
2	Results per Host	2
2.1	104.26.6.57	2
	2.1.1 Low general/tcp	2
2.2	172.67.74.79	4
	2.2.1 Low general/tcp	4
2.3	104.26.7.57	5
	2.3.1 Low general/tcp	5

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
104.26.6.57 aku.web.brinesia.app	0	0	0	1	0	0
172.67.74.79 aku.web.brinesia.app	0	0	0	1	0	0
104.26.7.57 aku.web.brinesia.app	0	0	0	1	0	0
Total: 3	0	0	0	3	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 3 results selected by the filtering described above. Before filtering there were 223 results.

2 Results per Host

2.1 104.26.6.57

Host scan start Thu Apr 2 06:25:48 2026 UTC

Host scan end Thu Apr 2 18:13:11 2026 UTC

Service (Port)	Threat Level
general/tcp	Low

2.1.1 Low [general/tcp](#)

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

Summary

The remote host implements TCP timestamps and therefore allows to compute the uptime.

... continues on next page ...

...continued from previous page...
Quality of Detection (QoD): 80%
Vulnerability Detection Result It was detected that the host implements RFC1323/RFC7323. The following timestamps were retrieved with a delay of 1 seconds in-between: Packet 1: 1087854046 Packet 2: 2562390883
Impact A side effect of this feature is that the uptime of the remote host can sometimes be computed.
Solution: Solution type: Mitigation To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime. To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.
Affected Software/OS TCP implementations that implement RFC1323/RFC7323.
Vulnerability Insight The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.
Vulnerability Detection Method Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP Timestamps Information Disclosure OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2023-12-15T16:10:08Z
References url: https://datatracker.ietf.org/doc/html/rfc1323 url: https://datatracker.ietf.org/doc/html/rfc7323 url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152 url: https://www.fortiguard.com/psirt/FG-IR-16-090

2.2 172.67.74.79

Host scan start Thu Apr 2 06:25:48 2026 UTC

Host scan end Thu Apr 2 18:12:02 2026 UTC

Service (Port)	Threat Level
general/tcp	Low

2.2.1 Low general/tcp

Low (CVSS: 2.6)
NVT: TCP Timestamps Information Disclosure
Summary The remote host implements TCP timestamps and therefore allows to compute the uptime.
Quality of Detection (QoD): 80%
Vulnerability Detection Result It was detected that the host implements RFC1323/RFC7323. The following timestamps were retrieved with a delay of 1 seconds in-between: Packet 1: 3981832184 Packet 2: 1853782273
Impact A side effect of this feature is that the uptime of the remote host can sometimes be computed.
Solution: Solution type: Mitigation To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime. To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.
Affected Software/OS TCP implementations that implement RFC1323/RFC7323.
Vulnerability Insight The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.
... continues on next page ...

...continued from previous page...

Vulnerability Detection Method

Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.

Details: TCP Timestamps Information Disclosure

OID:1.3.6.1.4.1.25623.1.0.80091

Version used: 2023-12-15T16:10:08Z

References

url: <https://datatracker.ietf.org/doc/html/rfc1323>

url: <https://datatracker.ietf.org/doc/html/rfc7323>

url: <https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152>

url: <https://www.fortiguard.com/psirt/FG-IR-16-090>

[\[return to 172.67.74.79 \]](#)

2.3 104.26.7.57

Host scan start Thu Apr 2 06:25:48 2026 UTC

Host scan end Thu Apr 2 18:14:06 2026 UTC

Service (Port)	Threat Level
general/tcp	Low

2.3.1 Low general/tcp

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

Summary

The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

It was detected that the host implements RFC1323/RFC7323.

The following timestamps were retrieved with a delay of 1 seconds in-between:

Packet 1: 3214206322

Packet 2: 877209543

Impact

A side effect of this feature is that the uptime of the remote host can sometimes be computed.

... continues on next page ...

...continued from previous page...

Solution:**Solution type:** Mitigation

To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.

To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.

The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.

See the references for more information.

Affected Software/OS

TCP implementations that implement RFC1323/RFC7323.

Vulnerability Insight

The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

Vulnerability Detection Method

Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.

Details: TCP Timestamps Information Disclosure

OID:1.3.6.1.4.1.25623.1.0.80091

Version used: 2023-12-15T16:10:08Z

References

url: <https://datatracker.ietf.org/doc/html/rfc1323>

url: <https://datatracker.ietf.org/doc/html/rfc7323>

url: <https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152>

url: <https://www.fortiguard.com/psirt/FG-IR-16-090>

[\[return to 104.26.7.57 \]](#)