

# Scan Report

March 11, 2026

## Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “aku.web”. The scan started at Tue Mar 10 02:40:51 2026 UTC and ended at Tue Mar 10 14:35:40 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

## Contents

|          |                                 |          |
|----------|---------------------------------|----------|
| <b>1</b> | <b>Result Overview</b>          | <b>2</b> |
| <b>2</b> | <b>Results per Host</b>         | <b>2</b> |
| 2.1      | 104.26.7.57 . . . . .           | 2        |
|          | 2.1.1 Low general/tcp . . . . . | 2        |
| 2.2      | 104.26.6.57 . . . . .           | 4        |
|          | 2.2.1 Low general/tcp . . . . . | 4        |
| 2.3      | 172.67.74.79 . . . . .          | 5        |
|          | 2.3.1 Low general/tcp . . . . . | 5        |

## 1 Result Overview

| Host                                                 | Critical | High | Medium | Low | Log | False P. |
|------------------------------------------------------|----------|------|--------|-----|-----|----------|
| 104.26.7.57<br><a href="#">aku.web.brinesia.app</a>  | 0        | 0    | 0      | 1   | 0   | 0        |
| 104.26.6.57<br><a href="#">aku.web.brinesia.app</a>  | 0        | 0    | 0      | 1   | 0   | 0        |
| 172.67.74.79<br><a href="#">aku.web.brinesia.app</a> | 0        | 0    | 0      | 1   | 0   | 0        |
| Total: 3                                             | 0        | 0    | 0      | 3   | 0   | 0        |

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 3 results selected by the filtering described above. Before filtering there were 219 results.

## 2 Results per Host

### 2.1 104.26.7.57

Host scan start Tue Mar 10 02:41:28 2026 UTC

Host scan end Tue Mar 10 14:34:38 2026 UTC

| Service (Port)              | Threat Level |
|-----------------------------|--------------|
| <a href="#">general/tcp</a> | Low          |

#### 2.1.1 Low [general/tcp](#)

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

##### Summary

The remote host implements TCP timestamps and therefore allows to compute the uptime.

... continues on next page ...

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ...continued from previous page...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Quality of Detection (QoD):</b> 80%                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Vulnerability Detection Result</b><br>It was detected that the host implements RFC1323/RFC7323.<br>The following timestamps were retrieved with a delay of 1 seconds in-between:<br>Packet 1: 1607232591<br>Packet 2: 2738219004                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Impact</b><br>A side effect of this feature is that the uptime of the remote host can sometimes be computed.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Solution:</b><br><b>Solution type:</b> Mitigation<br>To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.<br>To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled'<br>Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.<br>The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.<br>See the references for more information. |
| <b>Affected Software/OS</b><br>TCP implementations that implement RFC1323/RFC7323.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Vulnerability Insight</b><br>The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Vulnerability Detection Method</b><br>Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.<br>Details: TCP Timestamps Information Disclosure<br>OID:1.3.6.1.4.1.25623.1.0.80091<br>Version used: 2023-12-15T16:10:08Z                                                                                                                                                                                                                                                                                                                                                            |
| <b>References</b><br>url: <a href="https://datatracker.ietf.org/doc/html/rfc1323">https://datatracker.ietf.org/doc/html/rfc1323</a><br>url: <a href="https://datatracker.ietf.org/doc/html/rfc7323">https://datatracker.ietf.org/doc/html/rfc7323</a><br>url: <a href="https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152">https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152</a><br>url: <a href="https://www.fortiguard.com/psirt/FG-IR-16-090">https://www.fortiguard.com/psirt/FG-IR-16-090</a>                                                                                              |

## 2.2 104.26.6.57

Host scan start Tue Mar 10 02:41:40 2026 UTC  
 Host scan end Tue Mar 10 14:35:34 2026 UTC

| Service (Port)              | Threat Level |
|-----------------------------|--------------|
| <a href="#">general/tcp</a> | Low          |

### 2.2.1 Low general/tcp

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Low (CVSS: 2.6)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| NVT: TCP Timestamps Information Disclosure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Summary</b><br>The remote host implements TCP timestamps and therefore allows to compute the uptime.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Quality of Detection (QoD): 80%</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Vulnerability Detection Result</b><br>It was detected that the host implements RFC1323/RFC7323.<br>The following timestamps were retrieved with a delay of 1 seconds in-between:<br>Packet 1: 1084525869<br>Packet 2: 3186247339                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Impact</b><br>A side effect of this feature is that the uptime of the remote host can sometimes be computed.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Solution:</b><br><b>Solution type:</b> Mitigation<br>To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.<br>To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled'<br>Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.<br>The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.<br>See the references for more information. |
| <b>Affected Software/OS</b><br>TCP implementations that implement RFC1323/RFC7323.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Vulnerability Insight</b><br>The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| ... continues on next page ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

...continued from previous page...

**Vulnerability Detection Method**

Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.

Details: TCP Timestamps Information Disclosure

OID:1.3.6.1.4.1.25623.1.0.80091

Version used: 2023-12-15T16:10:08Z

**References**

url: <https://datatracker.ietf.org/doc/html/rfc1323>

url: <https://datatracker.ietf.org/doc/html/rfc7323>

url: <https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152>

url: <https://www.fortiguard.com/psirt/FG-IR-16-090>

[\[ return to 104.26.6.57 \]](#)

## 2.3 172.67.74.79

Host scan start Tue Mar 10 02:41:28 2026 UTC

Host scan end Tue Mar 10 14:33:04 2026 UTC

| Service (Port)              | Threat Level |
|-----------------------------|--------------|
| <a href="#">general/tcp</a> | Low          |

### 2.3.1 Low general/tcp

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

**Summary**

The remote host implements TCP timestamps and therefore allows to compute the uptime.

**Quality of Detection (QoD):** 80%

**Vulnerability Detection Result**

It was detected that the host implements RFC1323/RFC7323.

The following timestamps were retrieved with a delay of 1 seconds in-between:

Packet 1: 3248818236

Packet 2: 3534401090

**Impact**

A side effect of this feature is that the uptime of the remote host can sometimes be computed.

... continues on next page ...

...continued from previous page...

**Solution:****Solution type:** Mitigation

To disable TCP timestamps on linux add the line 'net.ipv4.tcp\_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.

To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.

The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.

See the references for more information.

**Affected Software/OS**

TCP implementations that implement RFC1323/RFC7323.

**Vulnerability Insight**

The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

**Vulnerability Detection Method**

Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.

Details: TCP Timestamps Information Disclosure

OID:1.3.6.1.4.1.25623.1.0.80091

Version used: 2023-12-15T16:10:08Z

**References**

url: <https://datatracker.ietf.org/doc/html/rfc1323>

url: <https://datatracker.ietf.org/doc/html/rfc7323>

url: <https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152>

url: <https://www.fortiguard.com/psirt/FG-IR-16-090>

[\[ return to 172.67.74.79 \]](#)