

Scan Report

March 11, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “Care B (Critical)”. The scan started at Wed Mar 11 02:30:52 2026 UTC and ended at Wed Mar 11 05:21:37 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
2	Results per Host	2
2.1	192.168.40.12	2
2.1.1	Medium 443/tcp	2
2.1.2	Low general/tcp	8

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
192.168.40.12 care-b.brins.co.id	0	0	3	1	0	0
Total: 1	0	0	3	1	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 4 results selected by the filtering described above. Before filtering there were 30 results.

2 Results per Host

2.1 192.168.40.12

Host scan start Wed Mar 11 02:31:27 2026 UTC

Host scan end Wed Mar 11 05:21:31 2026 UTC

Service (Port)	Threat Level
443/tcp	Medium
general/tcp	Low

2.1.1 Medium 443/tcp

Medium (CVSS: 5.0)

NVT: Missing 'HttpOnly' Cookie Attribute (HTTP)

Summary

The remote HTTP web server / application is missing to set the 'HttpOnly' cookie attribute for one or more sent HTTP cookie.

Quality of Detection (QoD): 70%

... continues on next page ...

...continued from previous page ...
Vulnerability Detection Result The cookie(s): Set-Cookie: AspxAutoDetectCookieSupport=***replaced***; path=/ Set-Cookie: TS010b4306=***replaced***; Path=/; Domain=.care-b.brins.co.id Set-Cookie: TY5Kn=***replaced***; Path=/; Expires=Thu, 12 Mar 2026 02:43:35 GMT; ↪ Secure Set-Cookie: 9T7T51=***replaced***; Path=/; Expires=Thu, 12 Mar 2026 02:43:35 GMT ↪; Secure Set-Cookie: f7upk0=***replaced***; Path=/; Secure Set-Cookie: Xpijz7=***replaced***; Path=/; Secure is/are missing the "HttpOnly" cookie attribute.
Solution: Solution type: Mitigation - Set the 'HttpOnly' cookie attribute for any session cookie - Evaluate / do an own assessment of the security impact on the web server / application and create an override for this result if there is none (this can't be checked automatically by this VT)
Affected Software/OS Any web application with session handling in cookies.
Vulnerability Insight The flaw exists if a session cookie is not using the 'HttpOnly' cookie attribute. This allows a cookie to be accessed by JavaScript which could lead to session hijacking attacks.
Vulnerability Detection Method Checks all cookies sent by the remote HTTP web server / application for a missing 'HttpOnly' cookie attribute. Details: Missing 'HttpOnly' Cookie Attribute (HTTP) OID:1.3.6.1.4.1.25623.1.0.105925 Version used: 2024-01-12T16:12:12Z
References url: https://www.rfc-editor.org/rfc/rfc6265#section-5.2.6 url: https://owasp.org/www-community/HttpOnly url: https://wiki.owasp.org/index.php/Testing_for_cookies_attributes_(OTG-SESS-002)
Medium (CVSS: 5.0) NVT: Missing 'Secure' Cookie Attribute (HTTP)
Summary ... continues on next page ...

...continued from previous page ...
The remote HTTP web server / application is missing to set the 'Secure' cookie attribute for one or more sent HTTP cookie.
Quality of Detection (QoD): 70%
Vulnerability Detection Result The cookie(s): Set-Cookie: AspxAutoDetectCookieSupport=***replaced***; path=/ Set-Cookie: TS010b4306=***replaced***; Path=/; Domain=.care-b.brins.co.id is/are missing the "Secure" cookie attribute.
Solution: Solution type: Mitigation - Set the 'Secure' cookie attribute for any cookies that are sent over a SSL/TLS connection - Evaluate / do an own assessment of the security impact on the web server / application and create an override for this result if there is none (this can't be checked automatically by this VT)
Affected Software/OS Any web application accessible via a SSL/TLS connection (HTTPS) and at the same time also accessible over a cleartext connection (HTTP).
Vulnerability Insight The flaw exists if a cookie is not using the 'Secure' cookie attribute and is sent over a SSL/TLS connection. This allows a cookie to be passed to the server by the client over non-secure channels (HTTP) and subsequently allows an attacker to e.g. conduct session hijacking attacks.
Vulnerability Detection Method Checks all cookies sent by the remote HTTP web server / application over a SSL/TLS connection for a missing 'Secure' cookie attribute. Details: Missing 'Secure' Cookie Attribute (HTTP) OID:1.3.6.1.4.1.25623.1.0.902661 Version used: 2024-09-27T05:05:23Z
References url: https://www.rfc-editor.org/rfc/rfc6265#section-5.2.5 url: https://owasp.org/www-community/controls/SecureCookieAttribute url: https://wiki.owasp.org/index.php/Testing_for_cookies_attributes_(OTG-SESS-0↪02)
Medium (CVSS: 4.3)
NVT: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection
Product detection result
... continues on next page ...

...continued from previous page ...
cpe:/a:ietf:transport_layer_security:1.0 Detected by SSL/TLS: Version Detection (OID: 1.3.6.1.4.1.25623.1.0.105782)
Summary It was possible to detect the usage of the deprecated TLSv1.0 and/or TLSv1.1 protocol on this system.
Quality of Detection (QoD): 98%
Vulnerability Detection Result In addition to TLSv1.2+ the service is also providing the deprecated TLSv1.0 and ↔ TLSv1.1 protocols and supports one or more ciphers. Those supported ciphers c ↔an be found in the 'SSL/TLS: Report Supported Cipher Suites' (OID: 1.3.6.1.4.1 ↔.25623.1.0.802067) VT.
Impact An attacker might be able to use the known cryptographic flaws to eavesdrop the connection between clients and the service to get access to sensitive data transferred within the secured connection. Furthermore newly uncovered vulnerabilities in this protocols won't receive security updates anymore.
Solution: Solution type: Mitigation It is recommended to disable the deprecated TLSv1.0 and/or TLSv1.1 protocols in favor of the TLSv1.2+ protocols. Please see the references for more resources supporting you with this task.
Affected Software/OS - All services providing an encrypted communication using the TLSv1.0 and/or TLSv1.1 protocols - CVE-2023-41928: Kiloview P1 4G and P2 4G Video Encoder - CVE-2024-41270: Gorush v1.18.4 - CVE-2025-3200: Multiple products from Wiesemann & Theis
Vulnerability Insight The TLSv1.0 and TLSv1.1 protocols contain known cryptographic flaws like: - CVE-2011-3389: Browser Exploit Against SSL/TLS (BEAST) - CVE-2015-0204: Factoring Attack on RSA-EXPORT Keys Padding Oracle On Downgraded Legacy Encryption (FREAK)
Vulnerability Detection Method Checks the used TLS protocols of the services provided by this system. Details: SSL/TLS: Deprecated TLSv1.0 and TLSv1.1 Protocol Detection OID:1.3.6.1.4.1.25623.1.0.117274 Version used: 2025-04-30T05:39:51Z
... continues on next page ...

...continued from previous page ...

Product Detection Result

Product: cpe:/a:ietf:transport_layer_security:1.0

Method: SSL/TLS: Version Detection

OID: 1.3.6.1.4.1.25623.1.0.105782)

Referencesurl: <https://ssl-config.mozilla.org>

cve: CVE-2011-3389

cve: CVE-2015-0204

cve: CVE-2023-41928

cve: CVE-2024-41270

cve: CVE-2025-3200

url: <https://www.bsi.bund.de/SharedDocs/Downloads/EN/BSI/Publications/TechGuidelines/TG02102/BSI-TR-02102-1.html>url: https://www.bsi.bund.de/EN/Themen/Oeffentliche-Verwaltung/Mindeststandards/TLS-Protokoll/TLS-Protokoll_node.htmlurl: <https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Publikationen/TechnischeRichtlinien/TR03116/BSI-TR-03116-4.html>url: https://www.bsi.bund.de/SharedDocs/Downloads/DE/BSI/Mindeststandards/Mindeststandard_BSI_TLS_Version_2_4.htmlurl: <https://web.archive.org/web/20240113175943/https://www.bettercrypto.org>url: <https://www.enisa.europa.eu/publications/algorithms-key-size-and-parameters-report-2014>url: <https://datatracker.ietf.org/doc/rfc8996/>url: <https://vnhacker.blogspot.com/2011/09/beast.html>url: <https://web.archive.org/web/20201108095603/https://censys.io/blog/freak>url: <https://certvde.com/en/advisories/VDE-2025-031/>url: <https://gist.github.com/nyxfqq/cfae38fada582a0f576d154be1aeb1fc>url: <https://advisories.ncsc.nl/advisory?id=NCSC-2024-0273>

cert-bund: WID-SEC-2023-1435

cert-bund: CB-K18/0799

cert-bund: CB-K16/1289

cert-bund: CB-K16/1096

cert-bund: CB-K15/1751

cert-bund: CB-K15/1266

cert-bund: CB-K15/0850

cert-bund: CB-K15/0764

cert-bund: CB-K15/0720

cert-bund: CB-K15/0548

cert-bund: CB-K15/0526

cert-bund: CB-K15/0509

cert-bund: CB-K15/0493

cert-bund: CB-K15/0384

cert-bund: CB-K15/0365

cert-bund: CB-K15/0364

... continues on next page ...

...continued from previous page ...

cert-bund: CB-K15/0302
 cert-bund: CB-K15/0192
 cert-bund: CB-K15/0079
 cert-bund: CB-K15/0016
 cert-bund: CB-K14/1342
 cert-bund: CB-K14/0231
 cert-bund: CB-K13/0845
 cert-bund: CB-K13/0796
 cert-bund: CB-K13/0790
 dfn-cert: DFN-CERT-2020-0177
 dfn-cert: DFN-CERT-2020-0111
 dfn-cert: DFN-CERT-2019-0068
 dfn-cert: DFN-CERT-2018-1441
 dfn-cert: DFN-CERT-2018-1408
 dfn-cert: DFN-CERT-2016-1372
 dfn-cert: DFN-CERT-2016-1164
 dfn-cert: DFN-CERT-2016-0388
 dfn-cert: DFN-CERT-2015-1853
 dfn-cert: DFN-CERT-2015-1332
 dfn-cert: DFN-CERT-2015-0884
 dfn-cert: DFN-CERT-2015-0800
 dfn-cert: DFN-CERT-2015-0758
 dfn-cert: DFN-CERT-2015-0567
 dfn-cert: DFN-CERT-2015-0544
 dfn-cert: DFN-CERT-2015-0530
 dfn-cert: DFN-CERT-2015-0396
 dfn-cert: DFN-CERT-2015-0375
 dfn-cert: DFN-CERT-2015-0374
 dfn-cert: DFN-CERT-2015-0305
 dfn-cert: DFN-CERT-2015-0199
 dfn-cert: DFN-CERT-2015-0079
 dfn-cert: DFN-CERT-2015-0021
 dfn-cert: DFN-CERT-2014-1414
 dfn-cert: DFN-CERT-2013-1847
 dfn-cert: DFN-CERT-2013-1792
 dfn-cert: DFN-CERT-2012-1979
 dfn-cert: DFN-CERT-2012-1829
 dfn-cert: DFN-CERT-2012-1530
 dfn-cert: DFN-CERT-2012-1380
 dfn-cert: DFN-CERT-2012-1377
 dfn-cert: DFN-CERT-2012-1292
 dfn-cert: DFN-CERT-2012-1214
 dfn-cert: DFN-CERT-2012-1213
 dfn-cert: DFN-CERT-2012-1180
 dfn-cert: DFN-CERT-2012-1156
 dfn-cert: DFN-CERT-2012-1155
 dfn-cert: DFN-CERT-2012-1039

...continues on next page ...

...continued from previous page ...

```
dfn-cert: DFN-CERT-2012-0956
dfn-cert: DFN-CERT-2012-0908
dfn-cert: DFN-CERT-2012-0868
dfn-cert: DFN-CERT-2012-0867
dfn-cert: DFN-CERT-2012-0848
dfn-cert: DFN-CERT-2012-0838
dfn-cert: DFN-CERT-2012-0776
dfn-cert: DFN-CERT-2012-0722
dfn-cert: DFN-CERT-2012-0638
dfn-cert: DFN-CERT-2012-0627
dfn-cert: DFN-CERT-2012-0451
dfn-cert: DFN-CERT-2012-0418
dfn-cert: DFN-CERT-2012-0354
dfn-cert: DFN-CERT-2012-0234
dfn-cert: DFN-CERT-2012-0221
dfn-cert: DFN-CERT-2012-0177
dfn-cert: DFN-CERT-2012-0170
dfn-cert: DFN-CERT-2012-0146
dfn-cert: DFN-CERT-2012-0142
dfn-cert: DFN-CERT-2012-0126
dfn-cert: DFN-CERT-2012-0123
dfn-cert: DFN-CERT-2012-0095
dfn-cert: DFN-CERT-2012-0051
dfn-cert: DFN-CERT-2012-0047
dfn-cert: DFN-CERT-2012-0021
dfn-cert: DFN-CERT-2011-1953
dfn-cert: DFN-CERT-2011-1946
dfn-cert: DFN-CERT-2011-1844
dfn-cert: DFN-CERT-2011-1826
dfn-cert: DFN-CERT-2011-1774
dfn-cert: DFN-CERT-2011-1743
dfn-cert: DFN-CERT-2011-1738
dfn-cert: DFN-CERT-2011-1706
dfn-cert: DFN-CERT-2011-1628
dfn-cert: DFN-CERT-2011-1627
dfn-cert: DFN-CERT-2011-1619
dfn-cert: DFN-CERT-2011-1482
```

[\[return to 192.168.40.12 \]](#)

2.1.2 Low general/tcp

Low (CVSS: 2.6)
NVT: TCP Timestamps Information Disclosure
Summary The remote host implements TCP timestamps and therefore allows to compute the uptime.
Quality of Detection (QoD): 80%
Vulnerability Detection Result It was detected that the host implements RFC1323/RFC7323. The following timestamps were retrieved with a delay of 1 seconds in-between: Packet 1: 3672684683 Packet 2: 3672685727
Impact A side effect of this feature is that the uptime of the remote host can sometimes be computed.
Solution: Solution type: Mitigation To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime. To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.
Affected Software/OS TCP implementations that implement RFC1323/RFC7323.
Vulnerability Insight The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.
Vulnerability Detection Method Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP Timestamps Information Disclosure OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2023-12-15T16:10:08Z
References url: https://datatracker.ietf.org/doc/html/rfc1323 url: https://datatracker.ietf.org/doc/html/rfc7323 url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/d ... continues on next page ...

...continued from previous page ...

↪ownload/details.aspx?id=9152

url: <https://www.fortiguard.com/psirt/FG-IR-16-090>

[[return to 192.168.40.12](#)]

This file was automatically generated.