

Website Vulnerability Scanner Report

✓ <http://brins.co.id>

Summary

Overall risk level:

Medium

Risk ratings:

Critical:	0
High:	0
Medium:	2
Low:	4
Info:	1

Scan information:

Start time:	Sep 08, 2026 / 11:50:56 UTC+07
Finish time:	Sep 08, 2026 / 11:51:47 UTC+07
Scan duration:	51 sec
Tests performed:	40
Scan status:	Finished

Findings



Communication is not secure

CONFIRMED

port 80/tcp

URL	Response URL	Evidence
http://brins.co.id/	http://brins.co.id/	Communication is made over unsecure, unencrypted HTTP.

Details

Risk description:

The risk is that an attacker who manages to intercept the communication at the network level can read and modify the data transmitted (including passwords, secret tokens, credit card information and other sensitive data).

Recommendation:

We recommend you to reconfigure the web server to use HTTPS - which encrypts the communication between the web browser and the server.

Classification:

CWE : [CWE-319](#)

OWASP Top 10 - 2017 : [A3 - Sensitive Data Exposure](#)

OWASP Top 10 - 2021 : [A4 - Insecure Design](#)

OWASP Top 10 - 2025 : [A04 - Cryptographic Failures](#)



Passwords are submitted unencrypted over the network

CONFIRMED

port 80/tcp

URL	Evidence
-----	----------

http://brins.co.id/webAuth/	Password input detected over insecure HTTP. Login form: <pre><form method="post"> <div class="login_body"> <div class="login_head"> <dl> <dt class="user_ico"></dt> <dd>Provide your credentialbefore accessing the Internet.</dd> </dl> </div> <div class="login_operate"> <li class="username_li_press"> <label class="txt_default" for="une" default_txt="Username">Username</label> <input name="une" id="une" class="input focus" type="text"><input type="hidden" id="username" na me="username"> <li class="password"> <label class="txt_default" for="passwd" default_txt="Password">Password</label> <input name="pass_wd" id="passwd" class="input" value="" type="password"><input type="hidden" id ="pwd" name="pass_word"> </div> <div class="login_box_msg shiftKey" style="display: none;"> <dl> <dt></dt> <dd>Caps lock is on!</dd> </dl> </div> <div class="login_box_msg emptyName" style="display: none;"> <dl> <dt></dt> <dd>Username is required!</dd> </dl> </div> </div> </form></pre> ... (truncated) Request / Response
---	--

▼ Details

Risk description: The risk is that malicious actors could employ various techniques, such as packet sniffing or man-in-the-middle attacks, to capture plaintext passwords. Once intercepted, the attacker gains unauthorized access to user accounts, potentially leading to identity theft, unauthorized data access, or other malicious activities. The risk remains unchanged even if the password's form submission triggers a redirect response to an HTTPS page. Recommendation: We recommend you to reconfigure the web server so it uses HTTPS - which encrypts the communication between the web browser and the server. This way, the attacker will not be able to obtain the clear-text passwords, even though he manages to intercept the network communication. Classification: CWE : CWE-523 OWASP Top 10 - 2017 : A3 - Sensitive Data Exposure OWASP Top 10 - 2021 : A2 - Cryptographic Failures OWASP Top 10 - 2025 : A04 - Cryptographic Failures

 **Missing security header: Referrer-Policy**

port 80/tcp

CONFIRMED

URL	Evidence
-----	----------

http://brins.co.id/	Response headers do not include the Referrer-Policy HTTP security header as well as the <meta> tag with name 'referrer' is not present in the response. Request / Response
---	---

▼ Details

Risk description:

The risk is that if a user visits a web page (e.g. "http://example.com/pricing/") and clicks on a link from that page going to e.g. "https://www.google.com", the browser will send to Google the full originating URL in the **Referer** header, assuming the Referrer-Policy header is not set. The originating URL could be considered sensitive information and it could be used for user tracking.

Recommendation:

The Referrer-Policy header should be configured on the server side to avoid user tracking and inadvertent information leakage. The value **no-referrer** of this header instructs the browser to omit the Referer header entirely.

References:

https://developer.mozilla.org/en-US/docs/Web/Security/Referer_header:_privacy_and_security_concerns

Classification:

CWE : [CWE-693](#)

OWASP Top 10 - 2017 : [A6 - Security Misconfiguration](#)

OWASP Top 10 - 2021 : [A5 - Security Misconfiguration](#)

OWASP Top 10 - 2025 : [A02 - Security Misconfiguration](#)

🚩 Missing security header: Content-Security-Policy

CONFIRMED

port 80/tcp

URL	Evidence
http://brins.co.id/	Response does not include the HTTP Content-Security-Policy security header or meta tag Request / Response

▼ Details

Risk description:

The risk is that if the target application is vulnerable to XSS, lack of this header makes it easily exploitable by attackers.

Recommendation:

Configure the Content-Security-Header to be sent with each HTTP response in order to apply the specific policies needed by the application.

References:

https://cheatsheetseries.owasp.org/cheatsheets/Content_Security_Policy_Cheat_Sheet.html

<https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Content-Security-Policy>

Classification:

CWE : [CWE-1021](#)

OWASP Top 10 - 2017 : [A6 - Security Misconfiguration](#)

OWASP Top 10 - 2021 : [A5 - Security Misconfiguration](#)

OWASP Top 10 - 2025 : [A02 - Security Misconfiguration](#)

🚩 Missing security header: X-Content-Type-Options

CONFIRMED

port 80/tcp

URL	Evidence
http://brins.co.id/	Response headers do not include the X-Content-Type-Options HTTP security header Request / Response

▼ Details

Risk description:

The risk is that lack of this header could make possible attacks such as Cross-Site Scripting or phishing in Internet Explorer browsers.

Recommendation:

We recommend setting the X-Content-Type-Options header such as **X-Content-Type-Options: nosniff**.

References:

<https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Content-Type-Options>

Classification:

CWE : [CWE-693](#)

OWASP Top 10 - 2017 : [A6 - Security Misconfiguration](#)

OWASP Top 10 - 2021 : [A5 - Security Misconfiguration](#)

OWASP Top 10 - 2025 : [A02 - Security Misconfiguration](#)

Robots.txt file found

port 80/tcp

CONFIRMED

URL

<http://brins.co.id/robots.txt>

▼ Details

Risk description:

There is no particular security risk in having a robots.txt file. However, it's important to note that adding endpoints in it should not be considered a security measure, as this file can be directly accessed and read by anyone.

Recommendation:

We recommend you to manually review the entries from robots.txt and remove the ones which lead to sensitive locations in the website (ex. administration panels, configuration files, etc).

References:

<https://www.theregister.co.uk/2015/05/19/robotstxt/>

Classification:

OWASP Top 10 - 2017 : [A6 - Security Misconfiguration](#)

OWASP Top 10 - 2021 : [A5 - Security Misconfiguration](#)

OWASP Top 10 - 2025 : [A06 - Insecure Design](#)

Login Interface Found

port 80/tcp

CONFIRMED

URL

<http://brins.co.id/webAuth/>

Evidence

```
<input type="hidden" id="username" name="username">
<input name="pass_wd" id="passwd" class="input" value="" type="password">
<input name="btlogin" class="button" id="submit_btn" type="submit" onclick="javascript:return onApply(
);" value="Log In" tabindex="5">
```

[Request / Response](#)

▼ Details

Risk description:

The risk is that an attacker could use this interface to mount brute force attacks against known passwords and usernames combinations leaked throughout the web.

Recommendation:

Ensure each interface is not bypassable using common knowledge of the application or leaked credentials using occasional password audits.

References:

<https://pentest-tools.com/network-vulnerability-scanning/password-auditor>

<http://capec.mitre.org/data/definitions/16.html>

Classification:

CWE : [CWE-287](#)

OWASP Top 10 - 2025 : [A06 - Insecure Design](#)

Scan coverage information

List of tests performed (40)

Port 80

- ✓ Scanned for secure communication
- ✓ Scanned for passwords submitted unencrypted
- ✓ Scanned for missing HTTP header - Content Security Policy
- ✓ Scanned for missing HTTP header - Referrer
- ✓ Scanned for missing HTTP header - X-Content-Type-Options
- ✓ Scanned for robots.txt file
- ✓ Scanned for login interfaces
- ✓ Scanned for website technologies
- ✓ Scanned for version-based vulnerabilities of server-side software
- ✓ Scanned for client access policies
- ✓ Scanned for absence of the security.txt file
- ✓ Scanned for use of untrusted certificates
- ✓ Scanned for enabled HTTP debug methods
- ✓ Scanned for enabled HTTP OPTIONS method
- ✓ Scanned for directory listing
- ✓ Scanned for error messages
- ✓ Scanned for debug messages
- ✓ Scanned for code comments
- ✓ Scanned for missing HTTP header - Strict-Transport-Security
- ✓ Scanned for passwords submitted in URLs
- ✓ Scanned for domain too loose set for cookies
- ✓ Scanned for mixed content between HTTP and HTTPS
- ✓ Scanned for cross domain file inclusion
- ✓ Scanned for internal error code
- ✓ Scanned for HttpOnly flag of cookie
- ✓ Scanned for Secure flag of cookie
- ✓ Scanned for secure password submission
- ✓ Scanned for sensitive data
- ✓ Scanned for unsafe HTTP header Content Security Policy
- ✓ Scanned for OpenAPI files
- ✓ Scanned for file upload
- ✓ Scanned for SQL statement in request parameter
- ✓ Scanned for password returned in later response
- ✓ Scanned for Path Disclosure
- ✓ Scanned for Session Token in URL
- ✓ Scanned for API endpoints
- ✓ Scanned for emails
- ✓ Scanned for missing HTTP header - Rate Limit
- ✓ Scanned for PEM-encoded private key material
- ✓ Scanned for partial PEM-encoded private key material

Scan parameters

target:	http://brins.co.id
scan_type:	Light
authentication:	False

Scan stats

Unique Injection Points Detected:	16
URLs spidered:	4
Total number of HTTP requests:	15
Average time until a response was received:	242ms
Total number of HTTP request errors:	2