

Network Vulnerability Scanner Report

✓ 192.168.40.122

Summary

Overall risk level:

Medium

Risk ratings:

Critical:	0
High:	0
Medium:	1
Low:	0
Info:	9

Scan information:

Start time:	Jul 07, 2026 / 16:29:16 UTC+07
Finish time:	Jul 07, 2026 / 19:09:40 UTC+07
Scan duration:	2 hrs, 40 min, 24 sec
Tests performed:	26
VPN Profile:	Scan Internal
Scan status:	Finished

Findings

🚩 SMB Signing Not Required

port 445/tcp

CONFIRMED

We managed to detect a SMB Signing Not Required, using the following Request / Response chain.

▼ Details

Vulnerability description:

The SMB server accepts connections without requiring SMB packet signing, as indicated by the protocol metadata reporting signing as not required. This affects SMB protocol implementations that advertise SigningRequired=false during session negotiation and can include SMBv2 and later stacks when misconfigured. An unauthenticated remote attacker with network access between client and server can modify or replay SMB traffic, and may perform man-in-the-middle or relay attacks against clients and services that do not enforce signing. No local privileges on the target are required for an attacker who can intercept or manipulate network traffic to exploit this weakness.

Risk description:

An attacker able to intercept or manipulate network traffic can tamper with SMB sessions, capture or alter credentials, perform NTLM relay attacks, and gain unauthorized access to resources, leading to data exposure and lateral movement. The likelihood of exploitation is moderate to high in environments where clients and servers communicate over untrusted or flat networks without additional protections.

Recommendation:

Require and enforce SMB signing on servers and clients by enabling packet signing in the operating system or file server configuration (for example via Group Policy for Windows) and apply vendor guidance; additionally restrict SMB access to trusted networks and disable legacy SMB versions where possible.

References:

<https://www.tenable.com/plugins/nessus/57608>
<https://nmap.org/nsedoc/scripts/smb2-security-mode.html>

🚩 Open ports discovery

CONFIRMED

Port	State	Service	Product	Product Version
80	open	http	Microsoft IIS httpd	10.0
135	open	msrpc	Microsoft Windows RPC	-
139	open	netbios-ssn	Microsoft Windows netbios-ssn	-
445	open	microsoft-ds	-	-
1433	open	ms-sql-s	Microsoft SQL Server 2019	15.00.2000
2107	open	msrpc	Microsoft Windows RPC	-

3389	open	ms-wbt-server	Microsoft Terminal Services	-
5022	open	mice	-	-
5357	open	http	Microsoft HTTPAPI httpd	2.0
5985	open	http	Microsoft HTTPAPI httpd	2.0
9182	open	unknown	-	-

[▼ Details](#)

Risk description:

This is the list of ports that have been found on the target host. Having unnecessary open ports may expose the target to more risks because those network services and applications may contain vulnerabilities.

Recommendation:

We recommend reviewing the list of open ports and closing the ones which are not necessary for business purposes.

Microsoft SQL(mssql)

port 1433/tcp

CONFIRMED

We managed to detect a Microsoft SQL(mssql), using the following Request / Response chain.

[▼ Details](#)

Vulnerability description:

Microsoft SQL Server instances that accept TCP connections on the default port (1433) are identifiable by responding to the Tabular Data Stream (TDS) protocol handshake and prelogin messages. The detection indicates an accessible MSSQL service but does not itself imply a specific software flaw or CVE. An exposed MSSQL endpoint typically accepts authentication attempts and may reveal version or instance metadata during initial protocol exchange. Network reachability and an open port are the primary prerequisites for this discovery.

Risk description:

An exposed MSSQL service increases the risk of unauthorized access attempts, credential brute force, and enumeration of database instance details that aid attackers in planning further exploits. If credentials are compromised or the server runs unpatched vulnerable components, an attacker could achieve data theft, privilege escalation, or lateral movement within the network.

Recommendation:

Restrict network access to database ports using firewalls or network ACLs and place database servers on isolated management networks; if the service is not required, disable or remove it. Ensure strong authentication, enable encryption for connections, and keep SQL Server patched to the latest supported updates.

SMB Version

port 445/tcp

CONFIRMED

We managed to detect a SMB Version, using the following Request / Response chain.

We extracted the following information from the target: **SMB 2.1**

[▼ Details](#)

Vulnerability description:

This finding identifies the Server Message Block (SMB) protocol version in use on a target system by querying the SMB service typically accessible on TCP port 445. The detection relies on the SMB negotiation phase where the server advertises its protocol version string and capabilities, allowing an enumerator to extract the Version.VerString value. The discovery applies to hosts running SMB services (Windows, Samba, embedded devices, or honeypots) that respond to standard SMB negotiation and information queries. No exploitation is performed; the outcome is an informational disclosure of protocol version and features.

Risk description:

Exposed SMB version information enables attackers to determine whether a target supports legacy, insecure SMB variants (for example SMBv1) or unpatched implementations, increasing the likelihood of targeted exploitation using known vulnerabilities. Information disclosure of protocol version is low-impact by itself but materially raises attack efficiency and prioritization for lateral movement, ransomware, or remote code execution attempts.

Recommendation:

Restrict SMB access to trusted networks and management hosts, disable legacy SMB protocol versions where possible, and apply vendor security updates and configuration hardening to SMB services. Regularly audit exposed services and block TCP port 445 at network boundaries unless explicitly required.

SMB2 Server Time

port 445/tcp

CONFIRMED

We managed to detect a SMB2 Server Time, using the following Request / Response chain.

We extracted the following information from the target: **SystemTime: 2026-07-07T12:09:10.000Z ServerStartTime: 2009-04-22T19:24:48.000Z**

[▼ Details](#)

Vulnerability description:

Certain SMB2 servers disclose their current system time and server start time during the SMB negotiation phase. The server returns fields such as SystemTime and ServerStartTime over an unauthenticated connection to the SMB service (typically TCP/445). An attacker able to connect to the SMB endpoint can retrieve these timestamps remotely without credentials. This behavior is present in SMB2 implementations that expose negotiation metadata and requires only network access to the listening SMB port.

Risk description:

Information disclosure of system and uptime timestamps can aid an attacker in fingerprinting hosts, correlating events, planning timed attacks, or narrowing windows for exploitation and lateral movement. The likelihood of remote retrieval is high whenever the SMB service is reachable and permits unauthenticated negotiation, though the direct impact is low compared with code-execution flaws.

Recommendation:

Restrict access to SMB services from untrusted networks using firewalls or network segmentation and disable public exposure of TCP/445. Where possible enforce authentication and apply vendor-recommended configurations and updates to reduce unnecessary information leakage.

References:

<https://nmap.org/nsedoc/scripts/smb2-time.html>

🚩 smb2-capabilities - Enumeration

port 445/tcp

CONFIRMED

We managed to detect a smb2-capabilities - Enumeration, using the following Request / Response chain.

We extracted the following information from the target: ["DFSSupport", "LargeMTU", "Leasing"]

[▼ Details](#)

Vulnerability description:

SMBv2/SMBv3 implementations expose a Capabilities field in the protocol negotiation response that enumerates supported features and dialect-specific behaviors. An unauthenticated remote actor can query the SMB negotiate/connection response over TCP port 445 to obtain a list of enabled capabilities for each supported dialect. The information reveals protocol features such as multi-channel, leasing, persistent handles, encryption support, and other extensions implemented by the server. An exposed capabilities list enables accurate fingerprinting of the SMB implementation and its supported feature set.

Risk description:

Disclosure of SMB capabilities does not directly grant access, but significantly reduces attacker uncertainty by revealing supported features and protocol behaviors, which can guide exploitation or chaining of other SMB vulnerabilities. Because the vector requires only network access to the SMB service, the likelihood of reconnaissance and targeted follow-up attacks is moderate to high in exposed environments.

Recommendation:

Restrict access to SMB services by blocking or filtering TCP/445 at network boundaries and applying network segmentation; disable unused SMB dialects and features on servers where feasible and keep SMB implementations updated with vendor fixes. Monitor and log SMB negotiation activity to detect suspicious scanning or fingerprinting attempts.

References:

<https://nmap.org/nsedoc/scripts/smb2-capabilities.html>

🚩 SMB - Enumeration

port 445/tcp

CONFIRMED

We managed to detect a SMB - Enumeration, using the following Request / Response chain.

We extracted the following information from the target: **ForestName:** , **OSVersion:** 10.0.17763, **NetBIOSComputerName:** MW-BA_ASMIK01, **NetBIOSDomainName:** MW-BA_ASMIK01, **DNSComputerName:** MW-BA_ASMIK01, **DNSComputerName:** MW-BA_ASMIK01

[▼ Details](#)

Vulnerability description:

The SMB service exposes machine and domain metadata through unauthenticated SMB protocol calls (SMBv2 metadata enumeration) when the SMB port (TCP/445) is reachable. An attacker who can connect to the SMB endpoint can query fields such as OS version, NetBIOS and DNS computer names, domain names, and forest name. This information disclosure occurs without exploiting a software flaw; it relies on the SMB implementation permitting anonymous or unauthenticated metadata responses. The issue affects systems that expose SMB services to untrusted networks or allow anonymous/guest enumeration regardless of vendor or product version.

Risk description:

Exposed SMB metadata enables reconnaissance that significantly reduces attacker effort for targeted attacks, credential harvesting, and lateral movement inside a network. The severity is medium to high in environments where SMB is reachable from untrusted networks or where additional weak controls (guest access, missing firewall rules) exist, and exploitation likelihood is high whenever TCP/445 is exposed.

Recommendation:

Restrict remote access to SMB by blocking or filtering TCP/445 at network boundaries and apply network segmentation to isolate file-sharing hosts. Require authenticated access for SMB, disable anonymous/guest enumeration where possible, and monitor SMB traffic and authentication attempts for suspicious activity.

References:

<https://nmap.org/nsedoc/scripts/smb-security-mode.html>

SMB - Enum Domains

CONFIRMED

port 445/tcp

We managed to detect a SMB - Enum Domains, using the following Request / Response chain.

We extracted the following information from the target: **DomainName: MW-BA_ASMIK01**

[Details](#)

Vulnerability description:

SMB domain enumeration occurs when an SMBv2-capable server responds to unauthenticated metadata queries (over TCP/445) that disclose domain-related information such as DNS domain name and domain membership. Systems running SMB services that implement the metadata listing functions will return domain identifiers and related configuration details when queried. An attacker or automated scanner can invoke these SMB calls without credentials as long as the SMB port is reachable. The information disclosure requires network-level access to the SMB service but does not require authentication to perform basic enumeration.

Risk description:

Exposed domain and membership details provide actionable reconnaissance that attackers can use to map network topology, identify authentication targets, and plan lateral movement or social engineering campaigns. Because SMB is commonly reachable on internal networks and often reachable from poorly segmented hosts, the likelihood of successful enumeration is moderate to high when port 445 is accessible. While the issue itself is informational, it meaningfully increases the attack surface and can accelerate follow-on compromises.

Recommendation:

Block or restrict inbound SMB (TCP/445) to trusted hosts only using firewall rules and network segmentation, and disable SMB services on systems that do not require them. Require authentication for SMB interactions where possible, apply least-privilege access controls, and monitor/log SMB access attempts to detect and respond to unauthorized enumeration.

References:

<https://nmap.org/nsedoc/scripts/smb-enum-domains.html>

SMB Operating System

CONFIRMED

port 445/tcp

We managed to detect a SMB Operating System, using the following Request / Response chain.

We extracted the following information from the target: **Windows Server 2019, Version 1809**

[Details](#)

Vulnerability description:

The SMB service (typically TCP port 445) discloses operating system information through its SMB protocol metadata (SMBv1/SMBv2 responses). When an unauthenticated SMB connection is established, the server may return an OSVersion field that reveals specific Windows build and edition strings. This behavior affects hosts running SMB services across a wide range of Windows releases and any device implementing SMB that returns version metadata. The attack vector requires network connectivity to the SMB service (reachable port 445) but does not require valid credentials, making remote fingerprinting possible.

Risk description:

Exposing exact OS and build information enables attackers to precisely identify exploitable systems and tailor follow-on attacks, increasing the likelihood of successful exploitation. The severity is informational for disclosure itself but materially raises risk by reducing attacker reconnaissance effort and facilitating targeted exploitation of known vulnerabilities.

Recommendation:

Limit exposure of SMB services to untrusted networks by blocking or filtering TCP/445 at network boundaries and using network segmentation; disable legacy SMB versions when not required and ensure hosts are patched to current supported releases.

References:

<https://nmap.org/nsedoc/scripts/smb-os-discovery.html>

OS Detection

UNCONFIRMED 

Operating System	Accuracy
Microsoft Windows Server 2012 R2	88%

[Details](#)

Vulnerability description:

Scan coverage information

List of tests performed (26)

Port 80

✓ Scanned for version-based vulnerabilities

Port 135

✓ Scanned for version-based vulnerabilities

Port 139

✓ Scanned for version-based vulnerabilities

✓ Scanned for vulnerabilities using Sniper modules

Sniper modules

Microsoft EternalBlue - Remote Code Execution (MS17-010 - CVE-2017-0144)

SMB - Anonymous Access

SMB - Anonymous Write Access

Port 445

✓ Checked for "SMB Signing Not Required"

✓ Checked for "SMB - Enum Domains"

✓ Checked for "SMB - Enumeration"

✓ Checked for "SMB Operating System"

✓ Checked for "SMB Version"

✓ Checked for "SMB2 Server Time"

✓ Checked for "smb2-capabilities - Enumeration"

✓ Scanned for version-based vulnerabilities

✓ Scanned for vulnerabilities using Sniper modules

Sniper modules

Microsoft EternalBlue - Remote Code Execution (MS17-010 - CVE-2017-0144)

SMB - Anonymous Access

SMB - Anonymous Write Access

Port 1433

✓ Checked for "Microsoft SQL(mssql)"

✓ Scanned for version-based vulnerabilities

Port 2107

✓ Scanned for version-based vulnerabilities

Port 3389

✓ Scanned for version-based vulnerabilities

✓ Scanned for vulnerabilities using Sniper modules

Sniper modules

Bluekeep - Remote Code Execution (CVE-2019-0708)

Port 5022

✓ Scanned for version-based vulnerabilities

Port 5357

✓ Scanned for version-based vulnerabilities

Port 5985

✓ Scanned for version-based vulnerabilities

Port 9182

✓ Scanned for version-based vulnerabilities

Generic tests

- ✔ Performed OS detection
- ✔ Performed port discovery
- ✔ Performed version-based engine detections
- ✔ Performed Nuclei engine detections

Scan parameters

Target:	192.168.40.122
Preset:	Deep
Scanning engines:	Version_based, Sniper, Nuclei
Check alive:	True
Extensive modules:	False
Protocol type:	TCP
Ports to scan:	Top 5000 ports
CVEs:	
Requests per second:	-