

# Biglsim04's puzzle — Reverse Engineering Write-up


Challenge link: <https://crackmes.one/crackme/691de1d12d267f28f69b7f16>

Author: Biglsim04

Write-up by: SenorGPT

Tools used: CFF Explorer, Detect It Easy (DIE), x64dbg

Platform	Difficulty	Quality	Arch	Language
Windows	2.5	3.5	x86-64	C/C++



Status: WIP

Goal: Document a clean path from initial recon → locating key-check logic → validation/reversal strategy



# 1. Executive Summary

This document captures my reverse-engineering process for the crackme `puzzle` by `Biglsim04`. The target appears to be a simple command line process that prompts the user for a password.

I successfully:

- Performed basic static reconnaissance.
  - Surveyed imports. Confirmed there appears to be anti-debugging measures.
  - Tried to locate strings associated with success & failure dialogs.
  - Added breakpoints on functions that may be used for anti-debugging and begun to trace logic.
- 


## 2. Target Overview

### 2.1 UI / Behaviour

- Inputs: *Enter password:*
- Outputs: *Access Denied*, *Access Accepted* (assumption based on wrong answer string).

### 2.2 Screens

#### 2.2.1 Start-up




```
C:\Users\david\Desktop\crack>
Hello World!
Enter password:
```

A screenshot of a Windows terminal window. The title bar shows the file path 'C:\Users\david\Desktop\crack'. The terminal content displays 'Hello World!' followed by 'Enter password:' on the next line. The cursor is positioned at the end of the second line.

### 2.2.2 Failure case

Followed by exit on next key input.



```
C:\Users\david\Desktop\crack>
Hello World!
Enter password: helloworld
Access Denied!
|
```

A screenshot of a Windows terminal window, similar to the one above. The title bar shows the file path 'C:\Users\david\Desktop\crack'. The terminal content displays 'Hello World!' followed by 'Enter password: helloworld' on the next line. The third line shows 'Access Denied!'. A vertical bar '|' is visible on the fourth line, indicating the cursor position.

## 3. Tooling & Environment

- OS: *Windows 11*
- Debugger: *x64dbg*
- Static tools: *CFF Explorer*, *Detect It Easy (DIE)*

## 4. Static Recon

### 4.1 File & Headers

There appears to be no obvious signs of packing or obfuscation. The classic boring set of sections `.text`, `.rdata`, `.data`, `.reloc` represent a very typical layout for an unprotected Visual Studio type Portable Executable (*PE*).

The sizes also seem reasonable for a small console application.

puzzle.exe									
Name	Virtual Size	Virtual Address	Raw Size	Raw Address	Reloc Address	Linenumbers	Relocations N...	Linenumbers ...	Characteristics
Byte[8]	Dword	Dword	Dword	Dword	Dword	Dword	Word	Word	Dword
.text	00020000	00001000	0001FE00	00000400	00000000	00000000	0000	0000	60000020
.rdata	0000F000	00021000	0000EC00	00020200	00000000	00000000	0000	0000	40000040
.data	00008000	00030000	00001400	0002EE00	00000000	00000000	0000	0000	C0000040
.reloc	00000934	00038000	00000A00	00030200	00000000	00000000	0000	0000	42000040

Packed binaries often show one or more of these red flags:

- **Weird section names:**  
`.UPX0`, `.UPX1`, `.aspack`, `.petite`, or just random gibberish.
- **Very few sections:**  
Sometimes just one or two suspicious ones.
- **Abnormal size balance:**  
A tiny `.text` with a huge other section holding compressed payload.

It is *IMPORTANT* to note that headers alone can not confirm if the *PE* has been packed or obfuscated as the packer/obfuscator used might utilize normal looking section names, keep a standard layout, and/or hide the real tell in entropy or runtime behaviour.

## 4.2 Entropy

Entropy is a measure of how *random-looking* the bytes are in a section.

- Low entropy = looks like normal code/data (more patterns, more repetition).
- High entropy = looks compressed or encrypted (more random).


Why this matters:

- Packed or encrypted payloads often have high entropy.
- Normal `.text` code usually has moderate entropy.

Rule of thumb (quick reference, not 100%):

- ~6.0–7.2 = often normalish
- ~7.4–8.0 = suspicious for compression/encryption

Unfortunately, *CFF Explorer* does not have an entropy viewer so I switch to *DIE*.



The top blue bar shows *DIE*'s overall heuristic guess based mostly on entropy patterns and layout. This is not necessarily proof, but a strong hint that this is not classically packed.

The table shows each row as a region - header + each *PE* section - with an entropy score.

Section Name	Entropy Score	Note
PE Header	2.51659	Low entropy is normal for headers.
.text	6.44770	normal looking code entropy. If this was packed or encrypted the value would be closer to ~7.5–8.0.
.rdata	4.66111	Normal for constants/strings/tables.
.data	2.64577	Very normal (initialized globals).
.reloc	5.29263	Also not unusual.

Nothing here also seems to scream that this *PE* is packed.

Finally, the graph represents a rolling entropy line across the file from start to end. The long flatish area around ~6 matches the `.text` region.

The later dips and spikes reflect transitions into `.rdata`, `.data`, `.reloc`.

Again, if this *PE* was packed the graph would have a big chunk of the line hovering around ~7.4-8.

## 4.3 Build & Toolchain Information

Screenshot summary provided by *DIE*

PE64		
Operation system: Windows(Vista)[AMD64, 64-bit, Console]	S	?
Linker: Microsoft Linker(14.36.34123)	S	?
Compiler: Microsoft Visual C/C++ (19.36.34123)[LTCG/C]	S	?
Language: C	S	?
Tool: Visual Studio(2022, v17.6)	S	?

**Operation system: Windows(Vista)AMD64, 64-bit, Console**

The binary is a *64-bit Windows console app*. The *Vista* part usually reflects the *minimum subsystem version* or tool heuristics and *NOT* that it only runs on Vista.

**Linker: Microsoft Linker (14.36.34123)**

The exact *MSVC linker version* used to produce the EXE.

**Compiler: Microsoft Visual C/C++ (19.36.34123) [LTCG/C]**

Identifies the *Visual C++ compiler version*.

**LTCG** = *Link-Time Code Generation* (whole-program optimization). The `/C` part is just the tool's way of labelling the language/compile family.

**Language: C**

*DIE*'s best guess for source language. In practice, this likely means *C* or *C++* with a C-like signature.

**Tool: Visual Studio(2022, v17.6)**

Maps those version numbers to the likely *IDE/toolchain family* that was used to build the EXE.



## 4.4 Imports / Exports

Since it is a simple console application, the only import *SEEMS* to be `KERNEL32.dll`.

OFTs	FTs (IAT)	Hint	Name
Qword	Qword	Word	szAnsi
000000000002F3E0	000000000002F3E0	0337	GetTickCount64
000000000002F3F2	000000000002F3F2	0336	GetTickCount
000000000002FA0E	000000000002FA0E	0657	WriteConsoleW
000000000002F410	000000000002F410	047B	QueryPerformanceCounter
000000000002F42A	000000000002F42A	023C	GetCurrentProcessId
000000000002F440	000000000002F440	0240	GetCurrentThreadId
000000000002F456	000000000002F456	0314	GetSystemTimeAsFileTime
000000000002F470	000000000002F470	0394	InitializeListHead
000000000002F486	000000000002F486	0501	RtlCaptureContext
000000000002F49A	000000000002F49A	0509	RtlLookupFunctionEntry
000000000002F4B4	000000000002F4B4	0510	RtlVirtualUnwind
000000000002F4C8	000000000002F4C8	03AA	IsDebuggerPresent
000000000002F4DC	000000000002F4DC	05F3	UnhandledExceptionFilter
000000000002F4F8	000000000002F4F8	05B0	SetUnhandledExceptionFilter
000000000002F516	000000000002F516	02FB	GetStartupInfoW
000000000002F528	000000000002F528	03B2	IsProcessorFeaturePresent
000000000002F544	000000000002F544	029F	GetModuleHandleW
000000000002F558	000000000002F558	0151	EnterCriticalSection
000000000002F570	000000000002F570	03EA	LeaveCriticalSection
000000000002F588	000000000002F588	0391	InitializeCriticalSectionEx
000000000002F5A6	000000000002F5A6	012B	DeleteCriticalSection
000000000002F5BE	000000000002F5BE	014D	EncodePointer
000000000002F5CE	000000000002F5CE	0124	DecodePointer
000000000002F5DE	000000000002F5DE	041D	MultiByteToWideChar
000000000002F5F4	000000000002F5F4	0644	WideCharToMultiByte
000000000002F60A	000000000002F60A	03DD	LCMapStringEx
000000000002F61A	000000000002F61A	0302	GetStringTypeW
000000000002F62C	000000000002F62C	01E4	GetCPInfo
000000000002F638	000000000002F638	050F	RtlUnwindEx
000000000002F646	000000000002F646	050B	RtlPcToFileHeader

000000000002F852	000000000002F852	01CD	FreeEnvironmentStringsW
000000000002F86C	000000000002F86C	0552	SetEnvironmentVariableW
000000000002F886	000000000002F886	058B	SetStdHandle
000000000002F896	000000000002F896	028B	GetLocaleInfoW
000000000002F8A8	000000000002F8A8	03BA	IsValidLocale
000000000002F8B8	000000000002F8B8	0343	GetUserDefaultLCID
000000000002F8CE	000000000002F8CE	0175	EnumSystemLocalesW
000000000002F8E4	000000000002F8E4	01BC	FlsAlloc
000000000002F8F0	000000000002F8F0	01BE	FlsGetValue
000000000002F8FE	000000000002F8FE	01C0	FlsSetValue
000000000002F90C	000000000002F90C	01BD	FlsFree
000000000002F916	000000000002F916	0612	VirtualProtect
000000000002F928	000000000002F928	00B2	CompareStringW
000000000002F93A	000000000002F93A	03DE	LCMapStringW
000000000002F94A	000000000002F94A	02DE	GetProcessHeap
000000000002F95C	000000000002F95C	009C	CloseHandle
000000000002F96A	000000000002F96A	01C2	FlushFileBuffers
000000000002F97E	000000000002F97E	0223	GetConsoleOutputCP
000000000002F994	000000000002F994	021F	GetConsoleMode
000000000002F9A6	000000000002F9A6	04A3	ReadFile
000000000002F9B2	000000000002F9B2	0272	GetFileSizeEx
000000000002F9C2	000000000002F9C2	0561	SetFilePointerEx
000000000002F9D6	000000000002F9D6	04A0	ReadConsoleW
000000000002F9E6	000000000002F9E6	037D	HeapReAlloc
000000000002F9F4	000000000002F9F4	037F	HeapSize
000000000002FA00	000000000002FA00	00E2	CreateFileW
000000000002FA1E	000000000002FA1E	050E	RtlUnwind

OFTs	FTs (IAT)	Hint	Name
Qword	Qword	Word	szAnsi
000000000002F65A	000000000002F65A	0492	RaiseException
000000000002F66C	000000000002F66C	0287	GetLastError
000000000002F67C	000000000002F67C	0570	SetLastError
000000000002F68C	000000000002F68C	0390	InitializeCriticalSectionAndSpinCou...
000000000002F6B4	000000000002F6B4	05E2	TlsAlloc
000000000002F6C0	000000000002F6C0	05E4	TlsGetValue
000000000002F6CE	000000000002F6CE	05E6	TlsSetValue
000000000002F6DC	000000000002F6DC	05E3	TlsFree
000000000002F6E6	000000000002F6E6	01CE	FreeLibrary
000000000002F6F4	000000000002F6F4	02D7	GetProcAddress
000000000002F706	000000000002F706	03F0	LoadLibraryExW
000000000002F718	000000000002F718	023B	GetCurrentProcess
000000000002F72C	000000000002F72C	05D0	TerminateProcess
000000000002F740	000000000002F740	02FD	GetStdHandle
000000000002F750	000000000002F750	0658	WriteFile
000000000002F75C	000000000002F75C	029B	GetModuleFileNameW
000000000002F772	000000000002F772	0180	ExitProcess
000000000002F780	000000000002F780	029E	GetModuleHandleExW
000000000002F796	000000000002F796	01F9	GetCommandLineA
000000000002F7A8	000000000002F7A8	01FA	GetCommandLineW
000000000002F7BA	000000000002F7BA	037A	HeapFree
000000000002F7C6	000000000002F7C6	0274	GetFileType
000000000002F7D4	000000000002F7D4	0376	HeapAlloc
000000000002F7E0	000000000002F7E0	0197	FindClose
000000000002F7EC	000000000002F7EC	019D	FindFirstFileExW
000000000002F800	000000000002F800	01AE	FindNextFileW
000000000002F810	000000000002F810	03B8	IsValidCodePage
000000000002F822	000000000002F822	01D5	GetACP
000000000002F82C	000000000002F82C	02C0	GetOEMCP
000000000002F838	000000000002F838	025C	GetEnvironmentStringsW

### 4.4.1 KERNEL32.dll

Off the bat I notice at least one *VERY* interesting function that is commonly used as a direct check for anti-debugging, `IsDebuggerPresent`.

Other functions that caught my eye are the timing functions;

`QueryPerformanceCounter`, `GetTickCount`, `GetTickCount64`, `GetSystemTimeAsFileTime`. These aren't necessarily indicative of anything, but *could* be used to support debugger detection logic by performing timing checks.

`GetCurrentProcessId`, `GetStartupInfoW`, and `GetCurrentThreadId` *could* also be used as anti-debug logic to check for certain flags or conditions on the program itself.

`LoadLibraryExW`, `GetProcAddress` and `FreeLibrary` *could* be used to hide libraries/modules by dynamic resolution.

`GetLastError`, `SetLastError`, `RaiseException`, `UnhandledExceptionFilter`, and `SetUnhandledExceptionFilter` *could* all be used in exception based anti-debugging measures.

`IsProcessorFeaturePresent` is also interesting as it *could* be used for certain anti-debug exception tricks.

`VirtualProtect` is often used for unpacking, self-modifying code, patching stubs, and flipping page protections around anti-debug regions.

Some additional functions that are not in the import table from `KERNEL32.dll` that might be worth adding breakpoints to are; `CheckRemoteDebuggerPresent`, `OutputDebugStringA/W`, `NtQueryInformationProcess`

Furthermore, adding breakpoints on `NTDLL.DLL` functions that are used for anti-debug logic just in case; `NtQueryInformationProcess`, `NtSetInformationThread`, and `RtlAddVectoredExceptionHandler` / `RtlRemoveVectoredExceptionHandler`.

---

## 5. Dynamic Analysis

### 5.1 String-Driven Entry

Starting the program in *x64dbg* to see if any immediate anti-debug code triggers yields nothing, yet...

As always, my first point of attack is a string-driven entry. Searching for string references in *x64dbg* yields the following results:

(Specifically looking for strings that I observed during **start-up** and **failure case**;

**Hello World!**, **Enter password:**, and **Access Denied!**)

Address	Disassembly	String Address	String
00007FF621CA1354	lea rax,qword ptr ds:[7FF621CCB560]	00007FF621CCB560	"Unknown exception"
00007FF621CA1484	lea rcx,qword ptr ds:[7FF621CCB590]	00007FF621CCB590	"bad array new length"
00007FF621CA16EC	lea r9,qword ptr ds:[7FF621CCB5A0]	00007FF621CCB5A0	": "
00007FF621CA1980	lea rax,qword ptr ds:[7FF621CCB5A8]	00007FF621CCB5A8	"iostream"
00007FF621CA19C0	movups xmm0,xmmword ptr ds:[7FF621CCB638]	00007FF621CCB638	"iostream stream error"
00007FF621CA1A06	mov ecx,qword ptr ds:[7FF621CCB648]	00007FF621CCB648	"error"
00007FF621CA1A70	lea rax,qword ptr ds:[7FF621CCB5B8]	00007FF621CCB5B8	"bad cast"
00007FF621CA1B93	lea rcx,qword ptr ds:[7FF621CCB5C8]	00007FF621CCB5C8	"bad locale name"
00007FF621CA2B56	lea rbx,qword ptr ds:[7FF621CCB5E0]	00007FF621CCB5E0	"ios_base::badbit set"
00007FF621CA2B62	lea rbx,qword ptr ds:[7FF621CCB5F8]	00007FF621CCB5F8	"ios_base::failbit set"
00007FF621CA2B69	lea rax,qword ptr ds:[7FF621CCB610]	00007FF621CCB610	"ios_base::eofbit set"
00007FF621CA2C53	lea rbx,qword ptr ds:[7FF621CCB5E0]	00007FF621CCB5E0	"ios_base::badbit set"
00007FF621CA2C5E	lea rbx,qword ptr ds:[7FF621CCB5F8]	00007FF621CCB5F8	"ios_base::failbit set"
00007FF621CA2C65	lea rax,qword ptr ds:[7FF621CCB610]	00007FF621CCB610	"ios_base::eofbit set"
00007FF621CA2DA7	lea rbx,qword ptr ds:[7FF621CCB5E0]	00007FF621CCB5E0	"ios_base::badbit set"
00007FF621CA2DB2	lea rbx,qword ptr ds:[7FF621CCB5F8]	00007FF621CCB5F8	"ios_base::failbit set"
00007FF621CA2DB9	lea rax,qword ptr ds:[7FF621CCB610]	00007FF621CCB610	"ios_base::eofbit set"
00007FF621CA2F90	lea rbx,qword ptr ds:[7FF621CCB5E0]	00007FF621CCB5E0	"ios_base::badbit set"
00007FF621CA2F9C	lea rbx,qword ptr ds:[7FF621CCB5F8]	00007FF621CCB5F8	"ios_base::failbit set"
00007FF621CA2FA3	lea rax,qword ptr ds:[7FF621CCB610]	00007FF621CCB610	"ios_base::eofbit set"
00007FF621CA3265	lea rcx,qword ptr ds:[7FF621CCB5C8]	00007FF621CCB5C8	"bad locale name"
00007FF621CA329	lea rbx,qword ptr ds:[7FF621CCB5E0]	00007FF621CCB5E0	"ios_base::badbit set"
00007FF621CA3354	lea rbx,qword ptr ds:[7FF621CCB5F8]	00007FF621CCB5F8	"ios_base::failbit set"
00007FF621CA3358	lea rax,qword ptr ds:[7FF621CCB610]	00007FF621CCB610	"ios_base::eofbit set"
00007FF621CA33B4	lea rcx,qword ptr ds:[7FF621CCB628]	00007FF621CCB628	"vector too long"
00007FF621CA33C4	lea rax,qword ptr ds:[7FF621CC1460]	00007FF621CC1460	"bad allocation"
00007FF621CA3A99	lea rbx,qword ptr ds:[7FF621CCB5E0]	00007FF621CCB5E0	"ios_base::badbit set"
00007FF621CA3B8C	lea rbx,qword ptr ds:[7FF621CCB5F8]	00007FF621CCB5F8	"ios_base::failbit set"
00007FF621CA5893	lea rax,qword ptr ds:[7FF621CCB610]	00007FF621CCB610	"ios_base::eofbit set"
00007FF621CA5A38	lea rbx,qword ptr ds:[7FF621CCB5E0]	00007FF621CCB5E0	"ios_base::badbit set"
00007FF621CA5A43	lea rbx,qword ptr ds:[7FF621CCB5F8]	00007FF621CCB5F8	"ios_base::failbit set"
00007FF621CA5A4A	lea rax,qword ptr ds:[7FF621CCB610]	00007FF621CCB610	"ios_base::eofbit set"
00007FF621CA6C58	lea rcx,qword ptr ds:[7FF621CC17E8]	00007FF621CC17E8	"invalid random_device value"
00007FF621CA6C77	lea rdx,qword ptr ds:[7FF621CC1FA0]	00007FF621CC1FA0	"success"
00007FF621CA6C83	lea rax,qword ptr ds:[7FF621CC2658]	00007FF621CC2658	"unknown error"
00007FF621CA6B85	lea rax,qword ptr ds:[7FF621CC3778]	00007FF621CC3778	"bad exception"
00007FF621CA8BA5	lea rdx,qword ptr ds:[7FF621CC3838]	00007FF621CC3838	L"api-ms-"
00007FF621CA8C59	lea r9,qword ptr ds:[7FF621CC3850]	00007FF621CC3850	"FisAlloc"
00007FF621CA8C69	lea rdx,qword ptr ds:[7FF621CC3850]	00007FF621CC3850	"FisAlloc"
00007FF621CA8CA0	lea r9,qword ptr ds:[7FF621CC3868]	00007FF621CC3868	"FisFree"
00007FF621CA8CB3	lea rdx,qword ptr ds:[7FF621CC3868]	00007FF621CC3868	"FisFree"
00007FF621CA8CB8	lea r9,qword ptr ds:[7FF621CC3878]	00007FF621CC3878	"FisGetValue"
00007FF621CA8CFB	lea rdx,qword ptr ds:[7FF621CC3878]	00007FF621CC3878	"FisGetValue"
00007FF621CA8D35	lea r9,qword ptr ds:[7FF621CC3890]	00007FF621CC3890	"FisSetValue"
00007FF621CA8D3E	lea rdx,qword ptr ds:[7FF621CC3890]	00007FF621CC3890	"FisSetValue"
00007FF621CA8D8E	lea r9,qword ptr ds:[7FF621CC38A8]	00007FF621CC38A8	"InitializeCriticalSectionEx"
00007FF621CA8DA1	lea rdx,qword ptr ds:[7FF621CC38A8]	00007FF621CC38A8	"InitializeCriticalSectionEx"
00007FF621CA8CA37	lea rbx,qword ptr ds:[7FF621CD1A70]	00007FF621CD1A70	"C:\\Users\\david\\Desktop\\crackmes.one\\BigIsim04 - puzzle\\binary\\puzzle.exe"
00007FF621CA8CA4E	mov r11,qword ptr ds:[7FF621CD1B00]	00007FF621CD1B00	&"C:\\Users\\david\\Desktop\\crackmes.one\\BigIsim04 - puzzle\\binary\\puzzle.exe\\\""
00007FF621CA8CA55	mov qword ptr ds:[7FF621CD1B80],rbx	00007FF621CD1B80	&"C:\\Users\\david\\Desktop\\crackmes.one\\BigIsim04 - puzzle\\binary\\puzzle.exe"
00007FF621CAD1CC	lea rdx,qword ptr ds:[7FF621CC3A20]	00007FF621CC3A20	L"mscoree.dll"
00007FF621CAD1E4	lea rdx,qword ptr ds:[7FF621CC3A38]	00007FF621CC3A38	"CoExitProcess"
00007FF621CAD2DA	mov qword ptr ds:[7FF621CD1B00],rax	00007FF621CD1B00	&"C:\\Users\\david\\Desktop\\crackmes.one\\BigIsim04 - puzzle\\binary\\puzzle.exe\\\""
00007FF621CAD2E7	mov qword ptr ds:[7FF621CD1B08],rax	00007FF621CD1B08	&"C:\\Users\\david\\Desktop\\crackmes.one\\BigIsim04 - puzzle\\binary\\puzzle.exe\\\""
00007FF621CAD867	lea rdx,qword ptr ds:[7FF621CC3C00]	00007FF621CC3C00	L" "
00007FF621CADFD9	mov r9,qword ptr ds:[7FF621CC3AE8]	00007FF621CC3AE8	&"LC_COLLATE"
00007FF621CAE002	lea rbp,qword ptr ds:[7FF621CC3AE8]	00007FF621CC3AE8	&"LC_COLLATE"
00007FF621CAE07E	lea rax,qword ptr ds:[7FF621CC3B48]	00007FF621CC3B48	&"LC_TIME"
00007FF621CAE1E2	lea rdx,qword ptr ds:[7FF621CC3BE0]	00007FF621CC3BE0	L"= "
00007FF621CAE21C	lea r15,qword ptr ds:[7FF621CC3AE8]	00007FF621CC3AE8	&"LC_COLLATE"
00007FF621CAE24E	lea rax,qword ptr ds:[7FF621CC3B48]	00007FF621CC3B48	&"LC_TIME"
00007FF621CAE786	lea rdx,qword ptr ds:[7FF621CC3BF0]	00007FF621CC3BF0	L"= "
00007FF621CB4914	mov rax,qword ptr ds:[7FF621CC4D58]	00007FF621CC4D58	&"zh-TW"
00007FF621CB491D	mov rax,qword ptr ds:[7FF621CC4D50]	00007FF621CC4D50	&"ko-KR"
00007FF621CB4926	mov rax,qword ptr ds:[7FF621CC4D48]	00007FF621CC4D48	&"zh-CN"
00007FF621CB492F	mov rax,qword ptr ds:[7FF621CC4D40]	00007FF621CC4D40	&"ja-JP"
00007FF621CB49FC	mov rbx,qword ptr ds:[7FF621CC4D58]	00007FF621CC4D58	&"zh-TW"
00007FF621CB4A05	mov rbx,qword ptr ds:[7FF621CC4D50]	00007FF621CC4D50	&"ko-KR"
00007FF621CB4A0E	mov rbx,qword ptr ds:[7FF621CC4D48]	00007FF621CC4D48	&"zh-CN"
00007FF621CB4A17	mov rbx,qword ptr ds:[7FF621CC4D40]	00007FF621CC4D40	&"ja-JP"
00007FF621CB6385	lea rbx,qword ptr ds:[7FF621CC46C0]	00007FF621CC46C0	&"Sun"
00007FF621CB6395	lea rax,qword ptr ds:[7FF621CC46C0]	00007FF621CC46C0	&"Sun"
00007FF621CB6397	lea rax,qword ptr ds:[7FF621CC46C0]	00007FF621CC46C0	&"Sun"
00007FF621CB63A5	lea rax,qword ptr ds:[7FF621CC46C0]	00007FF621CC46C0	&"Sun"
00007FF621CB63A6	lea rdx,qword ptr ds:[7FF621CC46C0]	00007FF621CC46C0	L"Sun"

00007FF621C8715D	lea rdx,qword ptr ds:[7FF621CC5D58]	00007FF621CC5D58	L"ACP"
00007FF621C87160	lea rdx,qword ptr ds:[7FF621CC5D48]	00007FF621CC5D48	L"utf8"
00007FF621C87180	lea rdx,qword ptr ds:[7FF621CC5D60]	00007FF621CC5D60	L"utf-8"
00007FF621C87193	lea rdx,qword ptr ds:[7FF621CC5D70]	00007FF621CC5D70	L"oCP"
00007FF621C8736B	lea rcx,qword ptr ds:[7FF621CC51C0]	00007FF621CC51C0	&L"america"
00007FF621C873A4	lea rcx,qword ptr ds:[7FF621CC4DA0]	00007FF621CC4DA0	&L"american"
00007FF621C87511	lea r8,qword ptr ds:[7FF621CC5D48]	00007FF621CC5D48	L"utf8"
00007FF621C87B8D	lea rdx,qword ptr ds:[7FF621CC5D58]	00007FF621CC5D58	L"ACP"
00007FF621C87B9D	lea rdx,qword ptr ds:[7FF621CC5D70]	00007FF621CC5D70	L"oCP"
00007FF621C87DD7	lea rcx,qword ptr ds:[7FF621CC51C0]	00007FF621CC51C0	&L"america"
00007FF621C87E3A	lea rcx,qword ptr ds:[7FF621CC4DA0]	00007FF621CC4DA0	&L"american"
00007FF621C88069	lea r9,qword ptr ds:[7FF621CC6398]	00007FF621CC6398	"CompareStringEx"
00007FF621C8807C	lea rdx,qword ptr ds:[7FF621CC6398]	00007FF621CC6398	"CompareStringEx"
00007FF621C88118	lea rdx,qword ptr ds:[7FF621CC3838]	00007FF621CC3838	L"api-ms-"
00007FF621C8812E	lea rdx,qword ptr ds:[7FF621CC6368]	00007FF621CC6368	L"ext-ms-"
00007FF621C88257	lea r9,qword ptr ds:[7FF621CC64C8]	00007FF621CC64C8	"AppPolicyGetProcessTerminationMethod"
00007FF621C88265	lea rdx,qword ptr ds:[7FF621CC64C8]	00007FF621CC64C8	"AppPolicyGetProcessTerminationMethod"
00007FF621C882BE	lea rdx,qword ptr ds:[7FF621CC6380]	00007FF621CC6380	"ArefileApisANSI"
00007FF621C883D6	lea r9,qword ptr ds:[7FF621CC6380]	00007FF621CC6380	"EnumSystemLocalesEx"
00007FF621C883E4	lea rdx,qword ptr ds:[7FF621CC6380]	00007FF621CC6380	"EnumSystemLocalesEx"
00007FF621C884A9	lea r9,qword ptr ds:[7FF621CC6400]	00007FF621CC6400	"GetLocaleInfoEx"
00007FF621C884B7	lea rdx,qword ptr ds:[7FF621CC6400]	00007FF621CC6400	"GetLocaleInfoEx"
00007FF621C8852D	lea r9,qword ptr ds:[7FF621CC6430]	00007FF621CC6430	"GetUserDefaultLocaleName"
00007FF621C8853B	lea rdx,qword ptr ds:[7FF621CC6430]	00007FF621CC6430	"GetUserDefaultLocaleName"
00007FF621C8859F	lea r9,qword ptr ds:[7FF621CC6458]	00007FF621CC6458	"IsValidLocaleName"
00007FF621C885AD	lea rdx,qword ptr ds:[7FF621CC6458]	00007FF621CC6458	"IsValidLocaleName"
00007FF621C8861D	lea r9,qword ptr ds:[7FF621CC6490]	00007FF621CC6490	"LCIDToLocaleName"
00007FF621C8862B	lea rdx,qword ptr ds:[7FF621CC6490]	00007FF621CC6490	"LCIDToLocaleName"
00007FF621C886A5	lea r9,qword ptr ds:[7FF621CC6478]	00007FF621CC6478	"LCMapStringEx"
00007FF621C886B3	lea rdx,qword ptr ds:[7FF621CC6478]	00007FF621CC6478	"LCMapStringEx"
00007FF621C88789	lea r9,qword ptr ds:[7FF621CC6480]	00007FF621CC6480	"LocaleNameToLCID"
00007FF621C88797	lea rdx,qword ptr ds:[7FF621CC6480]	00007FF621CC6480	"LocaleNameToLCID"
00007FF621C887ED	lea r9,qword ptr ds:[7FF621CC64F8]	00007FF621CC64F8	"SystemFunction036"
00007FF621C887FB	lea rdx,qword ptr ds:[7FF621CC64F8]	00007FF621CC64F8	"SystemFunction036"
00007FF621C88860	lea rdx,qword ptr ds:[7FF621CC6380]	00007FF621CC6380	"ArefileApisANSI"
00007FF621C8887D	lea r9,qword ptr ds:[7FF621CC6380]	00007FF621CC6380	"EnumSystemLocalesEx"
00007FF621C8888B	lea rdx,qword ptr ds:[7FF621CC6380]	00007FF621CC6380	"EnumSystemLocalesEx"
00007FF621C888A6	lea r9,qword ptr ds:[7FF621CC63E8]	00007FF621CC63E8	"GetDateFormatEx"
00007FF621C888B4	lea rdx,qword ptr ds:[7FF621CC63E8]	00007FF621CC63E8	"GetDateFormatEx"
00007FF621C888CF	lea r9,qword ptr ds:[7FF621CC6400]	00007FF621CC6400	"GetLocaleInfoEx"
00007FF621C888DD	lea rdx,qword ptr ds:[7FF621CC6400]	00007FF621CC6400	"GetLocaleInfoEx"
00007FF621C888F8	lea r9,qword ptr ds:[7FF621CC6418]	00007FF621CC6418	"GetTimeFormatEx"
00007FF621C88906	lea rdx,qword ptr ds:[7FF621CC6418]	00007FF621CC6418	"GetTimeFormatEx"
00007FF621C88921	lea r9,qword ptr ds:[7FF621CC6430]	00007FF621CC6430	"GetUserDefaultLocaleName"
00007FF621C8892F	lea rdx,qword ptr ds:[7FF621CC6430]	00007FF621CC6430	"GetUserDefaultLocaleName"
00007FF621C8894A	lea r9,qword ptr ds:[7FF621CC6458]	00007FF621CC6458	"IsValidLocaleName"
00007FF621C88958	lea rdx,qword ptr ds:[7FF621CC6458]	00007FF621CC6458	"IsValidLocaleName"
00007FF621C88973	lea r9,qword ptr ds:[7FF621CC6478]	00007FF621CC6478	"LCMapStringEx"
00007FF621C88981	lea rdx,qword ptr ds:[7FF621CC6478]	00007FF621CC6478	"LCMapStringEx"
00007FF621C8899C	lea r9,qword ptr ds:[7FF621CC6490]	00007FF621CC6490	"LCIDToLocaleName"
00007FF621C889AA	lea rdx,qword ptr ds:[7FF621CC6490]	00007FF621CC6490	"LCIDToLocaleName"
00007FF621C889C5	lea r9,qword ptr ds:[7FF621CC6480]	00007FF621CC6480	"LocaleNameToLCID"
00007FF621C889D3	lea rdx,qword ptr ds:[7FF621CC6480]	00007FF621CC6480	"LocaleNameToLCID"
00007FF621C88A32	lea r9,qword ptr ds:[7FF621CC63D0]	00007FF621CC63D0	"FlsGetValue2"
00007FF621C88A40	lea rdx,qword ptr ds:[7FF621CC63D0]	00007FF621CC63D0	"FlsGetValue2"
00007FF621C8BD248	lea rax,qword ptr ds:[7FF621CD0C30]	00007FF621CD0C30	&L"PST"
00007FF621C8BD256	lea rax,qword ptr ds:[7FF621CD0C40]	00007FF621CD0C40	&L"PST"
00007FF621C8BED42	lea rcx,qword ptr ds:[7FF621CC9848]	00007FF621CC9848	L"CONOUT\$"
00007FF621C8BEDF1	lea rcx,qword ptr ds:[7FF621CC9848]	00007FF621CC9848	L"CONOUT\$"
00007FF621CC101A	or ch,byte ptr ds:[7FF621CC901C]	00007FF621CC901C	L"-gr"
00007FF621CC104A	or ebp,dword ptr ds:[7FF621CC904C]	00007FF621CC904C	L"-ca"
00007FF621CC107A	or ebp,dword ptr ds:[7FF621CC907C]	00007FF621CC907C	L"-ie"
00007FF621CC108A	or ebp,dword ptr ds:[7FF621CC908C]	00007FF621CC908C	L"-tt"
00007FF621CC112A	or ebp,dword ptr ds:[7FF621CC912C]	00007FF621CC912C	L"-co"
00007FF621CC113A	or ebp,dword ptr ds:[7FF621CC913C]	00007FF621CC913C	L"-cr"
00007FF621CC114A	or ch,byte ptr ds:[7FF621CC914C]	00007FF621CC914C	L"-do"
00007FF621CC115A	or ebp,dword ptr ds:[7FF621CC915C]	00007FF621CC915C	L"-ec"
00007FF621CC11FA	or ebp,dword ptr ds:[7FF621CC91FC]	00007FF621CC91FC	L"-sv"
00007FF621CC121A	or ebp,dword ptr ds:[7FF621CC921C]	00007FF621CC921C	L"-ve"
00007FF621CC123A	or ebp,dword ptr ds:[7FF621CC923C]	00007FF621CC923C	L"-es"

That's a lot of references! Utilizing the search functionality at the bottom of the **References** tab will help make searching for the desired string references a breeze.

Search:  [Click here to filter results...](#) Page

Nada! Well that's a first for me, never before have I had it where there are zero string references found. Something new is always interesting!

Time to switch to a breakpoint approach.

## 5.2 Break-it down-point Time

### 5.2.1 Anti-Debugging Breakpoints

Before I start adding breakpoints trying to trace any flag related logic, I first want to see where and how some of the functions for anti-debugging measures are being used.

Function	Reason for Interest
<code>IsDebuggerPresent</code>	The simplest direct debugger check; breaking here often shows the exact branch that decides the <i>good vs bad</i> branch paths.
<code>SetUnhandledExceptionFilter</code>	Programs use this to install custom crash/exception handling; it's commonly part of exception-based anti-debug tricks.
<code>UnhandledExceptionFilter</code>	Often hit when the program deliberately triggers an exception; breaking here helps you see whether the exception flow is being used as a debugger test.
<code>RaiseException</code>	A strong indicator of intentional exception-based detection; it usually marks the start of an anti-debug probe.
<code>QueryPerformanceCounter</code>	Used for high-resolution timing checks; stepping/breakpoints can cause delays that the program detects.
<code>GetTickCount</code> , <code>GetTickCount64</code>	Lower-resolution timing checks; still commonly used to detect "debugger slowdowns" around sensitive code blocks.

Function	Reason for Interest
<code>VirtualProtect</code>	Frequently used for unpacking or self-modifying anti-debug stubs; breaking here can lead you to the real code being revealed or patched in memory.
<code>GetProcAddress</code>	Shows when the binary dynamically resolves hidden anti-debug APIs (often from <code>ntdll</code> ); the requested function name is a big giveaway.
<code>LoadLibraryExW</code>	Often paired with <code>GetProcAddress</code> to pull in <code>ntdll</code> / <code>user32</code> at runtime; breaking here can expose the moment advanced anti-debug tooling gets loaded.

For those that are following along, here is an `x64dbg` command to add all these breakpoints:

```
bp kernel32.IsDebuggerPresent; bp kernel32.SetUnhandledExceptionFilter; bp  
kernel32.UnhandledExceptionFilter; bp kernel32.RaiseException; bp  
kernel32.QueryPerformanceCounter; bp kernel32.GetTickCount; bp  
kernel32.GetTickCount64; bp kernel32.VirtualProtect; bp  
kernel32.GetProcAddress; bp kernel32.LoadLibraryExW
```

See [Anti-Debugging Breakpoints](#) for a more detailed breakpoint breakdown and logic tracing.

### 5.2.2 Input Breakpoints

After, I decide to start with breakpoints that might be used for obtaining the user input from the console;



Function	Reason for Interest
<code>ReadConsoleA/W</code>	Catches direct keyboard input from the console, can see exactly where the program reads the name/serial and what buffer it lands in.
<code>WriteConsoleA/W</code>	Hits when the program prints prompts or messages; stepping right after often leads straight into the input and validation flow.
<code>ReadFile</code>	Many console apps read STDIN via a handle as if it were a file, so this is a reliable fallback when <code>ReadConsoleA/W</code> isn't used.
<code>WriteFile</code>	Console output is sometimes routed through file-style writes, so it helps catch prompts and trace the execution path around user interaction.
<code>GetStdHandle</code>	Usually called right before <code>ReadConsoleA/W</code> / <code>ReadFile</code> or output calls, so it's a great "early warning" breakpoint for the I/O path.
<code>GetCommandLineA/W</code>	Useful when input is passed as command-line args; you can see raw input early before it gets parsed or transformed. Doesn't seem necessary for this CTF as it doesn't appear to use command line arguments, although it does not hurt to add it.
<code>GetProcAddress</code>	Reveals dynamically resolved APIs (often hidden checks or CRT - C Runtime - calls); the requested function name can instantly expose the program's real strategy.

For those that are following along, here is an *x64dbg* command to add all these breakpoints:

```
bp kernel32.ReadConsoleW; bp kernel32.ReadConsoleA; bp kernel32.WriteConsoleW; bp
kernel32.WriteConsoleA; bp kernel32.ReadFile; bp kernel32.WriteFile; bp
kernel32.GetStdHandle; bp kernel32.GetCommandLineA; bp kernel32.GetCommandLineW;
bp kernel32.GetProcAddress
```

See [Input Breakpoints](#) for a more detailed breakpoint breakdown and logic tracing.

## 6. Dynamic Analysis - Tracing Breakpoints and Stepping Over Logic

See [Windows x64 Calling Convention](#) for a quick refresher on Windows x64 calling convention.

### 6.1 Anti-Debugging Breakpoints

With the new breakpoints added, I resume program execution from the entry breakpoint.

Address	Module/Label/Exception	State	Disassembly	Hits
00007FFDA1B72800	<kernel32.dll.GetTickCount64>	Enabled	mov ecx,dword ptr ds:[7FFE0004]	1
00007FFDA1B78600	<kernel32.dll.GetTickCount>	Disabled	mov ecx,7FFE0320	27
00007FFDA1B83FB0	<kernel32.dll.QueryPerformanceCounter>	Enabled	jmp qword ptr ds:[<QueryPerformanceCounter>]	0
00007FFDA1B93C70	<kernel32.dll.GetProcAddress>	Enabled	mov r8,qword ptr ss:[rsp]	17
00007FFDA1B982B0	<kernel32.dll.VirtualProtect>	Enabled	jmp qword ptr ds:[<VirtualProtect>]	27
00007FFDA1B9B110	<kernel32.dll.RaiseException>	Enabled	jmp qword ptr ds:[<RaiseException>]	0
00007FFDA1B9C600	<kernel32.dll.LoadLibraryExW>	Enabled	jmp qword ptr ds:[<LoadLibraryExW>]	9
00007FFDA1B9D9A0	<kernel32.dll.IsDebuggerPresent>	Enabled	jmp qword ptr ds:[<IsDebuggerPresent>]	0
00007FFDA1BA3600	<kernel32.dll.SetUnhandledExceptionFilter>	Enabled	jmp qword ptr ds:[<SetUnhandledExceptionFilter>]	1
00007FFDA1BBE600	<kernel32.dll.UnhandledExceptionFilter>	Enabled	jmp qword ptr ds:[<UnhandledExceptionFilter>]	0

I disabled the `GetTickCount` breakpoint as it was getting triggered on each frame, instead replacing it with a breakpoint in the caller that I hope will bring me closer to the flag comparison logic.

There seems to be more going on than a simple console checker. `GetProcAddress` (x17) + `LoadLibraryExW` (x9) on start-up shows that the binary is *OR* might-be keeping the static import table small/boring and resolving lots of APIs at runtime.

I also noticed that `IsDebuggerPresent` breakpoint never gets triggered, even upon input validation.



## 6.1.1 kernel32.dll.LoadLibraryExW

See [LoadLibraryExW Function Definition](#) for function definition details.

Switching over to the *Call Stack* tab I can see that it is being directly called by the *PE*. This means that the target binary is the one actually making the call to `LoadLibraryExW` and not some other module/code.

Address	To	From	Size	Party	Comment
000000B6B374F908 000000B6B374F910	00007FF621CAB88B 0000000000000000	00007FFC2D0BC600 00007FF621CAB88B	8	User User	kernel32.LoadLibraryExW puzzle.00007FF621CAB88B

Continuing the execution into `KERNEL32.DLL.LoadLibraryExW` I see that the following registers have the values:

- **Call #1** - Most likely *normal OS dependency resolution* with a *safe flag* restricting search to *System32*.

Register	Value	Note
RCX	00007FF685B937E0	L"api-ms-win-core-synch-l1-2-0"
RDX	0000000000000000	
R8	0000000000000800	<code>LOAD_LIBRARY_SEARCH_SYSTEM32</code> = 0x00000800

- **Call #2** - Most likely *normal OS dependency resolution* with a *safe flag* restricting search to *System32*.

Register	Value	Note
RCX	00007FF685B937A0	L"api-ms-win-core-fibers-l1-1-1"
RDX	0000000000000000	
R8	0000000000000800	<code>LOAD_LIBRARY_SEARCH_SYSTEM32</code> = 0x00000800

- **Call #3** - Most likely *normal OS dependency resolution* with a *safe flag*

restricting search to *System32*.

Register	Value	Note
RCX	00007FF685B95E90	L"api-ms-win-core-fibers-l1-1-2"
RDX	0000000000000000	
R8	0000000000000800	LOAD_LIBRARY_SEARCH_SYSTEM32 = 0x00000800

- **Call #4** - Most likely *normal OS dependency resolution* with a *safe flag* restricting search to *System32*.

Register	Value	Note
RCX	00007FF685B95F80	L"api-ms-win-core-localization-l1-2-1"
RDX	0000000000000000	
R8	0000000000000800	LOAD_LIBRARY_SEARCH_SYSTEM32 = 0x00000800

- **Call #5** - Likely normal runtime/loader behaviour.

Register	Value	Note
RCX	00007FF685B93820	L"kernel32"
RDX	0000000000000000	
R8	0000000000000800	LOAD_LIBRARY_SEARCH_SYSTEM32 = 0x00000800

- **Call #6** - Most likely *normal OS dependency resolution* with a *safe flag* restricting search to *System32*.

Register	Value	Note
RCX	00007FF685B96080	L"api-ms-win-core-string-l1-1-0"

Register	Value	Note
RDX	0000000000000000	
R8	0000000000000800	LOAD_LIBRARY_SEARCH_SYSTEM32 = 0x00000800

- **Call #7** - Most likely *normal OS dependency resolution* with a *safe flag* restricting search to *System32*.

Register	Value	Note
RCX	00007FF685B95E50	L"api-ms-win-core-datetime-l1-1-1"
RDX	0000000000000000	
R8	0000000000000800	LOAD_LIBRARY_SEARCH_SYSTEM32 = 0x00000800

- **Call #8** - Most likely *normal OS dependency resolution* with a *safe flag* restricting search to *System32*.

Register	Value	Note
RCX	00007FF685B95FD0	L"api-ms-win-core-localization-obsolete-l1-2-0"
RDX	0000000000000000	
R8	0000000000000800	LOAD_LIBRARY_SEARCH_SYSTEM32 = 0x00000800

- **Call #9** - Most likely *normal OS dependency resolution* with a *safe flag* restricting search to *System32*.

Register	Value	Note
RCX	00007FF685B961D0	L"api-ms-win-security-systemfunctions-l1-1-0"

Register	Value	Note
RDX	0000000000000000	
R8	0000000000000800	LOAD_LIBRARY_SEARCH_SYSTEM32 = 0x00000800

The binary consistently restricts DLL search to System32 during early initialization which aligns with modern safe-loading practices and reduces the likelihood of DLL search-order hijacking. The `api-ms-win-*` entries reflect Windows API-set indirection. Their presence here is typical for modern MSVC builds and does not by itself indicate obfuscation. None of the observed `LoadLibraryExW` function calls directly load `ntdll.dll` or other modules - `user32.dll`, `dbghelp.dll` - commonly associated with advanced anti-debug checks. The initial loads appear consistent with baseline OS/runtime dependencies.

### 6.1.2 kernel32.dll.SetUnhandledExceptionFilter

See [SetUnhandledExceptionFilter Function Definition](#) for function definition details.

Return value is `NULL` (00000000), indicating no prior top-level exception filter was registered before this call. Nothing interesting happening here, so I continue on to the next breakpoint.

### 6.1.3 kernerl32.dll.GetTickCount64

See [GetTickCount64 Function Definition](#) for function definition details.

Since `GetTickCount64` is only called once I decide to investigate what it's being used for. Upon hitting the breakpoint, I hit Debug - Execute till return (CTRL + F9) and get to the caller. Alternatively, using the *Call Stack* would bring me to the same location by clicking on the frame underneath the `GetTickCount64` frame.

My first guess without diving too deep into this function is that it might be generating some kind of value from the system time. This value could then be used as an encoding seed of sorts (*just a guess*).

00007FF685B71080	48:83EC 28	sub rsp,28
00007FF685B71084	0F31	rdtsc
00007FF685B71086	48:C1E2 20	shl rdx,20
00007FF685B7108A	48:08C2	or rax,rdx
00007FF685B7108D	48:894424 38	mov qword ptr ss:[rsp+38],rax
00007FF685B71092	FF15 68FF0100	call qword ptr ds:[<GetTickCount64> ]
00007FF685B71098	48:894424 40	mov qword ptr ss:[rsp+40],rax
00007FF685B7109D	48:8D4424 38	lea rax,qword ptr ss:[rsp+38]
00007FF685B710A2	48:894424 30	mov qword ptr ss:[rsp+30],rax
00007FF685B710A7	48:884424 40	mov rax,qword ptr ss:[rsp+40]
00007FF685B710AC	4C:884424 30	mov r8,qword ptr ss:[rsp+30]
00007FF685B710B1	48:884424 30	mov rax,qword ptr ss:[rsp+30]
00007FF685B710B6	48:8B5424 38	mov rdx,qword ptr ss:[rsp+38]
00007FF685B710BB	0FB6C8	movzx ecx,al
00007FF685B710BE	6BC1 3B	imul eax,ecx,3B
00007FF685B710C1	B9 A7000000	mov ecx,A7
00007FF685B710C6	49:C1E8 07	shr r8,7
00007FF685B710CA	41:32D0	xor dl,r8b
00007FF685B710CD	32D0	xor dl,al
00007FF685B710CF	0FB6C2	movzx eax,dl
00007FF685B710D2	0F45C8	cmovne ecx,eax
00007FF685B710D5	884C24 30	mov byte ptr ss:[rsp+30],cl
00007FF685B710D9	0FB64424 30	movzx eax,byte ptr ss:[rsp+30]
00007FF685B710DE	8805 80210300	mov byte ptr ds:[7FF685BA3264 ],al
00007FF685B710E4	C64424 30 00	mov byte ptr ss:[rsp+30],0
00007FF685B710E9	48:83C4 28	add rsp,28
00007FF685B710ED	C3	ret

An interesting instruction I notice is `rdtsc` which reads the CPU's *Time Stamp Counter (TSC)*. The return is a *64-bit number* that usually increases constantly whilst the system runs. After the instruction, `EAX` holds the *low 32-bits* and `EDX` holds the *high 32-bits*. These are then usually combined by an `or` instruction.

rdtsc	read time stamp counter
shl rdx,20	shift high 32-bits into upper half of RDX
or rax,rdx	combine low and high bits into 64-bit TSC value in RAX

It also appears to be doing some kind of encoding and transformation based off the return values from `rdtsc` and `GetTickCount64`.

After spending some time decoding each instruction it does indeed seem like it creates some kind of seed value and stores it within a global.

<pre> sub rsp,28 rdtsc shl rdx,20 or rax,rdx mov qword ptr ss:[rsp+38],rax call qword ptr ds:[&lt;GetTickCount64&gt; ] mov qword ptr ss:[rsp+40],rax lea rax,qword ptr ss:[rsp+38] mov qword ptr ss:[rsp+30],rax mov rax,qword ptr ss:[rsp+40] mov r8,qword ptr ss:[rsp+30] mov rax,qword ptr ss:[rsp+30] mov rdx,qword ptr ss:[rsp+38] movzx ecx,al imul eax,ecx,3B mov ecx,A7 shr r8,7 xor dl,r8b xor dl,al movzx eax,dl cmovne ecx,eax mov byte ptr ss:[rsp+30],cl movzx eax,byte ptr ss:[rsp+30] mov byte ptr ds:[7FF685BA3264],al mov byte ptr ss:[rsp+30],0 add rsp,28 ret </pre>	<pre> Seeding function based on system time? read time stamp counter shift high 32-bits into upper half of RDX combine low and high bits into 64-bit TSC value in RAX save TSC to local var RSP+38 call kernel32.dll.GetTickCount64 - get ms since boot save GetTickCount64 return value to local var RSP+40 load TSC into RAX save pointer to local TSC to local var RSP+30 load GetTickCount64 return value into RAX load pointer to local TSC into R8 register load pointer to local TSC into RAX register load TSC into RDX register ECX = lower 8 bits of RAX (TSC pointer) - zero extended EAX = ECX (lower 8 bits of TSC pointer) * 0x3B load constant 0xA7 into ECX register shift right R8 (pointer to local TSC) 0x7 xor lower 8 bits of RDX (TSC) by R8 (pointer to local TSC) xor lower 8 bits of RDX (transformed TSC) by lower 8 bits of RAX (imul result) EAX = xor result - zero extended move EAX into ECX if XOR result is non-zero move lower 8 bits of RCX into local var RSP+30 EAX = local var RSP+30 - zero extended move lower 8-bits (1 byte) of RAX into global move 0 into local var RSP+30 deallocate 0x28 bytes of allocated memory </pre>
---	---

Seems like progress. I added a breakpoint of the instruction `mov byte ptr ds:[7FF685BA3264], al` to keep track of the seed on subsequent executions and proceeded to the return, which lands me in another function.

<pre> 48:3BCA 74 30 48:895C24 08 57 48:83EC 20 48:8BF8 48:8BD9 48:8B03 48:85C0 74 05 E8 FE270100 48:83C3 08 48:3BDF 75 EA 48:8B5C24 30 48:83C4 20 5F C3 </pre>	<pre> cmp rcx,rdx je puzzle.7FF685B7CF65 mov qword ptr ss:[rsp+8],rbx push rdi sub rsp,20 mov rdi,rdx mov rbx,rcx mov rax,qword ptr ds:[rbx] test rax,rax je puzzle.7FF685B7CF52 call puzzle.7FF685B8F750 add rbx,8 cmp rbx,rdi jne puzzle.7FF685B7CF45 mov rbx,qword ptr ss:[rsp+30] add rsp,20 pop rdi ret </pre>
--	---

This function appears to loop until `RBX == RDI`, at which point it calls the seeding function that uses `GetTickCount64`. What exactly `RDI` is I am unaware of yet.

## 6.1.4 Switching my approach

I'm starting to think that a lot of functions might have been imported and never used OR just imported as red-herrings. This has caused me to search in unnecessary areas instead of trying to track down any anti-debugging logic. I will switch gears to attempt to find the flag and see if I trip up any anti-debug code along the way.

## 6.2 Input Breakpoints

Two of the breakpoints that end up producing interesting results are `WriteFile` and `ReadFile`. There seems to be some kind of loop that iteratively prints `Hello World!\nEnter password:`. This would explain why I was unable to find any string references in *x64dbg*, as it seems to be dynamically loading and printing the value. This doesn't seem an avenue worth exploring as it just handles the output to console. Taking note of this, I continue to where the user input is captured as I feel that would achieve more desirable results.

### 6.2.1 kernel32.dll.WriteFile

After stepping around I land on an interesting function.

8BC8	mov ecx,eax
83F8 0A	cmp eax,A
✓ 74 36	je puzzle.7FF685B72840
48:8D45 F7	lea rax,qword ptr ss:[rbp-9]
BB 01000000	mov ebx,1
48:2BD8	sub rbx,rax
48:8D7D F7	lea rdi,qword ptr ss:[rbp-9]
66:0F1F4400 00	nop word ptr ds:[rax+rax],ax
83F9 FF	cmp ecx,FFFFFFFF
✓ 74 1B	je puzzle.7FF685B72840
48:8D043B	lea rax,qword ptr ds:[rbx+rdi]
48:83F8 40	cmp rax,40
✓ 73 05	jae puzzle.7FF685B72834
880F	mov byte ptr ds:[rdi],cl
48:FFC7	inc rdi
E8 37980000	call puzzle.7FF685B7C070
8BC8	mov ecx,eax
83F8 0A	cmp eax,A
^ 75 E0	jne puzzle.7FF685B72820
0FB645 F7	movzx eax,byte ptr ss:[rbp-9]
33C9	xor ecx,ecx
48:8B9C24 18010000	mov rbx,qword ptr ss:[rsp+118]
84C0	test al,al
✓ 74 55	je puzzle.7FF685B728A7
48:83F9 40	cmp rcx,40
✓ 73 0C	jae puzzle.7FF685B72864
0FB6440D F8	movzx eax,byte ptr ss:[rbp+rcx-8]
48:FFC1	inc rcx
84C0	test al,al
^ 75 EE	jne puzzle.7FF685B72852
48:83F9 09	cmp rcx,9
✓ 75 3D	jne puzzle.7FF685B728A7
33D2	xor edx,edx
48:8D3D DD8C0200	lea rdi,qword ptr ds:[7FF685B98550]
0F1F40 00	nop dword ptr ds:[rax],eax
66:0F1F8400 00000000	nop word ptr ds:[rax+rax],ax
0FB6043A	movzx eax,byte ptr ds:[rdx+rdi]
34 9F	xor al,9F
8845 67	mov byte ptr ss:[rbp+67],al
0FB64C15 F7	movzx ecx,byte ptr ss:[rbp+rdx-9]
0FB645 67	movzx eax,byte ptr ss:[rbp+67]
C645 67 00	mov byte ptr ss:[rbp+67],0
3AC8	cmp cl,al
✓ 75 0D	jne puzzle.7FF685B728A7
48:FFC2	inc rdx
48:83FA 09	cmp rdx,9
^ 72 DD	jb puzzle.7FF685B72880
B2 01	mov dl,1
✓ EB 02	jmp puzzle.7FF685B728A9
32D2	xor dl,dl
33C0	xor eax,eax
48:8D7D F7	lea rdi,qword ptr ss:[rbp-9]
B9 40000000	mov ecx,40
F3:AA	rep stosb
B0 DE	mov al,DE
84D2	test dl,dl
✓ 74 3C	je puzzle.7FF685B728F8
C745 9F DEFCFCFA	mov dword ptr ss:[rbp-61],FAFCFCDE
48:8D7D 9F	lea rdi,qword ptr ss:[rbp-61]
C745 A3 ECECBFD8	mov dword ptr ss:[rbp-5D],D8BFECEC
C745 A7 EDFEF1EB	mov dword ptr ss:[rbp-59],EBF1FEED
C745 AB FAFBBE95	mov dword ptr ss:[rbp-55],95BEFBFA
C645 AF 9F	mov byte ptr ss:[rbp-51],9F

The first immediate thing that stands out to me is the repeated loops to an index of `0x40`.

The two loops at the start take some time but eventually click for me. The first loop I found in the long function just takes the user input up until a newline character and then checks if it is 9 characters long.



cmp ecx,FFFFFFFF	loop until 0xFFFFFFFF (probably a while loop?)
je puzzle.7FF685B72840	encoding / checking loop?
lea rax,qword ptr ds:[rbx+rdi]	
cmp rax,40	loop 0x40 times max
jae puzzle.7FF685B72834	
mov byte ptr ds:[rdi],cl	
inc rdi	increment loop index
call puzzle.7FF685B7C070	get next character?
mov ecx,eax	
cmp eax,A	loop until we find 0xA in the user input - loop til newline character
jne puzzle.7FF685B72820	
movzx eax,byte ptr ss:[rbp-9]	
xor ecx,ecx	
mov rbx,qword ptr ss:[rsp+118]	[rsp+118]:&"C:\\Users\\david\\Desktop\\crackmes.one\\BigIsim04 - puzzl
test al,al	empty check on user input?
je puzzle.7FF685B728A7	jump if empty user input
cmp rcx,40	loop 0x40 times max
jae puzzle.7FF685B72864	
movzx eax,byte ptr ss:[rbp+rcx-8]	
inc rcx	increment loop index
test al,al	
jne puzzle.7FF685B72852	loop until string delimiter
cmp rcx,9	09: '\t'
jne puzzle.7FF685B728A7	jump if string is not 0x9 characters long

Continuing the execution, I get to the loop that prints "Access Denied" onto the screen.

mov dword ptr ss:[rsp+20],FAFCFCDE	
lea rdi,qword ptr ss:[rsp+20]	
mov dword ptr ss:[rsp+24],DB8FECEC	
mov dword ptr ss:[rsp+28],FAF6F1FA	
mov dword ptr ss:[rbp-7D],9F95BEFB	
nop dword ptr ds:[rax],eax	
xor al,9F	[L2] print "Access Denied" loop
movzx edx,al	
call puzzle.7FF685B73280	
movzx eax,byte ptr ds:[rdi+1]	
lea rdi,qword ptr ds:[rdi+1]	
cmp al,9F	
jne puzzle.7FF685B72920	[L2] loop end

Above it, I notice a similar looking loop. Considering the conditional before it, I assume that it is the "Access Allowed" branch.

test dl,dl	
je puzzle.7FF685B728F8	jump over "Access Allowed" printing loop
mov dword ptr ss:[rbp-61],FAFCFCDE	[rbp-61]:SystemFunction036+D
lea rdi,qword ptr ss:[rbp-61]	
mov dword ptr ss:[rbp-5D],DB8FECEC	
mov dword ptr ss:[rbp-59],EBF1FEED	
mov dword ptr ss:[rbp-55],95BEFBFA	
mov byte ptr ss:[rbp-51],9F	
xor al,9F	[L1] "Access Allowed" loop?
movzx edx,al	
call puzzle.7FF685B73280	
movzx eax,byte ptr ds:[rdi+1]	
lea rdi,qword ptr ds:[rdi+1]	
cmp al,9F	
jne puzzle.7FF685B728E0	[L1] loop end
jmp puzzle.7FF685B72936	jump over "Access Denied" printing loop
mov dword ptr ss:[rsp+20],FAFCFCDE	
lea rdi,qword ptr ss:[rsp+20]	
mov dword ptr ss:[rsp+24],DB8FECEC	
mov dword ptr ss:[rsp+28],FAF6F1FA	
mov dword ptr ss:[rbp-7D],9F95BEFB	
nop dword ptr ds:[rax],eax	
xor al,9F	[L2] print "Access Denied" loop
movzx edx,al	
call puzzle.7FF685B73280	
movzx eax,byte ptr ds:[rdi+1]	
lea rdi,qword ptr ds:[rdi+1]	
cmp al,9F	
jne puzzle.7FF685B72920	[L2] loop end

Great, so I - *think* I - have found where the comparison takes place before the right/wrong branches. My next step revolves around setting a breakpoint on that `test dl, dl` and restarting program execution to see what the registers look like.

<pre> lea rdi,qword ptr ss:[rbp-9] mov ecx,40 rep stosb mov al,DE test dl,dl je puzzle.7FF685B728F8 </pre>	load the address of the user input into RDI move 0x40 into ECX for REP instruction following  jump over "Access Allowed" printing loop
--	---

One thing that I am really starting to notice is the repeated use of the value `0x40`, especially for loops. Breaking there, it seems that the important code is not around there but a bit higher.

A bit above there seems to be a loop that checks if the user input is 9 characters long. If it's not, it jumps to the "Access Denied" code branch.

<pre> test al,al je puzzle.7FF685B728A7 cmp rcx,40 jae puzzle.7FF685B72864 movzx eax,byte ptr ss:[rbp+rcx-8] inc rcx test al,al jne puzzle.7FF685B72852 cmp rcx,9 jne puzzle.7FF685B728A7 </pre>	empty check on user input? jump if empty user input loop 0x40 times max  increment loop index  loop until string delimiter 09: '\t' jump if string is not 0x9 characters long
--	---

Changing my input from `helloworld` to `helloworl` I confirm that it indeed is checking the length of the user input and ensuring it is 9 characters long. With that, I continue into the logic that was being jumped over.

<pre> 75 3D jne puzzle.7FF685B728A7 33D2 xor edx,edx 48:8D3D DD8C0200 lea rdi,qword ptr ds:[7FF685B9B550] 0F1F40 00 nop dword ptr ds:[rax],eax 66:0F1F8400 00000000 nop word ptr ds:[rax+rax],ax 0FB6043A movzx eax,byte ptr ds:[rdx+rdi] 34 9F xor al,9F 8845 67 mov byte ptr ss:[rbp+67],al 0FB64C15 F7 movzx ecx,byte ptr ss:[rbp+rdx-9] 0FB645 67 movzx eax,byte ptr ss:[rbp+67] C645 67 00 mov byte ptr ss:[rbp+67],0 3AC8 cmp cl,al 75 0D jne puzzle.7FF685B728A7 48:FFC2 inc rdx 48:83FA 09 cmp rdx,9 72 DD jnb puzzle.7FF685B72880 B2 01 mov dl,1 EB 02 jmp puzzle.7FF685B728A9 32D2 xor dl,dl </pre>	jump if string is not 0x9 characters long  09: '\t'
---	---

And I think I spot the smoking gun.

## 7. Validation Path

The actual flag comparison logic!

`RAX` (`AL`) represents a character from our user input being compared against `RCX` (`CL`) which I assume is the respective index character of the flag.

<pre> 00007FF685B72896 3AC8 cmp cl,al 00007FF685B72898 75 0D jne puzzle.7FF685B728A7 </pre>
---

Now to just extract the flag character. BUT, before doing so I temporarily `nop` the `jne` instruction as to not jump to the "Access Denied" branch.

3AC8	<code>cmp cl,al</code>
90	<code>nop</code>
90	<code>nop</code>
48:FFC2	<code>inc rdx</code>
48:83FA 09	<code>cmp rdx,9</code>
72 DD	<code>jb puzzle.7FF685B72880</code>
B2 01	<code>mov dl,1</code>
EB 02	<code>jmp puzzle.7FF685B728A9</code>
32D2	<code>xor dl,dl</code>
33C0	<code>xor eax,eax</code>

As I run the program from my breakpoint on the `cmp cl, al` instruction; the `RAX` register spell out: `M, Y, P, A, S, S, 1, 2, 3`.

Time to enter the password `MYPASS123` and see if it is indeed the correct flag.

```
C:\Users\David\Desktop\crack x
+ v
Hello World!
Enter password: MYPASS123
Access Granted!
|
```

**Great success!**

Now I just want to figure out how the password is being stored and transformed.

It appears that it is loading in the bytes `D2 C6 CF DE CC CC AE AD AC` one byte at a time and xoring it with `0x9F`.

00007FF685B98550	D2	C6	CF	DE	CC	CC	AE	AD	AC
------------------	----	----	----	----	----	----	----	----	----



### 8.1.3 Stack Alignment

Windows x64 requires the stack to be 16-byte aligned at the moment of a `call`. This is because the `call` instruction pushes an 8-byte return address, which shifts `RSP` by 8 and can break 16-byte alignment.

## 8.2 Function Definitions

### 8.2.1 kernel32.dll.LoadLibraryExW

`LoadLibraryExW` has three parameters and returns an *HMODULE* (or *NULL* on failure).

```
HMODULE LoadLibraryExW(  
    LPCWSTR lpLibFileName,  
    HANDLE hFile,  
    DWORD dwFlags  
);
```

#### 1. `lpLibFileName` ( `LPCWSTR` )

- Path or name of the DLL to load.
- Often something like:
  - `L"kernel32.dll"`
  - `L"C:\\Windows\\System32\\something.dll"`
  - Or an app-local DLL name.

#### 2. `hFile` ( `HANDLE` )

- Usually `NULL`.
- Historically used for loading from an already-open file handle.

#### 3. `dwFlags` ( `DWORD` )

- Controls *how* the module is loaded / searched.
- Common ones include:

Flag	Value	Note
	0x00000000	Default load behaviour (normal DLL search order).
DONT_RESOLVE_DLL_REFERENCES	0x00000001	Maps the DLL but <i>doesn't call</i> <code>DllMain</code> or resolve imports - useful for inspection.
LOAD_LIBRARY_AS_DATAFILE	0x00000002	Loads the module <i>as a data file</i> (resources), not for code execution.
LOAD_LIBRARY_AS_IMAGE_RESOURCE	0x00000020	Loads <i>only as an image resource</i> , mostly for resource access.
LOAD_LIBRARY_AS_DATAFILE_EXCLUSIVE	0x00000040	Like <code>AS_DATAFILE</code> but tries to keep it exclusive so others can't modify it.
LOAD_WITH_ALTERED_SEARCH_PATH	0x00000008	Changes search order to prioritize the DLL's directory - older/legacy pattern.
LOAD_LIBRARY_SEARCH_DLL_LOAD_DIR	0x00000100	Search the directory of the DLL being loaded
LOAD_LIBRARY_SEARCH_APPLICATION_DIR	0x00000200	Search the executable's directory
LOAD_LIBRARY_SEARCH_USER_DIRS	0x00000400	Search directories added via <code>AddDllDirectory</code>
LOAD_LIBRARY_SEARCH_SYSTEM32	0x00000800	Search <code>System32</code> only

Flag	Value	Note
<code>LOAD_LIBRARY_SEARCH_DEFAULT_DIRS</code>	<code>0x00001000</code>	A safe default set: app directory + system32 + user-added directories (recommended modern choice).

If a weird flag value is present, it may be a *bitwise OR* of multiple flags.

- **Return Value**

- Success: `HMODULE` for the loaded module.
- Failure: `NULL` ( `RAX = 0` ).
  - Then `GetLastError()` can inform you as to why.

[Jump Back](#)

## 8.2.2 kernel32.dll.SetUnhandledExceptionFilter

`SetUnhandledExceptionFilter` accepts one parameter and returns an `LPTOP_LEVEL_EXCEPTION_FILTER` which is the previous unhandled exception filter (or `NULL` if none).

```
LPTOP_LEVEL_EXCEPTION_FILTER SetUnhandledExceptionFilter(
    LPTOP_LEVEL_EXCEPTION_FILTER lpTopLevelExceptionFilter
);
```

### 1. lpTopLevelExceptionFilter ( LPTOP\_LEVEL\_EXCEPTION\_FILTER )

- Pointer to a *custom unhandled exception filter* function.
- This function is called when an exception *isn't handled* by structured exception handling in the process.
- Often something like:
  - `MyUnhandledExceptionFilter`
  - `NULL` (to clear/disable a previously set filter)

- **Return Value** ( `LPTOP_LEVEL_EXCEPTION_FILTER` )
  - Returns a pointer to the *previous* unhandled exception filter.
  - Often:
    - Another filter function pointer if one was already set
    - `NULL` if no previous filter was registered

[Jump Back](#)

### 8.2.3 `kernel32.dll.GetTickCount64`

`GetTickCount64` takes no parameters and returns a `ULONGLONG` representing the number of milliseconds that have elapsed since the system was started.

```
ULONGLONG GetTickCount64(
    VOID
);
```

- **Return Value** ( `ULONGLONG` )
  - Returns the number of **milliseconds since system boot**.
  - Often used for:
    - timing measurements
    - detecting delays (e.g., anti-debug “single-step slowdown” checks)

[Jump Back](#)

## 8.3 x64 Register Size Cheat Sheet

Each 64-bit register has smaller *views*; Example with `RAX` :

Size	Name	What it is
64-bit	<code>RAX</code>	full register



Size	Name	What it is
32-bit	EAX	low 32 bits of RAX
16-bit	AX	low 16 bits
8-bit (low)	AL	low 8 bits
8-bit (high)	AH	bits 8–15 (upper half of AX)

So `AX = AH:AL`. The same pattern applies to others

**Common Registers;** High *8-bit* forms exist only for these classic registers:

64-bit	32-bit	16-bit	8-bit low	8-bit high*
RAX	EAX	AX	AL	AH
RBX	EBX	BX	BL	BH
RCX	ECX	CX	CL	CH
RDX	EDX	DX	DL	DH

**Pointer/Index Registers;** These do *NOT* have `AH/BH/CH/DH` style high *8-bit* forms.

64-bit	32-bit	16-bit	8-bit low
RSI	ESI	SI	SIL
RDI	EDI	DI	DIL
RBP	EBP	BP	BPL
RSP	ESP	SP	SPL

**Extended registers (x64-only);** No high *8-bit* halves here either:

64-bit	32-bit	16-bit	8-bit low
R8	R8D	R8W	R8B
R9	R9D	R9W	R9B
R10	R10D	R10W	R10B
R11	R11D	R11W	R11B
R12	R12D	R12W	R12B
R13	R13D	R13W	R13B
R14	R14D	R14W	R14B
R15	R15D	R15W	R15B

Important to note that writing to a *32-bit* register, such as `EAX`, zeroes the upper 32 bits of the 64-bit register ( `RAX` ).

---

## 9. Conclusion

- Summary of final understanding.
  - What you'd improve next time.
  - Optional lessons learned.
- 
- Spent too much time on anti debugging code when none was really present
  - Wasted a lot of time investigating code that had nothing to do with my end goal of finding the flag
  - It was Access Granted not Access Allowed as I guess, but close