

Application—Configurable Messaging**Foreword**

This series of SAE Recommended Practices have been developed by the Truck and Bus Control and Communications Network Subcommittee of the Truck and Bus Electrical and Electronics Committee. The objectives of the subcommittee are to develop information reports, recommended practices, and standards concerned with the requirements, design, and usage of devices that transmit electronic signals and control information among vehicle components. The usage of these Recommended Practices is not limited to truck and bus applications; other applications may be accommodated with immediate support being provided for construction and agricultural equipment, and stationary power systems.

These SAE Recommended Practices are intended as a guide toward standard practice and are subject to change so as to keep pace with experience and technical advances.

This application layer may be used for all SAE J1939 applications. It is the characteristic that is common across all SAE J1939 applications.

TABLE OF CONTENTS

1	Scope	4
1.1	Rationale	4
2	References	4
2.1	Applicable Publications	4
2.1.1	SAE Publications	4
2.2	Related Publications	4
2.2.1	ISO Publications	4
3	Definitions	5
4	Abbreviations	5
5	Technical Requirements	5
5.1	General	5
5.2	Overview of Configuration Services	5
5.2.1	Developmental History	5
5.2.2	Harmonization	6

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2006 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
<http://www.sae.org>

SAE J1939-74 Revised NOV2006

5.2.3	Operation and Related Requirements	6
5.2.3.1	Effects Upon Request Messages	7
5.2.3.2	Additional CA Requirements	8
5.2.3.3	Application for New Parameter Definitions	8
5.2.3.4	Continuity Across Power Cycles	9
5.3	The Configuration Service	9
5.3.1	Configuration Identification Message	9
5.3.1.1	PGN of Message Being Configured	10
5.3.1.2	Parameter Being Included	10
5.3.1.3	Position of Configured Parameter	11
5.3.1.4	Number of Parameters Included	11
5.3.1.5	Message Will Be Used Proprietarily	11
5.3.1.6	Message Will Use Transport Protocol	12
5.3.1.7	First Parameter Only Being Identified	13
5.3.1.8	Starting Bit for this Parameter	13
5.3.1.9	Requirements Related to Configuration Identification Message	15
5.3.2	Parameter Locate Message	16
5.3.2.1	Parameter to be Located	16
5.3.2.2	Parameter Locate Command	17
5.3.3	Request for Complete Configurable Message Set	17
5.3.3.1	Message Selection Control	18
5.3.3.2	PGN of Configurable Message Desired	18
5.4	The Set of Destination Specific Proprietarily Configurable Messages	19
5.4.1	Destination Specific Proprietarily Configurable Message 1	19
5.4.1.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	19
5.4.1.2	DLC for Destination Specific Proprietarily Configurable Messages	20
5.4.2	Destination Specific Proprietarily Configurable Message 2	20
5.4.2.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	20
5.4.2.2	DLC for Destination Specific Proprietarily Configurable Messages	20
5.4.3	Destination Specific Proprietarily Configurable Message 3	21
5.4.3.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	21
5.4.3.2	DLC for Destination Specific Proprietarily Configurable Messages	21
5.4.4	Destination Specific Proprietarily Configurable Message 4	21
5.4.4.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	22
5.4.4.2	DLC for Destination Specific Proprietarily Configurable Messages	22
5.4.5	Destination Specific Proprietarily Configurable Message 5	22
5.4.5.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	23
5.4.5.2	DLC for Destination Specific Proprietarily Configurable Messages	23
5.4.6	Destination Specific Proprietarily Configurable Message 6	23
5.4.6.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	23
5.4.6.2	DLC for Destination Specific Proprietarily Configurable Messages	24
5.4.7	Destination Specific Proprietarily Configurable Message 7	24
5.4.7.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	24
5.4.7.2	DLC for Destination Specific Proprietarily Configurable Messages	24
5.4.8	Destination Specific Proprietarily Configurable Message 8	25
5.4.8.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	25
5.4.8.2	DLC for Destination Specific Proprietarily Configurable Messages	25

SAE J1939-74 Revised NOV2006

5.4.9	Destination Specific Proprietarily Configurable Message 9	25
5.4.9.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	26
5.4.9.2	DLC for Destination Specific Proprietarily Configurable Messages	26
5.4.10	Destination Specific Proprietarily Configurable Message 10	26
5.4.10.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	26
5.4.10.2	DLC for Destination Specific Proprietarily Configurable Messages	27
5.4.11	Destination Specific Proprietarily Configurable Message 11	27
5.4.11.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	27
5.4.11.2	DLC for Destination Specific Proprietarily Configurable Messages	27
5.4.12	Destination Specific Proprietarily Configurable Message 12	28
5.4.12.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	28
5.4.12.2	DLC for Destination Specific Proprietarily Configurable Messages	28
5.4.13	Destination Specific Proprietarily Configurable Message 1	28
5.4.13.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	29
5.4.13.2	DLC for Destination Specific Proprietarily Configurable Messages	29
5.4.14	Destination Specific Proprietarily Configurable Message 14	29
5.4.14.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	29
5.4.14.2	DLC for Destination Specific Proprietarily Configurable Messages	30
5.4.15	Destination Specific Proprietarily Configurable Message 15	30
5.4.15.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	30
5.4.15.2	DLC for Destination Specific Proprietarily Configurable Messages	30
5.4.16	Destination Specific Proprietarily Configurable Message 16	31
5.4.16.1	Parameter Content of Destination Specific Proprietarily Configurable Messages	31
5.4.16.2	DLC for Destination Specific Proprietarily Configurable Messages	31
5.5	The Set of Parameters for Use within the Configurable Messages	31
6	Notes	32
6.1	Marginal Indicia	32
Appendix A	ASSUMPTIONS USED TO DESIGN CONFIGURABLE MESSAGING	33
Appendix B	APPLICATION RULES REGARDING CONFIGURABLE MESSAGING	35
Appendix C	PARAMETERS FOR CONFIGURABLE MESSAGING	36

LIST OF FIGURES

There are no Figures contained in this document

LIST OF TABLES

There are no Tables contained in this document

1. Scope

The SAE J1939 documents are intended for light, medium, and heavy-duty vehicles used on or off road as well as appropriate stationary applications which use vehicle derived components (e.g. generator sets). Vehicles of interest include, but are not limited to, on- and off-highway trucks and their trailers, construction equipment, and agricultural equipment and implements.

The purpose of these documents is to provide an open interconnect system for electronic systems. It is the intention of these documents to allow Electronic Control Units to communicate with each other by providing a standard architecture.

This particular document, SAE J1939-74, describes the message structure for a set of messages which enable the user to determine and announce to others on the network, the parameter placement within a particular message from the special set of messages defined within this document.

1.1 Rationale

The purpose of this revision is to add the first list of parameters to Appendix C only. No changes were made to the main body of the document with the exception of a correction to a pgn in Section 5.3.3.

2. References

2.1 Applicable Publications

General information regarding this series of recommended practices is found in SAE J1939. The latest issue of SAE publications shall apply.

2.1.1 SAE PUBLICATIONS

Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.

SAE J1939—Recommended Practice for a Serial Control and Communications Vehicle Network is the parent document and should be referenced in general

SAE J1939-21—Data Link Layer

SAE J1939-71—Vehicle Application Layer

SAE J1939-73—Application Layer - Diagnostics

SAE J1939-81—Network Management

2.2 Related Publications

The following publications are provided for information purposes only and are not a required part of this document.

2.2.1 ISO PUBLICATIONS

Available from ANSI, 25 West 43rd Street, New York, NY 10036-8002, Tel: 212-642-4900, www.ansi.org.

ISO 11783—Tractors, machinery for agriculture and forestry Serial control and communications data network

3. Definitions

Terms and definitions are defined in SAE J1939.

4. Abbreviations

CA Controller Application – the function of a system receiving a NAME within an ecu – see SAE J1939–81, Network Management, for more details
SPN Suspect Parameter Number

See SAE J1939 for any terms and or definitions not found in this document.

5. Technical Requirements

This configurable messaging application provides for the variable packing of certain parameters within a particular message from a set of messages.

5.1 General

The definitions provided herein are intended to satisfy the needs of all potential users of the SAE J1939 network. These definitions are intended to be suitable for applications in any of the industry groups defined within SAE J1939. The capabilities provided allow CAs to configure and identify to other network CAs the location of certain parameters (each identified by its SPN) within certain special messages (each identified by PGN). These capabilities also provide the means by which a CA can request the identification of the message (PGN) containing a certain parameter (SPN). This document will define the configuration process, a set of messages which can and may be configured, and the messages used to identify this configuration to the rest of a network. This document will also contain the definitions of the only set of parameters (identified by SPN) to be used exclusively within one of the configured messages defined herein. It is intended that these parameters be completely defined within this document before use on a network. New features, Parameter Groups and Parameter definitions will be added over time; it is anticipated that this document will continuously evolve as long as the SAE J1939 network is an active Recommended Practice. Such growth will be implemented in such a way as to ensure backward compatibility with earlier versions. At the time of initial publication, many of these growth areas are identified but are yet to be defined. Such identification is provided so that the reader will be aware of those additions that are already planned for the document. This procedure will define a number of messages that may be configured, presently there are 16 configurable PDU 1 messages.

5.2 Overview of Configuration Services

The configuration messages and processes are intended to provide services needed to improve utilization of bus bandwidth, facilitate organization of data within messages in a fashion that can allow optimization of vehicle topology, and allow identification of this organization to other CAs.

5.2.1 DEVELOPMENTAL HISTORY

These messages were originally proposed for Agricultural Applications, but have been harmonized and standardized for all Industry Groups. In the Agricultural Industry specific example, self-propelled vehicles with very different topologies need to use common parameters, so that third party vendors can know the identity of parameters on the networks. But the message groupings must fit the vehicle topology in order to have sufficient time to transmit all of the parameters. For this Agricultural need it is desired that the source and destination addresses, as well as, the message configuration, be used to identify the data

within a particular message (just as source and destination address are needed to identify the data within the proprietary A message identified in SAE J1939-21). These messages need to be configurable in the sense that the groupings of parameters within a message were not predefined within one of the network standard documents, but by the data within another message (the Proprietary Message Configuration Identification Message). The parameters being used are to be predefined within this network document, just as other parameters are defined within one of the other network documents.

The Agricultural need was limited to destination specific messages and thus the original proposal was tailored to that end. Several revisions studied allowing other messages, but committee work has deemed it best to maintain this restriction, that the only configurable messages are destination specific messages.

The new aspect of this document is the technique by which the grouping of certain parameters (defined within this standard) can be arranged appropriately for the vehicle topology and then identified to other network members by a configuration process, using the data content of a special initialization message. This configuration process identifies the message being configured (by PGN), the parameters being sent within said message (by SPN), as well as their placement within said message (by bit position). After some discussion it was deemed that the feature could be handy for all Industry Groups and a working group was sent out to develop a harmonized version.

5.2.2 HARMONIZATION

These messages have been harmonized for use in all Industry Groups. It is not the intent that all CAs will use (or even need) these processes, but should they be used, this application document (SAE J1939-74) is to be considered the driving document. This document defines the configuration process, the configurable messages, the configuration messages and an associated set of certain parameters, which are envisioned only for transmission within one of the configurable messages. There are 16 destination specific messages (5.3.3), which are labeled as proprietarily configurable (5.3.1.5.1). These messages may only include parameters from this application document (in other words parameters from the other SAE J1939 documents are not to be sent via the configurable messages at this time, see also 5.3.1.2 and 5.3.1.5). Transmission of the Configuration Identification Message (5.3.1) is the means used to identify the data within one of these messages. Transmission of the Configuration Identification Message is required if using any configurable messages. This is to provide the information about each message's contents to potential receivers as the Agricultural Industry Group desired.

5.2.3 OPERATION AND RELATED REQUIREMENTS

This configuration is not meant to be a dynamic process but rather is normally expected to be alterable only at initialization. In fact in most systems the topology will be stable and hence the configuration will likely not change from one ignition cycle (power-up of the system) to another (5.2.3.4). It is required that CAs receiving configured messages check the NAMEs of the CA configuring the particular messages and verify that they have not changed since a complete configuration list was received for each particular message. If a NAME change is detected then the complete configuration list for the particular message should be requested. It is also required that CAs on an agricultural implement bus must maintain the latest configuration while powered down (this is just like the current addresses association requirement of all network members of an agricultural implement bus). For this reason and since it is desired to have the quickest possible initialization process, there exists a bit parameter (5.3.1.7) that identifies that only the data relevant to the first configured parameter (by SPN) is being identified with a Configuration Identification Message. This is used so that the software may verify that a given message still comes from a particular CA. (The reasoning here is that it is highly unlikely that a CA with the same NAME of Controller Application parameter (SPN 2848) will be transmitting a message with a particular configured message containing the same first parameter but with differences in the remainder of the message and

without knowing about it. Hence, this partial "Claim" will suffice to show others on the network whether the list of messages in their memory is still usable). This form is to be used on each power-up event for each CA transmitting a configurable message. Should a receiver note that the NAME of the source, the number of parameters or the location of a parameter does not match what is contained within its own memory then it should request the complete configuration identification between that CA and itself. Should a transmitting CA know that it has changed (or will change) the message content of a configured message, it should send (re-send) the complete new configuration identification for that message, whether it is at start-up or during operation. Should the location of individual specific SPNs be needed after a network is running, the Parameter Locate message (5.3.2) can be used. Should a complete configuration between any two CAs be needed, a destination specific 'Request for' of the PGN of the Configuration Identification Message can be used. The complete configuration of the specific message (identified by PGN) from that particular source would then be transmitted upon the network.

5.2.3.1 Effects Upon Request Messages

For a CA seeking to find the configuration of messages on a network (necessary when for example it has powered up separately from the rest of the network), there are two choices. It may send a "Request for" (PGN 59904, see SAE J1939-21) the PGN of the Configuration Identification Message or it may send a Request for Complete Configurable Message Set. A CA might also need the data from one of the configurable messages, which is found by sending a 'Request For' the PGN of Any of the Configurable Messages. The rules for these cases are outlined in the following sections.

5.2.3.1.1 Global Request for PGN of Configuration Identification Message

A global 'Request for' the PGN of the Configuration Identification Message is intended to cause all CAs that transmit a configurable message to send only the shortened Configuration Identification Message (where only the first SPN is identified (5.3.1.7)) for the configurable messages that they transmit, regardless of source of the request. These messages should be sent exactly as at power-up. A response is required for a 'Request for' message for the PGN of the Configuration Identification Message. (If a tool (or other CA) should need to obtain the complete configuration on a vehicle, it should use the Request for Complete Configurable Message Set message (5.3.3 & 5.2.3.1.3)).

5.2.3.1.2 Directed Request for PGN of Configuration Identification Message

A 'Request for' the PGN of the Configuration Identification Message directed to a specific address is intended to cause the CA at that address to transmit (or answer with) the complete sequence of configuration identification messages for all of the configured messages that said destination sends to the source of the request. Hence it is preferred that the 'Request for Configuration Identification Message' be sent only to one specific destination at a time. (If a tool (or other CA) should need to obtain the complete configuration on a vehicle, it should use the Request for Complete Configurable Message Set message (5.3.3 & 5.2.3.1.3)).

5.2.3.1.3 Request for Complete Configurable Message Set

There exists a separate message (5.3.3) designed to cause all CAs to respond with the complete sequence of configuration identification messages for the configurable messages that they send. The request may be for all configurable messages sent or a particular one, identified by PGN (5.3.3.2), controlled by the parameter, Message Selection Control (5.3.3.1). If a tool (or other CA) is using this message to obtain the complete configuration on a vehicle, it must then also listen for all Configuration Identification Messages regardless of the actual destination address of the Configuration Identification Message. This is required since each of the Proprietary Configured messages may be for a CA other

than said Tool, and hence the Configuration Identification Messages will not be directed to said Tool. (Note that this requirement is only for a tool (or another CA needing the complete configurable set for the vehicle) and normal CAs need understand only what is sent to it by any of the other CAs.)

5.2.3.1.4 'Request For' the PGN of Any of the Configurable Messages

A 'Request for' message for the PGN of any of the Configurable Messages (5.3.3) is intended to function just like a 'Request for' any PGN defined elsewhere within SAE J1939. The CA receiving the 'Request for' the PGN of one of the Configurable Messages should then send the message identified by said PGN and the data values appropriate for that message (providing of course that it sends said configurable message).

5.2.3.1.5 Software Mapping of Message Configurations

Configuration maps should be made a function of the NAME of Address Claimed of the CAs (this is not to say that the parameter NAME of Controller Application (SPN 2848) should be the index or pointer but only that an association should be maintained with the NAME of Address Claimed parameter). The address tables may be used to translate from network address to a particular function by this association with NAME of Address Claimed parameter. This way it is possible for a CA to recognize that it has been moved or that another CA has been added or changed. Then the CA may appropriately request the configuration of the new network. Note that a CA need only request a configuration update if a CA that it communicates with using a configurable message has been changed (in other words if the change is in a CA that is not communicated with, there is no need to form a configuration map).

5.2.3.1.6 Time-Outs Needed for Request for PGN of the Configuration Identification Message

Any CA which plans to make requests for the PGN of the Configuration Identification Message will need to have a time-out mechanism to determine when the list of configuration identification messages has ended. This is due in part to the fact that the number of configured messages is not known prior to sending the request. The value of this time-out will need to be based upon the actual application being handled and is not identified within this document.

5.2.3.2 *Additional CA Requirements*

The length of each parameter must be known from the SLOT assignment in the definition of that particular parameter. This requires that any CA that is going to use a particular parameter must contain the SLOT data for that parameter.

5.2.3.3 *Application for New Parameter Definitions*

All parameters need to be requested, defined, and assigned SPNs just as is currently done (see SAE J1939 no-dash appendices). The placement of the new parameter(s) within this document (by whatever database means) will identify that the new parameter may be used within the Proprietarily Configurable messages. CAs using these parameters will need additional application software to handle the calculation work which must be done to determine the location of the particular parameter within the message and whether the total length of the configured message will be such that transport protocol will be required (5.3.1.6).

5.2.3.4 *Continuity Across Power Cycles*

It is required that any CA sending or using one of the configured messages remember the configuration across power cycles.

5.3 The Configuration Service

The Proprietarily Configurable Messaging application includes a service to identify the configuration of messages, including the association of parameters within the particular message. (Note: This means to identify by listing the details of what exists and is not a capability to command (or force) a particular configuration).

5.3.1 CONFIGURATION IDENTIFICATION MESSAGE

This is the message used to identify the data content (by SPN) of one of the configurable messages (identified by PGN). Configuration is normally a vehicle build occurrence with a short Initialization procedure to enable Controller Applications, CAs (see SAE J1939-81), to verify that they are operating on the same network with the same other CAs as when they last operated (see 5.2.3.4 & 5.3.1.7 for discussion). The Configuration Identification message identifies the configuration (or location within a message) of only one parameter at a time. Therefore, it takes 'n' transmissions of this Configuration Identification Message to completely identify the configuration of one of the Configurable Messages in which 'n' parameters will be transmitted.

This message is also used to identify the location within a message of any particular parameter (identified by SPN), in response to the Parameter Locate Message (5.3.2). In this role, a Configuration Identification message is sent whenever a CA receives a Parameter Locate Message for a parameter that it is transmitting.

The rules regarding use of this message are in 5.3.1.9. The rules regarding interaction between this message and the 'Request for PGN' (PGN 59904, see SAE J1939-21) are outlined in 5.2.3.1. Remember that since the Destination Address is used to help define (interpret) the data content, the Configuration Identification Messages is NOT necessarily sent to the address from which the 'Request for' message was sent. Since this would effectively change the configuration and meaning of these Proprietarily Configured Messages, the destination of each Configuration Identification Message must be the address to which the configured message will normally be sent.

Transmission Rate: As needed

Data Length: 8

Data Page: 0

PDU Format: 176

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 45056

CONFIGURATION_IDENTIFICATION_MESSAGE

Byte: 1-3 PGN Of Message Being Configured
(bit order per SAE J1939-21 Table 2)

5.3.1.1

SAE J1939-74 Revised NOV2006

Byte:	4	bits 8-1 Parameter Being Included, 8 least significant bits (most significant at bit 8)	5.3.1.2
Byte:	5	bits 8-1 Parameter Being Included, second byte (most significant at bit 8)	
Byte:	6	bits 8-6 Parameter Being Included, 3 most significant bits (most significant at bit 8)	
		bits 5-1 Position Of Configured Parameter (most significant at bit 5)	5.3.1.3
Byte:	7	bit 8 Message Will Be Used Proprietarily	5.3.1.5
		bit 7 Message Will Use Transport Protocol	5.3.1.6
		bit 6 First Parameter Only Being Identified	5.3.1.7
		bits 5-1 Number Of Parameters Included (most significant at bit 5)	5.3.1.4
Byte:	8	Starting Bit For This Parameter	5.3.1.8

5.3.1.1 PGN of Message Being Configured

This is the PGN of the message whose configuration is being identified by this Configuration Identification Message. A 3 byte slot is used.

Data Length: 24 bits (3 bytes)
Resolution: 1 message/count
Data Range: (16 Numeric values, one for each configurable message, to be selected by database after ballot approval from the range 0, 256, ... 61184, 61440, 61441, ... 65535, 65536, 65792, ... 126720, 126976, 126977, ... 131071 – i.e. Only 8672 values are available/valid even though 24 bits)
Type: Measured
Suspect Parameter Number: 3146
Reference: 5.3.1

5.3.1.2 Parameter Being Included

This is the SPN of the parameter whose location is presently being identified for grouping into the message whose PGN is in this Configuration Identification Message. The 19 bit SPN slot is to be used (with a bit arrangement as in SAE J1939-73 diagnostics). The least significant bit is to be in data bit 25 of the message (i.e. the lowest bit of data byte 4), with eight bits in byte 4, the next 8 bits in byte 5, and the final 3 bits in byte 6, with the most significant bit to be in data bit 48 (i.e. the 8th bit of data byte 6). (Note: This leaves bits 1 through 5 of data byte 6 for assignment to other parameters, see 5.3.1.3). The list of parameters that may be located is contained within Appendix C. (This again indicates that the configurable messages are, at this time, not to be used with parameters from other of the SAE J1939 documents, see also 5.2.2 and 5.3.1.5.)

Data Length: 19 bits
Resolution: 1 parameter(or object)/count

Data Range: 0 to 524,287
Type: Measured
Suspect Parameter Number: 3147
Reference: 5.3.1

5.3.1.3 *Position of Configured Parameter*

This is a number identifying a particular parameter's position within a configured message in particular for differentiating the parameter (identified by SPN) whose location is presently being identified from the other parameters which will be grouped into the message whose PGN is in this Configuration Identification Message. It is used to verify that all of the parameters to be included within the message being configured have been received. A 5 bit slot with the values 0 and 31 is NOT allowed (0, since it would imply no SPNs and 31, since it would imply an unknown number).

Data Length: 5 bits
Resolution: 1 item/count
Data Range: 1 to 30
Type: Measured
Suspect Parameter Number: 3148
Reference: 5.3.1

5.3.1.4 *Number of Parameters Included*

This is the number of parameters, which will be grouped into the message whose PGN is in this Configuration Identification Message. It is used in the verification that all of the SPNs to be included within the message being configured have been received. A 5 bit slot with 0 and 31 are NOT allowed (0, since it would imply this is not a member and 31, since it would imply that the member is not known - both poor choices).

Data Length: 5 bits
Resolution: 1 parameter/count
Data Range: 1 to 30
Type: Measured
Suspect Parameter Number: 3152
Reference: 5.3.1

5.3.1.5 *Message Will Be Used Proprietarily*

This is a single bit flag used to indicate that the message being configured is a member of the set of destination specific proprietarily configurable messages, and that hence the Source Address and Destination Address are needed to interpret the data as with the destination specific Proprietary A message of SAE J1939-21. A single bit slot is needed. This parameter is necessary in case the application is ever expanded to allow inclusion of parameters from other SAE J1939 documents. Since this is not presently allowed this parameter should always be set to a '1'. (This again indicates that the configurable messages are, at this time, not to be used with parameters from other of the SAE J1939 documents, see also 5.2.2 and 5.3.1.2.)

Data Length: 1 bit
Resolution: n/a
Data Range: 1 (0 would be added should the committee ever decide to allow this application for standard SAE J1939 parameters)
Type: Measured
Suspect Parameter Number: 3149
Reference: 5.3.1

5.3.1.5.1 Proprietarily Configured Message

A '1' in this parameter signifies that the message being configured is a member of the set of destination specific proprietarily configurable messages (presently the only option) and that the interpretation of the data is to be based upon a combination of the source address, the destination address and the SPN of the specific data item. Hence the only parameters, which may be used, are those identified within this document. Also any CA wishing to use data from the message being configured must associate the source and the destination addresses as well as the Configuration Identification Message for the desired SPN within said configured message to obtain an interpretation of the data. Presently a '1' is the only option here and this parameter only exists to allow future expansion of this application should the committee ever deem necessary.

5.3.1.5.2 Not Proprietarily Configured Message

This is identified only as the mechanism necessary to extend this application to all SAE J1939 parameters, should the committee ever deem necessary. A value of '0' in this parameter would then be used to signify that the parameters were not necessarily from within this document. Presently a value of '0' is not allowed.

5.3.1.6 Message Will Use Transport Protocol

This is a single bit flag used to indicate that the message being configured is one that will use transport protocol. This bit must be properly set by all CAs configuring messages, as some receivers may need to know this (as opposed to being able to calculate), since the length of the SPN is not contained within the Configuration Identification Message and receivers are only required to know the length of SPNs they are using (i.e. NOT all existing SPNs), and hence may not be able to calculate how long any particular message is going to be. A single bit slot is needed.

Data Length: 1 bit
Resolution: n/a
Data Range: 0 or 1
Type: Measured
Suspect Parameter Number: 3150
Reference: 5.3.1

5.3.1.6.1 Transport Required

A '1' in this parameter signifies that the message being configured will require transport protocol.

5.3.1.6.2 Transport Not Required

A '0' in this parameter signifies that the message being configured will NOT require transport protocol.

5.3.1.7 First Parameter Only Being Identified

This is a single bit, which is used to identify that only the first parameter that will be sent within one of the Configurable Messages is being identified with a Configuration Identification Message. This form is to be used on each power-up event for any CA. This function has been generated so that the software can verify that a given message still comes from a particular CA but with the shortest possible initialization times. Identification of the location of individual specific parameters can then be handled with the Parameter Locate message (5.3.2).

Data Length: 1 bit
 Resolution: n/a
 Data Range: 0 or 1
 Type: Measured
 Suspect Parameter Number: 3151
 Reference: 5.3.1

5.3.1.7.1 First Parameter Only

A '1' in this parameter signifies that only the first parameter of the particular message being configured is being identified with a Configuration Identification message. See use note in 5.3.1.7.2.1.

5.3.1.7.2 All Parameters Being Identified

A '0' in this parameter signifies that all of the parameters that will be transmitted in the particular configurable message, are being identified using a separate Configuration Identification message for each parameter (identified by SPN).

5.3.1.7.2.1 Configuration Change

Should a transmitting CA know that it has changed message content it should send (re-send) the whole configuration identification list, thus this parameter would be '0', whether at start-up or during operation.


5.3.1.8 Starting Bit for this Parameter

The bit position within the configurable message being identified by the PGN in bytes 1-3 that the least significant bit of the data for the parameter, whose SPN is identified in bytes 4-6, is to occupy. This parameter will use an 8 bit SLOT with range of 0 to 250. Bit numbering is detailed below (see 5.3.1.8.1). Since this parameter identifies only the position of the least significant bit, it must be remembered that the length is to already be in the CA's parameter database (see 5.3.1.9.2). This parameter is to be in data byte 8 of the configuration message. (Note: While the data range maximum of 250 does not allow a full-length transport message to be generated it allows quite a long message, which was felt to be a suitable compromise necessary to generate this service. Remember this service is about improving throughput and an extremely long message certainly will not help that much).

Data Length: 8 bits (1 byte)
Resolution:
Data Range: 0 to 250
Type: Measured
Suspect Parameter Number: 3153
Reference: 5.3.1

5.3.1.8.1 Bit Numbering


The bit numbering within the data fields is defined with 1 for the least significant bit of the first data byte, 8 for the most significant bit of the first data byte, 9 for the least significant bit of the second data byte. . . (continuing sequence) , 57 for the least significant bit of the eighth data byte, and 64 for the most significant bit of the eighth data byte. For messages using SAE J1939 transport protocol the bit numbering is the same (remember however that the first data byte (bits 1 through 8) of each transport packet contains the sequence number). However for transport messages the complete bit identification is the sequence number times the bit number within the packet less eight (SAE J1939-21 3.10.1.2 Sequence Numbers & 3.10.1.3 Packetization). (Also remember that bits 1 through 8 of each packet are not available for data as they contain the sequence numbers). (see: Byte alignment requirements).



DATA FIELD BIT NUMBERING DRAWING FOR 5.3.1.8.1.

5.3.1.8.2 Bit Placement Within A Message

Bit placement should be sequential from the starting bit. For example an '11' bit parameter with a starting bit of 19 (message data byte 3 bit 3) should end (bit containing its MSB) at bit 29 (message data byte 4 bit 5).



EXAMPLE FOR 5.3.1.8.2

5.3.1.8.3 Placing Undefined Bits Within a Message

Undefined bits may be placed between parameters within a configured message (although the DLC is to be maintained at 8, see 5.4.1.2). By undefined bits it is meant, bits to which no parameter is associated. Undefined bits should simply be ignored by any receivers of the particular configured message. Since undefined bits have no particular parameter association they should have no meaning associated with them.

This feature is used when it is desired to justify a particular parameter to a specific bit location within the configured message. To accomplish this the user need simply start the particular parameter where desired, leaving however many undefined bits between it and the previous parameter.

5.3.1.8.4 Configured Message Length

The length of any given configured message may be undeterminable to the CA(s) receiving it. This is because the CAs are only required to know the length of any parameters (identified by SPN) that they wish to receive and the last parameter may not be one they want to receive. Hence, the total message length will be effectively unknown to them. Thus application software for configurable messaging does not need to check for length. Also any software that was cross linking layers and being used to check for length should be modified (updated) to recognize this possibility. Remember that data length of a message is always a number of bytes since the protocol controllers have no provision to send part of a byte.

5.3.1.9 *Requirements Related to Configuration Identification Message*

The Configuration Identification message (5.3.1) is used to identify the data content (by SPN) of any of the configurable messages (identified by their PGN). This identification is handled by reporting the location of one parameter within one message with each Configuration Identification Message. For this application to be useful some requirements (restrictions) must be enforced on all. Some SAE J1939 documents allow non-interference to be exchanged with compliance. This document, however, must be interpreted more literally and hence any failure to conform exactly is considered non-compliance. Since features or parameters may be added to this application, no CA should use this application (or its parameters and messages) without having provisions for field updating of its application software to the newest application level of the document.

5.3.1.9.1 When Must a Configuration Identification Message Be Used

The Configuration Identification is required whenever a CA is using any of the Configurable Messages (5.4 & 5.3). When identifying configurable messages using the word 'proprietary', it is meant that the data content of the particular configurable message can only be fully identified by combining the source and the destination addresses of the particular configurable message with the data content of all the configuration identification messages that have been sent for that particular configurable message.

5.3.1.9.2 CA Parameter Database

Receivers planning to use Configurable Messaging are required to know the SLOT of the parameters they are expecting to use. (They are not required to know the length of all existing parameters).

5.3.2 PARAMETER LOCATE MESSAGE

This message is designed to cause other CAs to respond with the identity of any message that they send in which the particular parameter (identified by specific SPN) is contained. A command byte (5.3.2.2) within this message is used to select the function to identify the location of a parameter. Other functions may be added later (in fact the remainder of the command byte is reserved). The destination to which this message is sent is to determine who answers. If the 'global' destination address is used then all CAs (supporting this function of course) that know and send the identified parameter will answer with a CONFIGURATION IDENTIFICATION MESSAGE identifying any message, where this parameter is presently being sent within 200 mS of the receipt of the Parameter Locate Message. If the parameter is not being sent then there will be no response sent. In light of this and the fact that the number messages containing a given SPN may not be known there must be time-outs (250 mS) in the CA sending the Parameter Locate Message to identify that no one is going to answer and/or that the answering is done. If this message is sent to a specific destination address then only the CA at that address should answer.

Transmission Rate: As needed

Data Length: 8

Data Page: 0

PDU Format: 175

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 44800

PARAMETER_LOCATE

Byte:	1	bits 8-1 Parameter to be located, 8 least significant bits	5.3.2.1
		(most significant at bit 8)	
Byte:	2	bits 8-1 Parameter to be located, second byte of SPN	
		(most significant at bit 8)	
Byte:	3	bits 8-6 Parameter to be located, 3 most significant bits	
		(most significant at bit 8)	
		bits 5-1 Reserved (to be '11111 ₂ ') (to be sent as '11111111 ₂ ') (to be sent as '11111111 ₂ ') (to be sent as '11111111 ₂ ') (to be sent as '11111111 ₂ ') (to be sent as '11111111 ₂ ')	
Byte:	4	bits 8-1 Reserved	
Byte:	5	bits 8-1 Reserved	
Byte:	6	bits 8-1 Reserved	
Byte:	7	bits 8-1 Reserved	
Byte:	8	bits 8-1 Parameter Locate Command	5.3.2.2

5.3.2.1 Parameter to be Located

This is the parameter, identified by SPN, that it is desired to locate or initiate the transmission of. Locating implies identifying any message from the given source (i.e. the destination of this Parameter LOCATE MESSAGE, all other CAs when 'global' address is used) that contains this particular parameter.

Data Length: 19 bit

Resolution: 1 parameter (or object)/count

Data Range: 0 to 524,287
 Type: Measured
 Suspect Parameter Number: 3154
 Reference: 5.3.2

5.3.2.2 *Parameter Locate Command*

A byte used to identify the particular command that the Parameter Locate message is presently being used for.

Data Length: 8 bit
 Resolution: 1 command/count
 Data Range: 0 with 1 to 250 reserved by SAE
 Type: Measured
 Suspect Parameter Number: 3155
 Reference: 5.3.2

5.3.2.2.1 Identify Parameter's Location

This is the state of the Parameter Locate Command parameter (value of '0') used to identify that the intent of this Parameter Locate message is to request that the position of a particular parameter (identified by SPN) within any transmitted message being used by the identified destination. This value is to mean that the position of said parameter within any message where it is presently being transmitted by the destination of this Parameter Locate message will be identified using a Configuration Identification message. The destination of this particular Parameter Locate message will identify whether all (the global destination address) other CAs, which contain the particular parameter or only a specific CA should answer with the messages.

5.3.3 REQUEST FOR COMPLETE CONFIGURABLE MESSAGE SET

This message is designed to cause all CAs to respond with the complete sequence of configuration identification messages for a particular one or all of the configurable messages that they send. The choice of all configurable messages or a particular one, identified by PGN, is controlled by the Message Selection Control parameter (5.3.3.1). A receiving CA which uses no configurable messages is not required to take any action in response to this request. The requesting CA must build the message set table and consider that any network CAs not heard from are not using this service.

Transmission Rate: As needed
 Data Length: 8
 Data Page: 0
 PDU Format: 253
 PDU Specific: 173
 Default Priority: 6
 Parameter Group Number: 64941

REQUEST_FOR_COMPLETE_CONFIGURABLE_MESSAGE_SET

Byte:	1	bits 8-1	Message selection control	5.3.3.1
Byte:	2-4		PGN of configurable message desired	5.3.3.2
			(bit order per SAE J1939-21 Table 2)	
Byte:	5	bits 8-1	Reserved	(to be sent as '11111111' ₂)
Byte:	6	bits 8-1	Reserved	(to be sent as '11111111' ₂)
Byte:	7	bits 8-1	Reserved	(to be sent as '11111111' ₂)
Byte:	8	bits 8-1	Reserved	(to be sent as '11111111' ₂)

5.3.3.1 Message Selection Control

This is the parameter that identifies whether the configuration set is desired for a particular configurable message or for all of the configurable messages.

Data Length: 8 bits
Resolution: 1 choice (or object)/count
Data Range: 0 and 1
Type: Measured
Suspect Parameter Number: 3329
Reference: 5.3.3

5.3.3.1.1 Identify All Configurable Messages

A '1' in this parameter signifies that it is desired to identify the configuration for all of the configurable messages in use by the receiver. The PGN of Configurable Message Desired parameter (5.3.3.2) is meaningless for this case and shall be ignored by any receiver.

5.3.3.1.2 Identify Particular Configurable Message

A '0' in this parameter signifies that it is desired to identify the configuration for a particular configurable message. That particular message will be identified by the PGN in the PGN of Configurable Message Desired parameter, 5.3.3.2.

5.3.3.2 PGN of Configurable Message Desired

This is the PGN of the configurable message whose configuration is being requested by this Request for Complete Configurable Message Set. A 3 byte slot is used. The all 1's value shall be transmitted when the request is for all configurable messages (5.3.3.1.1), otherwise the PGN of one of the configurable messages should be used. Should an invalid PGN be received the complete set for all of the configurable messages in use should be sent.

Data Length: 24 bits (3 bytes)
Resolution: 1 message/count

Data Range: (17 Numeric values, one for each configurable message, to be selected by database after ballot approval from the range 0, 256, ... 61184, 61440, 61441, ... 65535, 65536, 65792, ... 126720, 126976, 126977, ... 131071 – i.e. Only 8672 values are available/valid even though 24 bits and FFFFFFF16)

Type: Measured

Suspect Parameter Number: 3330

Reference: 5.3.3

5.4 The Set of Destination Specific Proprietarily Configurable Messages

This is the set of PDU type 1 messages that may be used in a proprietary fashion for sending only parameters defined within this SAE J1939 document (note: more parameters may be added at a later date). Configured messages from this set will be identified on the network using a Configuration Identification Message. Also note that since the use of these messages is destination specific the use of the global destination address (value 255) would not make sense and is hence not allowed. Should a receiving device detect one of these messages directed to the global address, it should consider the message meaningless and not to be processed (in other words just dispose of it).

5.4.1 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 1

The first message of the set assigned for use as a proprietarily configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 177

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 45312

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_1

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.1.1 Parameter Content of Destination Specific Proprietarily Configurable Messages

The parameters sent within any of the Proprietarily Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietarily Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietarily Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietarily Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietarily Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.1.2 *DLC for Destination Specific Proprietary Configurable Messages*

The minimum data length of each of the Destination Specific Proprietary Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.2 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 2

This is the second message in the set of messages assigned for use as a proprietary configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 178

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 45568

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_2

Byte: 1-8 As defined within the appropriate Configuration Identification Message(s)

5.4.2.1 *Parameter Content of Destination Specific Proprietary Configurable Messages*

The parameters sent within any of the Proprietary Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietary Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietary Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietary Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietary Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.2.2 *DLC for Destination Specific Proprietary Configurable Messages*

The minimum data length of each of the Destination Specific Proprietary Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.3 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 3

This is the third message in the set of messages assigned for use as a proprietarily configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 179

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 45824

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_3

Byte: 1-8 As defined within the appropriate Configuration Identification Message(s)

5.4.3.1 Parameter Content of Destination Specific Proprietarily Configurable Messages

The parameters sent within any of the Proprietarily Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietarily Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietarily Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietarily Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietarily Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.3.2 DLC for Destination Specific Proprietarily Configurable Messages

The minimum data length of each of the Destination Specific Proprietarily Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.4 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 4

This is the fourth message in the set of messages assigned for use as a proprietarily configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 180

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 46080

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_4

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.4.1 Parameter Content of Destination Specific Proprietary Configurable Messages

The parameters sent within any of the Proprietary Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietary Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietary Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietary Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietary Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.4.2 DLC for Destination Specific Proprietary Configurable Messages

The minimum data length of each of the Destination Specific Proprietary Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.5 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 5

This is the fifth message in the set of messages assigned for use as a proprietary configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 181

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 46336

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_5

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.5.1 *Parameter Content of Destination Specific Proprietary Configurable Messages*

The parameters sent within any of the Proprietary Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietary Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietary Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietary Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietary Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.5.2 *DLC for Destination Specific Proprietary Configurable Messages*

The minimum data length of each of the Destination Specific Proprietary Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.6 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 6

This is the sixth message in the set of messages assigned for use as a proprietary configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 182

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 46592

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_6

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.6.1 *Parameter Content of Destination Specific Proprietary Configurable Messages*

The parameters sent within any of the Proprietary Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietary Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietary Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietary Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietary Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.6.2 *DLC for Destination Specific Proprietary Configurable Messages*

The minimum data length of each of the Destination Specific Proprietary Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.7 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 7

This is the seventh message in the set of messages assigned for use as a proprietary configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 183

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 46848

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_7

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.7.1 *Parameter Content of Destination Specific Proprietary Configurable Messages*

The parameters sent within any of the Proprietary Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietary Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietary Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietary Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietary Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.7.2 *DLC for Destination Specific Proprietary Configurable Messages*

The minimum data length of each of the Destination Specific Proprietary Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.8 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 8

This is the eighth message in the set of messages assigned for use as a proprietarily configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 184

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 47104

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_8

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.8.1 Parameter Content of Destination Specific Proprietarily Configurable Messages

The parameters sent within any of the Proprietarily Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietarily Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietarily Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietarily Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietarily Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.8.2 DLC for Destination Specific Proprietarily Configurable Messages

The minimum data length of each of the Destination Specific Proprietarily Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.9 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 9

This is the ninth message in the set of messages assigned for use as a proprietarily configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 185

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 47360

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_9

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.9.1 Parameter Content of Destination Specific Proprietary Configurable Messages

The parameters sent within any of the Proprietary Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietary Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietary Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietary Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietary Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.9.2 DLC for Destination Specific Proprietary Configurable Messages

The minimum data length of each of the Destination Specific Proprietary Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.10 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 10

This is the tenth message in the set of messages assigned for use as a proprietary configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 186

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 47616

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_10

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.10.1 Parameter Content of Destination Specific Proprietary Configurable Messages

The parameters sent within any of the Proprietary Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietary Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietary Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietary Configurable Message.

Remember that only parameters from within this document are to be included within any Destination Specific Proprietary Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.10.2 DLC for Destination Specific Proprietary Configurable Messages

The minimum data length of each of the Destination Specific Proprietary Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.11 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 11

This is the eleventh message in the set of messages assigned for use as a proprietary configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 187

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 47872

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_11

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.11.1 Parameter Content of Destination Specific Proprietary Configurable Messages

The parameters sent within any of the Proprietary Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietary Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietary Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietary Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietary Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.11.2 DLC for Destination Specific Proprietary Configurable Messages

The minimum data length of each of the Destination Specific Proprietary Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.12 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 12

This is the twelfth message in the set of messages assigned for use as a proprietarily configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 188

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 48128

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_12

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.12.1 Parameter Content of Destination Specific Proprietarily Configurable Messages

The parameters sent within any of the Proprietarily Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietarily Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietarily Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietarily Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietarily Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.12.2 DLC for Destination Specific Proprietarily Configurable Messages

The minimum data length of each of the Destination Specific Proprietarily Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.13 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 13

This is the thirteenth message in the set of messages assigned for use as a proprietarily configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 189

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 48384

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_13

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.13.1 Parameter Content of Destination Specific Proprietary Configurable Messages

The parameters sent within any of the Proprietary Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietary Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietary Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietary Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietary Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.13.2 DLC for Destination Specific Proprietary Configurable Messages

The minimum data length of each of the Destination Specific Proprietary Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.14 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 14

This is the fourteenth message in the set of messages assigned for use as a proprietary configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 190

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 48640

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_14

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.14.1 Parameter Content of Destination Specific Proprietary Configurable Messages

The parameters sent within any of the Proprietary Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietary Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietary Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietary Configurable Message.

Remember that only parameters from within this document are to be included within any Destination Specific Proprietary Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.14.2 DLC for Destination Specific Proprietary Configurable Messages

The minimum data length of each of the Destination Specific Proprietary Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.15 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 15

This is the fifteenth message in the set of messages assigned for use as a proprietary configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 191

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 48896

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_15

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.15.1 Parameter Content of Destination Specific Proprietary Configurable Messages

The parameters sent within any of the Proprietary Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietary Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietary Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietary Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietary Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.15.2 DLC for Destination Specific Proprietary Configurable Messages

The minimum data length of each of the Destination Specific Proprietary Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.4.16 DESTINATION SPECIFIC PROPRIETARILY CONFIGURABLE MESSAGE 16

This is the sixteenth message in the set of messages assigned for use as a proprietarily configurable destination specific message.

Transmission Rate: As needed

Data Length: 8 to n (based on Configuration Identification Message, see 5.3.1.6)

Data Page: 0

PDU Format: 192

PDU Specific: DA

Default Priority: 6

Parameter Group Number: 49152

DESTINATION_SPECIFIC_PROPRIETARILY_CONFIGURABLE_MESSAGE_16

Byte: 1-n As defined within the appropriate Configuration Identification Message(s)

5.4.16.1 Parameter Content of Destination Specific Proprietarily Configurable Messages

The parameters sent within any of the Proprietarily Configurable Messages are identified within a set of Configuration Identification Messages each of which contains the PGN of the particular Destination Specific Proprietarily Configurable Message. Each of the Configuration Identification Messages also contains the location information for a single SPN. Thus a CA sending a particular Destination Specific Proprietarily Configurable Message with 'n' parameters will need to send 'n' Configuration Identification Messages to any CA it wishes to decode said Destination Specific Proprietarily Configurable Message. Remember that only parameters from within this document are to be included within any Destination Specific Proprietarily Configurable Message (presently the committee has chosen to not allow configurable messaging with parameters from other SAE J1939 document(s)).

5.4.16.2 DLC for Destination Specific Proprietarily Configurable Messages

The minimum data length of each of the Destination Specific Proprietarily Configurable Messages is to be 8. Hence, the DLC will be 8. (Remember the DLC is the packet data length and not the message data length.) Any bits within the message which have not had parameters associated shall be sent as '1' (5.3.1.8.3). This is the most general form found for other SAE J1939 messages, although there are a few special cases where the DLC is other than 8. The packet DLC will be 8, even when transport protocol is used, because the total message data length exceeds 8 (see 5.3.1.6).

5.5 The Set of Parameters for Use Within the Configurable Messages

The set of parameters available for use within the Configurable messages is contained within Appendix C. Certain operational rules still apply to these parameters just like any others from other SAE J1939 documents. When one of the parameters from this set is used, it will be transmitted on the network in one of the Configurable messages and its location within said message will have been identified on the network using the Configuration Identification Message.

6. Notes

6.1 Marginal Indicia

The change bar (I) located in the left margin is for the convenience of the user in locating areas where technical revisions have been made to the previous issue of the report. An (R) symbol to the left of the document title indicates a complete revision of the report.

PREPARED BY THE SAE TRUCK AND BUS CONTROL AND COMMUNICATIONS NETWORK
SUBCOMMITTEE OF THE SAE TRUCK AND BUS ELECTRICAL AND ELECTRONICS COMMITTEE

SAE J1939-74 Revised NOV2006

APPENDIX A
ASSUMPTIONS USED TO DESIGN CONFIGURABLE MESSAGING

A.1 *Assumptions Used In the Design of Configurable Messaging*

- A.1.1** Some applications require pre-defined parameters but must have groupings (messages) that can be reconfigured when the vehicle is 'built'.
- A.1.2** Message reconfiguration does not need to be dynamic but there is no need to eliminate the possibility if not required simply to complete the design.
- A.1.3** Some will desire to re-group existing parameters, while others will wish to re-group only members of a special set. Hence allow for both if possible.
- A.1.4** Some will desire proprietary message definition and some will not, so again allow both if possible.
- A.1.4.1** To allow proprietary identification requires that the 'identification' message to be destination specific so choose that.
- A.1.5** Some will desire destination specific and some global destination so again allow both. However since the interpretation of a global proprietary message would have to be the same to all CAs it reduces to the same case as the global destination non-proprietary message.
- A.1.5.1** Hence need three set of messages.
- A.1.6** Since regrouping is essentially a time improvement scheme there is no real need for a large number of messages or for extremely long messages. They both kind of defeat the purpose.
- A.1.6.1** So as a first guess try 16 messages in each set of messages.
- A.1.7** Some will desire this process, while others will hope to avoid it entirely, so assign it to an entirely new application document.
- A.1.8** Some will wish to place SPNs at specific bit boundaries within the message so as to ease software in some fashion, so allow 'unused' bit to separate SPNs.
- A.1.9** Since will need to know things (length, SLOT, etc.) about an SPN to use it, this might as well be a requirement for use of this process and it can be designed that way.
- A.1.10** Once the capability to identify where an SPN is sent, why not have a means of asking where they are being sent. Hence create a 'Locate SPN' message, which can request the identification of any message in which the particular SPN is presently being sent.
- A.1.11** While there is space within the message structure to allow for other functions within the SPN Locate message it is felt by the working group that no other functions should be pursued at this time.

- A.1.12** Configuration maps should be made with an association of function, of CA, and of the NAME of Address Claimed parameter using address tables to translate between network address and CA NAME. (This is not to imply that the indexing structure of the software should use the NAME of Address Claimed parameter but only that the expansion along a particular completed path through the indexing structure should identify a specific NAME of Address Claimed). This way it is possible for a CA to recognize that it has been moved or that another CA has been changed and then appropriately request the configuration of the new network. Note that a CA need only request a configuration update if a CA that it communicates with using a configurable message has been changed (in other words if the change is in a CA that is not communicated with, there is no need to form a configuration map).
- A.1.13** A separate message has been added to allow the determination of the complete set of configurable messages in use on the vehicle.

APPENDIX B APPLICATION RULES REGARDING CONFIGURABLE MESSAGING

B.1 General Rules

The following general rules must be adhered to:

- B.1.1** When a Configuration Identification Message is sent to the 'global' destination address the configuration must remain independent of the destination address. This should in general only be done with a configurable message from either the set of destination specific non-proprietary configurable messages or the set of global destination non-proprietary configurable messages.
- B.1.2** Messages should in general only be sent to a specific destination when they are from the set of destination specific proprietary configurable messages.
- B.1.3** For a CA seeking to find the configuration of messages on a network, when it has powered up separately from the rest of the network (such as a tool being plugged in), a Request for Complete Configurable Message Set may be sent. If the configuration need only be verified then the 'Request for Configuration Identification Message' can be sent to the global destination so that everyone sending configurable messages answers with the shortened form (i.e. only the first SPN for each of the configurable messages (see 5.3.1.7 & 5.2.3.1)).
- B.1.4** A Tool sending a destination specific request for message for the PGN of the Configuration Identification Message must watch for any Configuration Identification Messages sent on the network. These Configuration Identification messages are to be sent to the normally intended destinations address. There should also be the number of messages to the particular address that there are SPNs in the Configured Message.

The tool may obtain the complete configuration of an operating vehicle by sending Request for Complete Configurable Message Set on the network (remember this is not merely to all CAs, since any given CA may have more than one address). The tool will need to maintain the association between the source and destination addresses of any Configuration Identification Messages sent for members of the set of Destination Specific Proprietary Configurable Messages with the data, since the CA may be configuring communications with CAs other than the tool. Hence the messages may not have been addressed to the tool, thus the destination address of the Configuration Identification Messages will not necessarily be the tool's address.

- B.1.5** If a Tool has made a Request for message of the PGN of the Configuration Identification Message to the 'global destination address', then the Tool will only see the Configuration Identification Messages of the first SPN (5.3.1.7) of each of the Configured Messages used within the network.
- B.1.6** CAs sending configured messages must answer a Request for message for the PGN of the Configuration Identification Message with all of the configurations that they use (see also 5.2.3.1.1).

B.2 Message Exchange Rules

Presently all exchange rules are outlined within the main sections of the document and are not repeated here.

APPENDIX C PARAMETERS FOR CONFIGURABLE MESSAGING

C.1 General Items

The same general issues of SLOT, Type, Length, Operating Range, Units as identified in –71 must be adhered to for parameters for configurable messaging.

C.2 Parameter Design Rules

Presently the rules to assist in creating a new parameter are in development.

C.3 Parameter List

SPN 1488 *Thresher Speed*

Speed of the thresher such as found in a combine

Data Length: 2 bytes

Resolution: 0.125 rpm/bit, 0 offset

Data Range: 0 to 8,031.875 rpm Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1489 *Cleaning Fan Speed*

The speed of the cleaning fan

Data Length: 1 byte

Resolution: 10 rpm/bit, 0 offset

Data Range: 0 to 2,500 rpm Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1490 *Header Backshaft Speed*

The speed of the feederhouse. The feederhouse is the entry point of crop into the combine

Data Length: 2 bytes

Resolution: 1 rpm/bit, 0 offset

Data Range: 0 to 64255 rpm Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1497 Unloading Auger Drive

The mode of the unloading Auger driver

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits
Resolution: 4 states/2 bit, 0 offset
Data Range: 0 to 3 Operational Range: same as data range
Type: Measured
Supporting information:
PGN reference:

SPN 1498 Header Drive

The mode of the Header driver

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits
Resolution: 4 states/2 bit, 0 offset
Data Range: 0 to 3 Operational Range: same as data range
Type: Measured
Supporting information:
PGN reference:

SPN 1499 Separator Drive

The mode of the Separator driver

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits
Resolution: 4 states/2 bit, 0 offset
Data Range: 0 to 3 Operational Range: same as data range
Type: Measured
Supporting information:
PGN reference:

SPN 1505 Automatic Header Sensitivity Adjustment

A control system parameter. This is the sensitivity adjustment to the automatic header control loop.

Data Length: 1 byte
Resolution: 0.4 %/bit, 0 offset
Data Range: 0 to 100 % Operational Range: same as data range
Type: Status
Supporting information:
PGN reference:

SPN 1506 *Automatic Header Rate Adjustment Input*

An adjustment to the response rate of the automatic header control loop.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 1508 *Hydraulic Reservoir Temperature*

The temperature of the hydraulic fluid, measured in the hydraulic reservoir.

Data Length: 1 byte

Resolution: 1 deg C/bit, -40 deg C offset

Data Range: -40 to 210 deg C

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1509 *Thresher Separator Hydraulic Drive 1 Temperature*

The temperature of the hydraulic fluid in the Thresher Separator Hydraulic Drive #1 gear case

Data Length: 1 byte

Resolution: 1 deg C/bit, -40 deg C offset

Data Range: -40 to 210 deg C

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1510 *Chopper Vane Angle Adjustment*

The control adjustment of the chopper vane angle. This is relative to the centerline of the machine. Negative is to the left of the centerline of the machine facing forward.

Data Length: 1 byte

Resolution: 1 deg/bit, -125 deg offset

Data Range: -125 to 125 deg

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 1511 *Right side Cleaning Shoe Relative Grain Loss*

A scalar that represents an amount of grain loss exiting the right side of the cleaning shoe

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1512 *Left side Cleaning Shoe Relative Grain Loss*

A scalar that represents an amount of grain loss exiting the left side of the cleaning shoe

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 % Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1513 *Right side Separator Relative Grain Loss*

The amount of grain loss at the right side of the separator

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 % Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1514 *Left side Separator Relative Grain Loss*

The amount of grain loss at the left side of the separator

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 % Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1517 *Header Lift Cylinder Pressure*

The pressure in the header lift cylinder

Data Length: 1 byte

Resolution: 50 kPa/bit, 0 offset

Data Range: 0 to 12,500 kPa Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1518 *Header Sensor Identification*

The system identification of the header sensor configuration. e.g. Ultrasonic sensor, ground contacting sensors, flex pressure sensors, etc. This can be used as a map type ID to know which sensors are installed and their location on the system.

Data Length: 1 byte

Resolution: 1 count/bit, 0 offset

Data Range: 0 to 250 Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1519 Header Raise Valve Drive

The mode of the Header raise valve driver

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1520 Header Lower Valve Drive

The mode of the Header lower valve driver

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1521 Header Tilt Left Valve Drive

The mode of the Header tilt left valve driver

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1522 Header Tilt Right Valve Drive

The mode of the Header tilt right valve driver

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1523 Header Lift Cylinder Pressure Diverted Valve Drive

The mode of the diverted valve driver, related to the Header lift cylinder pressure

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1524 Reel Position Forward Actuator

The mode of the Reel position forward actuator

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1525 Reel Position Aft Actuator

The mode of the Reel position aft actuator

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1526 Reel Position Raise Actuator

The mode of the Reel position raise actuator

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1527 *Reel Position Lower Actuator*

The mode of the Reel position lower actuator

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits
Resolution: 4 states/2 bit, 0 offset
Data Range: 0 to 3 Operational Range: same as data range
Type: Measured
Supporting information:
PGN reference:

SPN 1528 *Header Drop Rate Control Valve Drive*

The mode of the driver for the valve which controls the drop rate of the header

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits
Resolution: 4 states/2 bit, 0 offset
Data Range: 0 to 3 Operational Range: same as data range
Type: Measured
Supporting information:
PGN reference:

SPN 1529 *Header Lift Cylinder Accumulator Shutoff Valve Drive*

The mode of the driver for the Header Lift Cylinder Accumulator Shutoff Valve

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits
Resolution: 4 states/2 bit, 0 offset
Data Range: 0 to 3 Operational Range: same as data range
Type: Measured
Supporting information:
PGN reference:

SPN 1530 *Unloading auger flow bypass valve drive*

The mode of the driver for the unloading auger flow bypass valve

00 - Off
01 - On
10 - Error
11 - Not available or not installed

Data Length: 2 bits
Resolution: 4 states/2 bit, 0 offset
Data Range: 0 to 3 Operational Range: same as data range
Type: Measured
Supporting information:
PGN reference:

SPN 1531 *Reel Drive Motor Speed Increase Valve Drive*

The mode of the driver for the reel drive motor speed increase valve.

00 - Off

01 - On

10 - Error

11 - Not available or not installed

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1532 *Reel Drive Motor Speed Decrease Valve Drive*

The mode of the driver for the reel drive motor speed decrease valve.

00 - Off

01 - On

10 - Error

11 - Not available or not installed

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1534 *Header Leftmost Height*

Height of: Left (or left side of) header, measured relative to the ground

Data Length: 2 bytes

Resolution: 0.1 mm/bit, 0 offset

Data Range: 0 to 6,425.5 mm (0 to 6.4255m) Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1535 *Header Rightmost Height*

Height of: right (or right side of) header, measured relative to the ground

Data Length: 2 bytes

Resolution: 0.1 mm/bit, 0 offset

Data Range: 0 to 6,425.5 mm (0 to 6.4255m) Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1536 Header Center Height

Height of: center (or center of the) header, measured relative to the ground

Data Length: 2 bytes

Resolution: 0.1 mm/bit, 0 offset

Data Range: 0 to 6,425.5 mm (0 to 6.4255m) Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1537 Reel Fore-Aft Position

A mechanical range of adjustment to position the reel along this axis. 0% to be toward the rear of the machine, 100% toward the front end.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 % Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1538 Reel Up-Down Position

A mechanical range of adjustment to position the reel along this axis. 0% to be toward the ground & 100% will be in the vertical upward direction

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 % Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1539 Header Lateral Tilt Angle

The lateral tilt angle of the header (feederhouse) relative to the combine chassis. Negative angle is a CCW rotation from straight ahead. A Positive angle is CW from straight ahead

Data Length: 1 byte

Resolution: 0.1 deg/bit, -12.5 deg offset

Data Range: -12.5 to 12.5 deg Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1540 Reel Speed Actuator Position

The position of the Reel speed actuator. 0% indicates the slowest speed possible and 100% indicates the fastest reel speed possible

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 % Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 1541 *Reel Speed*

The rotational velocity of the Reel. The Reel is a device on the platform that pushes the crop onto the header.

Data Length: 2 bytes
 Resolution: 1 rpm/bit, 0 offset
 Data Range: 0 to 64255 rpm Operational Range: same as data range
 Type: Measured
 Supporting information:
 PGN reference:

SPN 1554 *Clean Grain Elevator Speed*

The speed of the clean grain elevator

Data Length: 2 bytes
 Resolution: 1 rpm/bit, 0 offset
 Data Range: 0 to 64255 rpm Operational Range: same as data range
 Type: Measured
 Supporting information:
 PGN reference:

SPN 2989 *Combine separator speed*

Speed of the Combine separator.

Data Length: 2 bytes
 Resolution: 0.125 rpm/bit, 0 offset
 Data Range: 0 to 8,031.875 rpm Operational Range: same as data range
 Type: Measured
 Supporting information:
 PGN reference:

SPN 2991 *Tailings volume*

Tailings Elevator Volume measurement (as a percent of full). Zero percent represents empty.

Data Length: 1 byte
 Resolution: 0.4 %/bit, 0 offset
 Data Range: 0 to 100 % Operational Range: same as data range
 Type: Measured
 Supporting information:
 PGN reference:

SPN 2992 *Move reel forward*

Move the platform reel toward the forward part of the machine.

00 Stop
 01 Move
 10 Reserved
 11 Don't care/take no action

Data Length: 2 bits
 Resolution: 4 states/2 bit, 0 offset
 Data Range: 0 to 3 Operational Range: same as data range
 Type: Status
 Supporting information:
 PGN reference:

SPN 2993 *Move reel aft*

Move the platform reel toward the back part of the machine.

00 Stop
01 Move
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 2994 *Reel raise*

Raise the platform reel.

00 Stop
01 Raise
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 2995 *Reel lower*

Lower the platform reel.

00 Stop
01 Lower
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 2996 *Header raise slow*

Raise the header (slow speed mode).

00 Stop
01 Raise
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 2997 Header lower slow

Lower the header (slow speed mode).

00 Stop
01 Lower
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 2998 Header raise fast

Raise the header (fast speed mode).

00 Stop
01 Raise
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 2999 Header lower fast

Lower the header (fast speed mode).

00 Stop
01 Lower
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3000 Tilt header left

Tilt the header down to the left.

00 Stop
01 Tilt
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3001 *Tilt header right*

Tilt the header down to the right.

00 Stop
01 Tilt
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3002 *Header fold*

Fold the header in.

00 Stop
01 Fold
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3003 *Header unfold*

Unfold the header.

00 Stop
01 Unfold
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3004 *Draper speed increment*

Increase speed of the draper.

00 Stop
01 Increase
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3005 *Draper speed decrement*

Decrease speed of the draper.

00 Stop
01 Decrease
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3006 *Reel speed increment*

Increase the platform reel speed.

00 Stop
01 Increase
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3007 *Reel speed decrement*

Decrease the platform reel speed.

00 Stop
01 Decrease
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3008 *Threshing clearance increment*

Increase threshing clearance.

00 Stop
01 Increase
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3009 *Threshing clearance decrement*

Decrease threshing clearance.

00 Stop
01 Decrease
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3010 *Threshing speed increment*

Increase threshing speed.

00 Stop
01 Increase
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3011 *Threshing speed decrement*

Decrease threshing speed.

00 Stop
01 Decrease
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3012 *Product fan speed increment*

Increase Product fan speed. The Product may be either the harvested crop material or the material being applied or handled.

00 Stop
01 Increase
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3013 *Product fan speed decrement*

Decrease Product fan speed. The Product may be either the harvested crop material or the material being applied or handled.

00 Stop
01 Decrease
10 Reserved
11 Don't care/take no action

Data Length: 2 bits
Resolution: 4 states/2 bit, 0 offset
Data Range: 0 to 3 Operational Range: same as data range
Type: Status
Supporting information:
PGN reference:

SPN 3015 *Implement fold down*

Move the implement down from travel to work position

00 Stop
01 Move
10 Reserved
11 Don't care/take no action

Data Length: 2 bits
Resolution: 4 states/2 bit, 0 offset
Data Range: 0 to 3 Operational Range: same as data range
Type: Status
Supporting information:
PGN reference:

SPN 3016 *Implement fold up*

Move the implement up from work to travel position.

00 Stop
01 Move
10 Reserved
11 Don't care/take no action

Data Length: 2 bits
Resolution: 4 states/2 bit, 0 offset
Data Range: 0 to 3 Operational Range: same as data range
Type: Status
Supporting information:
PGN reference:

SPN 3017 *RH header raise*

Raise the right hand header of the system.

00 Stop
01 Raise
10 Reserved
11 Don't care/take no action

Data Length: 2 bits
Resolution: 4 states/2 bit, 0 offset
Data Range: 0 to 3 Operational Range: same as data range
Type: Status
Supporting information:
PGN reference:

SPN 3018 *LH header raise*

Raise the left hand header of the system.

00 Stop
01 Raise
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3019 *Product fan engage mode*

Engage/disengage the (harvested or applied) Product fan. The Product may be either the harvested crop material or the material being applied or handled.

00 Disengage
01 Engage
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3020 *Augers engage mode*

Engage/disengage all the augers.

00 Disengage
01 Engage
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3021 *Product basket fill state*

The state of the capacity of the Product storage basket.

00 Not Full
01 Full
10 Error
11 Not Available

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3022 *Augers enable mode*

Enable/disable all the augers.

00 Disable
01 Enable
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3023 *Header height control mode*

Header height controller engaged/disengaged.

00 Not Engaged
01 Engaged
10 Error
11 Not available

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3024 Header remote tether control mode

Tether control mode of the Product Handling system. Used for remote operator control of the headers.

00 Off
01 On
10 Error
11 Not available

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3025 Lubrication control mode

Lubrication control of the Product Handling system.

00 Off
01 On
10 Error
11 Not available

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3032 Right Brake Pedal Position

Ratio of the right brake pedal position to maximum right brake pedal position. 0% means no braking. The maximum of this (Right Brake Pedal Position) and SPN 3033 (Left Brake Pedal Position) should be transmitted as SPN 521 (Brake Pedal Position). For applications with only one brake pedal use SPN 521.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3033 Left Brake Pedal Position

Ratio of the left brake pedal position to maximum left brake pedal position. 0% means no braking. The maximum of this (Left Brake Pedal Position) and SPN 3032 (Right Brake Pedal Position) should be transmitted as SPN 521 (Brake Pedal Position). For applications with only one brake pedal use SPN 521.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3042 Requested Wheel Speed

When at rated engine speed, this is the wheel speed that the transmission will attempt to attain. This is actually equivalent to a gear ratio command that would produce the stated wheel speed at rated engine speed. If the actual engine speed is higher or lower than rated speed then the actual wheel speed will be higher or lower than the value sent in this parameter.

Data Length: 2 bytes
 Resolution: 2 m/h per bit, 0 offset
 Data Range: 0 to 128510 m/h Operational Range: same as data range
 Type: Status
 Supporting information:
 PGN reference:

SPN 3088 Header height vertical rate control

Setting for the header height raise/lower control speed rate

Data Length: 1 byte
 Resolution: 0.4 %/bit, 0 offset
 Data Range: 0 to 100 % Operational Range: same as data range
 Type: Status
 Supporting information:
 PGN reference:

SPN 3089 Header height sensitivity control

Control setting for the header height system's sensitivity to ground contour changes

Data Length: 1 byte
 Resolution: 0.4 %/bit, 0 offset
 Data Range: 0 to 100 % Operational Range: same as data range
 Type: Status
 Supporting information:
 PGN reference:

SPN 3090 Header height setpoint change

Number of clicks of the encoder used for header height setting since last transmitted CAN message

Data Length: 1 byte
 Resolution: 1 count/bit, -125 offset
 Data Range: -125 to 125 counts Operational Range: same as data range
 Type: Status
 Supporting information:
 PGN reference:

SPN 3091 Header height setpoint change sequence number

Sequence number of the Header Height Setpoint Change

Data Length: 1 byte
 Resolution: 1 count/bit, 0 offset
 Data Range: 0 to 250 Operational Range: same as data range
 Type: Status
 Supporting information:
 PGN reference:

SPN 3092 *Header platform height*

Height of the cutting platform

Data Length: 2 bytes

Resolution: 1 mm/bit, 0 offset

Data Range: 0 to 64,255 mm (0 to 64.255 m) Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3093 *Header platform height maximum*

Maximum height of the cutting platform.

Data Length: 2 bytes

Resolution: 1 mm/bit, 0 offset

Data Range: 0 to 64,255 mm (0 to 64.255 m) Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3096 *Header float pressure*

Pressure of the header height system lift cylinders.

Data Length: 1 byte

Resolution: 50 kPa/bit, 0 offset

Data Range: 0 to 12,500 kPa Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3097 *Header float pressure maximum*

Maximum pressure of the header height system lift cylinders

Data Length: 1 byte

Resolution: 50 kPa/bit, 0 offset

Data Range: 0 to 12,500 kPa Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3098 *Header position percent*

Header height position, as a percent of maximum

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 % Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3099 *Header position percent maximum*

Maximum mechanically allowable header height as a percentage of the allowed display height.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3102 *Unloading Auger swing out*

Swing the unloading auger out, away from vehicle

00 Off

01 On

10 Reserved

11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3103 *Unloading auger swing in*

Swing the unloading auger in, toward the vehicle

00 Off

01 On

10 Reserved

11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3104 *Unloading auger swing out-auto*

Swing the unloading auger out, away from the vehicle, auto mode

00 Off

01 On

10 Reserved

11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3105 *Unloading auger swing in-auto*

Swing the unloading auger in, toward the vehicle, auto mode

- 00 Off
- 01 On
- 10 Reserved
- 11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3106 *Side hill left tilt*

Tilt the machine chassis down to the left

- 00 Off
- 01 On
- 10 Reserved
- 11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3107 *Side hill right tilt*

Tilt the machine chassis down to the right

- 00 Off
- 01 On
- 10 Reserved
- 11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3108 *Spreader speed increment*

Increase the speed of the spreader

- 00 Off
- 01 On
- 10 Reserved
- 11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3109 *Spreader speed decrement*

Decrease the speed of the spreader

00 Off
01 On
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3110 *Precleaner open*

Open the precleaner

00 Off
01 On
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3111 *Precleaner close*

Close the precleaner

00 Off
01 On
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3112 *Open chaffer*

Open the chaffer

00 Off
01 On
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3113 *Close chaffer*

Close the chaffer

00 Off
01 On
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3114 *Open sieve*

Open the sieve

00 Off
01 On
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3115 *Close sieve*

Close the sieve

00 Off
01 On
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3116 *Move chopper vane left*

Move the chopper vane towards the left side of the machine

00 Off
01 On
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3117 *Move chopper vane right*

Move the chopper vane towards the right side of the vehicle

- 00 Off
- 01 On
- 10 Reserved
- 11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3118 *Quick stop switch*

Master quick stop switch for stopping the product related systems on the vehicle.

- 00 Off
- 01 On
- 10 Reserved
- 11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3119 *Unloading auger engage/disengage*

Engage or disengage the (single) unloading auger

- 00 Off
- 01 On
- 10 Reserved
- 11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3120 *Unloading auger fold*

Fold the unloading auger

- 00 Off
- 01 On
- 10 Reserved
- 11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3121 *Unloading auger unfold*

Unfold the unloading auger

00 Off
01 On
10 Reserved
11 Don't care/take no action

Data Length: 2 bits

Resolution: 4 states/2 bit, 0 offset

Data Range: 0 to 3

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3122 *Max allowable cleaning shoe travel*

Max cleaning shoe travel allowed

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3123 *Right hand header height setpoint*

Setpoint for the machine to control to.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3124 *Left hand header height setpoint*

Setpoint for the machine to control to.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3125 *Left hand header height*

Height of the Left hand header.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3126 *Right hand header height*

Height of the Right hand header.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3127 *Header control response rate setpoint*

Setpoint for the machine to control to. Rate of response to header control command changes

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3128 *Header control response rate maximum setpoint*

Header control response rate maximum setpoint. Limits are usually determined by calibration process.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3129 *Header control response rate minimum setpoint*

Header control response rate minimum setpoint. Limits are usually determined by calibration process.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3130 *Product system tank water level*

Product system tank water level

Data Length: 2 bytes

Resolution: 0.5 L/bit, 0 offset

Data Range: 0 to 32127.5 liters

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3131 *Product fan speed*

Product fan speed

Data Length: 2 bytes

Resolution: 1 rpm/bit, 0 offset

Data Range: 0 to 64255 rpm

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3132 *Product system manifold pressure*

Pressure of the liquid in the product system as measured at the manifold or main distribution point.

Data Length: 1 byte

Resolution: 5 kPa/bit, 0 offset

Data Range: 0 to 1,250 kPa

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3133 *Product system pump discharge pressure*

Pressure of the liquid in the product system as measured at the pump discharge

Data Length: 2 bytes

Resolution: 0.5 kPa/bit, 0 offset

Data Range: 0 to 32,127.5 kPa

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3134 *Product fan hours*

Total Product fan running hours.

Data Length: 2 bytes

Resolution: 0.1 hr/bit, 0 offset

Data Range: 0 to 6,425.5 hours

Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3135 *Right hand header height max setpoint*

Maximum setpoint measured during calibration. Used to set max limit of control range.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 %

Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3136 *Right hand header height min setpoint*

Minimum setpoint measured during calibration. Used to set min limit of control range.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 % Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3137 *Left hand header height min setpoint*

Minimum setpoint measured during calibration. Used to set min limit of control range.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 % Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3138 *Left hand header height max setpoint*

Maximum setpoint measured during calibration. Used to set max limit of control range.

Data Length: 1 byte

Resolution: 0.4 %/bit, 0 offset

Data Range: 0 to 100 % Operational Range: same as data range

Type: Status

Supporting information:

PGN reference:

SPN 3139 *Right hand header unit speed*

Right hand header unit speed

Data Length: 2 bytes

Resolution: 1 rpm/bit, 0 offset

Data Range: 0 to 64255 rpm Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3140 *Left hand header unit speed*

Left hand header unit speed.

Data Length: 2 bytes

Resolution: 1 rpm/bit, 0 offset

Data Range: 0 to 64255 rpm Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference:

SPN 3329 *Message Selection Control*

Used to identify all configurable messages.

Data Length: 1 byte

Resolution: 1 count/bit, 0 offset

Data Range: 0 to 250 Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference: 64941

SPN 3330 *PGN of Configurable Message Desired*

To identify the configurable message whose configuration is being requested. If the request is for all configurable PGNs then this SPN is set to all ones.

Data Length: 3 bytes

Resolution: Binary, 0 offset

Data Range: 0 to 16,777,215 Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference: 64941

SPN 3333 *Feederhouse Height*

The height of the Feederhouse as measured from the ground to the bottom of the Feederhouse

Data Length: 2 bytes

Resolution: 1 mm/bit, 0 offset

Data Range: 0 to 64,255 mm (0 to 64.255 m) Operational Range: same as data range

Type: Measured

Supporting information:

PGN reference: