

ChromeFileEditViewHistoryBookmarksProfilesTabWindowHelp

Notes/CCNA/SN-CN-B1/St xUntitled xPNETLab | Topology xlab4 static xStatic Route Configuration xAsk Gemini

labs.surennetwork.com/legacy/topology

Notifications

Terminal

Win-1 xWin-2 xR1 xR2 xR3 x

My Documents

My Computer

My Network Places

Recycle Bin

Internet Explorer

Cisco ASDM-1...

Old Java ASDM

Putty

Tftp32

Start

C:\WINDOWS\system32\cmd.exe

Windows IP Configuration

Ethernet adapter Local Area Connection:

Connection-specific DNS Suffix . : 10.0.0.10

IP Address. : 255.0.0.0

Subnet Mask : 10.0.0.1

Default Gateway

C:\Documents and Settings\User>ping 40.0.0.10

Pinging 40.0.0.10 with 32 bytes of data:

Reply from 40.0.0.10: bytes=32 time=3ms TTL=125

Reply from 40.0.0.10: bytes=32 time=1ms TTL=125

Reply from 40.0.0.10: bytes=32 time=1ms TTL=125

Reply from 40.0.0.10: bytes=32 time=2ms TTL=125

Ping statistics for 40.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 1ms, Maximum = 3ms, Average = 1ms

C:\Documents and Settings\User>

1

e0

Win-2

40.0.0.10

Static Route

TERMINAL (5)

Physical

01 : 00 : 00

START

Thu 16

zoom

Chrome

FileEditViewHistoryBookmarksProfilesTabWindowHelp

Notes/CCNA/SN-CN-B1/St

Untitled

PNETLab | Topology

lab4 static

Static Route Configuration

+

Ask Gemini

labs.surennetwork.com/legacy/topology

Notifications

Terminal

Win-1 x Win-2 x R1 x R2 x R3 x

My Documents

My Computer

My Network Places

Recycle Bin

Internet Explorer

Cisco ASDM-1...

Old Java ASDM

PuTTY

Tftp32

C:\WINDOWS\system32\cmd.exe

Microsoft Windows [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.
C:\Documents and Settings\user>ping 10.0.0.10
Pinging 10.0.0.10 with 32 bytes of data:
Reply from 10.0.0.10: bytes=32 time=1ms TTL=125
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Reply from 10.0.0.10: bytes=32 time=1ms TTL=125
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Ping statistics for 10.0.0.10:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 2ms, Average = 1ms
C:\Documents and Settings\user>_

Start

C:\WINDOWS\system...

1:34 PM

1

e0

Win-2

40.0.0.10

Static Route

TERMINAL (5)

Physical

16

zoom

Chrome

FileEditViewHistoryBookmarksProfilesTabWindowHelp

Notes/CCNA/SN-CN-B1/St xUntitled xPNETLab | Topology xlab4 static xStatic Route Configuration xAsk Gemini

labs.surennetwork.com/legacy/topology

Notifications

Terminal

Win-1 xWin-2 xR1 xR2 xR3 x

*Jul 16 12:28:50.242: %SYS-5-CONFIG_I: Configured from console by console

R1#show ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP

D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area

N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2

E1 - OSPF external type 1, E2 - OSPF external type 2

i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2

ia - IS-IS inter area, * - candidate default, U - per-user static route

o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP

a - application route

+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

C 10.0.0.0/8 is directly connected, Ethernet0/0

L 10.0.0.1/32 is directly connected, Ethernet0/0

20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

C 20.0.0.0/8 is directly connected, Ethernet0/1

L 20.0.0.1/32 is directly connected, Ethernet0/1

S 30.0.0.0/8 [1/0] via 20.0.0.2

S 40.0.0.0/8 [1/0] via 20.0.0.2

R1#

Static Route

TERMINAL (5)

Physical

1

e0

Win-2

40.0.0.10

Static Route

TERMINAL (5)

Physical

1

e0

Win-2

40.0.0.10

Chrome

FileEditViewHistoryBookmarksProfilesTabWindowHelp

Notes/CCNA/SN-CN-B1/St

Untitled

PNETLab | Topology

lab4 static

Static Route Configuration

+

Ask Gemini

labs.surennetwork.com/legacy/topology

Notifications

Terminal

Win-1 x Win-2 x R1 x R2 x R3 x

```
R2(config)#ip route 10.0.0.0 255.0.0.0 20.0.0.2
%Invalid next hop address (it's this router)
R2(config)#ip route 10.0.0.0 255.0.0.0 20.0.0.1
R2(config)#ip route 40.0.0.0 255.0.0.0 30.0.0.2
R2(config)#exit
R2#s
*Jul 16 12:30:42.683: %SYS-5-CONFIG_I: Configured from console by console
R2#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

S    10.0.0.0/8 [1/0] via 20.0.0.1
    20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C    20.0.0.0/8 is directly connected, Ethernet0/0
```

1

e0

Win-2

40.0.0.10

Static Route

TERMINAL (5)

Physical

Static Route

TERMINAL (5)

Physical

Static Route

TERMINAL (5)

Physical

Chrome

FileEditViewHistoryBookmarksProfilesTabWindowHelp

Notes/CCNA/SN-CN-B1/St

Untitled

PNETLab | Topology

lab4 static

Static Route Configuration

+

Ask Gemini

labs.surennetwork.com/legacy/topology

Notifications

Terminal

Win-1 x Win-2 x R1 x R2 x R3 x

*Jul 16 12:32:14.146: %SYS-5-CONFIG_I: Configured from console by console

R3#show ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP

D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area

N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2

E1 - OSPF external type 1, E2 - OSPF external type 2

i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2

ia - IS-IS inter area, * - candidate default, U - per-user static route

o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP

a - application route

+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

S 10.0.0.0/8 [1/0] via 30.0.0.1

S 20.0.0.0/8 [1/0] via 30.0.0.1

30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

C 30.0.0.0/8 is directly connected, Ethernet0/1

L 30.0.0.2/32 is directly connected, Ethernet0/1

40.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

C 40.0.0.0/8 is directly connected, Ethernet0/0

L 40.0.0.1/32 is directly connected, Ethernet0/0

R3#

1

e0

Win-2

40.0.0.10

Static Route

TERMINAL (5)

Physical

Static Route

TERMINAL (5)

Physical