


# Process Management

- The OS also manages the use of CPU by individual processes.
- A process moves through specific states during its lifecycle while managed by the OS.
  - New State
  - Ready State
  - Running State
  - Wait State
  - Terminated State

# Process Management



The Process life cycle  
© 2012. AUKBC.

# Process Scheduling

- The Process Control Block -- Data structure used by the operating system to manage information about a process.
  - Each state is represented by a list of PCBs, once for each process in that state.
  - The PCB stores a variety of information
    - Value of program counter and other CPU registers
    - CPU scheduling information
    - Memory management information
    - Accounting Information
- Context Switch – The exchange of register information that occurs when one process is removed from the CPU and another takes its place

# CPU Scheduling

- Act of determining which process in the ready state is moved to the running state.
- Non-preemptive scheduling – CPU scheduling that occurs when the currently executing process gives up CPU voluntarily.
- Preemptive scheduling – CPU scheduling that occurs when the operating system decided to favor another process, preempting the currently executing process.

# CPU Scheduling

- Turnaround time – The CPU scheduling metric that measures the elapsed time between a process's arrival in the ready state and its ultimate completion.
- Ideally the turnaround time for the processes should be small.
- First-Come First-Served scheduling (FCFS)
  - Processes are moved to CPU in the order they arrive in the running state.
  - Non-preemptive.
  - Easy to implement, not efficient.

# CPU Scheduling

- Shortest Job Next scheduling (SJN)
  - The algorithm looks at all the processes in ready state and dispatches one with the shortest service time.
  - Non-preemptive.
  - Relies on knowledge of future – the estimated time for completion of each job.
  - Provably optimal, but sub-optimal in practice due to not knowing the service time of all the jobs that are waiting to be executed.

# CPU Scheduling

- Round Robin CPU scheduling
  - Distributes the processing time equitably among all ready processes.
  - Establishes a time slice – the amount of time given to each process – before a process is preempted and returned to the ready state to allow another process to take its turn.
  - Eventually the preempted process will be given another time slice.
  - Procedure continues until the process gets all the time it needs to complete.
  - Supports all kinds of jobs and is considered the most fair algorithm – probably the most widely used.

# Disk Scheduling

- The act of deciding which outstanding request for disk I/O to satisfy first.
- Hard disk is the most important secondary storage device.
- It is also the worst bottleneck in a general computer system.
- Hard disks – a stack of platters – a number of tracks – a number of sectors.



# Disk Scheduling

- The seek time is the amount of time it takes for the read/write heads to reach the appropriate cylinder.
- The latency is the additional time it takes for the platter to rotate into the proper position so that the data can be read or written.
- Seek time is more restrictive of the two parameters and is the primary issue dealt with by disk scheduling algorithms.

# Disk Scheduling

- First-Come, First-Served Disk Scheduling
  - Similar to FCFS.
  - Easiest to implement, not efficient.
- Shortest-Seek-Time-First Disk Scheduling (SSTF)
  - Moves the head by the minimum amount necessary to satisfy any pending request.
  - Improved performance over FCFS.
  - Can suffer starvation unlike FCFS.

# Disk Scheduling

- SCAN Disk Scheduling
  - The read/write heads move in toward the spindle, then move toward the platter edge, then back toward the spindle and so forth, servicing requests on the way.
  - New requests are not given any special treatment.
  - No starvation since all requests are guaranteed to be processed.
  - Circular SCAN – when the head reaches one extreme it returns to other extreme without processing requests.
  - LOOK disk scheduling – move only as the outermost or innermost request.

# File system

- File – A named collection of data, used for organizing secondary memory.
- File system – The operating system's logical view of the files it manages.
- Virtual File System – an abstraction layer on top of a more concrete file system providing access to files in an uniform way.
- Specifies an interface between the kernel and concrete file system.
- The Filesystem in Userspace (FUSE) mechanism allows userland code to plug into the virtual file system mechanism.

# Device Drivers

- A computer program allowing higher-level computer programs to interact with a hardware device.
- Operating System specific.
- Higher level code can be independent of specific hardware device.
- Abstracted into
  - Logical layer – device driver for Ethernet ports.
  - Physical layer – for a specific hardware device.

# Device Drivers

- Written by engineers with an in-depth understanding of how the hardware and the software of a given platform function.
- The Logical Device Driver is written by the operating system vendor.
- The Physical Device Driver written by the hardware manufacturer.
  - Outsiders can write provided vendors provide specifications.
  - Reverse engineering not as efficient.

# Networking

- The OS is responsible for connecting various computer and devices to form a computer network.
- An OS can connect to a remote computer and use the resources as if they were connected locally.
- Client/Server.
- Vendor specific or open protocols.

# Security


- The OS provides access to a number of resources which are available to software running on the system and over the network.
- The OS must be capable of distinguishing between requests which should be allowed to be processed and others which should not be processed.
- Authentication.
- Authorization.




# User Interfaces

- Not actually part of the OS.
- Main means by which users interact with the computer.
- Deals with requests coming from any input device and request the OS to provide the output in an output device.
- Common types:
  - Command Line Interface (CLI)
  - Graphical User Interface (GUI)

# GNOME




# KDE



# KDE Plasma Netbook



# Unity





# Xfce

