HeroDots / PlaceSecrets

Project Documentation

Generated: 2026-04-03 | Version: 1.0

Metric	Value
Database Tables	19
Total Columns	196
Foreign Key Relationships	28
Total Use Cases	105
Flutter (Mobile) Use Cases	50
React (Web Admin) Use Cases	55
Implemented	102
Partial	3

Table of Contents

Section 1: Database Schema (UML Entity-Relationship Diagrams)

Geography: countries, cities
POI: poi_types, pois, poi_audio_guides, poi_audio_guide_ratings, poi_ratings, poi_premium_content
Auth & Users: user_profiles, admin_users, contributor_profiles, acl_permissions
Payments: user_access, payment_receipts, payment_config, user_poi_purchases, user_city_premium_purchases
Activity: free_visit_log, audit_logs

Section 2: Use Case Inventory

1. Authentication & Onboarding (13 use cases)
2. POI Discovery & Browsing (9 use cases)
3. POI Detail & Content Access (14 use cases)
4. Premium / Payment Flow (14 use cases)
5. User Profile & Settings (16 use cases)
6. Admin - POI Management (12 use cases)
7. Admin - User & Access Management (15 use cases)
8. Activity & Travel Log (6 use cases)
9. Other / System (6 use cases)

Section 1: Database Schema

19 tables | 196 columns | 28 foreign key relationships | All tables have Row-Level Security enabled

Geography Tables

countries		Geography
PK code	TEXT	PK
name	TEXT	NOT NULL
aliases	TEXT[]	NOT NULL, = '{}'
created_at	TIMESTAMPTZ	NOT NULL, = NOW()
updated_at	TIMESTAMPTZ	NOT NULL, = NOW()

cities		Geography
PK id	UUID	PK
name	TEXT	NOT NULL
FK country_code	TEXT	NOT NULL, FK, = 'CZ'
latitude	DOUBLE PRECISION	NOT NULL
longitude	DOUBLE PRECISION	NOT NULL
bounding_box_radius_km	DOUBLE PRECISION	NOT NULL, = 10
price_eur	DECIMAL(10,2)	NOT NULL, = 1.00
is_active	BOOLEAN	NOT NULL, = TRUE
slug	TEXT	UNIQUE
FK registered_sample_poi_id	UUID	FK
premium_bundle_price	NUMERIC(10,2)	
aliases	TEXT[]	NOT NULL, = '{}'
created_at	TIMESTAMPTZ	NOT NULL, = NOW()
updated_at	TIMESTAMPTZ	NOT NULL, = NOW()

Foreign Key Relationships:
cities.country_code -> countries.code
cities.registered_sample_poi_id -> pois.id

POI Tables

poi_types		POI
PK id	UUID	PK
name	JSONB	NOT NULL
slug	TEXT	NOT NULL, UNIQUE
icon_name	TEXT	NOT NULL, = 'place'
color_hex	TEXT	NOT NULL, = '#2D6A4F'
sort_order	INTEGER	NOT NULL, = 0
is_active	BOOLEAN	NOT NULL, = TRUE
created_at	TIMESTAMPTZ	NOT NULL
updated_at	TIMESTAMPTZ	NOT NULL

pois

POI

PK id	UUID	PK
FK city_id	UUID	NOT NULL, FK
name	JSONB	NOT NULL
description	JSONB	NOT NULL
latitude	DOUBLE PRECISION	NOT NULL
longitude	DOUBLE PRECISION	NOT NULL
geofence_radius	DOUBLE PRECISION	NOT NULL, = 100
photo_urls	JSONB	NOT NULL, = '[]'
audio_urls	JSONB	NOT NULL, = '{}'
is_premium	BOOLEAN	NOT NULL, = TRUE
sort_order	INTEGER	NOT NULL, = 0
is_active	BOOLEAN	NOT NULL, = TRUE
slug	TEXT	UNIQUE(city)
access_level	TEXT	NOT NULL, CHK
perex	JSONB	
premium_price	NUMERIC(10,2)	
FK contributor_id	UUID	FK
contributor_note	TEXT	
avg_rating	DECIMAL(3,2)	
total_ratings	INTEGER	NOT NULL, = 0
FK type_id	UUID	FK
aliases	TEXT[]	NOT NULL, = '{}'
created_at	TIMESTAMPTZ	NOT NULL
updated_at	TIMESTAMPTZ	NOT NULL

poi_audio_guides

POI

PK id	UUID	PK
FK poi_id	UUID	NOT NULL, FK
lang_code	TEXT	NOT NULL, CHK
title	TEXT	NOT NULL, = ''
url	TEXT	NOT NULL
duration_sec	INTEGER	
sort_order	INTEGER	NOT NULL, = 0
FK uploaded_by	UUID	FK
avg_rating	DECIMAL(3,2)	= 0
total_ratings	INTEGER	= 0
created_at	TIMESTAMPTZ	NOT NULL
updated_at	TIMESTAMPTZ	NOT NULL

poi_audio_guide_ratings

POI

PK id	UUID	PK
FK audio_guide_id	UUID	NOT NULL, FK
FK user_id	UUID	NOT NULL, FK
rating	SMALLINT	NOT NULL, CHK 1-5
created_at	TIMESTAMPTZ	NOT NULL

poi_ratings

POI

PK id	UUID	PK
FK poi_id	UUID	NOT NULL, FK
FK user_id	UUID	FK
device_id	TEXT	CHK
rating	SMALLINT	NOT NULL, CHK 1-5
reason	TEXT	CHK
lang_code	TEXT	NOT NULL, = 'cs'
comment	TEXT	CHK <=1000
is_hidden	BOOLEAN	NOT NULL, = FALSE
created_at	TIMESTAMPTZ	NOT NULL

poi_premium_content		POI
PK id	UUID	PK
FK poi_id	UUID	NOT NULL, FK, UNIQUE
audio_url	TEXT	
text_content	TEXT	
extra_photos	JSONB	= '[]'
related_poi_ids	UUID[]	= '{}'
created_at	TIMESTAMPTZ	= NOW()
updated_at	TIMESTAMPTZ	= NOW()

Foreign Key Relationships:
pois.city_id -> cities.id
pois.contributor_id -> auth.users.id
pois.type_id -> poi_types.id
poi_audio_guides.poi_id -> pois.id
poi_audio_guides.uploaded_by -> auth.users.id
poi_audio_guide_ratings.audio_guide_id -> poi_audio_guides.id
poi_audio_guide_ratings.user_id -> auth.users.id
poi_ratings.poi_id -> pois.id
poi_ratings.user_id -> auth.users.id
poi_premium_content.poi_id -> pois.id

Auth & Users Tables

user_profiles		Auth & Users
PK id	UUID	PK
FK user_id	UUID	UNIQUE, NOT NULL, FK
language	TEXT	NOT NULL, = 'en'
status	TEXT	NOT NULL, CHK, = 'active'
user_number	BIGINT	UNIQUE, NOT NULL, SEQ
backup_email	TEXT	
display_name	TEXT	UNIQUE, CHK
created_at	TIMESTAMPTZ	NOT NULL
updated_at	TIMESTAMPTZ	NOT NULL

admin_users		Auth & Users
PK id	UUID	PK
FK user_id	UUID	NOT NULL, UNIQUE, FK
role	TEXT	NOT NULL, CHK, = 'editor'
pin_hash	TEXT	
pin_set_at	TIMESTAMPTZ	
pin_attempts	INT	= 0
pin_locked_until	TIMESTAMPTZ	
must_change_pin	BOOLEAN	NOT NULL, = TRUE
created_at	TIMESTAMPTZ	NOT NULL

contributor_profiles		Auth & Users
PK id	UUID	PK
FK user_id	UUID	NOT NULL, UNIQUE, FK
display_name	TEXT	NOT NULL, CHK
bio	TEXT	CHK <=2000
avatar_url	TEXT	CHK
website_url	TEXT	CHK
specializations	TEXT[]	= '{}'
total_pois	INTEGER	NOT NULL, = 0
avg_rating	DECIMAL(3,2)	
total_ratings	INTEGER	NOT NULL, = 0
is_verified	BOOLEAN	NOT NULL, = FALSE
is_active	BOOLEAN	NOT NULL, = TRUE
created_at	TIMESTAMPTZ	NOT NULL
updated_at	TIMESTAMPTZ	NOT NULL

acl_permissions		Auth & Users
PK id	UUID	PK
role	TEXT	NOT NULL, CHK
resource	TEXT	NOT NULL, CHK
can_read	BOOLEAN	NOT NULL, = FALSE
can_write	BOOLEAN	NOT NULL, = FALSE
can_delete	BOOLEAN	NOT NULL, = FALSE
created_at	TIMESTAMPTZ	= NOW()
updated_at	TIMESTAMPTZ	= NOW()

Foreign Key Relationships:
user_profiles.user_id -> auth.users.id
admin_users.user_id -> auth.users.id
contributor_profiles.user_id -> auth.users.id

Payments Tables

user_access		Payments
PK id	UUID	PK
FK user_id	UUID	NOT NULL, FK
FK city_id	UUID	NOT NULL, FK
purchased_at	TIMESTAMPTZ	NOT NULL, = NOW()
valid_until	TIMESTAMPTZ	
payment_method	TEXT	NOT NULL, CHK
transaction_id	TEXT	
amount_eur	DECIMAL(10,2)	

payment_receipts		Payments
PK id	UUID	PK
FK user_id	UUID	NOT NULL, FK
FK city_id	UUID	NOT NULL, FK
purchased_at	TIMESTAMPTZ	NOT NULL, = NOW()
payment_method	TEXT	NOT NULL, CHK
transaction_id	TEXT	
amount_eur	DECIMAL(10,2)	NOT NULL
currency	TEXT	NOT NULL, = 'EUR'
status	TEXT	NOT NULL, CHK, = 'completed'
revolut_note	TEXT	
FK confirmed_by	UUID	FK
confirmed_at	TIMESTAMPTZ	
receipt_number	TEXT	UNIQUE, SEQ
receipt_pdf_url	TEXT	
receipt_sent_at	TIMESTAMPTZ	
created_at	TIMESTAMPTZ	NOT NULL

payment_config		Payments
PK id	UUID	PK
operator_name	TEXT	NOT NULL, = 'HeroDots'
revolut_username	TEXT	
revolut_iban	TEXT	
stripe_publishable_key	TEXT	
stripe_secret_key	TEXT	
google_pay_merchant_id	TEXT	
apple_pay_merchant_id	TEXT	
free_pois_per_month	INTEGER	NOT NULL, = 1
max_geofences	INTEGER	NOT NULL, = 100
max_photo_size_mb	INTEGER	NOT NULL, = 10
max_audio_size_mb	INTEGER	NOT NULL, = 50
admin_pin_attempts	INTEGER	NOT NULL, = 5
admin_pin_lockout_minutes	INTEGER	NOT NULL, = 15
receipt_prefix	TEXT	NOT NULL, = 'PS-'
updated_at	TIMESTAMPTZ	NOT NULL

user_poi_purchases		Payments
PK id	UUID	PK
FK user_id	UUID	NOT NULL, FK
FK poi_id	UUID	NOT NULL, FK
purchased_at	TIMESTAMPTZ	= NOW()
price_paid	NUMERIC(10,2)	
payment_id	TEXT	
stripe_session_id	TEXT	

user_city_premium_purchases		Payments
PK id	UUID	PK
FK user_id	UUID	NOT NULL, FK
FK city_id	UUID	NOT NULL, FK
purchased_at	TIMESTAMPTZ	= NOW()
price_paid	NUMERIC(10,2)	
payment_id	TEXT	
stripe_session_id	TEXT	

Foreign Key Relationships:
user_access.user_id -> auth.users.id
user_access.city_id -> cities.id
payment_receipts.user_id -> auth.users.id
payment_receipts.city_id -> cities.id
payment_receipts.confirmed_by -> auth.users.id
user_poi_purchases.user_id -> auth.users.id
user_poi_purchases.poi_id -> pois.id
user_city_premium_purchases.user_id -> auth.users.id
user_city_premium_purchases.city_id -> cities.id

Activity Tables

free_visit_log		Activity
PK id	UUID	PK
FK user_id	UUID	FK
device_id	TEXT	
FK poi_id	UUID	NOT NULL, FK
FK city_id	UUID	NOT NULL, FK
visited_at	TIMESTAMPTZ	NOT NULL, = NOW()
year_month	TEXT	NOT NULL

audit_logs		Activity
PK id	UUID	PK
FK actor_id	UUID	FK
action	TEXT	NOT NULL
target_type	TEXT	
target_id	TEXT	
metadata	JSONB	= '{}'
ip_address	INET	
created_at	TIMESTAMPTZ	NOT NULL

Foreign Key Relationships:
free_visit_log.user_id -> auth.users.id
free_visit_log.poi_id -> pois.id
free_visit_log.city_id -> cities.id
audit_logs.actor_id -> auth.users.id

Database Views

View Name	Description
contributor_rankings	Aggregated contributor stats per city with Hall of Fame score
web_user_roles	Effective role mapping (admin_users or contributor status)
admin_stats	High-level system statistics (cities, POIs, users, revenue)
admin_users_view	Aggregated user data with access counts and spending
user_all_purchases	Union view of all purchase types (POI, city premium, city access)

Sequences

receipt_number_seq: START 1 (generates PS-XXXXXX receipt numbers)
user_number_seq: START 100000 (generates 6-digit user IDs)

Section 2: Use Case Inventory

105 total use cases across 9 categories | 50 Flutter (mobile) | 55 React (web admin)

Category	Count	Flutter	React
Authentication & Onboarding	13	6	7
POI Discovery & Browsing	9	7	2
POI Detail & Content Access	14	11	3
Premium / Payment Flow	14	8	6
User Profile & Settings	16	8	8
Admin - POI Management	12	0	12
Admin - User & Access Management	15	0	15
Activity & Travel Log	6	6	0
Other / System	6	4	2
TOTAL	**105**	**50**	**55**

Breakdown by Actor

Actor	Count
Any user	27
Registered user	24
Admin/Superadmin	12
Anonymous user	7
Admin/Editor/Viewer	6
Admin/Editor	6
Superadmin	4
System	4
Registered+ user	3
Contributor	3
Any authenticated	2
Admin/Editor/Contributor	2
Anonymous/new user	1
Premium user	1
Android user	1
iOS user	1
User (post-payment)	1

Breakdown by Access Tier

Access Tier	Count

Public	43
Admin-only	30
Registered	28
Contributor	3
Premium POI	1

Authentication & Onboarding

#	Use Case	Actor	App	Entry Point	Tier	Status
1	First App Launch Onboarding	Anonymous user	Flutter	OnboardingScreen (/onboarding)	Public	Implemented
2	Anonymous Session Initialization	Anonymous user	Flutter	main.dart	Public	Implemented
3	Email Registration (with handle)	Anonymous/new user	Flutter	AuthScreen (/auth)	Public	Implemented
4	Email Sign-In	Registered user	Flutter	AuthScreen (/auth)	Registered	Implemented
5	Password Reset	Registered user	Flutter	AuthScreen (/auth)	Public	Implemented
6	Sign Out (return to anonymous)	Registered user	Flutter	SettingsScreen (/settings)	Registered	Implemented
7	User Registration (Email)	Anonymous user	React	RegisterPage (/register)	Public	Implemented
8	Contributor Registration	Anonymous user	React	ContributorRegisterPage (/register/contributor)	Public	Implemented
9	User Sign-In (Email/Password)	Any user	React	LoginPage (/login)	Public	Implemented
10	OAuth Social Authentication	Anonymous user	React	LoginPage, RegisterPage	Public	Implemented
11	Admin PIN Verification	Admin/Editor/Viewer	React	AdminPinPage (/admin-pin)	Admin-only	Implemented
12	Force Change Admin PIN	Admin/Editor/Viewer	React	ForceChangePinPage (/admin/force-change-pin)	Admin-only	Implemented
13	Sign Out (web)	Any authenticated	React	Account dropdown	Registered	Implemented

POI Discovery & Browsing

#	Use Case	Actor	App	Entry Point	Tier	Status
1	View Interactive Map with POIs	Any user	Flutter	MapScreen (/)	Public	Implemented
2	Detect Nearest City	Any user	Flutter	MapScreen (auto)	Public	Implemented
3	Fetch & Cache POIs for City	Any user	Flutter	MapScreen providers	Public	Implemented
4	Filter POIs by Access Level	Any user	Flutter	MapScreen filter chips	Public	Implemented
5	Color-Coded POI Markers	Any user	Flutter	MapScreen	Public	Implemented
6	Select POI (bottom sheet)	Any user	Flutter	MapScreen marker tap	Public	Implemented
7	View Hall of Fame for City	Any user	Flutter	HallOfFameScreen (/hall-of-fame/:cityId)	Public	Implemented
8	View Landing Page	Anonymous user	React	LandingPage (/)	Public	Implemented
9	Explore Map of Places	Registered user	React	AccountExplorePage (/account/explore)	Registered	Implemented

POI Detail & Content Access

#	Use Case	Actor	App	Entry Point	Tier	Status
1	View POI Detail Screen	Any user	Flutter	PoiDetailScreen (/poi/:id)	Public	Implemented
2	View POI Photo Gallery	Any user	Flutter	PoiDetailScreen (photo tap)	Public	Implemented
3	Access POI by Deep Link (slug)	Any user	Flutter	PoiBySlugScreen (/:cc/:city/:poi)	Public	Implemented
4	Check POI Access Level	Any user	Flutter	PoiDetailScreen (get_poi_access RPC)	Public	Implemented
5	Play Audio Guide	Registered+ user	Flutter	AudioPlayerWidget	Registered	Implemented
6	Select Audio Language	Registered+ user	Flutter	AudioPlayerWidget	Registered	Implemented
7	View Premium Content	Premium user	Flutter	PremiumPoiContent widget	Premium POI	Implemented
8	Premium Upgrade CTA	Registered user	Flutter	PoiDetailScreen	Registered	Implemented
9	Share POI Link	Any user	Flutter	SharePoiButton	Public	Implemented
10	Rate POI (1-5 stars + feedback)	Registered+ user	Flutter	RatingWidget	Registered	Implemented
11	View Existing Rating	Registered user	Flutter	RatingWidget	Registered	Implemented
12	View Place Detail (public web)	Any user	React	PlaceDetailPage (/:cc/:city/:poi)	Public	Implemented
13	Listen to Audio Guide (web)	Registered user	React	PlaceDetailPage	Registered	Implemented
14	Rate and Review POI (web)	Registered user	React	PlaceDetailPage	Registered	Implemented

Premium / Payment Flow

#	Use Case	Actor	App	Entry Point	Tier	Status
1	View City Paywall	Any user	Flutter	PaywallScreen (/paywall/:cityId)	Public	Implemented
2	Pay with Google Pay	Android user	Flutter	PaywallScreen	Public	Implemented
3	Pay with Apple Pay	iOS user	Flutter	PaywallScreen	Public	Implemented
4	Purchase Individual POI	Registered user	Flutter	PurchasePoiScreen (/purchase/poi/:id)	Registered	Implemented
5	Purchase City Premium Bundle	Registered user	Flutter	PurchasePoiScreen	Registered	Implemented
6	Handle Purchase Success Redirect	User (post-payment)	Flutter	DeepLinkHandler	Registered	Implemented
7	View Purchase History (mobile)	Registered user	Flutter	MyPurchasesScreen	Registered	Partial
8	Use Free Monthly POI Visit	Registered user	Flutter	AccessRepository	Registered	Implemented
9	Purchase City Pass (web)	Registered user	React	CityPricingPage	Registered	Implemented
10	Purchase Individual POI (web)	Registered user	React	PlaceDetailPage	Registered	Implemented
11	View Purchase History (web)	Registered user	React	AccountProfilePage (/account/profile)	Registered	Implemented
12	Admin: View Payment Analytics	Admin/Superadmin	React	PaymentsPage (/admin/payments)	Admin-only	Implemented
13	Admin: View Payment Detail	Admin/Superadmin	React	PaymentDetailPage (/admin/payments/:id)	Admin-only	Implemented
14	Admin: Grant Free Access	Admin/Superadmin	React	UserDetailPage + AccessGrantModal	Admin-only	Implemented

User Profile & Settings

#	Use Case	Actor	App	Entry Point	Tier	Status
1	View Settings Screen	Any user	Flutter	SettingsScreen (/settings)	Public	Implemented
2	Select Audio Language	Any user	Flutter	SettingsScreen (dialog)	Public	Implemented
3	Adjust Geofence Radius	Any user	Flutter	SettingsScreen (slider)	Public	Implemented
4	Toggle Notifications	Any user	Flutter	SettingsScreen (switch)	Public	Implemented
5	Set Backup Email	Registered user	Flutter	SettingsScreen	Registered	Implemented
6	Set/Update Handle	Registered user	Flutter	SettingsScreen	Registered	Implemented
7	View Account Status	Any user	Flutter	SettingsScreen	Public	Implemented
8	View About Information	Any user	Flutter	SettingsScreen (dialog)	Public	Implemented
9	View/Edit Profile (web)	Registered user	React	AccountProfilePage (/account/profile)	Registered	Implemented
10	Set/Change Handle (web)	Registered user	React	AccountProfilePage	Registered	Implemented
11	Change Password (web)	Registered user	React	AccountProfilePage	Registered	Implemented
12	Select Language (web)	Registered user	React	AccountProfilePage	Registered	Implemented
13	Set Backup Email (web)	Registered user	React	AccountProfilePage	Registered	Implemented
14	Delete User Account (web)	Registered user	React	AccountProfilePage	Registered	Implemented
15	View Visit History (web)	Registered user	React	AccountHistoryPage (/account/history)	Registered	Implemented
16	Contributor Profile Management	Contributor	React	AdminProfilePage (/admin/profile)	Contributor	Implemented

Admin - POI Management

#	Use Case	Actor	App	Entry Point	Tier	Status
1	View All Cities	Admin/Editor/Viewer	React	CitiesPage (/admin/cities)	Admin-only	Implemented
2	Create New City	Admin/Editor	React	CityNewPage (/admin/cities/new)	Admin-only	Implemented
3	Edit City	Admin/Editor	React	CityEditPage (/admin/cities/:id)	Admin-only	Implemented
4	Create New Country	Admin/Superadmin	React	CitiesPage (inline form)	Admin-only	Implemented
5	View POIs in City	Admin/Editor/Viewer	React	PoisPage (/admin/cities/:id/pois)	Admin-only	Implemented
6	Create New POI	Admin/Editor/Contributor	React	PoiNewPage (/admin/cities/:id/pois/new)	Admin-only	Implemented

#	Use Case	Actor	App	Entry Point	Tier	Status
7	Edit POI	Admin/Editor/Contributor	React	PoiEditPage (/admin/cities/:id/pois/:id)	Admin-only	Implemented
8	Manage POI Ratings	Admin/Editor	React	PoiEditPage (ratings tab)	Admin-only	Implemented
9	Contributor: Manage My POIs	Contributor	React	MyPoisPage (/admin/my-pois)	Contributor	Implemented
10	Contributor: Create New POI	Contributor	React	MyPoiEditorPage (/admin/my-pois/new)	Contributor	Implemented
11	Manage POI Types	Admin/Superadmin	React	PoiTypesPage (/admin/poi-types)	Admin-only	Implemented
12	Configure City Pricing	Admin/Superadmin	React	CityPricingPage (/admin/cities/:id/pricing)	Admin-only	Implemented

Admin - User & Access Management

#	Use Case	Actor	App	Entry Point	Tier	Status
1	View Dashboard	Admin/Editor/Viewer	React	DashboardPage (/admin/dashboard)	Admin-only	Implemented
2	View All Users	Admin/Superadmin	React	UsersPage (/admin/users)	Admin-only	Implemented
3	Create User Manually	Admin/Superadmin	React	UsersPage (dialog)	Admin-only	Implemented
4	View User Detail	Admin/Superadmin	React	UserDetailPage (/admin/users/:id)	Admin-only	Implemented
5	Grant City Access	Admin/Superadmin	React	UserDetailPage + AccessGrantModal	Admin-only	Implemented
6	Deactivate/Reactivate User	Admin/Superadmin	React	UserDetailPage	Admin-only	Implemented
7	Export User Data (GDPR)	Admin/Superadmin	React	UserDetailPage	Admin-only	Implemented
8	View All Contributors	Admin/Editor	React	ContributorsPage (/admin/contributors)	Admin-only	Implemented
9	View Contributor Detail	Admin/Editor	React	ContributorDetailPage (/admin/contributors/:id)	Admin-only	Implemented
10	Manage ACL Permissions	Superadmin	React	AclManagementPage (/admin/acl)	Admin-only	Implemented
11	Change Admin PIN	Admin/Editor/Viewer	React	SettingsPage + ChangePinForm	Admin-only	Implemented
12	Manage System Settings	Superadmin	React	SettingsPage (/admin/settings)	Admin-only	Implemented
13	Manage Admin Users	Superadmin	React	SettingsPage + InviteAdminForm	Admin-only	Implemented
14	Configure Payment Methods	Superadmin	React	SettingsPage	Admin-only	Implemented
15	View Hall of Fame (admin)	Admin/Editor	React	HallOfFamePage (/admin/hall-of-fame)	Admin-only	Implemented

Activity & Travel Log

#	Use Case	Actor	App	Entry Point	Tier	Status
1	Track POI Visit (geofence)	Any user	Flutter	GeofenceService + VisitRepository	Public	Implemented
2	View Visit History	Any user	Flutter	HistoryScreen (/history)	Public	Implemented
3	View Travel Statistics	Any user	Flutter	HistoryScreen (badges)	Public	Implemented
4	Add Note to Visit	Any user	Flutter	VisitRepository	Public	Partial
5	Add Photo to Visit	Any user	Flutter	VisitRepository	Public	Partial
6	Export Travel Log to PDF	Any user	Flutter	ExportScreen (/export)	Public	Implemented

Other / System

#	Use Case	Actor	App	Entry Point	Tier	Status
1	Sync Offline Data When Online	System	Flutter	SyncService + ConnectivityService	Public	Implemented
2	Device ID Tracking (anon ratings)	System	Flutter	DeviceService	Public	Implemented
3	Offline-First Local Database	System	Flutter	Drift AppDatabase (7 tables)	Public	Implemented
4	Fetch & Cache City List	System	Flutter	MapProviders + CityRepository	Public	Implemented
5	View Public Footer/Legal	Anonymous user	React	PublicFooter	Public	Implemented
6	Unauthorized Access Page	Any authenticated	React	UnauthorizedPage (/unauthorized)	Public	Implemented