


Debounce

- Debounce is a technique used to delay the execution of a function until after a certain time has passed since it was last called.'
- Prevents a function from running too often.
- Example use cases:
 - Search input (wait until user stops typing before sending API call).
 - Window resize events.



```
function debounce(fn, delay) {  
  let timer;  
  return (...args) => {  
    clearTimeout(timer);  
    timer = setTimeout(() => fn(...args), delay);  
  };  
}
```

Throttle


- Throttle ensures a function runs at most once in a specified interval, no matter how many times it's triggered.
- Limits execution rate for performance.
- Example use cases:
 - Scroll events.
 - Button clicks (to prevent double submission).



```
function throttle(fn, delay) {  
  let last = 0;  
  return (...args) => {  
    const now = Date.now();  
    if (now - last >= delay) {  
      last = now;  
      fn(...args);  
    }  
  };  
}
```

Deep Clone


- A method of creating a copy of an object along with all nested objects, instead of just referencing the original.
- Prevents accidental changes to the original object when modifying the clone.
- Example use cases:
 - State management in apps (React/Angular).
 - Copying configuration objects.



```
function deepClone(obj) {  
  if (obj === null || typeof obj !== "object") return obj;  
  if (Array.isArray(obj)) return obj.map(deepClone);  
  
  const clone = {};  
  for (let key in obj) {  
    clone[key] = deepClone(obj[key]);  
  }  
  return clone;  
}
```

Array Polyfills

- Custom implementations of built-in array methods.
- Useful for interview prep and core JavaScript understanding.
- **Example use cases:**
 - map → transform array values.
 - filter → return values matching a condition.
 - reduce → accumulate values into a single result (sum, average, object building).



```
Array.prototype.myMap = function(cb) {  
  const res = [];  
  for (let i = 0; i < this.length; i++) res.push(cb(this[i], i, this));  
  return res;  
};
```

```
Array.prototype.myFilter = function(cb) {  
  const res = [];  
  for (let i = 0; i < this.length; i++) if (cb(this[i], i, this)) res.push(this[i]);  
  return res;  
};
```

```
Array.prototype.myReduce = function(cb, init) {  
  let acc = init;  
  for (let i = 0; i < this.length; i++) acc = cb(acc, this[i], i, this);  
  return acc;  
};
```

Promise.all

- Helps you handle multiple asynchronous operations concurrently.
- Ensures that results from all promises are collected in the same order as the input array.
- **Example use cases:**
 - Fetching data from multiple APIs at once and processing them together.
 - Running several independent asynchronous tasks in parallel (e.g., reading multiple files, processing images).

```
function myPromiseAll(promises) {  
  return new Promise((resolve, reject) => {  
    let results = [];  
    let count = 0;  
  
    promises.forEach((p, i) => {  
      Promise.resolve(p).then(res => {  
        results[i] = res;  
        count++;  
        if (count === promises.length) resolve(results);  
      }).catch(reject);  
    });  
  });  
}
```