How Small Can VLA-JEPA Get? Post-Training Compression of a Robot Policy on LIBERO

Noah Sprenger Fernando Nogueira
CSI 5341, University of Ottawa Code: https://github.com/seofernando25/csi5341-vla-jepa

***Abstract*—VLA-JEPA couples a 2B-parameter vision–language model with a flow-matching action head and reaches 95% success on LIBERO-Spatial, with a measured peak of 5.6 GB allocated GPU memory at batch size one. We test whether post-training compression keeps that success on this suite. Quantizing only the language-decoder linear layers to NF4 cuts peak memory by 36.9% with a paired success change of +0.8 points (95% CI −0.6 to +2.2, 500 trials). LLM.int8 cuts 23.3% and misses our 25% target, which equals the ideal INT8 saving for the decoder weights. A sweep of 201 compression recipes finds that the language decoder is the precision bottleneck, while vision and action weights survive 2-bit quantization. Three joint recipes keep 93.4–98.0% success at 0.94–1.38 GB (75–83% less memory), but every compressed policy is 1.2–2.0× slower. Offline action divergence on fixed frames predicts gross failure ($\rho = -0.67$, 163 recipes) but cannot rank near-lossless ones. Replacing the backbone with SmolVLM2-500M failed (2.2%).**

I. Introduction

Vision–language–action (VLA) policies map camera images and an instruction to robot actions [1], [2]. VLA-JEPA [3] adds a V-JEPA 2 latent world model [4] during training to a Qwen3-VL-2B backbone [5] and a flow-matching action head. Its weights alone occupy 5.5 GB in BF16, which excludes many embedded GPUs. We ask how far the *trained* policy can be compressed without retraining, and what breaks first.

Our proposal stated one hypothesis. The feedback asked for justified thresholds and more depth, so we test four:

- **H1** Quantizing the language-decoder linear layers reduces peak inference memory by ≥25% and lowers LIBERO-Spatial success by ≤5 points.
- **H2** Tolerance to compression differs by module: the language decoder is more sensitive than the vision encoder or action head.
- **H3** At batch size one, lower memory does not imply lower latency.
- **H4** The change in predicted actions on fixed observations predicts closed-loop failure, so it can screen recipes without rollouts.

Thresholds. The 25% memory target is the ideal saving of 8-bit decoder weights: 1.41B linear parameters lose one byte each, 1.41 GB of a 5.61 GB peak, or 25.1% (Fig. 2). **H1** therefore asks whether runtime overhead consumes the theoretical saving. The 5-point bound allows the 5% baseline failure rate to at most double. With 500 paired trials, the 95% interval on a paired difference spans 2–4 points, narrow enough to separate a 5-point drop from no change.

Contributions. (i) A matched 500-trial evaluation of INT8 and NF4 decoder quantization with paired statistics. (ii) A module-level sensitivity map over 201 recipes and 21 component domains. (iii) Three deployable recipes below 1.4 GB with reserved-trial confirmation. (iv) A failure analysis linking offline action change to task success.




Fig. 1. VLA-JEPA inference path with parameter counts. Colored modules are the compression targets; mergers connect vision features to the decoder. The world model is loaded by default but unused at inference.

II. Related Work

VLA policies. OpenVLA [1] discretizes actions from a 7B language model; π_0 [2] and VLA-JEPA use flow matching. SmolVLA [6] trains a 0.45B policy from scratch on a SmolVLM backbone [7]. We compress an existing policy instead of training a small one.

Quantization. LLM.int8 [8] keeps outlier features in FP16; NF4 [9] stores 4-bit normal-float weights with double-quantized scales. GPTQ [10] and AWQ [11] calibrate weights on sample inputs; HQQ [12] quantizes without calibration down to 2 bits. QuantVLA [13] adapts post-training quantization to VLA action experts.

Pruning. Wanda [14] and SparseGPT [15] prune individual weights; structured pruning removes channels, heads or layers, and EcoVLA [16] applies it to VLAs. We rank layers by linear CKA [17] between block input and output. Unstructured masks save no memory without sparse kernels, so we report memory only for structured and packed formats.

III. Method

Policy. We use the released LIBERO checkpoint of the LeRobot port [18] (`VLA-JEPA-LIBERO`), pinned by revision (Fig. 1). The policy predicts seven actions with four Euler flow steps and executes all seven before replanning. Nothing in this report retrains Qwen.

Compression arms. *Study A* quantizes every `nn.Linear` in the 28-layer Qwen decoder after the checkpoint loads: Q8 with LLM.int8 (outlier threshold 6) and Q4 with NF4

TABLE I

EXPERIMENTAL DESIGN. ALL ROWS SHARE THE CHECKPOINT, TASK SUITE, STATES, SEEDS, ACTION HORIZON, FLOW STEPS, GPU AND SOFTWARE VERSIONS.

ID	Question	Varied	Sample	Analysis and decision rule
E1 (**H1**)	Does decoder quantization keep success?	Decoder linear precision: BF16, INT8, NF4	500 reserved rollouts per arm	Paired bootstrap; pass if memory reduction ≥25% and $\Delta \geq -5$ pp
E2 (**H2**)	Which modules tolerate compression?	Module × method × strength; 201 recipes	80 fixed frames; 10-trial smoke (163); 100-trial development (24)	Development gate ≥77/100 (B16 82 −5); selection frozen before E3
E3	Do joint recipes hold on reserved trials?	Three frozen joint recipes	500 reserved rollouts each	Wilson and paired intervals; report regardless of outcome
E4 (**H3**)	Does lower memory mean faster?	All E1/E3 arms	3×500 timed predictions	Median and p95 latency vs. peak memory
E5 (**H4**)	Where and why do arms fail?	—	Per-episode outcomes; 80-frame action change	Paired transitions per task; Spearman ρ
E6	Can a smaller backbone replace Qwen?	SmolVLM2-500M + adapter, 10k fine-tuning steps	500 reserved rollouts	Same as E1




Fig. 2. (a) B16 parameters by module. (b) Weight-only savings ceiling for quantizing the decoder linear layers versus the measured peak-memory reduction.

(double quantization, BF16 compute). Every other module stays BF16. *Study B* applies 201 recipes to individual modules and joint deployments: bitsandbytes INT8/NF4, HQQ 2–4 bit, GPTQ, AWQ-style scaling, TorchAO W8A8, magnitude/Wanda/SparseGPT sparsity, and structured removal of MLP channels, attention heads, layers and tokens. Calibrated methods use 20 development frames; no recipe sees reserved trials. Joint deployments also drop the unused world model and may restrict the vocabulary to the 53 token IDs that LIBERO instructions use.

Protocol. Table I lists the experiments. All runs use one RTX 3090, PyTorch 2.11, Transformers 5.5.4 and bitsandbytes 0.50.2. Rollouts use the ten LIBERO-Spatial tasks [19] and the 50 official initial states per task, with fixed per-episode seeds and a 280-step limit. Development trials use 10 different states per task, disjoint by hash. Success intervals are Wilson intervals [20]. Differences from B16 use a task-stratified paired bootstrap (10,000 resamples) over identical states and seeds. Latency is the synchronized observation-to-action time over 3×500 predictions after 20 warm-ups and excludes simulation. Memory is the peak allocated by PyTorch's CUDA allocator, in GB (10^9 bytes).

IV. RESULTS

A. *Decoder quantization (**H1**)*

Both quantized decoders keep success: neither paired interval excludes zero, and both exclude the 5-point bound (Table II). Q4 passes **H1** with 36.9% less memory. Q8 fails on memory: 23.3% against a 25.1% ceiling. The measured savings sit 1.8 and 0.4 points below the weight-only ceilings for INT8 and NF4 (Fig. 2b). Activations, quantization scales and LLM.int8's FP16 outlier path are the likely sources of the gap; we did not profile them separately. The decoder holds only 51% of the weights, so decoder-only quantization cannot save more than about 37%. Larger savings require compressing the other modules.

Our B16 reaches 95.0%, against 96.2% reported for LIBERO-Spatial [3]. We use the LeRobot port and our own evaluator, not the authors' evaluator.

B. *Where compression fails (**H2**)*

Fig. 4 shows 10-trial smoke results; B16 scores 8/10 on the same states. The language decoder is the precision bottleneck. Its best 3-bit and 2-bit variants score 7/10 and 1/10, and 3-bit results vary with the quantization axis (7/10 versus 0/10). Vision blocks and action MLPs keep 8/10 at 2 bits under every tested variant. Structure behaves the same way. Removing 8 of 28 language layers or 50% of its key–value heads scores 0/10 and 2/10, respectively. Vision keeps 8/10 with 50% of channels or heads removed and with 8 of 24 layers removed. Action modules degrade gradually. These smoke screens are coarse. At 100 development trials, removing 75% of action attention heads scores 69/100 and fails the 77/100 gate, although its smoke score was 7/10. Combining individually safe cuts also fails: joint channel and depth reductions score 70/100 and 65/100.

TABLE II

RESERVED-TRIAL RESULTS (500 ROLLOUTS EACH, RTX 3090). Δ: PAIRED SUCCESS CHANGE FROM B16 WITH 95% INTERVAL. GAIN/LOSS: STATES WHERE ONLY THE VARIANT OR ONLY B16 SUCCEEDS. STUDY B HAS ITS OWN B16 CONTROL (475/500, IDENTICAL PER-EPISODE OUTCOMES; MEDIAN 77.5 MS).

	Configuration	Success % [CI]	Δ pp [CI]	Gain/loss	Peak GB (−%)	Weights GB	Median (p95) ms	H1
	B16: BF16	95.0 [92.7, 96.6]	—	—	5.61	5.53	79.1 (84.3)	—
A	Q8: LLM.int8 decoder	94.8 [92.5, 96.4]	−0.2 [−1.2, +0.8]	3/4	4.30 (23.3)	4.13	157.4 (161.4)	**fail**
	Q4: NF4 decoder	95.8 [93.7, 97.2]	+0.8 [−0.6, +2.2]	8/4	3.54 (36.9)	3.44	93.6 (97.9)	**pass**
	C1: NF4 + lang./vision MLP −25/50%†	93.4 [90.9, 95.3]	−1.6 [−3.2, 0.0]	5/13	0.94 (83.2)	0.84	135.1 (138.0)	**pass**
B	C2: NF4 lang., HQQ2 vision/action†	98.0 [96.4, 98.9]	+3.0 [+1.2, +5.0]	22/7	1.07 (81.0)	0.98	143.5 (146.1)	**pass**
	C3: C2, full vocabulary (INT8 emb.)	96.8 [94.9, 98.0]	+1.8 [−0.2, +3.8]	19/10	1.38 (75.4)	1.29	142.9 (145.5)	**pass**
	S500: SmolVLM2-500M	2.2 [1.2, 3.9]	−92.8 [−94.8, −90.6]	—	3.30 (41.1)	2.30	1269.7 (1277.8)	**fail**

†Embedding table restricted to the 53 token IDs in LIBERO prompts; unseen tokens are rejected. C1–C3 also remove the unused world model.




Fig. 3. Reserved-trial trade-offs. (a) Success with 95% Wilson intervals; the green region meets **H1**'s memory and success targets. (b) Median latency with p95 tick. Q8/Q4 come from Study A, C1–C3 from Study B; both B16 controls produce identical outcomes.

These results guided the joint recipes. C2 keeps NF4 in the language decoder and uses 2-bit HQQ in the vision and action modules: 0.98 GB of weights and 1.07 GB peak memory. C1 adds MLP channel removal and reaches the smallest footprint, 0.84 GB. All three joint recipes pass **H1** by a wide margin on reserved trials (Fig. 3a).

C. *Memory is not speed (**H3**)*

Every compressed policy is slower than B16 (Fig. 3b). Q8 doubles latency (1.99×); by design, LLM.int8 splits each matrix multiplication into INT8 and FP16 outlier parts. Q4 costs 1.18×, and C1–C3 cost 1.74–1.85×. A plausible cause is that, at batch size one, the dequantization work these kernels add outweighs the memory traffic they save; we did not profile kernels. Fused GemLite kernels narrow the gap but do not close it: in the 80-frame screens, the 2-bit language decoder takes 99 ms with GemLite and 110 ms without, against 74 ms for B16. **H3** holds: memory and latency must be reported separately.

D. *Failure analysis (**H4**)*

Failures are timeouts in one task. Rollouts are deterministic given state and seed: the two B16 runs agree on all 500 episodes. All 25 B16 failures hit the 280-step limit; none crashed. Seventeen occur in task 5, "pick up the black bowl on the ramekin" (Fig. 5). Quantization mostly inherits these failures: 22 of Q8's 26 and 17 of Q4's 21 failed states also fail under B16.

Task 5 decides the aggregate. C2's net gain of 15 successes comes entirely from task 5 (33→48/50); changes in the other nine tasks cancel out. C1 loses 4 of its net 8 in task 5. A task where small action perturbations flip outcomes can create apparent "improvements" from compression. C2's +3.0-point gain is therefore not evidence that 2-bit weights improve the policy.

Offline divergence screens, but does not rank. For each recipe we measured the mean squared change in physical arm commands against B16 on 80 fixed frames, which needs no simulator. Across 163 recipes it correlates with smoke success ($\rho = -0.67$, $p < 10^{-21}$; Fig. 6). Below 10^{-4}, 64 of 65 recipes score ≥7/10; above 10^{-3}, only 30 of 62 do. Among the 24 recipes that reached development trials, the correlation is weak and not significant ($\rho = -0.27$, $p = 0.21$). **H4** holds for screening but not for ranking: closed-loop trials remain necessary among near-lossless recipes.




Fig. 4. Module sensitivity (10 trials per point; dotted line: B16 at 8/10). (a) Best tested variant per bit width; faint points show other variants. (b–d) Structured removal by module. Missing points were not tested because adjacent strengths already failed.




Fig. 5. Per-task success (%, 50 reserved trials per cell). Task 5 accounts for most failures and most differences between arms.




Fig. 6. Offline action change on 80 fixed development frames versus 10-trial success, for 163 recipes (jittered vertically). Recipes with identical actions sit at the left edge.

E. Negative result: smaller backbone

We replaced Qwen with SmolVLM2-500M [7] plus a trained adapter and fine-tuned the adapter, action head and predictor for 10,000 steps (7.1 GPU-hours, frozen backbone). It reached 2.2% on reserved trials and was 16× slower than B16, because SmolVLM tiles each image into 17 crops of 512 pixels. A later study fixed an image-scaling bug and adapted all decoder layers. It reached 31/100 development successes against 82/100 for B16. Within our budget, compressing the trained policy beats replacing its backbone.

V. Recommendations

1) **For a single-GPU deployment with a memory limit, start with Q4.** It uses a standard bitsandbytes configuration, saves 37% of peak memory, shows no detectable success loss, and costs 18% latency.
2) **Below 1.5 GB, use C3.** It keeps the full vocabulary. C1 and C2 are smaller but accept only the 53 token IDs in LIBERO prompts.
3) **Avoid LLM.int8 at batch size one.** It is slower than NF4 and saves less memory.
4) **Spend precision on the language decoder**, and compress vision and action modules first.
5) **Screen with offline action change, confirm with ≥500 paired trials.** Ten or even 100 trials cannot rank near-lossless recipes, and per-task paired transitions expose single-task effects such as task 5.

VI. Limitations and Conclusion

We evaluated one suite (LIBERO-Spatial), one checkpoint, one GPU and one seed per state. Success on Object, Goal or Long suites, on other hardware, and on a real robot is untested. Development and smoke selection used 10–100 trials, so sensitivity curves are coarse. We did not analyze attention maps; the failure analysis relies on action outputs and outcomes. Compressed archives are rebuilt from the original checkpoint plus a recipe and are not standalone Hugging Face checkpoints.

Post-training compression is effective for VLA-JEPA. NF4 decoder quantization meets our memory and success targets. Joint recipes keep ≥93% success in under 1.4 GB, a 4–6× reduction. The language decoder limits further compression, latency rises rather than falls, and a single hard task drives most

differences between arms. Fused low-bit kernels and evaluation on longer-horizon suites are the next steps.

References

[1] M. J. Kim *et al.*, "OpenVLA: An open-source vision-language-action model," in *CoRL*, 2024.

[2] K. Black *et al.*, "π_0: A vision-language-action flow model for general robot control," *arXiv:2410.24164*, 2024.

[3] J. Sun, W. Zhang, Z. Qi, S. Ren, Z. Liu, H. Zhu, G. Sun, X. Jin, and Z. Chen, "VLA-JEPA: Enhancing vision-language-action model with latent world model," *arXiv:2602.10098*, 2026.

[4] M. Assran *et al.*, "V-JEPA 2: Self-supervised video models enable understanding, prediction and planning," *arXiv:2506.09985*, 2025.

[5] Qwen Team, "Qwen3-VL-2B-Instruct," Hugging Face model card, 2025.

[6] M. Shukor *et al.*, "SmolVLA: A vision-language-action model for affordable and efficient robotics," *arXiv:2506.01844*, 2025.

[7] A. Marafioti *et al.*, "SmolVLM: Redefining small and efficient multimodal models," *arXiv:2504.05299*, 2025.

[8] T. Dettmers, M. Lewis, Y. Belkada, and L. Zettlemoyer, "LLM.int8(): 8-bit matrix multiplication for transformers at scale," in *NeurIPS*, 2022.

[9] T. Dettmers, A. Pagnoni, A. Holtzman, and L. Zettlemoyer, "QLoRA: Efficient finetuning of quantized LLMs," in *NeurIPS*, 2023.

[10] E. Frantar, S. Ashkboos, T. Hoefler, and D. Alistarh, "GPTQ: Accurate post-training quantization for generative pre-trained transformers," in *ICLR*, 2023.

[11] J. Lin *et al.*, "AWQ: Activation-aware weight quantization for on-device LLM compression and acceleration," in *MLSys*, 2024.

[12] H. Badri and A. Shaji, "Half-quadratic quantization of large machine learning models," https://github.com/dropbox/hqq, 2023.

[13] "QuantVLA," arXiv:2602.20309, 2026.

[14] M. Sun, Z. Liu, A. Bair, and J. Z. Kolter, "A simple and effective pruning approach for large language models," in *ICLR*, 2024.

[15] E. Frantar and D. Alistarh, "SparseGPT: Massive language models can be accurately pruned in one-shot," in *ICML*, 2023.

[16] "EcoVLA," arXiv:2602.00780, 2026.

[17] S. Kornblith, M. Norouzi, H. Lee, and G. Hinton, "Similarity of neural network representations revisited," in *ICML*, 2019.

[18] R. Cadene *et al.*, "LeRobot: State-of-the-art machine learning for real-world robotics in PyTorch," https://github.com/huggingface/lerobot, 2024.

[19] B. Liu, Y. Zhu, C. Gao, Y. Feng, Q. Liu, Y. Zhu, and P. Stone, "LIBERO: Benchmarking knowledge transfer for lifelong robot learning," in *NeurIPS Datasets and Benchmarks*, 2023.

[20] E. B. Wilson, "Probable inference, the law of succession, and statistical inference," *J. Amer. Statist. Assoc.*, vol. 22, pp. 209–212, 1927.