Assignment #2

Due date: April 3 (Mon.)

Submission

E-mail a zip file including the source codes, and a report to TA. An execution m-file should be included in the source codes. If the submitted execution m-file is executed, the result images of the problems should be displayed on a single screen. The filename should be named as student idn_name.zip (e.g. 20173000_kdhong.zip). TA's e-mail address is wschoi@issserver.kaist.ac.kr

Due date: **04/03 23:59**. (Refer to the delay policy in the web site)

Test images in the web site:

Color_baboon_256x256.raw Color_barbara_720x576.raw Color_lena_256x256.raw Gray_baboon_256x256.raw lenna tr1 256x256.raw lenna tr2 256x256.raw lenna tr2 256x256.raw lenna tr3 256x256.raw.

Notice

All the programming assignments are based on MATLAB. (Do not use any image processing function in MATLAB. But **you can use basic functions available in C++ standard library** like trigonometric, round, ceil, floor and rand, bitshift, sqrt etc. function.) All source codes for submission should include comments.

Describe your work and analyze the corresponding results in the report. A proper length of the report is 5 pages of A4 size without figures (if you include figures, the length would be less than 10 pages). Report exceeding the recommended length will get a penalty. The report should include the followings.

- 1. Simple theoretical backgrounds & programming strategies
- 2. Result images
- 3. Analysis of the results

If a **copy version** is found, the score will be **zero** point without any exception.

Scoring policy: implementation (60), processing time (10), and report (30)

For assignment #2, you may need to read or display color and gray raw images. For your convenient, the code to read or display images is given in the Appendix.

You can get test images in the website. Each pixel of a color image consists of three channel components, R (red), G (green), and B (blue). For a gray image, each pixel consists of a single channel component.

Data format of provided color images (H: image height, W: image width)

R ₁₁	G ₁₁	B ₁₁	R_{12}	G_{12}	B ₁₂	 •••	R _{1(W)}	$G_{1(W)}$	B _{1(W)}
				•••	•••	 •••	•••		•••
R _{(H)1}	G _{(H)1}	B _{(H)1}	R _{(H)2}	G _{(H)2}	B _{(H)2}	 	R _{(H)(W)}	$G_{(H)(W)}$	B _{(H)(W)}

1. Math preliminary

For a gray image, perform the convolution using the following kernels. (zero padding near the image boundaries) Show the result images and analyze them, respectively.

$$\mathbf{H}_{1} = \begin{bmatrix} 0.0751 & 0.1238 & 0.0751 \\ 0.1238 & 0.2044 & 0.1238 \\ 0.0751 & 0.1238 & 0.0751 \end{bmatrix}, \quad \mathbf{H}_{2} = \begin{bmatrix} 0.1667 & 0.6667 & 0.1667 \\ 0.6667 & -3.3333 & 0.6667 \\ 0.1667 & 0.6667 & 0.1667 \end{bmatrix}$$

2. Color Coordinate Transform

- 2.1. **For a color image**, display color components R, G, and B, respectively. Also, transform color coordinates RGB to HSI and YC_bC_r , respectively, and display each component of the HSI coordinates, and each component of the YC_bC_r coordinates, respectively. From the displayed results, compare the characteristics of the coordinates HSI, YC_bC_r , and RGB.
- 2.2. For three images transformed from the original color lenna image (lenna_tr1_256x256.raw, lenna_tr2_256x256.raw, lenna_tr3_256x256.raw), obtain the values of H, S, and I, respectively. Describe the relationship between the transformed images and the original, respectively.

3. Geometric Transform

For a color image, implement the affine transform of an image using homogeneous coordinates. The implementation should work for **any floating point parameter** values and any user can change the input parameters. By changing the parameters of the affine transform, perform the translation, rotation and scaling of the image respectively. (**Set the input parameters as in the bottom tables at the beginning of the code.**)

direction	translation	scaling	
X	Tr_x	Sc_x	
У	Tr_y	Sc_y	

rotation		
Ang		

4. Image down and up sampling

For a color image, down-sample a test image of 256x256 to an image of 128x128. And up-sample the down-sampled image to 384x384. Use **pyramid and Bell kernels**, respectively.

5. Quantization

5.1. **For a color image**, using the uniform quantizer, quantize an image into 2, 4 and 6 bits, respectively. Repeat the previous quantizations the compandor that is based on a compressor equation given below. Show those quantization results and provide corresponding PSNRs. (Set PSNR variables as given in the bottom table.)

Compressor equation:
$$f(x) = 255 \cdot \frac{\int_0^x [p_u(u)]^{1/3} du}{\int_0^{255} [p_u(u)]^{1/3} du}$$

Quantizer	2 bits	4 bits	6 bits	
Uniform	u_psnr_2	u_psnr_4	u_psnr_6	
Compandor	l_psnr_2	l_psnr_4	l_psnr_6	

5.2. **For a gray image**, repeat the above quantization process by adding the pseudo-random noise uniform over [-16, 16]. After subtracting the added noise from the quantization result, show and discuss your results. (Set PSNR variables as given in the bottom table.)

Quantizer	2 bits	4 bits	6 bits	
Uniform	un_psnr_2	un_psnr_4	un_psnr_6	
Lloyd-Max	ln_psnr_2	ln_psnr_4	ln_psnr_6	

Results

1.

- H1 kernel image
- H2 kernel image

2.1

- R, G, B, H, S, I, Y, Cb, Cr

2.2

- H,S,I images of lenna tr1
- H,S,I images of lenna tr2
- H,S,I images of lenna tr3

3.

- Geometric transformed image

4.

- Down sampling image
- Up sampling image using pyramid kernel
- Up sampling image using Bell kernel

5.1

- 2 bits uniform quantization image
- 4 bits uniform quantization image
- 6 bits uniform quantization image
- 2 bits compandor quantization image
- 4 bits compandor quantization image
- 6 bits compandor quantization image

5.2

- 2 bits uniform quantization image after subtracting noise
- 4 bits uniform quantization image after subtracting noise
- 6 bits uniform quantization image after subtracting noise
- 2 bits compandor quantization image after subtracting noise
- 4 bits compandor quantization image after subtracting noise
- 6 bits compandor quantization image after subtracting noise

Appendix

- A method for reading the input and displaying the output image in MATLAB.

```
% input image(gray)
file=fopen(fullfile('F:\Test images\Gray_lenna_256x256.raw'),'rb');
lena=fread(file,fliplr([256, 256]),'*uint8')';
fclose(file);
% input image(color)
file=fopen(fullfile('F:\Test images\Color_lenna_256x256.raw'),'rb');
lena=fread(file,fliplr([256, 256*3]),'*uint8')';
fclose(file);
%%%%% source code %%%%%
% output image (at once)
figure, title('Problem 1 H1 result');
imshow(uint8(H1_result));
figure, title('Problem_2_R');
imshow(uint8(lena_R));
figure, title('Problem_2_G');
imshow(uint8(lena_G));
figure, title('Problem_2_B');
imshow(uint8(lena_B));
```