Surface Mount

Power Splitter/Combiner

SP-2C1+

2 Way-0° 50Ω 640 to 1100 MHz

CASE STYLE: CA531
PRICE: $0.96 ea. QTY (20)

+RoHS Compliant
The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Available Tape and Reel at no extra cost

Reel Size	Devices/Reel
7"	20, 50, 100, 200, 500,1000

Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-65°C to 150°C
Power Input (as a splitter)	1.5W max.
Internal Dissipation	0.75W max.

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

SUM PORT	5
PORT 1	1
PORT 2	3
GROUND	2,4,6

Features

- wide bandwidth
- good isolation, 20 dB typ.
- excellent VSWR, 1.25:1 typ.
- excellent power handling, 1.5W
- small size
- aqueous washable

Applications

- cellular
- GSM
- Land Mobile
- ISM
- PDC

Outline Drawing



Outline Dimensions (inch / mm)

A	B	C	D	E	F	G	H	J
.052	.067	.106	.122	.035	.064	.087	.118	.067
1.32	1.70	2.69	3.10	0.89	1.63	2.21	3.00	1.70

K	L	M	N	P	Q	R	S	wt
.083	.033	.042	.012	.020	.012	.006	.018	grams
2.11	0.84	1.07	0.30	0.51	0.30	0.15	0.46	0.020

Electrical Specifications

FREQ. RANGE (MHz)	ISOLATION (dB)		INSERTION LOSS (dB) ABOVE 3.0 dB		PHASE UNBALANCE (Degrees)	AMPLITUDE UNBALANCE (dB)	VSWR (:1)	
	Typ.	Min.	Typ.	Max.	Max.	Max.	S-Port Typ.	Output Ports Typ.
640-1100	20	10	0.4	1.0	2	0.2	1.25	1.25

Typical Performance Data

Frequency (MHz)	Total Loss[1] (dB)		Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1	S-2						
640.00	3.42	3.43	0.01	12.16	0.05	1.39	1.25	1.26
680.00	3.40	3.41	0.01	14.02	0.05	1.34	1.20	1.20
720.00	3.39	3.39	0.01	16.44	0.05	1.29	1.15	1.15
760.00	3.37	3.38	0.01	19.75	0.04	1.24	1.11	1.12
800.00	3.37	3.38	0.01	24.99	0.04	1.20	1.11	1.11
840.00	3.37	3.38	0.01	37.94	0.04	1.17	1.14	1.14
860.00	3.37	3.38	0.01	36.99	0.04	1.16	1.16	1.16
880.00	3.38	3.39	0.01	29.21	0.04	1.17	1.19	1.19
900.00	3.39	3.39	0.01	25.08	0.04	1.17	1.22	1.21
940.00	3.41	3.42	0.01	20.29	0.03	1.21	1.27	1.27
960.00	3.43	3.43	0.01	18.66	0.02	1.24	1.30	1.30
980.00	3.44	3.45	0.01	17.32	0.03	1.27	1.33	1.33
990.00	3.46	3.47	0.01	16.73	0.03	1.29	1.35	1.35
1000.00	3.47	3.48	0.01	16.18	0.03	1.31	1.37	1.36
1100.00	3.64	3.65	0.01	12.18	0.04	1.56	1.52	1.51

1. Total Loss = Insertion Loss + 3dB splitter loss.

SP-2C1+
TOTAL LOSS



SP-2C1+
ISOLATION



SP-2C1+
VSWR



electrical schematic



Demo Board MCL P/N: TB-374
Suggested PCB Layout (PL-232)



NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .020" ± .0015"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)

DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

ESD Rating
Human Body Model (HBM): Class 1A (250 v to <500 v) in accordance with ANSI/ESD STM 5.1 - 2001
Machine Model (MM): Class M1 (< 100 v) in accordance with ANSI/ESD STM 5.2 - 1999 (pass 50V)

REV. B
M127604
ED-12348C/1+
SP-2C1+
RS/LC/CP/AM
120509