

Clumpy Medium Extension of LaRT: Algorithm Description (v2.00)

Contents

1. Overview	2
2. OOP Architecture (v2.10)	3
2.1 Abstract base type	3
2.2 Concrete clump type	3
2.3 Runtime selection in <code>main.f90</code>	4
2.4 Comparison with v2.00	4
3. Physical Setup	5
3.1 Geometry	5
3.2 Clump Count	5
3.3 Clump Physical Parameters	6
3.4 Derived Global Optical-Depth Quantities (τ_{homo} , $N_{\text{HI,homo}}$, τ_{max} , $N_{\text{HI,max}}$)	7
3.5 Clump Velocities	8
4. Clump Placement: Random Sequential Addition (RSA)	9
4.1 Concept	9
4.2 Uniform Sampling Inside the Shell	9
4.3 Fully-Inside Constraint	10
4.4 Placement Algorithm	11
4.5 Linked-List Hash Grid and the 27-Cell Rule	12
4.6 Acceptance Rate and Jamming Limit	13
4.7 Multi-node Correctness	13
5. CSR Acceleration Grid	13
5.1 Motivation	13
5.2 Data Structure: Compressed Sparse Row	13
5.3 Cell Grid and Domain	14
5.4 Clump Registration: AABB Overlap Test	14
5.5 Two-Pass Construction	14

6. Raytrace Through the Clump Medium	16
6.1 Overview	16
6.2 Ray–Sphere Intersection	16
6.3 DDA Search for Next Clump	16
6.4 Optical Depth Traversal	17
6.5 Optical Depth to Edge	18
7. Peel-Off Observations	18
8. FITS Output of Clump Information	19
9. Input Parameters Summary	20
10. Memory Layout	22
11. Validation and Examples	23
12. Spatially-Varying Clump Properties	24
12.1 Input parameters	24
12.2 Covering factor under non-uniformity	24
12.3 Implementation outline	25
12.4 Example inputs	25
13. Standalone Clump Generator (make_clumps.x)	26
14. Standalone Sight-line Tau Calculator (make_sightline_tau.x)	27

1. Overview

The clumpy medium mode adds a population of N non-overlapping spherical clumps inside a spherical domain of radius R . Each clump is a sphere of radius r_c with uniform Lyman- α opacity; the inter-clump medium is vacuum.

In **LaRT_v2.00** the mode is activated by setting

```
par%use_clump_medium = .true.
```

in the input namelist. The companion v2.10 branch additionally accepts

```
par%grid_type = 'clump'
```

which v2.00 does not understand. Existing v2.00 input files that use `par%use_clump_medium = .true.` continue to work in v2.10 unchanged.

New source files introduced for this mode:

File	Role
clump_mod.f90	Clump population: init, RSA placement, CSR grid, raytrace helpers
raytrace_clump.f90	Raytrace through the clump medium (DDA + sphere intersection)
grid_mod_clump.f90	Grid setup: creates Cartesian shell grid, then calls init_clumps

The OOP dispatch is handled by `grid_class.f90` through the concrete type `grid_clump_type` (see §2.).

2. OOP Architecture (v2.10)

2.1 Abstract base type

`grid_class.f90` defines an abstract base type:

```

1  type, abstract :: grid_base_type
2  contains
3      procedure(raytrace_tau_if), deferred :: raytrace_to_tau
4      procedure(raytrace_edge_if), deferred :: raytrace_to_edge
5      procedure(scatter_if), deferred :: scattering
6      procedure(output_if), deferred :: output_reduce
7      procedure(output_if), deferred :: output_normalize
8      procedure(write_if), deferred :: write_output
9      procedure(peel_simple_if), deferred :: peeling_direct
10     ...
11     procedure(grid_init_if), deferred :: grid_init
12     procedure(grid_destroy_if), deferred :: grid_destroy
13 end type grid_base_type

```

2.2 Concrete clump type

`grid_clump_type` extends `grid_base_type`:

```

1  type, extends(grid_base_type) :: grid_clump_type
2      type(grid_type) :: g      ! Cartesian shell grid (uniform clump parameters)
3  contains
4      procedure :: raytrace_to_tau      => clump_raytrace_to_tau
5      procedure :: raytrace_to_edge    => clump_raytrace_to_edge
6      procedure :: add_escaped_to_jout => clump_add_escaped_to_jout
7      procedure :: generate_photon     => clump_generate_photon
8      procedure :: scattering          => clump_scattering
9      procedure :: output_reduce       => clump_output_reduce
10     procedure :: output_normalize    => clump_output_normalize

```

```

11  procedure :: write_output      => clump_write_output
12  procedure :: observer_create   => clump_observer_create
13  procedure :: observer_destroy  => clump_observer_destroy
14  procedure :: make_sightline_tau => clump_make_sightline_tau
15  procedure :: grid_init         => clump_grid_init
16  procedure :: grid_destroy      => clump_grid_destroy
17  end type grid_clump_type

```

All procedures delegate to the same underlying subroutines used in v2.00 (raytrace_clump_mod, scattering_car, etc.).

2.3 Runtime selection in main.f90

Grid selection is performed once at startup:

```

1  class(grid_base_type), allocatable :: grid
2
3  select case (trim(par%grid_type))
4  case ('clump')
5      allocate(grid_clump_type :: grid)
6  case ('amr')
7      allocate(grid_amr_type :: grid)
8  case default ! 'car'
9      allocate(grid_car_type :: grid)
10 end select
11
12 call grid%grid_init()
13 ...
14 call grid%output_reduce()
15 call grid%output_normalize()
16 call grid%write_output(trim(par%out_file))
17 call grid%grid_destroy()

```

Scatter, peel-off, and observer routines are invoked identically for all grid types through the polymorphic grid variable.

2.4 Comparison with v2.00

In v2.00 the same dispatch was performed via module-level procedure pointers declared in define.f90 and assigned in setup_procedure():

```

1  ! v2.00 approach (procedure pointers in define.f90)

```

```

2 procedure(raytrace_tau_if), pointer :: raytrace_to_tau => null()
3 ...
4 ! setup.f90: setup_procedure()
5 if (par%use_clump_medium) then
6   raytrace_to_tau => raytrace_to_tau_clump
7   ...
8 end if

```

The v2.10 OOP approach is semantically equivalent but eliminates the global mutable state and makes the dispatch relationship explicit in the type system. The underlying physics routines (`clump_mod.f90`, `raytrace_clump.f90`, `grid_mod_clump.f90`) are *identical* between v2.00 and v2.10.

3. Physical Setup

3.1 Geometry

The outer domain is a sphere of radius $R = \text{par}\%r_{\text{max}}$ (code units). N spherical clumps of radius $r_c = \text{par}\%clump_radius$ are placed at random inside this sphere (non-overlapping).

A Cartesian grid of $N_x \times N_y \times N_z$ cells is created with the same bounding box $[-R, R]^3$. Grid arrays (`rhokap`, `Dfreq`, `voigt_a`, `vf`) are set to uniform values:

- `rhokap` = 0 everywhere (opacity lives only inside clumps);
- `Dfreq` = $\Delta\nu_D^{cl}$ (clump Doppler frequency);
- `voigt_a` = a_V^{cl} (clump Voigt parameter);
- `vfx` = `vfy` = `vfz` = 0.

Peel-off and scattering routines read these uniform grid values, so no special-casing is needed inside those modules.

3.2 Clump Count

The user specifies one of three equivalent parameters; the code derives N from whichever is set:

From f_{cov} (covering factor): The mean number of clumps intercepted by a radial ray from the center to the sphere surface is

$$f_{\text{cov}} = N \frac{\pi r_c^2}{\pi R^2} \cdot \frac{R}{\frac{4}{3}\pi R^3 / (4\pi R^2)} = \frac{3}{4} N \left(\frac{r_c}{R}\right)^2, \quad (1)$$

hence

$$N = \frac{4}{3} f_{\text{cov}} \left(\frac{R}{r_c}\right)^2. \quad (2)$$

Input parameter: `par%clump_f_cov`.

From f_{vol} (volume filling factor):

$$f_{\text{vol}} = N \left(\frac{r_c}{R} \right)^3, \quad N = f_{\text{vol}} \left(\frac{R}{r_c} \right)^3. \quad (3)$$

Input parameter: `par%clump_f_vol`.

Direct specification: `par%clump_N_clumps`.

3.3 Clump Physical Parameters

The clump temperature T_c defaults to `par%temperature` unless `par%clump_temperature > 0`. Derived quantities:

$$v_{\text{th}} = v_{\text{th},1} \sqrt{T_c}, \quad v_{\text{th},1} = \sqrt{2k_B/m_H} \approx 12.84 \text{ km s}^{-1} / \sqrt{10^4 \text{ K}}, \quad (4)$$

$$\Delta\nu_D^{cl} = v_{\text{th}} / (\lambda_0 \times \text{km2um}), \quad (5)$$

$$a_V^{cl} = \frac{A_{21}}{4\pi \Delta\nu_D^{cl}}, \quad (6)$$

where λ_0 is the Lyman- α rest wavelength.

Three mutually exclusive parameters specify the opacity of each individual clump (the first positive value in the priority order wins):

1. `par%clump_tau0` — line-center optical depth (dimensionless): The line-center τ of one clump from its center to its surface.

$$\kappa_c = \frac{\tau_0}{\phi(0, a_V^{cl}) r_c}, \quad (7)$$

where $\phi(x, a)$ is the Voigt profile at dimensionless frequency x .

2. `par%clump_NHI` — per-clump HI column density [cm^{-2}]: The HI column density of a *single clump* from its center to its surface. This must be clearly distinguished from the *total system* column density (`par%N_HI_max`), which is the average HI column density along a radial sightline through the entire clumpy sphere (center to outer boundary, averaged over all sightlines through the random clump population).

Given $N_{\text{HI}}^{cl} = n_H r_c d_{\text{cm}}$, the opacity follows as

$$\kappa_c = \frac{N_{\text{HI}}^{cl} \sigma_0}{r_c}, \quad (8)$$

where $\sigma_0 \equiv \text{line\%cross0} / \Delta\nu_D^{cl}$ [cm^2] is the line-center cross-section. (`line\%cross0` = $\pi e^2 f / (m_e c \sqrt{\pi})$ has units [$\text{cm}^2 \text{ Hz}$]; dividing by $\Delta\nu_D^{cl}$ [Hz] gives the physical cross-section [cm^2].) This is equivalent to $\tau_0 = N_{\text{HI}}^{cl} \sigma_0 \phi(0, a_V^{cl})$. Unlike `clump_nH`, this option does *not* require `par%distance_unit`.

3. `par%clump_nH` — hydrogen number density [cm^{-3}]: $\kappa_c = n_H \sigma_0 d_{\text{cm}}$, where $\sigma_0 \equiv \text{line\%cross0} / \Delta\nu_D^{cl}$ [cm^2] (requires `par%distance_unit`).

4. System-level fallback (`par%taumax` or `par%N_HI_max`): If none of the per-clump inputs above are given, LaRT back-solves the peak per-clump opacity so the realised radial-sightline target matches `par%taumax` (line-centre optical depth from box centre to outer surface) or `par%N_HI_max` (HI column density along the same sightline; `par%N_gas_max` is an alias). For uniform clumps this inverts the closed forms

$$\tau_{\max} = \frac{4}{3} f_{\text{cov}} \tau_{c,0}, \quad N_{\text{HI},\max} = \frac{4}{3} f_{\text{cov}} N_{\text{HI}}^{\text{cl}}. \quad (9)$$

For profile mode it inverts the radial quadrature

$$\tau_{\max} = \frac{4\pi}{3} A_{\text{norm}} r_{c,0}^3 \kappa_{c,0} \phi(0, a_V^{\text{cl}}) \int_{r_{\min}}^R S_n(r) S_r(r)^3 S_d(r) dr, \quad (10)$$

where S_n , S_r , S_d are the number, radius, and density shape factors, and A_{norm} is fixed by the population spec (`clump_N_clumps`, `clump_f_vol`, or `clump_f_cov`) before opacity is computed. An identical expression with $\phi(0, a)$ replaced by $\Delta\nu_D^{\text{cl}}/\sigma_0$ governs `N_HI_max`. When `par%clump_input_file` is in use, the loaded `cl_rhokap(i)` array is rescaled by a single factor $\alpha = \tau_{\max,\text{target}}/\tau_{\max,\text{realised}}$ (using the small-angle expected-column formula on the placed clumps), preserving the relative density structure of the file.

3.4 Derived Global Optical-Depth Quantities (τ_{homo} , $N_{\text{HI,homo}}$, $\tau_{\max}$, $N_{\text{HI},\max}$)

LaRT carries four scalar parameters that describe the line-center optical depth and HI column density of the medium as a whole:

`par%tauhomo`, `par%N_gashomo` — the line-center optical depth and HI column density of an equivalent *homogeneous* medium that contains the same total HI mass spread uniformly over the sphere volume.

`par%taumax`, `par%N_gas_max` — the line-center optical depth and HI column density along a single radial sightline from the center to the +z surface.

For a homogeneous medium these four numbers are equal up to geometric factors; for a clumpy medium `taumax` along any specific sightline fluctuates strongly (it can be zero if no clumps lie along the LOS, or many times the homogeneous value if several clumps are stacked), while `tauhomo` is a deterministic property of the medium (mass / volume).

The auto-detection of the simulation frequency range (`par%xfreq_max/xfreq_min`) inside `car_setup_freq_grid` uses both quantities:

$$a_{\tau,3} = (a_V \cdot \tau_{\text{homo}})^{1/3}, \quad x_{\max} \approx x_{\text{scale}}(\tau_{\max}) \cdot a_{\tau,3}. \quad (11)$$

Hence even when the user supplies `velocity_min/velocity_max` explicitly, having physically meaningful `tauhomo` and `taumax` is important for the FITS header to be informative and for the fall-back auto-range to produce a usable grid.

Derivation in clump mode. `init_clumps()` is called BEFORE `grid_create()` inside `grid_create_clump`, so the realized clump count N_c , opacity κ_c , and Voigt parameter a_V^{cl} are all known when the global τ/N values are derived. When clumps populate the radial shell $r_{\min} \leq r \leq R$ (the default `par%rmin = -999` is treated as $r_{\min} = 0$, recovering the full-sphere case), the volume filling factor and the LaRT covering factor are

$$f_{\text{vol}} = \frac{N_c r_c^3}{R^3 - r_{\min}^3}, \quad f_{\text{cov}} = \frac{3}{4} \frac{N_c r_c^2}{R^2 + R r_{\min} + r_{\min}^2}. \quad (12)$$

With $r_{\min} = 0$ these reduce to the original expressions $N_c (r_c/R)^3$ and $\frac{3}{4} N_c (r_c/R)^2$. The line-center optical depth of one clump (center to surface) is $\tau_0 = \kappa_c \phi(0, a_V^{cl}) r_c$. Distributing the same total HI mass uniformly over the shell of volume $V_{\text{shell}} = \frac{4}{3} \pi (R^3 - r_{\min}^3)$ gives the homogeneous-equivalent opacity per unit length $\langle \kappa \rangle_{\text{lc}} = f_{\text{vol}} \kappa_c \phi(0, a_V^{cl})$, and the volume-averaged τ along a shell sightline of length $R - r_{\min}$ is

$$\tau_{\text{homo}} = \langle \kappa \rangle_{\text{lc}} \cdot (R - r_{\min}) = \frac{4}{3} f_{\text{cov}} \tau_0. \quad (13)$$

The simplification uses the identity $(R - r_{\min}) / (R^3 - r_{\min}^3) = 1 / (R^2 + R r_{\min} + r_{\min}^2)$. This is also the EXPECTED radial τ_{max} for a random sightline through the clumpy shell, so τ_{homo} and τ_{max} have the same expectation. The HI columns follow by replacing τ_0 with the per-clump column N_{HI}^{cl} :

$$N_{\text{HI,homo}} = N_{\text{HI,max}}^{(\text{expected})} = \frac{4}{3} f_{\text{cov}} N_{\text{HI}}^{cl}, \quad N_{\text{HI}}^{cl} = \frac{\kappa_c}{\sigma_0} = \frac{\kappa_c \Delta \nu_D^{cl}}{\text{line\%cross0}} r_c. \quad (14)$$

For the canonical `clump_NHI = 7.5e17 cm-2`, $f_{\text{cov}} = 1$, $T = 10^4$ K test case this gives $N_{\text{HI,homo}} = 1.0 \times 10^{18} \text{ cm}^{-2}$, $\tau_{\text{homo}} = 5.9 \times 10^4$, and $a_{\tau,3} = 3.0$. When the user supplies the system-level target `par%N_HI_max` (or `par%taumax`) and lets `init_clumps` back-solve κ_c via the shell formula, the realized $N_{\text{HI,homo}}$ matches the input target exactly (modulo `nint` rounding of N_c). Example: `clump_NHI18_fcov1.in` with `par%rmin = 0.1`, $f_{\text{cov}} = 1$, `par%N_HI_max = 1.0 × 1018` reports $N_{\text{gashomo}} = 1.000 \times 10^{18}$ as expected.

The derivation only overrides parameters that the user did not specify (stored as ≤ 0 before `read_input`); explicit user values are always preserved.

3.5 Clump Velocities

Each clump's velocity is the sum of two independent components:

$$\mathbf{v}_i = \mathbf{v}_{\text{sys}}(\mathbf{r}_i) + \mathbf{v}_{\text{rand},i}, \quad (15)$$

where $\mathbf{v}_{\text{sys}}$ is a position-dependent systematic flow (set by `par%velocity_type`) and $\mathbf{v}_{\text{rand}}$ is an independent Gaussian random component (set by `par%clump_sigma_v`). Either component can be zero.

Random component: If `par%clump_sigma_v > 0`, each clump is assigned $\mathbf{v}_{\text{rand},i} \sim \mathcal{N}(0, \sigma_v^2)$ per component (drawn in `generate_clumps`).

Systematic component (par%velocity_type): After RSA placement, `assign_clump_velocities_from_type` evaluates the flow velocity at each clump center and adds it to the existing (possibly non-zero) velocity. Supported types:

velocity_type	Formula	Parameters
'hubble'	$\mathbf{v} = V_{\text{exp}} \mathbf{r}/R$	V_{exp}
'constant_radial'	$\mathbf{v} = V_{\text{exp}} \hat{\mathbf{r}}$	V_{exp}
'parallel_velocity'	$\mathbf{v} = (V_x, V_y, V_z)$	V_x, V_y, V_z
'ssh'	see below	$V_{\text{peak}}, r_{\text{peak}}, \Delta V$
'rotating_solid_body'	$\mathbf{v} = V_{\text{rot}}(-y, x, 0)/R$	V_{rot}
'rotating_galaxy_halo'	flat rotation about z	$V_{\text{rot}}, r_{\text{inner}}$

All velocity magnitudes are in km/s. The 'ssh' model (Song, Seon & Hwang 2020) gives a linear rise inside r_{peak} and a Hubble-like outer flow:

$$v(r) = \begin{cases} V_{\text{peak}} r/r_{\text{peak}} & r < r_{\text{peak}}, \\ V_{\text{peak}} + \Delta V (r - r_{\text{peak}})/(R - r_{\text{peak}}) & r \geq r_{\text{peak}}. \end{cases} \quad (16)$$

The 'rotating_galaxy_halo' model uses the cylindrical radius $\rho = \sqrt{x^2 + y^2}$ and gives solid-body rotation inside r_{inner} and a flat curve ($v_\phi = V_{\text{rot}}$) outside.

4. Clump Placement: Random Sequential Addition (RSA)

4.1 Concept

Random Sequential Addition (RSA) is a simple stochastic algorithm for generating configurations of non-overlapping hard spheres. Candidate positions are drawn at random one at a time; each is tested against all previously accepted clumps and either accepted (no overlap) or discarded irreversibly (overlap detected). Because accepted positions are never moved, RSA requires no iterative relaxation.

The non-overlap condition enforces a minimum center-to-center distance of $2r_c$. RSA reliably converges for volume filling factors $f_{\text{vol}} \lesssim 35\%$; above this threshold, the fraction of unblocked placement space decreases so steeply that placing the last few clumps may require enormous numbers of attempts. The theoretical 3-D jamming limit for RSA is $f_{\text{vol}} \approx 38\%$.

4.2 Uniform Sampling Inside the Shell

Candidate positions must be distributed *uniformly* inside the radial shell $r_{\text{min}} \leq r \leq R$, where $r_{\text{min}} = \max(0, \text{par}\%r_{\text{min}})$ and $R = \text{par}\%r_{\text{max}}$. The default `par%rmin = -999` is treated as $r_{\text{min}} = 0$ and reproduces the original “filled sphere” behavior; setting $r_{\text{min}} > 0$ carves out an inner cavity in which no clumps are placed.

This is achieved by box-rejection on the spherical shell:

1. Draw x_c, y_c, z_c each uniformly from $[-R, R]$.
2. Compute $d^2 = x_c^2 + y_c^2 + z_c^2$.
3. Accept if $r_{\min}^2 \leq d^2 \leq R^2$; otherwise draw again.

The acceptance probability is

$$\frac{\pi}{6} \frac{R^3 - r_{\min}^3}{R^3}, \quad (17)$$

which reduces to $\pi/6 \approx 52\%$ when $r_{\min} = 0$. Box-rejection avoids trigonometric functions and yields an exactly uniform distribution in 3-D Cartesian space.

4.3 Fully-Inside Constraint

By default the placement requires the *whole* clump to fit inside the shell, not just its center. A clump of radius r_c centered at distance d from the box origin is accepted only when

$$r_{\min} \leq d - r_c \quad \text{and} \quad d + r_c \leq R. \quad (18)$$

This is controlled by the namelist switch

```
1 par%clump_fully_inside = .true.      ! default
2 par%rmin                = -999      ! default (no inner cavity)
```

- Uniform-radius case: the placement shell is inset on both sides – from $[r_{\min}, R]$ to $[r_{\min} + r_c, R - r_c]$ – so the box-rejection draw above samples uniformly inside the inset shell. All accepted clumps automatically satisfy Eq. (18); no per-sample rejection is needed.
- Spatially-varying clump radii (clump_radius_profile not 'constant'): the inverse-CDF radial draw is built so that $n_{cl}(r) = 0$ for $r < r_{\min}$, ensuring centers land in the shell automatically. If $d + r_c > R$ or $d - r_c < r_{\min}$, the sample is discarded and a new pair is drawn.
- If $r_{\min} + 2r_{c,\max} > R$ – the shell is too narrow to hold a single clump – the run aborts with an error. Likewise the run aborts if the largest possible clump radius exceeds R (a steep clump_radius_profile would yield $r_c \geq R$ near the surface).

Setting `par%clump_fully_inside = .false.` restores the legacy behavior, in which only the clump center is required to lie in $[r_{\min}, R]$. Clumps near either boundary may then protrude past $r = R$ or into the cavity below $r = r_{\min}$; this reproduces results generated before these options were introduced. As an illustration, the `clump_radius_powerlaw` test case (`par%clump_radius = 0.01, r_0 = 0.5, \alpha = -1, N = 10^4, R = 1, r_{\min} = 0`) yields ~ 564 outer-edge protruding clumps with the legacy setting and zero with the new default.

The conversion of `clump_f_vol` or `clump_f_cov` to `N_clumps` uses the shell volume $V_{\text{shell}} = \frac{4}{3}\pi(R^3 - r_{\min}^3)$ and the shell sightline factor $R^2 + Rr_{\min} + r_{\min}^2$, so f_{vol} and f_{cov} refer to the shell rather than the full sphere.

With $r_{\min} = 0$ these reduce exactly to the original $(R/r_c)^3$ and $(R/r_c)^2$ expressions, preserving prior runs. When `clump_fully_inside` is on, the realized f_{vol} and f_{cov} fall slightly below the target whenever r_c is a non-trivial fraction of $R - r_{\min}$, since the available placement volume shrinks from $\frac{4}{3}\pi(R^3 - r_{\min}^3)$ to $\frac{4}{3}\pi[(R - r_c)^3 - (r_{\min} + r_c)^3]$. Specify a slightly larger $f_{\text{vol}}/f_{\text{cov}}$ if exact matching is required.

4.4 Placement Algorithm

```

1  do while (icl < N_clumps)
2
3      !--- Step 1: draw candidate inside the shell [rmin, R]
4      !           (with R, rmin inset by r_c when clump_fully_inside)
5      do
6          xc = (2.0*rand() - 1.0) * R_outer
7          yc = (2.0*rand() - 1.0) * R_outer
8          zc = (2.0*rand() - 1.0) * R_outer
9          d2 = xc**2 + yc**2 + zc**2
10         if (R_inner**2 <= d2 .and. d2 <= R_outer**2) exit
11     enddo
12
13     !--- Step 2: locate candidate in hash-grid cell (ig, jg, kg)
14     ig = int((xc - xmin) / cell_size)
15     jg = int((yc - ymin) / cell_size)
16     kg = int((zc - zmin) / cell_size)
17
18     !--- Step 3: check 27 neighboring cells for overlap
19     overlap = .false.
20     outer: do kg2 = kg-1, kg+1
21         do jg2 = jg-1, jg+1
22             do ig2 = ig-1, ig+1
23                 if (out of bounds) cycle
24                 jnb = head(ig2, jg2, kg2)      ! first clump in this hash cell
25                 do while (jnb > 0)
26                     if (dist2(xc,yc,zc, cl_x(jnb),cl_y(jnb),cl_z(jnb)) < (2*rc)**2) then
27                         overlap = .true.; exit outer ! reject immediately on first overlap
28                     endif
29                     jnb = nxt(jnb)              ! follow linked list to next clump
30                 enddo
31             enddo; enddo; enddo outer
32

```

```

33  if (overlap) cycle                ! reject: draw new candidate
34
35  !--- Step 4: accept -- record position and random velocity
36  icl = icl + 1
37  cl_x(icl) = xc; cl_y(icl) = yc; cl_z(icl) = zc
38  if (sigma_v > 0.0) then
39      cl_vx(icl) = sigma_v * gauss_random() ! one independent draw per component
40      cl_vy(icl) = sigma_v * gauss_random()
41      cl_vz(icl) = sigma_v * gauss_random()
42  endif
43
44  !--- Step 5: prepend clump to the linked list for cell (ig, jg, kg)
45  nxt(icl) = head(ig, jg, kg)
46  head(ig, jg, kg) = icl
47
48  enddo
    
```

4.5 Linked-List Hash Grid and the 27-Cell Rule

Naively, checking candidate n against all $n-1$ accepted clumps costs $O(n)$, giving $O(N^2)$ total work. The linked-list hash grid reduces each overlap check to $O(1)$ expected cost by spatially indexing accepted clumps.

The domain $[-R, R]^3$ is partitioned into N_g^3 uniform cells with

$$N_g = \min(512, \lfloor N^{1/3} \rfloor + 1), \quad \ell_{\text{RSA}} = \frac{2R}{N_g}. \quad (19)$$

Two integer arrays encode the linked lists: $\text{head}(i, j, k)$ is the index of the first clump in cell (i, j, k) (0 if empty), and $\text{nxt}(icl)$ is the next clump in the same cell list (0 = end of list). When a new clump is accepted (Step 5 above), it is prepended to the head of its cell's list in $O(1)$.

Why 27 cells are sufficient. Two clumps overlap iff their center separation is $< 2r_c$. If the candidate lies in cell (i, j, k) , any overlapping clump must satisfy $|x_{cl} - x_c| < 2r_c$. Since $\ell_{\text{RSA}} \geq 2r_c$ by construction (eq. 19), the overlapping clump's cell index i' satisfies $i' \in \{i-1, i, i+1\}$, and likewise for j' and k' . Checking all $3^3 = 27$ cells centered on (i, j, k) is therefore both sufficient and complete — no overlapping clump can lie outside this neighborhood.

Cell-size constraint. The 27-cell rule requires $\ell_{\text{RSA}} \geq 2r_c$, i.e. $N_g \leq R/r_c$. For the reference case ($R = 1, r_c = 0.01$): $R/r_c = 100, N_g = \lfloor 66667^{1/3} \rfloor + 1 = 42, \ell_{\text{RSA}} = 2/42 \approx 0.048 \gg 2r_c = 0.02$. ✓

4.6 Acceptance Rate and Jamming Limit

As more clumps are placed, their exclusion zones (spheres of radius $2r_c$ around each accepted clump) collectively block an increasing fraction of the placement domain. The per-candidate acceptance probability p_{acc} decreases monotonically with f_{vol} and approaches zero at the jamming limit.

For the reference case ($f_{\text{cov}} = 5$, $r_c/R = 0.01$, $N = 66667$, $f_{\text{vol}} = 0.067$), the overall acceptance rate is $\approx 74\%$: roughly 90 000 candidates are drawn to place 66 667 clumps. The algorithm remains practical for $f_{\text{vol}} \lesssim 35\%$.

4.7 Multi-node Correctness

In a multi-node MPI run, naively executing RSA on each node independently would produce different clump layouts per node (each node has its own random-number state), corrupting photon transport across node boundaries. Clump positions are therefore generated *only on global rank 0* (`p_rank==0`). The resulting `cl_x/y/z` and `cl_vx/vy/vz` arrays are then broadcast to all other node-head processes via six `MPI_BCAST` calls on `mpar%SAME_HRANK_COMM` (the communicator containing exactly one rank-0 process per node). Ranks within the same node share the arrays through MPI-3 shared memory, requiring no further communication. The CSR build is fully deterministic given the positions, so every node constructs the same acceleration grid without any additional broadcast.

This corrects an earlier bug in which `h_rank==0` (the within-node head rank) triggered independent RSA passes on each node, producing different clump layouts per node.

5. CSR Acceleration Grid

5.1 Motivation

During radiative transfer, a photon in vacuum must find the nearest clump along its current flight direction at every propagation step. Checking all N clumps per step would cost $O(N)$ per query and become prohibitive for large populations ($N \sim 10^4\text{--}10^5$). The CSR acceleration grid pre-sorts clumps into spatial cells; the DDA traversal (§6.3) then visits only the cells the ray crosses, and within each cell tests only the few registered clumps. Together, DDA+CSR achieves $O(1)$ amortised cost per nearest-clump query, independent of N .

5.2 Data Structure: Compressed Sparse Row

Instead of a list-of-lists (which requires many small dynamic allocations), all per-cell clump lists are packed into two flat integer arrays in *Compressed Sparse Row* (CSR) format — the same layout used for sparse matrices:

- `cg_start(0:Ncell)`: `cg_start(icell)` is the 1-based index of the first entry for cell `icell` in `cg_list`. The entries for cell `icell` occupy positions `cg_start(icell) ... cg_start(icell+1)-1`; their count is `cg_start(icell+1) - cg_start(icell)`.

- `cg_list(1:Ntot)`: flat concatenation of all per-cell clump-index lists.

Retrieving the clump list for any cell is an $O(1)$ array slice with no pointer chasing. To illustrate: suppose four cells contain the clumps $\{2, 5\}$, $\{\}$, $\{1, 3\}$, $\{4\}$ respectively:

$$\begin{aligned} \text{cg_start} &= [1, 3, 3, 5, 6], \\ \text{cg_list} &= [2, 5, 1, 3, 4]. \end{aligned}$$

The clumps in cell 2 are `cg_list(3:4) = {1, 3}`. Both arrays reside in MPI-3 shared memory (one copy per compute node).

5.3 Cell Grid and Domain

The CSR grid reuses the same cell count $M = N_g$ as the RSA hash grid (§4.5), but covers a slightly larger domain $[-R - r_c, R + r_c]^3$ with uniform cell size

$$\delta = \frac{2(R + r_c)}{M}. \quad (20)$$

Expanding the domain by r_c in each direction ensures two properties:

1. A clump centered exactly on the outer sphere surface ($|\mathbf{c}| = R$) fits entirely inside the grid.
2. A photon entering from outside the outer sphere starts inside a valid grid cell, so the DDA traversal can begin immediately.

5.4 Clump Registration: AABB Overlap Test

A clump of radius r_c centered at (c_x, c_y, c_z) is registered in every cell whose axis-aligned bounding box (AABB) overlaps the clump sphere. Cell (i, j, k) spans $[x_{\min} + i\delta, x_{\min} + (i+1)\delta]$ along x . The range of cell indices that overlap $[c_x - r_c, c_x + r_c]$ is

$$i \in \left[\left\lfloor \frac{c_x - r_c - x_{\min}}{\delta} \right\rfloor, \left\lfloor \frac{c_x + r_c - x_{\min}}{\delta} \right\rfloor \right], \quad (21)$$

and likewise for j and k . The clump is registered in every cell in the Cartesian product of these three index ranges. For the reference case ($r_c = 0.01$, $\delta \approx 0.048$, so $r_c/\delta \approx 0.21 < 1$), each clump's index range spans at most 2 values per dimension, so a clump touches at most $2^3 = 8$ cells. The total registration count satisfies $N \leq N_{\text{tot}} \leq 8N$.

5.5 Two-Pass Construction

The CSR arrays are built in two sequential passes over all N clumps, avoiding any intermediate list storage (the standard technique for CSR sparse-matrix assembly):

Pass 1 (count): Compute the cell ranges (eq. 21) for each clump and increment a counter `cnt(icell)` for every touched cell. Then compute the exclusive prefix sum:

$$\text{cg_start}(0) = 1, \quad \text{cg_start}(\text{icell}+1) = \text{cg_start}(\text{icell}) + \text{cnt}(\text{icell}).$$

Allocate `cg_list` of length $N_{\text{tot}} = \text{cg_start}(\text{Ncell}) - 1$ as an MPI-3 shared-memory window.

Pass 2 (fill): Repeat the same cell-range loop. For each touched cell, write the clump index at write pointer `ptr(icell)`, then advance the pointer by one. Initialize `ptr(icell) = cg_start(icell)` before this pass.

```

1  !--- Pass 1: count registrations per cell
2  cnt(:) = 0
3  do icl = 1, N_clumps
4      i0 = max(0, floor((cl_x(icl) - rc - xmin) / delta))
5      i1 = min(M-1, floor((cl_x(icl) + rc - xmin) / delta))
6      j0 = ...; j1 = ...                ! analogous for y
7      k0 = ...; k1 = ...                ! analogous for z
8      do k = k0,k1; do j = j0,j1; do i = i0,i1
9          cnt(cell_idx(i,j,k)) = cnt(cell_idx(i,j,k)) + 1
10     enddo; enddo; enddo
11 enddo
12 ! exclusive prefix sum -> cg_start
13 cg_start(0) = 1
14 do icell = 0, Ncell-1
15     cg_start(icell+1) = cg_start(icell) + cnt(icell)
16 enddo
17 Ntot = cg_start(Ncell) - 1
18 ! allocate cg_list(Ntot) as MPI-3 shared-memory window
19
20 !--- Pass 2: fill cg_list
21 ptr(0:Ncell-1) = cg_start(0:Ncell-1)    ! one write pointer per cell
22 do icl = 1, N_clumps
23     ... (same i0,i1,j0,j1,k0,k1 as Pass 1)
24     do k = k0,k1; do j = j0,j1; do i = i0,i1
25         ic = cell_idx(i,j,k)
26         cg_list(ptr(ic)) = icl
27         ptr(ic) = ptr(ic) + 1
28     enddo; enddo; enddo
29 enddo
30 ! invariant: ptr(icell) == cg_start(icell+1) for all cells after Pass 2

```

6. Raytrace Through the Clump Medium

6.1 Overview

Photon propagation is split into two phases:

1. **Advance through vacuum** – use the DDA traversal of the CSR grid (§6.3) to find the next clump hit.
2. **Traverse through a clump** – accumulate optical depth along a straight path through the sphere (§6.4).

Frequency shifts due to individual clump bulk velocities are applied at clump entry and reversed at clump exit.

6.2 Ray–Sphere Intersection

Given a ray $\mathbf{p}(t) = \mathbf{o} + t\hat{\mathbf{k}}$ and a sphere centered at $\mathbf{c}$ with squared radius r_c^2 , define $\mathbf{r} = \mathbf{o} - \mathbf{c}$, $b = \mathbf{r} \cdot \hat{\mathbf{k}}$, $\Delta = b^2 - |\mathbf{r}|^2 + r_c^2$.

If $\Delta < 0$ there is no intersection. Otherwise

$$t_{\text{entry}} = -b - \sqrt{\Delta}, \quad t_{\text{exit}} = -b + \sqrt{\Delta}. \quad (22)$$

A hit is recorded when $t_{\text{exit}} > 0$.

6.3 DDA Search for Next Clump

The Amanatides & Woo (1987) digital differential analyser (DDA) traverses the CSR cells along the ray in order of increasing path length. For each cell, all registered clumps are tested with the ray–sphere formula. The traversal stops as soon as the current cell’s entry distance exceeds the best hit distance found so far.

```

1 best_te = huge; best_icl = 0
2 d = 0 ! path length to current cell entry
3
4 do while (.true.)
5   if (d > best_te .or. d > t_max) exit
6   ! test all clumps in current cell
7   do ip = cg_start(icell), cg_start(icell+1)-1
8     icl = cg_list(ip)
9     if (icl == skip_icl) cycle
10    call ray_sphere_isect(..., te, tx2, hit)
11    if (hit .and. tx2>0 .and. te<best_te) then
12      best_te=te; best_tx2=tx2; best_icl=icl
13    endif
14  enddo
15  ! advance to next cell (Amanatides & Woo)
16  if (tx<=ty .and. tx<=tz) then

```



```

17      d=tx; ci=ci+si; tx=tx+delx
18      elseif (ty<=tz) then
19          d=ty; cj=cj+s; ty=ty+dely
20      else
21          d=tz; ck=ck+s; tz=tz+delz
22      endif
23  enddo
    
```

6.4 Optical Depth Traversal

`raytrace_to_tau_clump` advances the photon until optical depth τ_{in} is accumulated or the outer sphere is exited.

Inside a clump (`icell_clump` > 0): The remaining path through the current clump is $s = t_{\text{exit}}(\mathbf{p}, \hat{\mathbf{k}}, \text{icl})$. Opacity at the current frequency: $\kappa = \kappa_c \phi(x, a_V)$. If $\tau_{\text{rem}} \leq \kappa s$, scatter at $ds = \tau_{\text{rem}}/\kappa$. Otherwise subtract κs from τ_{rem} , advance to clump exit, shift frequency back to the global frame, and continue in vacuum.

In vacuum (`icell_clump` = 0): Call `find_next_clump` (DDA, §6.3) to find the nearest clump. If none is found along the ray, advance to the sphere boundary and exit (`photon%inside` = `.false.`).

Frequency convention: The photon frequency x (in units of $\Delta\nu_D^{cl}$) is maintained in the local clump rest frame while inside a clump, and in the global frame in vacuum:

$$\text{at clump entry: } x \leftarrow x - u_{\text{los}}, \quad (23)$$

$$\text{at clump exit: } x \leftarrow x + u_{\text{los}}, \quad (24)$$

where $u_{\text{los}} = (\mathbf{v}_i \cdot \hat{\mathbf{k}})/v_{\text{th}}$ is the line-of-sight component of the host clump's bulk velocity in units of the clump thermal velocity $v_{\text{th}} = \Delta\nu_D^{cl} \lambda_0$.

Internal storage of clump bulk velocities: `cl_vx/y/z` are stored as $\mathbf{v}/v_{\text{th}}$ (dimensionless), matching the Cartesian/AMR convention for `grid%vfx` (which is also pre-normalized to $\mathbf{v}/v_{\text{th}}$ in `grid_mod_car.f90`). The clump velocity assignment routines fill the arrays in km/s; `init_clumps` divides by `cl_vtherm` after the `MPI_BCAST` step so that all subsequent raytrace and peel-off code can use `cl_v*` directly in u_{los} without a per-call division. The user-facing FITS output (Section 8.) multiplies back by `cl_vtherm` to keep the stored `VX/VY/VZ` columns in km/s.

Jout accumulation: When the photon exits the outer sphere (`photon%inside` becomes `.false.`), the photon weight is accumulated into the escape spectrum:

$$J_{\text{out}}[i_x] += w, \quad i_x = \left\lfloor \frac{x - x_{\text{min}}}{\delta x} \right\rfloor + 1, \quad (25)$$

where x is the photon frequency (global frame, in units of $\Delta\nu_D$) and w is the photon weight. This mirrors the behavior of `raytrace_to_tau_car`, where `Jout` is accumulated upon grid exit. There are three exit paths (clump-then-sphere exit, already-outside-sphere, and no-clump-found), all handled identically.

6.5 Optical Depth to Edge

`raytrace_to_edge_clump` computes τ from the current position to the sphere boundary without moving the photon (read-only input). The same DDA logic is used; frequency shifts at clump entry/exit are tracked locally. This is called by peel-off routines and by the forced-first-scatter initialization in `run_simulation_mod`.

7. Peel-Off Observations

Peel-off is handled by the standard `peelingoff_rect` routines (`peeling_direct_outside`, `peeling_resonance_nostokes_outside`, etc.). Each of those routines invokes a small mode-aware helper `peel_raytrace_to_edge` (in the same module) which, in clump mode, calls the new `raytrace_to_edge_clump_capped(..., tau_max=tau_huge_clump)` in `raytrace_clump_mod`. The cap (`tau_huge_clump` ≈ 745) makes the integration bail out once $\exp(-\tau)$ underflows in double precision. In Cartesian / AMR mode the helper falls back to the original `raytrace_to_edge` procedure pointer (set by `setup_procedure` to one of the `_car` / `_amr` variants). The original `raytrace_to_edge_clump` (3-arg signature) is preserved so that the `raytrace_to_edge` procedure-pointer interface in `define.f90` stays intact. The sight-line wrappers `raytrace_to_edge_tau_gas_clump` / `raytrace_to_dist_tau_gas_clump` call the uncapped originals so that the sight-line FITS output reports the FULL integrated tau (sight-line is unaffected by the cap). The observer distance defaults to $d = 100R$ and the image pixel size is set so that the full sphere subtends the image:

$$\delta\theta = \frac{1}{N_x/2} \arcsin\left(\frac{R}{d}\right) [\text{rad}] \approx \frac{R}{d(N_x/2)} [\text{rad}]. \quad (26)$$

For $R = 1$, $d = 100$, $N_x = 129$: $\delta\theta \approx 0^\circ 0089$, covering $\pm 0^\circ 57$ (total $1^\circ 14$), which exactly spans the sphere.

Clump-aware lab-frame conversion: At the moment a peel-off is computed, scattering happens INSIDE a clump, so `photon%xfreq` is in the host clump's rest frame. The peel-off output must be in the lab (observer) frame, hence the routines compute

$$x_{\text{ref}} = x_{\text{photon}} + u_1, \quad u_1 = \mathbf{v}_{\text{cell}} \cdot \hat{\mathbf{k}}_{\text{obs}} / v_{\text{th}}. \quad (27)$$

For the standard Cartesian path $\mathbf{v}_{\text{cell}}$ comes from `grid%vfx/y/z`; in clump mode `grid%vfx/y/z` are zero everywhere (the inter-clump medium is vacuum and the bulk velocities live on the clumps), so the peel-off routines branch on `par%use_clump_medium` .and. `photon%icell_clump > 0` and use the host

clump's velocity instead:

$$u_1 = \text{cl_vx}(\text{icl})k_x + \text{cl_vy}(\text{icl})k_y + \text{cl_vz}(\text{icl})k_z, \quad (28)$$

where $\text{icl} = \text{photon\%icell_clump}$. The `peeling_direct_outside` routine, called only at photon birth when $\text{photon\%icell_clump} = 0$, needs no special case.

Without this branch the peel-off spectra would remain in the clump frame while `grid\%Jout` (the angular average) is in the lab frame, producing a systematically narrower peel-off line profile whenever the clump bulk velocity field is non-trivial (e.g. rotating-halo or Hubble-flow runs).

FITS WCS for the 3D peel-off cube: The peel-off cube is allocated as `obs\%scatt (par\%nxfreq, par\%nxim, par\%nyim)`, so the FITS file has `NAXIS1 = nxfreq (wavelength)`, `NAXIS2 = nxim (RA)`, `NAXIS3 = nyim (DEC)`. The header carries a three-axis WCS:

Axis	CTYPE	CUNIT	step
NAXIS1	WAVE	Angstrom	$\text{CD1_1} = -\delta\lambda$
NAXIS2	RA--TAN	deg	$\text{CD2_2} = \delta\theta_x$
NAXIS3	DEC-TAN	deg	$\text{CD3_3} = \delta\theta_y$

CD1_1 is negative because x_{freq} increases with the pixel index while wavelength $\lambda(x) = (1 - v_{\text{th}}x/c)\lambda_0$ decreases with x . `CRPIX1 = 1`, `CRVAL1 = grid\%wavelength(1)` (largest wavelength, at pixel 1). The scalar header keywords `XFREQ1`, `XFREQ2`, `DXFREQ`, and `DWAVE` are also retained for backward compatibility with existing analysis scripts that compute the spectral axis from those instead of from the WCS.

8. FITS Output of Clump Information

When `par\%save_clump_info = .true.`, the subroutine `write_clumps_fits` (in `clump_mod.f90`) writes a binary-table FITS file `<base>_clumps.fits.gz` containing:

BinTable columns: `X`, `Y`, `Z` (clump centers, code units) and `VX`, `VY`, `VZ` (bulk velocities, km/s) are always written. The internal arrays `cl_vx/y/z` are stored dimensionlessly as $\mathbf{v}/v_{\text{th}}$; `write_clumps_fits` multiplies each component by `cl_vtherm` before writing so that the file always carries velocities in km/s.

In addition the per-clump physical columns `R_CLUMP`, `RHOKAP`, and `TEMP` are written when they carry useful spatial variation. For each one independently the relative spread $(\text{max} - \text{min})/|\text{mean}|$ is compared against 10^{-3} ; if the column is below that threshold (i.e. effectively constant) it is dropped and only the corresponding header keyword (`CL_RAD`, `RHOKAP`, `TEMP_CL`) is kept. The diagnostic line printed by `write_clumps_fits` reports the per-column decision, e.g.

```
Clumps: per-clump columns saved (R_CLUMP/RHOKAP/TEMP) =  T F F
```

When `read_clumps_fits` consumes the file and a column is absent, the corresponding `cl_*` array is filled uniformly with the header-keyword value. This makes the read path equally able to handle: (i) pre-Phase-6 files which never had these columns; (ii) new files where a column was dropped because it was constant; and (iii) externally produced files where the column carries genuine per-clump variation.

For the RHOKAP slot the read path additionally accepts `DENSITY` and `DENS` as alternative column names: the priority order is `RHOKAP` $\rightarrow$ `DENSITY` $\rightarrow$ `DENS`, with the header keyword `RHOKAP` as the final fallback. This lets clump files generated by external pipelines that label the per-clump opacity proxy differently be consumed without renaming columns.

Header keywords (in the BinTable HDU):

Keyword	Value	Description
<code>N_CLUMPS</code>	N	number of clumps (realized)
<code>SPHERE_R</code>	R	outer sphere radius (code units)
<code>CL_RAD</code>	r_c	clump radius (code units)
<code>F_VOL</code>	f_{vol}	volume filling factor (realized)
<code>F_COV</code>	f_{cov}	covering factor (realized)
<code>TAU0</code>	τ_0	line-center τ per clump
<code>SIGMA_V</code>	σ_v	bulk velocity dispersion (km/s)
<code>TEMP_CL</code>	T_c	clump temperature used (K)
<code>RHOKAP</code>	κ_c	opacity per code unit
<code>CL_DFREQ</code>	$\Delta\nu_D^{cl}$	Doppler frequency (Hz)
<code>VTHERM</code>	v_{th}	thermal velocity (km/s)
<code>VOIGT_A</code>	a_v	Voigt damping parameter
<code>RMAX</code>	R	<code>par%rmax</code> (input)
<code>IN_FCOV</code>	<code>par%clump_f_cov</code>	input covering factor
<code>IN_FVOL</code>	<code>par%clump_f_vol</code>	input filling factor
<code>IN_NCL</code>	<code>par%clump_N_clumps</code>	input N
<code>IN_NHI</code>	<code>par%clump_NHI</code>	per-clump N_{HI} (cm^{-2} , clump center to surface)
<code>IN_NH</code>	<code>par%clump_nH</code>	input n_H (cm^{-3})
<code>IN_TEMP</code>	<code>par%clump_temperature</code>	input T_c (K)

Note: column data are written first (which creates the BinTable HDU); header keywords are then written into that same HDU. FITS keyword names must not exceed 8 characters.

9. Input Parameters Summary

Parameter	Default	Description
par%grid_type	'car'	'clump' selects clump mode (v2.10)
par%use_clump_medium	.false.	deprecated alias: maps to grid_type='clump'
par%rmax	—	outer sphere radius (code units)
par%clump_radius	—	clump radius r_c (code units)
par%clump_f_cov	-1	covering factor (input; specify one of f_cov/f_vol/N_clumps)
par%clump_f_vol	-1	volume filling factor (input)
par%clump_N_clumps	-1	number of clumps (input, direct)
par%clump_tau0	-1	line-center τ of one clump (center to surface)
par%clump_NHI	-1	per-clump N_{HI} (cm^{-2} , clump center to surface; no distance_unit needed)
par%clump_nH	-1	clump n_H (cm^{-3} ; requires distance_unit)
par%clump_temperature	-1	clump T (K); $< 0 \Rightarrow$ par%temperature
par%clump_sigma_v	0	random velocity σ per component (km/s)
par%velocity_type	"	systematic flow type (see §3.4)
par%Vexp	0	expansion speed for hubble/constant_radial (km/s)
par%Vx, Vy, Vz	0	bulk velocity for parallel_velocity (km/s)
par%Vpeak	0	peak speed for ssh (km/s)
par%rpeak	0	peak radius for ssh (code units)
par%DeltaV	0	outer velocity increment for ssh (km/s)
par%Vrot	0	rotation speed for rotating models (km/s)
par%rinner	0	solid-body radius for rotating_galaxy_halo
par%save_clump_info	.false.	write clump FITS file
par%clump_input_file	"	if non-empty, load the clump population from this FITS file (see §13.) instead of generating internally

Example input (v2.10 OOP interface):

```

1 &parameters
2   par%grid_type      = 'clump'
3   par%rmax           = 1.0
4   par%clump_radius   = 0.01
5   par%clump_f_cov    = 5.0
6   par%clump_tau0     = 1.0e3
7   par%temperature    = 1.0e4
8   par%clump_sigma_v  = 0.0
9   par%no_photons     = 1e6
10  par%spectral_type   = 'voigt'
11  par%nxfreq         = 301

```

```

12 par%velocity_min      = -100.0
13 par%velocity_max      = 100.0
14 par%nx = 11, par%ny = 11, par%nz = 11
15 par%save_clump_info   = .true.
16 par%out_file          = 'clump_tau3_fcov5.fits.gz'
17 /

```

Backward-compatible input (v2.00 style, accepted by v2.10):

```

1 &parameters
2 par%use_clump_medium = .true.      ! mapped to par%grid_type = 'clump'
3 par%rmax              = 1.0
4 par%clump_radius      = 0.01
5 par%clump_f_cov       = 5.0
6 par%clump_tau0        = 1.0e3
7 par%temperature       = 1.0e4
8 par%no_photons        = 1e6
9 par%spectral_type     = 'voigt'
10 par%nxfreq            = 301
11 par%velocity_min      = -100.0
12 par%velocity_max      = 100.0
13 par%nx = 11, par%ny = 11, par%nz = 11
14 par%save_clump_info   = .true.
15 par%out_file          = 'clump_tau3_fcov5.fits.gz'
16 /

```

10. Memory Layout

Clump positions, velocities, and CSR arrays are allocated as MPI-3 shared-memory windows via `create_shared_mem` from `memory_mod`, giving one copy per compute node rather than per MPI rank. On systems with multiple ranks per node this significantly reduces memory usage for large clump populations. Cleanup is performed by `destroy_clumps` which calls `destroy_shared_mem_all` (collective `MPI_WIN_FREE` across all ranks) followed by explicit `nullify` of all pointers. The individual `destroy_mem` is not used because `MPI_WIN_SHARED_QUERY` returns the rank-0 base address, which differs from the local pointer on non-root ranks.

11. Validation and Examples

The directory `examples/clump_sphere/` contains a suite of six reference runs covering the main parameter space. All use $R = 1$, $r_c = 0.01$, 10^6 photons, and `par%grid_type = 'clump'`:

Input file	τ_0	Notes
<code>clump_tau3_fcov5.in</code>	10^3	$f_{\text{cov}} = 5$, static (reference)
<code>clump_tau4_fcov5.in</code>	10^4	$f_{\text{cov}} = 5$, static
<code>clump_tau3_fcov20.in</code>	10^3	$f_{\text{cov}} = 20$, dense covering
<code>clump_tau3_fcov5_hubble.in</code>	10^3	$f_{\text{cov}} = 5$, Hubble $V_{\text{exp}} = 200$ km/s
<code>clump_tau3_fcov5_sigv.in</code>	10^3	$f_{\text{cov}} = 5$, $\sigma_v = 50$ km/s
<code>clump_tau3_fcov5_peel.in</code>	10^3	$f_{\text{cov}} = 5$, peel-off 129×129

Run with `bash run.sh` (uses 4 MPI ranks by default) or individually:

```
cd LaRT_v2.00/examples/clump_sphere
mpirun -np 4 ../../LaRT.x clump_tau3_fcov5.in
```

Python post-processing:

```
python plot_clump.py          # all runs
python plot_clump.py clump_tau3_fcov5  # single run
```

For the reference case ($f_{\text{cov}} = 5$, $\tau_0 = 10^3$):

- Realized $f_{\text{cov}} \approx 5.00$, $f_{\text{vol}} \approx 0.067$;
- RSA acceptance rate $\sim 74\%$, $N = 66667$ clumps placed;
- Mean scattering count ≈ 6400 per photon;
- Wall time ≈ 3.75 min (10 ranks, 10^5 photons).

The escaped spectrum $J_{\text{out}}(x)$ shows the characteristic double-peak expected for a clumpy Lyman- α source. The peel-off output (`_obs.fits.gz`) contains `Scattered` (HDU 0) and `Direct` (HDU 1) spectral image cubes of shape (301, 129, 129).

Sight-line tau in clump mode: A clump-aware sight-line traversal is now implemented in `sightline_tau_clump.f90`; the type-bound dispatch `clump_make_sightline_tau` (v2.10) and the procedure-pointer assignment in `setup_procedure` (v2.00) route to it whenever `par%save_sightline_tau = .true.`. The standalone driver `make_sightline_tau.x` consumes the same input file and writes `<base>_tau.fits.gz` (TAU_gas, N_gas, optionally TAU_dust). See `examples/sightline_tau/clump_sightline.in` for a complete reference run.

Peel-off vs Jmu validation (verify_peel_jmu.ipynb): The notebook `examples/clump_sphere/verify_peel_jmu.ipynb` checks that the integrated peel-off Stokes- I spectrum matches the sky-mean of J_{mu} (the angle-binned escape spectrum). Cells covering $f_{\text{cov}} = 1, 2$, and 5 confirm that the measured $\text{Scatt}/J_{\text{mu}}$ reproduces the analytic single-scattering escape fraction $1 - \exp(-f_{\text{cov}})$ to 1% across four observer β angles. The $f_{\text{cov}} = 5$ case in particular validates the new `tau_huge_clump = 745.2 cap` added to the peel-off raytrace (Sect. “Peel-off”): even at $\tau_{\text{max}} \sim 6.7 \times 10^3$ the cap preserves the answer because every capped contribution has $\exp(-\tau) \approx 0$.

12. Spatially-Varying Clump Properties

The default clump population is uniform in radius, internal density, and spatial number density. Three optional radial-profile inputs allow each of these to vary as a function of distance from the box center. When all three profile flags are set to ‘constant’ (the default) the behavior is identical to the uniform implementation.

12.1 Input parameters

```

1 par%clump_radius_profile = 'constant' | 'powerlaw' | 'gaussian'
2                           | 'exponential' | 'file'
3 par%clump_density_profile = (same options ; controls n_H(r) inside clump)
4 par%clump_number_profile = (same options ; controls spatial n_cl(r))
5 par%clump_radius_alpha,   par%clump_radius_r0
6 par%clump_density_alpha,  par%clump_density_r0
7 par%clump_number_alpha,   par%clump_number_r0
8 par%clump_profile_file    = ''      ! 5-column tabulated profile
    
```

Built-in shapes (same convention on each axis; f multiplies the user-supplied peak value):

$$\begin{aligned}
 \text{constant} : f(r) &= 1, \\
 \text{powerlaw} : f(r) &= \left(\max(r, r_{\text{fl}}) / \max(r_0, r_{\text{fl}}) \right)^{-\alpha}, \quad r_{\text{fl}} = 0.05 r_0, \\
 \text{gaussian} : f(r) &= \exp[-(r/r_0)^2], \\
 \text{exponential} : f(r) &= \exp(-r/r_0).
 \end{aligned}$$

For ‘file’, the named ASCII file should contain columns `r`, `r_cl_factor`, `n_H_factor`, `T[K]`, `n_cl_shape`, one row per radial sample point, and the relevant column is interpolated linearly.

12.2 Covering factor under non-uniformity

The covering factor with non-uniform profiles is defined as the radial line-of-sight integral

$$f_{\text{cov}} = \int_0^R n_c(r) \pi r_c(r)^2 dr, \quad (29)$$

which reduces to the uniform formula $\frac{3}{4}N(r_c/R)^2$ when all three profiles are constant. See `covering_factor_definitions.tex` for the derivation and alternatives.

12.3 Implementation outline

- Per-clump physical quantities (`cl_radius`, `cl_rhokap`, `cl_voigt_a`, `cl_Dfreq`, `cl_vtherm`, `cl_temperature`) are MPI shared-memory arrays of dimension `N_clumps`; reference scalars (`cl*_ref`) carry the peak values.
- Clump positions are sampled by inverse CDF on $n_c(r)4\pi r^2$, with isotropic angles. The RSA 27-neighbor overlap test compares $(r_c^i + r_c^j)^2$ so non-uniform clump radii are handled correctly.
- `N_clumps` is derived in two ways: closed-form for the uniform case, numerical quadrature with the LOS f_{cov} definition otherwise. Any one of `clump_N_clumps`, `clump_f_vol`, `clump_f_cov` can be specified; the other two are obtained from quadrature.
- Per-clump opacity in the temperature-varying case picks up the Doppler-frequency rescaling $\rho\kappa(\mathbf{r}) = \rho\kappa_{\text{peak}}(n_H/n_{H,\text{peak}})(\Delta\nu_D^{\text{ref}}/\Delta\nu_D(\mathbf{r}))$ so that the local cross-section $\sigma_0/\Delta\nu_D$ is consistent with the local thermal width.
- The clump FITS table now includes per-clump `R_CLUMP`, `RHOKAP`, `TEMP` columns in addition to positions and velocities. Stdout prints the realized f_{vol} , f_{cov} , r_c range, mean τ_{perclump} , and integrated HI mass.

12.4 Example inputs

```

1 ! Gaussian-concentrated clump cloud (constant clump radius)
2 par%clump_number_profile = 'gaussian'
3 par%clump_number_r0      = 0.4
4 par%clump_f_cov          = 5.0
5
6 ! Clump radius growing linearly with r (constant n_cl).
7 ! Specifying clump_f_cov lets the profile-aware quadrature back-solve
8 ! the spatial normalization; N_clumps is reported from the integral.
9 par%clump_radius_profile = 'powerlaw'
10 par%clump_radius_alpha   = -1.0
11 par%clump_radius_r0      = 0.5
12 par%clump_f_cov          = 1.0

```

For full working setups see, in `examples/clump_sphere/`:

- `clump_powerlaw_density.in`
- `clump_radius_powerlaw.in`

13. Standalone Clump Generator (`make_clumps.x`)

The clump-generation pathway used inside LaRT is also exposed as a small standalone executable so that a clump population can be produced once and reused across many transport runs (or shared with external analyses). The driver source is `make_clumps.f90`; build with

```
1 make make_clumps          # builds make_clumps.x
```

The driver re-uses the same Fortran routines LaRT calls internally (namely `read_input`, `init_clumps`, and `write_clumps_fits`); the only difference is the program entry point and the absence of the photon-transport stage.

Usage.

```
1 mpirun -np N make_clumps.x clumps_input.in
```

The input file uses the same namelist syntax as `LaRT.x`. All clump-related parameters listed in §9. are honored, including the radial-profile inputs. The driver writes `<base_name>_clumps.fits.gz` using the FITS layout described in §8. (column-skipping rule applied) and exits.

Loading the file from LaRT. Pass the path through `par%clump_input_file`:

```
1 &parameters
2   par%grid_type      = 'clump'
3   par%rmax           = 1.0
4   par%clump_radius   = 0.01
5   par%clump_tau0     = 1.0e3
6   par%temperature    = 1.0e4
7   par%no_photons     = 1e6
8   par%spectral_type  = 'voigt'
9   par%nxfreq         = 301
10  par%nx = 11, par%ny = 11, par%nz = 11
11  par%out_file        = 'clump_run.fits.gz'
12
13  ! Reuse a previously generated population
14  par%clump_input_file = 'clumps_input_clumps.fits.gz'
15 /
```

When `par%clump_input_file` is non-empty, `init_clumps` skips the profile detection and RSA-generation path entirely. The population is read from the FITS file and distributed across MPI ranks using the standard `host-comm / SAME_HRANK_COMM` pattern; the CSR acceleration grid is then rebuilt deterministically on every node. The internal `generate_clumps` routine is left untouched so that runs without `clump_input_file` reproduce previous results byte-for-byte.

Reproducibility. With `par%iseed` fixed to a non-zero value, the FITS table produced by `make_clumps.x` matches the `_clumps.fits.gz` written by a regular LaRT.x run with `par%save_clump_info = .true.` byte-for-byte across all columns (X, Y, Z, VX, VY, VZ, plus R_CLUMP/RHOKAP/TEMP when they survive the column-skipping rule). The transport-stage scattering count when LaRT reads back via `clump_input_file` differs from the native run only at RNG-noise level ($\sim 0.4\%$) because the load path consumes fewer RNG draws before the photon launch.

Round-trip example. The reference round-trip lives in `examples/clump_sphere/`:

- `clump_make_test.in` – input for `make_clumps.x` (uniform clumps, `iseed=12345`).
- `clump_make_test_native.in` – regular LaRT run that regenerates the population internally. Used as the byte-identical reference.
- `clump_make_test_load.in` – LaRT input that consumes `clump_make_test_clumps.fits.gz` via `par%clump_input_file`.

14. Standalone Sight-line Tau Calculator (`make_sightline_tau.x`)

A second standalone driver, `make_sightline_tau.f90`, builds the per-observer sight-line maps without running the Monte Carlo photon loop. The output FITS file matches the layout produced by an ordinary LaRT run with `par%save_sightline_tau = .true.` (see the LaRT user manual, §Observers and Peel-off):

HDU	Content
TAU_gas	gas optical depth $\tau(\nu, x, y)$
N_gas	HI column density $N_{\text{HI}}(x, y)$
TAU_dust	dust optical depth $\tau_{\text{dust}}(x, y)$ (only when <code>par%DGR > 0</code>)

Build and run.

```

1 make sightline_tau                                # builds make_sightline_tau.x
2 mpirun -np N ./make_sightline_tau.x sl.in         # writes <base>_tau.fits.gz
```

Clump-mode wiring. The default sight-line path inside LaRT (`sightline_tau_rect`) uses Cartesian box-face geometry and the `raytrace_to_edge_car` dispatch. In clump mode `grid%rhokap=0` everywhere; opacity lives in `cl_rhokap(:)` and is reached only by the CSR DDA traversal in `raytrace_clump.f90`. A new module, `sightline_tau_clump.f90`, mirrors `sightline_tau_amr.f90` but for clump mode: it intersects the bounding sphere of radius `sphere_R` (instead of the AABB), initializes `photon%icell_clump = 0`, and calls `raytrace_to_edge_tau_gas_clump` and `raytrace_to_edge_column_clump`. In v2.10 the type-bound `clump_make_sightline_tau` now calls this new module; in v2.00 the procedure pointer `make_sightline_tau` is set to `make_sightline_tau_clump` inside the `use_clump_medium`

branch of `setup_procedure`. This wiring change also fixes the same path when the regular `LaRT.x` run is launched with `par%save_sightline_tau = .true.` on a clump input (previously such a run produced all-zero sight-line maps).

Example inputs.

- `examples/clump_sphere/clump_sightline_test.in`
- `examples/sphere/sphere_sightline_test.in`