

Five lanes. No silent transfer.

Shared vocabulary does not make the objects interchangeable.



MGW categorical SxPID

FINITE EMPIRICAL PMF • EVENT-BASED SHARED EXCLUSIONS

Paper-defined signed decomposition; pid-rs evaluates categorical data directly.
The stable implementation covers two to four sources.

REPOSITORY ROLE

IMPLEMENTED • STABLE

Categorical theorem lane only



Ehrlich continuous shared exclusions

CONTINUOUS FUNCTIONAL + SOURCE-DISJUNCTION KNN ESTIMATOR

Gauge-dependent redundancy with a two-source PID2 reconstruction.
pid-rs exposes it behind default-off experimental continuous APIs.

REPOSITORY ROLE

IMPLEMENTED

Experimental; no categorical proof transfer



Williams–Beer $I_{\min}$

FINITE-ALPHABET SPECIFIC-INFORMATION MINIMUM

A different redundancy definition on the Williams–Beer lattice.
pid-rs provides a stable two- and three-source legacy comparator.

REPOSITORY ROLE

IMPLEMENTED

Comparator; atoms are never pooled with SxPID



BROJA

OPTIMIZATION-DEFINED PID • EXTERNAL COMPARISON

A distinct PID proposal used to compare conclusions and desiderata.
The repository does not provide a BROJA estimator.

REPOSITORY ROLE

COMPARISON ONLY

No local implementation or proof claim



KSG mutual-information estimator

CONTINUOUS MI • EXPLICIT REGULAR-SUPPORT CONTRACT

A k-nearest-neighbour estimator used by some continuous reports.
It estimates mutual information; it is not a PID definition.

REPOSITORY ROLE

IMPLEMENTED

Conditional estimator; core evidence $\neq$ full proof

FIREWALL RULE

No equality • no atom transfer • no theorem transfer • no estimator-validity transfer