
PROVISIONAL PATENT APPLICATION

V-Twin Gyroscope with Phase-Offset Rotors and Reversible-Domain Control

Inventor: Matthew J. Campbell

Filing Type: Provisional Patent Application under 35 USC 111(b)

Revision: v1.0

Status: Filing-Ready

TITLE OF THE INVENTION

Gyroscope System with Phase-Offset Dual Rotors and Entropy-Bounded Reversible-Domain Operation

ABSTRACT

A gyroscope system comprising two rotors arranged at a fixed angular offset inspired by V-type engine geometry. The rotors operate with controlled phase alignment and torque smoothing to minimize drift and maintain reversible-domain operation. A computational control system monitors rotational entropy, angular drift, and multi-spiral convergence across geometry, control, material, and ledger spirals. The system provides enhanced stability, reduced drift, and predictable dynamic behavior under perturbations. Optional integration of TitanA16 alloy or quasicrystal-modulated hubs improves resonance stability and mechanical coherence.

BACKGROUND OF THE INVENTION

Traditional gyroscopes rely on single-axis rotors or coaxial dual-rotor systems. These designs suffer from:

- cumulative angular drift
- uncontrolled entropy accumulation
- sensitivity to perturbations
- lack of phase-offset stabilization
- absence of reversible-domain control

Existing gyroscopes do not incorporate:

- V-Twin-style angular offset
- entropy-bounded rotational control
- multi-spiral convergence validation

- TitanA16 or quasicrystal-modulated stabilizers

This invention introduces a novel dual-rotor geometry and control method that significantly improves stability and drift resistance.

SUMMARY OF THE INVENTION

The invention provides a gyroscope system comprising:

1. Two rotors mounted at a fixed angular offset (preferably $\sim 45^\circ$).
2. Phase-synchronized operation, where one rotor reaches top-dead-center (TDC) as the other is offset.
3. Torque smoothing to distribute rotational forces.
4. Entropy-bounded control, ensuring rotational drift remains below defined thresholds.
5. Multi-spiral convergence validation, ensuring geometric, material, and control alignment.
6. Optional TitanA16 or quasicrystal-modulated hubs for resonance stability.

The system maintains reversible-domain operation and reduces drift through phase-offset dynamics.

DETAILED DESCRIPTION OF THE INVENTION

1. Mechanical Configuration

Dual Rotor Assembly

- Two rotors mounted on a shared base.
- Angular offset: 30° – 60° (preferred: 45°).
- Each rotor has its own inertia profile and torque input.
- Rotors are synchronized such that Rotor A reaches TDC as Rotor B is offset.

Base Structure

- Supports both rotors.
- May include damping materials or TitanA16 inserts.
- Designed to distribute torque evenly.

Phase Relationship

- Rotor A and Rotor B maintain a fixed phase offset.
- This offset creates natural drift cancellation through counter-phase dynamics.

2. Control System (ORR-Aligned)

Entropy Monitoring

The system tracks:

- instantaneous entropy rate $\left(\frac{dS}{dt} \right)$
- cumulative entropy $\left(\sum S \right)$
- angular drift $\left(\frac{\Delta \theta}{dt} \right)$

Reversible-Domain Operation

The system enforces:

- $\left(\frac{dS}{dt} \leq S_{\text{max}\text{rate}} \right)$
- $\left(\sum S \leq S_{\text{max}\text{total}} \right)$
- $\left(\frac{\Delta \theta}{dt} \leq \theta_{\text{max}\text{rate}} \right)$

Corrective Torque Application

If thresholds are exceeded:

- torque is adjusted
- rotor speed is modulated
- phase alignment is corrected

Multi-Spiral Convergence

The system validates:

- Geometry Spiral: rotor alignment, offset angle
- Control Spiral: entropy and drift behavior
- Material Spiral: hub integrity, damping
- Ledger A Spiral: ≥ 3 independent measurements
- Ledger B Spiral: safety and operational ethics

3. Optional TitanA16 / QC Integration

TitanA16 Rotor Hubs

- Triple-helix geometry
- Golden-ratio alignment
- High resonance stability

Quasicrystal-Modulated Inserts


- Reduce vibrational drift
- Improve coherence under load

These materials enhance stability and reduce noise.

4. ASCII FIGURES

FIG. 1 — Rotor Geometry


,



,

FIG. 2 — Control Logic Flow

,



CLAIMS (Provisional Format)

1. A gyroscope system comprising two rotors arranged at a fixed angular offset to achieve phase-dependent drift mitigation.
2. The system of claim 1, wherein the rotors are synchronized such that one rotor reaches top-dead-center while the other is offset.
3. The system of claim 1, wherein a control system monitors rotational entropy and angular drift to maintain reversible-domain operation.
4. The system of claim 1, wherein torque smoothing is applied to distribute rotational forces and reduce drift.
5. The system of claim 1, wherein multi-spiral convergence validation is applied across geometry, control, material, and ledger spirals.
6. The system of claim 1, wherein rotor hubs comprise TitanA16 alloy or quasicrystal-modulated structures.

PREFERRED EMBODIMENTS

- Rotor offset: 45°
 - TitanA16 hubs for resonance stability
 - Python-based ORR witness for entropy monitoring
 - Damping materials integrated into base
 - Rotor inertia tuned for high stability
 - Multi-spiral convergence validated before operation
-