

Sequence Learning

Comparing Sequences

Korbinian Riedhammer

Dynamic programming and edit distance

Ben Langmead



JOHNS HOPKINS

WHITING SCHOOL
of ENGINEERING

Department of Computer Science

You are free to use these slides. If you do, please sign the guestbook (www.langmead-lab.org/teaching-materials), or email me (ben.langmead@gmail.com) and tell me briefly how you're using them. For original Keynote files, email me.

Beyond approximate matching: sequence similarity

In many settings, Hamming and edit distance are too simple. Biologically-relevant distances require algorithms. We will expand our tool set accordingly.

```

Score = 248 bits (129), Expect = 1e-63
Identities = 213/263 (80%), Gaps = 34/263 (12%)
Strand = Plus / Plus

Query: 161 atatcaccacgtcaaaggtgactccaactcca---ccactccattttgttcagataaatgc 217
      ||||||||||||||||||||||||||||| | | | || |||||||||||||||
Sbjct: 481 atatcaccacgtcaaaggtgactccaact-tattgatagtgttttatgttcagataaatgc 539

Query: 218 ccgatgatcatgtcatgcagctccaccgattgtgagaacgacagcgacttccgtcccagc 277
      ||||||| ||||||||||||||||||||| || | |||||||||||||
Sbjct: 540 ccgatgactttgtcatgcagctccaccgattttg-g-----ttccgtcccagc 586

Query: 278 c-gtgcc--aggtgctgcctcagattcaggttatgccgctcaattcgctgcgtatatcgcg 334
      | || | | ||||||||||||||||||| ||||||||||||| |||||||||
Sbjct: 587 caatgacgta-gtgctgcctcagattcaggttatgccgctcaattcgctgggtatatcgcg 645

Query: 335 ttgctgattacgtgcagctttcccttcaggcgggga-----ccagccatccgctc 382
      ||||||||||||||||||||||||||||| |||||||||||||
Sbjct: 646 ttgctgattacgtgcagctttcccttcaggcgggattcatacagcggccagccatccgctc 705

Query: 383 ctccatatac-accacgtcaaagg 404
      ||||||| |||||||||
Sbjct: 706 atccatatacaaccacgtcaaagg 728

```

Example BLAST alignment

Example BLAST alignment

Approximate string matching

A *mismatch* is a single-character substitution:

X:	G	T	A	G	C	G	G	C	G
Y:	G	T	A	A	C	G	G	C	G

An *edit* is a single-character substitution or *gap* (insertion or deletion):

X:	G	T	A	G	C	G	G	C	G
Y:	G	T	A	A	C	G	G	C	G

										Gap in X
X:	G	T	A	G	C	-	G	C	G	
Y:	G	T	A	G	C	G	G	C	G	

AKA insertion in Y or deletion in X

X:	G	T	A	G	C	G	G	C	G	
Y:	G	T	-	G	C	G	G	C	G	

Gap in Y

AKA insertion in X or deletion in Y

Alignment

```
X:  G C G T A T G A G G C T A - A C G C
    | |   | | | |   | | | |   | | | |
Y:  G C - T A T G C G G C T A T A C G C
```

Above is an *alignment*: a way of lining up the characters of x and y

Could include mismatches, gaps or both

Vertical lines are drawn where opposite characters match

Hamming and edit distance

Finding Hamming distance between 2 strings is easy:

```
def hammingDistance(x, y):  
    assert len(x) == len(y)  
    nmm = 0  
    for i in xrange(0, len(x)):  
        if x[i] != y[i]:  
            nmm += 1  
    return nmm
```

G	A	G	G	T	A	G	C	G	G	C	G	T	T	T	A	A	C
G	T	G	G	T	A	A	C	G	G	G	G	T	T	T	A	A	C

Edit distance is harder:

```
def editDistance(x, y):  
    ???
```

G	C	G	T	A	T	G	C	G	G	C	T	A	-	A	C	G	C
G	C	-	T	A	T	G	C	G	G	C	T	A	T	A	C	G	C

Edit distance

```
def editDistance(x, y):  
    return ???
```

G	C	G	T	A	T	G	C	G	G	C	T	A	-	A	C	G	C
G	C	-	T	A	T	G	C	G	G	C	T	A	T	A	C	G	C

If strings x and y are same length, what can we say about **editDistance**(x, y) relative to **hammingDistance**(x, y)?

$$\text{editDistance}(x, y) \leq \text{hammingDistance}(x, y)$$


If strings x and y are different lengths, what can we say about **editDistance**(x, y)?

$$\text{editDistance}(x, y) \geq ||x| - |y||$$

Python example: http://bit.ly/CG_DP_EditDist

Edit distance

Can think of edits as being introduced by an *optimal editor* working left-to-right.
Edit transcript describes how editor turns x into y .



Operations:

M = match, **R** = replace,

I = insert into x , **D** = delete from x

MMD

MMDMMMMMMMMMI

MMDMMMMMMMMMI MMMM

Edit distance

Alignments:

x: G C G T A T G C G G C T A - A C G C
| | | | | | | | | | | |
y: G C - T A T G C G G C T A T A C G C

x: G C G T A T G A G G C T A - A C G C
| | | | | | | | | | | |
y: G C - T A T G C G G C T A T A C G C

x: t h e l o n g e s t - - - -
| | | | | | |
y: - - - - l o n g e s t d a y

Edit transcripts with
respect to x:

M M D M M M M M M M M M M I M M M M

Distance = 2

M M D M M M M R M M M M M I M M M M


Distance = 3

D D D D M M M M M M M I I I I

Distance = 8

Edit distance

$D[i, j]$: edit distance between length- i prefix of x and length- j prefix of y



Think in terms of edit transcript. Optimal transcript for $D[i, j]$ can be built by extending a shorter one by 1 operation. Only 3 options:

Append **D** to transcript for $D[i-1, j]$

Append **I** to transcript for $D[i, j-1]$

Append **M** or **R** to transcript for $D[i-1, j-1]$

$D[i, j]$ is minimum of the three, and $D[|x|, |y|]$ is the overall edit distance

Edit distance

Let $D[0, j] = j$, and let $D[i, 0] = i$

$$\text{Otherwise, let } D[i, j] = \min \begin{cases} D[i-1, j] + 1 & \swarrow \text{D} \\ D[i, j-1] + 1 & \swarrow \text{I} \\ D[i-1, j-1] + \delta(x[i-1], y[j-1]) & \swarrow \text{M or R} \end{cases}$$

$\delta(a, b)$ is 0 if $a = b$, 1 otherwise

Edit distance

Let $D[0, j] = j$, and let $D[i, 0] = i$

Otherwise, let $D[i, j] = \min \begin{cases} D[i-1, j] + 1 \\ D[i, j-1] + 1 \\ D[i-1, j-1] + \delta(x[i-1], y[j-1]) \end{cases}$

$\delta(a, b)$ is 0 if $a = b$, 1 otherwise

A simple recursive algorithm:

```
def edDistRecursive(x, y):  
    if len(x) == 0: return len(y)  
    if len(y) == 0: return len(x)  
    delt = 1 if x[-1] != y[-1] else 0  
    diag = edDistRecursive(x[:-1], y[:-1]) + delt  
    vert = edDistRecursive(x[:-1], y) + 1  
    horz = edDistRecursive(x, y[:-1]) + 1  
    return min(diag, vert, horz)
```

prefixes of x and y currently under consideration

Recursively solve smaller problems

Python example: http://bit.ly/CG_DP_EditDist

Edit distance

```
def edDistRecursive(x, y):  
    if len(x) == 0: return len(y)  
    if len(y) == 0: return len(x)  
    delt = 1 if x[-1] != y[-1] else 0  
    diag = edDistRecursive(x[:-1], y[:-1]) + delt  
    vert = edDistRecursive(x[:-1], y) + 1  
    horz = edDistRecursive(x, y[:-1]) + 1  
    return min(diag, vert, horz)
```

```
>>> import datetime as d  
>>> st = d.datetime.now(); \  
... edDistRecursive("Shakespeare", "shake spear"); \  
... print (d.datetime.now()-st).total_seconds()  
3  
31.498284
```

Simple, but takes >30 seconds for a small problem

Edit distance: dynamic programming

Subproblems ($D[i, j]$ s) can be reused instead of being recalculated:

```
def edDistRecursive(x, y):  
    if len(x) == 0: return len(y)  
    if len(y) == 0: return len(x)  
    delt = 1 if x[-1] != y[-1] else 0  
    diag = edDistRecursive(x[:-1], y[:-1]) + delt  
    vert = edDistRecursive(x[:-1], y) + 1  
    horz = edDistRecursive(x, y[:-1]) + 1  
    return min(diag, vert, horz)
```

Reusing
solutions to
subproblems is
memoization:

Return
memoized
answer, if
available



```
def edDistRecursiveMemo(x, y, memo=None):  
    if memo is None: memo = {}  
    if len(x) == 0: return len(y)  
    if len(y) == 0: return len(x)  
    if (len(x), len(y)) in memo:  
        return memo[(len(x), len(y))]  
    delt = 1 if x[-1] != y[-1] else 0  
    diag = edDistRecursiveMemo(x[:-1], y[:-1], memo) + delt  
    vert = edDistRecursiveMemo(x[:-1], y, memo) + 1  
    horz = edDistRecursiveMemo(x, y[:-1], memo) + 1  
    ans = min(diag, vert, horz)  
    memo[(len(x), len(y))] = ans  
    return ans
```

Memoize $D[i, j]$ →

Python example: http://bit.ly/CG_DP_EditDist



JOHNS HOPKINS
WHITING SCHOOL
of ENGINEERING

Edit distance: dynamic programming

```
def edDistRecursiveMemo(x, y, memo=None):
    if memo is None: memo = {}
    if len(x) == 0: return len(y)
    if len(y) == 0: return len(x)
    if (len(x), len(y)) in memo:
        return memo[(len(x), len(y))]
    delt = 1 if x[-1] != y[-1] else 0
    diag = edDistRecursiveMemo(x[:-1], y[:-1], memo) + delt
    vert = edDistRecursiveMemo(x[:-1], y, memo) + 1
    horz = edDistRecursiveMemo(x, y[:-1], memo) + 1
    ans = min(diag, vert, horz)
    memo[(len(x), len(y))] = ans
    return ans
```

```
>>> import datetime as d
>>> st = d.datetime.now(); \
... edDistRecursiveMemo("Shakespeare", "shake spear"); \
... print (d.datetime.now()-st).total_seconds()
3
0.000593
```

Much better



JOHNS HOPKINS
WHITING SCHOOL
of ENGINEERING

Edit distance: dynamic programming

edDistRecursiveMemo is a *top-down* dynamic programming approach

Alternative is *bottom-up*. Here, bottom-up recursion is pretty intuitive and interpretable, so this is how edit distance algorithm is usually explained.

Fills in a table (matrix) of $D(i, j)$ s:

`import numpy` ← `numpy`: package for matrices, etc

```
def edDistDp(x, y):
    """ Calculate edit distance between sequences x and y using
        matrix dynamic programming. Return distance. """
    D = numpy.zeros((len(x)+1, len(y)+1), dtype=int)
    D[0, 1:] = range(1, len(y)+1)
    D[1:, 0] = range(1, len(x)+1)
    for i in xrange(1, len(x)+1):
        for j in xrange(1, len(y)+1):
            delt = 1 if x[i-1] != y[j-1] else 0
            D[i, j] = min(D[i-1, j-1]+delt, D[i-1, j]+1, D[i, j-1]+1)
    return D[len(x), len(y)]
```

Fill 1st row, col

Fill rest of matrix

Edit distance: dynamic programming

ϵ is empty string
 ϵ is empty string

y

ϵ G C T A T G C C A C G C

$D: x$

ϵ	ϵ	G	C	T	A	T	G	C	C	A	C	G	C
G													
C													
G													
T													
A													
T													
G													
C													
A													
C													
G													
C													

Let $n = |x|$, $m = |y|$

D : $(n+1) \times (m+1)$ matrix


$D[i, j]$ = edit distance b/t
length- i prefix of x and
length- j prefix of y



JOHNS HOPKINS

WHITING SCHOOL
of ENGINEERING

Edit distance: dynamic programming



Edit distance: dynamic programming

First few lines
of `edDistDp`:

```
D = numpy.zeros((len(x)+1, len(y)+1), dtype=int)
D[0, 1:] = range(1, len(y)+1)
D[1:, 0] = range(1, len(x)+1)
```

	€	G	C	T	A	T	G	C	C	A	C	G	C
€	0	1	2	3	4	5	6	7	8	9	10	11	12
G	1												
C	2												
G	3												
T	4												
A	5												
T	6												
G	7												
C	8												
A	9												
C	10												
G	11												
C	12												

Initialize $D[0, j]$ to j ,
 $D[i, 0]$ to i

Edit distance: dynamic programming

Loop from
edDistDp:

```

for i in xrange(1, len(x)+1):
    for j in xrange(1, len(y)+1):
        delt = 1 if x[i-1] != y[j-1] else 0
        D[i, j] = min(D[i-1, j-1]+delt, D[i-1, j]+1, D[i, j-1]+1)
    
```

	€	G	C	T	A	T	G	C	C	A	C	G	C
€	0	1	2	3	4	5	6	7	8	9	10	11	12
G	1												
C	2												
G	3												
T	4												
A	5												
T	6												
G	7												
C	8												
A	9												
C	10												
G	11												
C	12												

Fill remaining cells from
top row to bottom and
from left to right

Edit distance: dynamic programming

Loop from
edDistDp:

```

for i in xrange(1, len(x)+1):
    for j in xrange(1, len(y)+1):
        delt = 1 if x[i-1] != y[j-1] else 0
        D[i, j] = min(D[i-1, j-1]+delt, D[i-1, j]+1, D[i, j-1]+1)
    
```

	€	G	C	T	A	T	G	C	C	A	C	G	C
€	0	1	2	3	4	5	6	7	8	9	10	11	12
G	1	?											
C	2												
G	3												
T	4												
A	5												
T	6												
G	7												
C	8												
A	9												
C	10												
G	11												
C	12												

Fill remaining cells from
top row to bottom and
from left to right

What goes here in $i=1, j=1$?

$x[i-1] = y[j-1] = 'G'$,

SO $delt = 0$

```

D[i, j] = min(D[i-1, j-1]+delt,
              D[i-1, j]+1,
              D[i, j-1]+1)
          = min(0 + 0, 1 + 1, 1 + 1)
          = 0
    
```

Edit distance: dynamic programming

```

Loop from
edDistDp:
    for i in xrange(1, len(x)+1):
        for j in xrange(1, len(y)+1):
            delt = 1 if x[i-1] != y[j-1] else 0
            D[i, j] = min(D[i-1, j-1]+delt, D[i-1, j]+1, D[i, j-1]+1)
    
```

	€	G	C	T	A	T	G	C	C	A	C	G	C
€	0	1	2	3	4	5	6	7	8	9	10	11	12
G	1	0	1	2	3	4	5	6	7	8	9	10	11
C	2	1	0	1	2	3	4	5	6	7	8	9	10
G	3	2	1	1	2	3	3	4	5	6	7	8	9
T	4	3	2	1	2	2	3	4	5	6	7	8	9
A	5	4	3	2	1	2	3	4	5	5	6	7	8
T	6	5	4	3	2	1	2	3	4	5	6	7	8
G	7	6	5	4	3	2	1	2	3	4	5	6	7
C	8	7	6	5	4	3	2	1	2	3	4	5	6
A	9	8	7	6	5	4	3	2	2	2	3	4	5
C	10	9	8	7	6	5	4	3	2	3	2	3	4
G	11	10	9	8	7	6	5	4	3	3	3	2	3
C	12	11	10	9	8	7	6	5	4	4	3	3	2

Fill remaining cells from top row to bottom and from left to right

Edit distance for x, y



JOHNS HOPKINS
WHITING SCHOOL
of ENGINEERING

Edit distance: dynamic programming

Loop from
edDistDp:


```

for i in xrange(1, len(x)+1):
    for j in xrange(1, len(y)+1):
        delt = 1 if x[i-1] != y[j-1] else 0
        D[i, j] = min(D[i-1, j-1]+delt, D[i-1, j]+1, D[i, j-1]+1)
    
```

	€	G	C	T	A	T	G	C	C	A	C	G	C
€	0	1	2	3	4	5	6	7	8	9	10	11	12
G	1												
C	2												
G	3												
T	4												
A	5												
T	6												
G	7												
C	8												
A	9												
C	10												
G	11												
C	12												

Could we have filled the cells in a different order?

Edit distance: dynamic programming

Switched 

```
for j in xrange(1, len(y)+1):  
    for i in xrange(1, len(x)+1):  
        delt = 1 if x[i-1] != y[j-1] else 0  
        D[i, j] = min(D[i-1, j-1]+delt, D[i-1, j]+1, D[i, j-1]+1)
```

	€	G	C	T	A	T	G	C	C	A	C	G	C
€	0	1	2	3	4	5	6	7	8	9	10	11	12
G	1												
C	2												
G	3												
T	4												
A	5												
T	6												
G	7												
C	8												
A	9												
C	10												
G	11												
C	12												

etc

Yes: e.g. invert the loops

Edit distance: dynamic programming

	ε	G	C	T	A	T	G	C	C	A	C	G	C
ε	0	1	2	3	4	5	6	7	8	9	10	11	12
G	1												
C	2												
G	3												
T	4												
A	5												
T	6												
G	7												
C	8												
A	9												
C	10												
G	11												
C	12												

Or by anti-diagonal

Edit distance: dynamic programming

	ε	G	C	T	A	T	G	C	C	A	C	G	C
ε	0	1	2	3	4	5	6	7	8	9	10	11	12
G	1												
C	2												
G	3												
T	4												
A	5												
T	6												
G	7												
C	8												
A	9												
C	10												
G	11												
C	12												

Or blocked

etc

Edit distance: getting the alignment

Full **backtrace** path corresponds to an optimal alignment / edit transcript:

Start at end; at each step, ask: which predecessor gave the minimum?

	ε	G	C	T	A	T	G	C	C	A	C	G	C
ε	0	1	2	3	4	5	6	7	8	9	10	11	12
G	1	0	1	2	3	4	5	6	7	8	9	10	11
C	2	1	0	1	2	3	4	5	6	7	8	9	10
G	3	2	1	1	2	3	3	4	5	6	7	8	9
T	4	3	2	1	2	2	3	4	5	6	7	8	9
A	5	4	3	2	1	2	3	4	5	5	6	7	8
T	6	5	4	3	2	1	2	3	4	5	6	7	8
G	7	6	5	4	3	2	1	2	3	4	5	6	7
C	8	7	6	5	4	3	2	1	2	3	4	5	6
A	9	8	7	6	5	4	3	2	2	2	3	4	5
C	10	9	8	7	6	5	4	3	2	3	2	3	4
G	11	10	9	8	7	6	5	4	3	3	3	2	3
C	12	11	10	9	8	7	6	5	4	4	3	3	2

A: From here

Q: How did I get here?

Edit distance: getting the alignment

Full **backtrace** path corresponds to an optimal alignment / edit transcript:

Start at end; at each step, ask: which predecessor gave the minimum?

	ε	G	C	T	A	T	G	C	C	A	C	G	C
ε	0	1	2	3	4	5	6	7	8	9	10	11	12
G	1	0	1	2	3	4	5	6	7	8	9	10	11
C	2	1	0	1	2	3	4	5	6	7	8	9	10
G	3	2	1	1	2	3	3	4	5	6	7	8	9
T	4	3	2	1	2	2	3	4	5	6	7	8	9
A	5	4	3	2	1	2	3	4	5	5	6	7	8
T	6	5	4	3	2	1	2	3	4	5	6	7	8
G	7	6	5	4	3	2	1	2	3	4	5	6	7
C	8	7	6	5	4	3	2	1	2	3	4	5	6
A	9	8	7	6	5	4	3	2	2	2	3	4	5
C	10	9	8	7	6	5	4	3	2	3	2	3	4
G	11	10	9	8	7	6	5	4	3	3	3	2	3
C	12	11	10	9	8	7	6	5	4	4	3	3	2

A: From here

Q: How did I get here?

Edit distance: getting the alignment

Full **backtrace** path corresponds to an optimal alignment / edit transcript:

Start at end; at each step, ask: which predecessor gave the minimum?

	ε	G	C	T	A	T	G	C	C	A	C	G	C
ε	0	1	2	3	4	5	6	7	8	9	10	11	12
G	1	0	1	2	3	4	5	6	7	8	9	10	11
C	2	1	0	1	2	3	4	5	6	7	8	9	10
G	3	2	1	1	2	3	3	4	5	6	7	8	9
T	4	3	2	1	2	2	3	4	5	6	7	8	9
A	5	4	3	2	1	2	3	4	5	5	6	7	8
T	6	5	4	3	2	1	2	3	4	5	6	7	8
G	7	6	5	4	3	2	1	2	3	4	5	6	7
C	8	7	6	5	4	3	2	1	2	3	4	5	6
A	9	8	7	6	5	4	3	2	2	2	3	4	5
C	10	9	8	7	6	5	4	3	2	3	2	3	4
G	11	10	9	8	7	6	5	4	3	3	3	2	3
C	12	11	10	9	8	7	6	5	4	4	3	3	2

A: From here

Q: How did I get here?

Edit distance: getting the alignment

Full **backtrace** path corresponds to an optimal alignment / edit transcript:

Start at end; at each step, ask: which predecessor gave the minimum?

	ε	G	C	T	A	T	G	C	C	A	C	G	C
ε	0	1	2	3	4	5	6	7	8	9	10	11	12
G	1	0	1	2	3	4	5	6	7	8	9	10	11
C	2	1	0	1	2	3	4	5	6	7	8	9	10
G	3	2	1	1	2	3	3	4	5	6	7	8	9
T	4	3	2	1	2	2	3	4	5	6	7	8	9
A	5	4	3	2	1	2	3	4	5	5	6	7	8
T	6	5	4	3	2	1	2	3	4	5	6	7	8
G	7	6	5	4	3	2	1	2	3	4	5	6	7
C	8	7	6	5	4	3	2	1	2	3	4	5	6
A	9	8	7	6	5	4	3	2	2	2	3	4	5
C	10	9	8	7	6	5	4	3	2	3	2	3	4
G	11	10	9	8	7	6	5	4	3	3	3	2	3
C	12	11	10	9	8	7	6	5	4	4	3	3	2

Alignment:

```

G C G T A T G - C A C G C
| |   | | | |   | | | |
G C - T A T G C C A C G C
  
```

Edit transcript:

MMDMMMMIMMMMM

Edit distance: summary

Matrix-filling dynamic programming algorithm is $O(mn)$ time and space

Filling matrix is $O(mn)$ space and time, and yields edit distance

Backtrace is $O(m + n)$ time, yields optimal alignment / edit transcript

Levenshtein

Basic edit distance

- Works for different-length sequences
- Uniform cost for substitution/insertion/deletion

```
def edit(x, y):  
    D = np.zeros((len(x) + 1, len(y) + 1), dtype=int)  
    # for the empty word, costs match the length of  
    # the other string  
    D[0, 1:] = range(1, len(y) + 1)  
    D[1:, 0] = range(1, len(x) + 1)  
  
    for i in range(1, len(x) + 1):  
        for j in range(1, len(y) + 1):  
            delta = 1 if x[i-1] != y[j-1] else 0  
            D[i, j] = min(  
                D[i-1, j] + 1,  
                D[i, j-1] + 1,  
                D[i-1, j-1] + delta  
            )  
  
    return D[len(x), len(y)]
```


Levenshtein

Custom Cost

```
def edit(x, y, cost={'m': 0, 's': 1, 'i': 1, 'd': 1}):
    D = np.zeros((len(x) + 1, len(y) + 1), dtype=int)
    # for the empty word, costs match the length of the
    # other string
    D[0, 1:] = range(1, len(y) + 1)
    D[1:, 0] = range(1, len(x) + 1)
    for i in range(1, len(x) + 1):
        for j in range(1, len(y) + 1):
            delta = cost['m'] if x[i-1] == y[j-1] else cost['s']
            D[i, j] = min(
                D[i-1, j] + cost['d'],
                D[i, j-1] + cost['i'],
                D[i-1, j-1] + delta
            )
    return D[len(x), len(y)]
```

Needleman-Wunsch Algorithm

- Biology: not all edits “cost the same”, gaps typically treated separately
- Gap penalty (eg. -1)
- Similarity (match reward, mismatch penalty)
- DP finds maximum similarity

	A	G	C	T
A	10	-1	-3	-4
G	-1	7	-5	-3
C	-3	-5	9	0
T	-4	-3	0	8




Needleman-Wunsch Algorithm

```
def nw(x, y, d, sim):  
    D = np.zeros((len(x) + 1, len(y) + 1), dtype=int)  
  
    # for the empty word, costs match the length of the other string  
    D[0, 1:] = range(1, len(y) + 1); D[0, 1:] *= d  
    D[1:, 0] = range(1, len(x) + 1); D[1:, 0] *= d  
  
    for i in range(1, len(x)):  
        for j in range(1, len(y)):  
            cs = D[i-1, j-1] + sim(x[i], y[j])  
            cd = D[i-1, j] + d  
            ci = D[i, j-1] + d  
            D[i, j] = max(cs, cd, ci)  
  
    print(D)  
    return D[len(x)][len(y)]
```

Keyboard-aware Substitutions?

- Compute cost of substitution by proximity of keys
- Map keys to grid, compute euclidean distance
- What about g <> h etc.?



https://commons.wikimedia.org/wiki/File:KB_United_States.svg#/media/File:KB_United_States.svg


Outlook: Damerau-Levenshtein with adjacent transpositions

Comparing Sequences


...of non-discrete signals?




vs.



Dynamic Time Warping



https://en.wikipedia.org/wiki/File:Dynamic_time_warping.png



https://en.wikipedia.org/wiki/File:Two_repetitions_of_a_walking_sequence_of_an_individual_recorded_using_a_motion-capture_system.gif

Dynamic Time Warping

- Sequences assumed to be similar, no notion of insert
—> first row/col is *inf*!
- Observations are continuous (not drawn from vocab)
 - There is *always* a cost
 - No explicit modeling of insertion/deletion/substitution

Dynamic Time Warping

```
def dtw(x: list, y: list, d) -> float:
    D = np.full((len(x) + 1, len(y) + 1), np.inf, dtype=float)
    D[0, 0] = 0

    for i in range(1, len(x)):
        for j in range(1, len(y)):
            cost = d(x[i], y[j])
            D[i, j] = cost + min(D[i-1, j],
                                D[i, j-1],
                                D[i-1, j-1])

    return D[len(x)][len(y)]
```



Dynamic Time Warping

On audio data

- Raw sample data is way to numerous
- Compute spectral (cepstral) features, eg. MFCC
- Use euclidean distance on feature vectors

MFCC

pipeline




Multi-class Sequence Classification

Eg. Isolated word recognition

- Have (at least) one reference sequence per class (word)
- Compute DTW distance for test sequence to each reference
- Chose class with minimum distance
- How to speed up...?



Decoding Sequences



Dual-tone multi-frequency signaling (DTMF)

Decoding States

- Observation: *pause 1 pause 2 pause ...*
- If we ignore noise etc.: 12+1 classes
 - model each class, eg. with a reference vector
 - apply a sliding window, map each window to class
 - output: – – 1 1 1 – – 2 2 2 2 – – 3 3 ...
 - collapse (uniq)
 - output: 123



<https://en.wikipedia.org/wiki/File:66a3aDTMFpad.jpg>

Assignment 1

Due April 8

- Edit distances (Hamming, Levenshtein, Needleman-Wunsch)
- Auto-Complete (using basic word stats)
- Isolated Word Recognition using DTW (on digits)
- DTMF sequence decoding using DP on states
- Submit via Teams to Files > Assignment Submissions

<https://github.com/seqlrn/assignments/tree/master/1-dynamic-programming>