

Introduction to Sequential Parameter Optimization

Noise

- This notebook demonstrates how noisy functions can be handled by Spot.

1 Example: Spot and the Noisy Sphere Function

```
import numpy as np
from math import inf
from spotPython.fun.objectivefunctions import analytical
from spotPython.spot import spot
from scipy.optimize import shgo
from scipy.optimize import direct
from scipy.optimize import differential_evolution
import matplotlib.pyplot as plt
```

The Objective Function: Noisy Sphere

- The `spotPython` package provides several classes of objective functions.
- We will use an analytical objective function with noise, i.e., a function that can be described by a (closed) formula:


$$f(x) = x^2 + \epsilon$$

- Since `sigma` is set to 0.1, noise is added to the function:

```
fun = analytical().fun_sphere
fun_control = {"sigma": 0.1,
              "seed": 123}
```

- A plot illustrates the noise:

```
x = np.linspace(-1,1,100).reshape(-1,1)
y = fun(x, fun_control=fun_control)
plt.figure()
plt.plot(x,y, "k")
plt.show()
```




Spot is adopted as follows to cope with noisy functions:

1. `fun_repeats` is set to a value larger than 1 (here: 2)
2. `noise` is set to `true`. Therefore, a nugget (`Lambda`) term is added to the correlation matrix
3. `init_size` (of the `design_control` dictionary) is set to a value larger than 1 (here: 2)


```
spot_1_noisy = spot.Spot(fun=fun,
    lower = np.array([-1]),
    upper = np.array([1]),
    fun_evals = 10,
    fun_repeats = 2,
    noise = True,
    seed=123,
    show_models=True,
    fun_control = fun_control,
    design_control={"init_size": 3,
                    "repeats": 2},
    surrogate_control={"noise": True})
```


```
spot_1_noisy.run()
```

6. y (noise): 0.092465 y mean: 0.109622



8. y (noise): -0.064157 y mean: -0.03309





```
<spotPython.spot.spot.Spot at 0x29c6eb3d0>
```


Print the Results

```
spot_1_noisy.print_results()
```

```
min y: -0.06415721594238855
x0: 0.18642671238960512
min mean y: -0.03309048099839016
x0: 0.18642671238960512
```

```
[['x0', 0.18642671238960512], ['x0', 0.18642671238960512]]
```

```
spot_1_noisy.plot_progress(log_y=False)
```



2 Noise and Surrogates: The Nugget Effect

2.1 The Noisy Sphere

The Data

- We prepare some data first:

```
import numpy as np
import spotPython
from spotPython.fun.objectivefunctions import analytical
from spotPython.spot import spot
from spotPython.design.spacefilling import spacefilling
from spotPython.build.kriging import Kriging
import matplotlib.pyplot as plt

gen = spacefilling(1)
rng = np.random.RandomState(1)
lower = np.array([-10])
upper = np.array([10])
fun = analytical().fun_sphere
fun_control = {"sigma": 2,
               "seed": 125}
X = gen.scipy_lhd(10, lower=lower, upper = upper)
y = fun(X, fun_control=fun_control)
X_train = X.reshape(-1,1)
y_train = y
```

- A surrogate without nugget is fitted to these data:

```
S = Kriging(name='kriging',
            seed=123,
            log_level=50,
            n_theta=1,
            noise=False)
```


```

S.fit(X_train, y_train)

X_axis = np.linspace(start=-13, stop=13, num=1000).reshape(-1, 1)
mean_prediction, std_prediction, ei = S.predict(X_axis, return_val="all")

plt.scatter(X_train, y_train, label="Observations")
plt.plot(X_axis, mean_prediction, label="mue")
plt.legend()
plt.xlabel("$x$")
plt.ylabel("$f(x)$")
_ = plt.title("Sphere: Gaussian process regression on noisy dataset")

```



- In comparison to the surrogate without nugget, we fit a surrogate with nugget to the data:

```

S_nug = Kriging(name='kriging',
                seed=123,
                log_level=50,
                n_theta=1,
                noise=True)
S_nug.fit(X_train, y_train)

```




```

X_axis = np.linspace(start=-13, stop=13, num=1000).reshape(-1, 1)
mean_prediction, std_prediction, ei = S_nug.predict(X_axis, return_val="all")
plt.scatter(X_train, y_train, label="Observations")
plt.plot(X_axis, mean_prediction, label="mue")
plt.legend()
plt.xlabel("$x$")
plt.ylabel("$f(x)$")
_ = plt.title("Sphere: Gaussian process regression with nugget on noisy dataset")

```

Sphere: Gaussian process regression with nugget on noisy dataset



- The value of the nugget term can be extracted from the model as follows:

```
S.Lambda
```

```
S_nug.Lambda
```

```
9.088150066416743e-05
```

- We see:
 - the first model S has no nugget,
 - whereas the second model has a nugget value (Lambda) larger than zero.

Exercises

- Important:
 - Results from these exercises should be added to this document, i.e., you should submit an updated version of this notebook.
 - Please combine your results using this notebook.
 - Only one notebook from each group!
 - Presentation is based on this notebook. No additional slides are required!
 - spotPython version 0.16.11 (or greater) is required (see <http://www.gm.fh-koeln.de/~bartz/site/download/>)

Exercise 1

- Each team member should choose one of the following optimization algorithms.
- Please add your name to the section title!

1. Noisy fun_cubed

- Analyse the effect of noise on the `fun_cubed` function with the following settings:

```
fun = analytical().fun_cubed
fun_control = {"sigma": 10,
               "seed": 123}
lower = np.array([-10])
upper = np.array([10])
```

2. fun_runge

- Analyse the effect of noise on the `fun_runge` function with the following settings:

```
lower = np.array([-10])
upper = np.array([10])
fun = analytical().fun_runge
```

```
fun_control = {"sigma": 0.25,  
              "seed": 123}
```

3. fun_forrester

- Analyse the effect of noise on the `fun_forrester` function with the following settings:

```
lower = np.array([0])  
upper = np.array([1])  
fun = analytical().fun_forrester  
fun_control = {"sigma": 5,  
              "seed": 123}
```

4. fun_xsin

- Analyse the effect of noise on the `fun_xsin` function with the following settings:

```
lower = np.array([-1.])  
upper = np.array([1.])  
fun = analytical().fun_xsin  
fun_control = {"sigma": 0.5,  
              "seed": 123}
```